

## REFUELING OPERATIONS

### SURVEILLANCE REQUIREMENTS (Continued)

---

- b. Performance of a CHANNEL FUNCTIONAL TEST at least once per 7 days.
- c. Verifying that the channel count rate is at least 3.0 cps: \*
  - 1. Prior to control rod withdrawal,
  - 2. Prior to and at least once per 12 hours during CORE ALTERATIONS, and
  - 3. At least once per 24 hours.
- d. Verifying, within 8 hours prior to and at least once per 12 hours during, that the RPS circuitry "shorting links" have been removed during:
  - 1. The time any control rod is withdrawn\*\*, unless adequate shutdown margin has been demonstrated, or
  - 2. Shutdown margin demonstrations.

---

\*May be reduced, provided the source range monitor has an observed count rate and signal-to-noise ratio on or above the curve shown in Figure 3.3.6-1. These channels are not required when sixteen or fewer fuel assemblies, adjacent to the SRMs, are in the core.

\*\*Not required for control rods removed per Specification 3.9.10.1 or 3.9.10.2.

## REFUELING OPERATIONS

### SURVEILLANCE REQUIREMENTS (Continued)

---

- b. Performance of a CHANNEL FUNCTIONAL TEST at least once per 7 days.
- c. Verifying that the channel count rate is at least 3.0 cps: \*
  - 1. Prior to control rod withdrawal,
  - 2. Prior to and at least once per 12 hours during CORE ALTERATIONS, and
  - 3. At least once per 24 hours.
- d. Verifying, within 8 hours prior to and at least once per 12 hours during, that the RPS circuitry "shorting links" have been removed during:
  - 1. The time any control rod is withdrawn\*\*, unless adequate shutdown margin has been demonstrated, or
  - 2. Shutdown margin demonstrations.

---

\*May be reduced, provided the source range monitor has an observed count rate and signal-to-noise ratio on or above the curve shown in Figure 3.3.6-1. These channels are not required when sixteen or fewer fuel assemblies, adjacent to the SRMs, are in the core.

\*\*Not required for control rods removed per Specification 3.9.10.1 or 3.9.10.2.