

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 217 of 311

TABLE 5

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 24 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .7242 *	* .6060 *	* .5487 *	* .6085 *	* .5413 *	* .5793 *	* .4764 *	* .4036 *
	* 2.3821 *	* 3.0210 *	* 3.3791 *	* 2.9841 *	* 3.3407 *	* 3.0848 *	* 3.7301 *	* 4.3436 *
9	* .6060 *	* .5569 *	* .6094 *	* .5444 *	* .5971 *	* .5398 *	* .5135 *	* .3391 *
	* 3.0210 *	* 3.3739 *	* 3.0461 *	* 3.3670 *	* 3.0293 *	* 3.3241 *	* 3.5019 *	* 5.2412 *
10	* .5487 *	* .6099 *	* .5641 *	* .5214 *	* .5300 *	* .5773 *	* .5266 *	* .3242 *
	* 3.3791 *	* 3.0458 *	* 3.3048 *	* 3.5468 *	* 3.4687 *	* 3.2030 *	* 3.4710 *	* 5.5086 *
11	* .6085 *	* .5446 *	* .5206 *	* .4944 *	* .5642 *	* .5193 *	* .4778 *	* .2866 *
	* 2.9841 *	* 3.3663 *	* 3.5521 *	* 3.5149 *	* 3.1699 *	* 3.5428 *	* 3.8905 *	* 6.4435 *
12	* .5413 *	* .5969 *	* .5299 *	* .5641 *	* .4984 *	* .4924 *	* .3875 *	
	* 3.3407 *	* 3.0298 *	* 3.4691 *	* 3.1701 *	* 3.3616 *	* 3.4140 *	* 4.6198 *	
13	* .5793 *	* .5398 *	* .5772 *	* .5193 *	* .4924 *	* .4432 *	* .4238 *	
	* 3.0848 *	* 3.3243 *	* 3.2031 *	* 3.5431 *	* 3.4141 *	* 3.7613 *	* 4.1172 *	
14	* .4764 *	* .5137 *	* .5267 *	* .4778 *	* .3878 *	* .4236 *		
	* 3.7301 *	* 3.5002 *	* 3.4704 *	* 3.8905 *	* 4.6173 *	* 4.1186 *		
15	* .4036 *	* .3392 *	* .3243 *	* .2866 *	F-SUB-Q			
	* 4.3436 *	* 5.2372 *	* 5.5064 *	* 6.4430 *	M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 23 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9230 *	* 1.3124 *	* 1.0577 *	* 1.2772 *	* 1.0399 *	* 1.2216 *	* .9191 *	* .5325 *
	* 1.9269 *	* 1.4371 *	* 1.7852 *	* 1.4549 *	* 1.7699 *	* 1.4939 *	* 1.9760 *	* 3.3585 *
9	* 1.3124 *	* 1.0623 *	* 1.3202 *	* 1.0454 *	* 1.2571 *	* 1.0715 *	* 1.1870 *	* .6741 *
	* 1.4371 *	* 1.7960 *	* 1.4344 *	* 1.7866 *	* 1.4686 *	* 1.7101 *	* 1.5468 *	* 2.6819 *
10	* 1.0577 *	* 1.3201 *	* 1.0531 *	* 1.0821 *	* 1.0880 *	* 1.2009 *	* 1.1721 *	* .6444 *
	* 1.7852 *	* 1.4348 *	* 1.7958 *	* 1.7423 *	* 1.7385 *	* 1.5720 *	* 1.5900 *	* 2.8273 *
11	* 1.2772 *	* 1.0452 *	* 1.0801 *	* .9875 *	* 1.1896 *	* 1.0325 *	* 1.1038 *	* .5663 *
	* 1.4549 *	* 1.7873 *	* 1.7455 *	* 1.8521 *	* 1.5383 *	* 1.7992 *	* 1.7007 *	* 3.3253 *
12	* 1.0399 *	* 1.2568 *	* 1.0878 *	* 1.1894 *	* 1.0553 *	* 1.1788 *	* .7760 *	
	* 1.7699 *	* 1.4689 *	* 1.7389 *	* 1.5384 *	* 1.6430 *	* 1.5036 *	* 2.3561 *	
13	* 1.2216 *	* 1.0715 *	* 1.2008 *	* 1.0324 *	* 1.1787 *	* 1.0633 *	* .5556 *	
	* 1.4939 *	* 1.7101 *	* 1.5721 *	* 1.7992 *	* 1.5036 *	* 1.6488 *	* 3.2148 *	
14	* .9191 *	* 1.1874 *	* 1.1723 *	* 1.1038 *	* .7759 *	* .5555 *		
	* 1.9760 *	* 1.5463 *	* 1.5897 *	* 1.7007 *	* 2.3564 *	* 3.2150 *		
15	* .5325 *	* .6745 *	* .6446 *	* .5664 *	F-SUB-Q			
	* 3.3585 *	* 2.6806 *	* 2.8264 *	* 3.3252 *	M-SUB-Q			

CNEI-0400-25
Appendix A, Rev. 19
Page 218 of 311

F-SUB-O & M-SUB-O VALUES (F-SUB-O OP MARGIN) - POWER ESCALATION

	H	G	F	E	D	C	B	A
8	* 1.0709	* 1.3557	* 1.2308	* 1.3404	* 1.1949	* 1.2894	* 1.0353	* .6072
	* 1.7807	* 1.4357	* 1.5590	* 1.4141	* 1.5609	* 1.4371	* 1.7720	* 2.9722
9	* 1.3557	* 1.2305	* 1.3567	* 1.2173	* 1.3206	* 1.2135	* 1.2664	* .7538
	* 1.4357	* 1.5822	* 1.4136	* 1.5554	* 1.4222	* 1.5328	* 1.4670	* 2.4317
10	* 1.2308	* 1.3565	* 1.1735	* 1.2845	* 1.2596	* 1.2809	* 1.2267	* .7141
	* 1.5590	* 1.4153	* 1.6279	* 1.4892	* 1.5268	* 1.4915	* 1.5394	* 2.5875
11	* 1.3404	* 1.2163	* 1.2817	* 1.1664	* 1.2881	* 1.1711	* 1.2620	* .6402
	* 1.4141	* 1.5566	* 1.4925	* 1.6431	* 1.4526	* 1.6116	* 1.5078	* 2.9849
12	* 1.1949	* 1.3199	* 1.2589	* 1.2876	* 1.2561	* 1.2574	* .9052	*
	* 1.5609	* 1.4224	* 1.5276	* 1.4526	* 1.4701	* 1.4684	* 2.0606	*
13	* 1.2894	* 1.2134	* 1.2806	* 1.1710	* 1.2573	* 1.2489	* .6279	*
	* 1.4371	* 1.5330	* 1.4918	* 1.6117	* 1.4684	* 1.4587	* 2.9100	*
14	* 1.0353	* 1.2666	* 1.2267	* 1.2620	* .9050	* .6279	*	
	* 1.7720	* 1.4667	* 1.5394	* 1.5078	* 2.0610	* 2.9099	*	
15	* .6072	* .7541	* .7142	* .6402	* F-SUB-Q			
	* 2.9722	* 2.4309	* 2.5870	* 2.9849	* M-SUB-Q			

	H	G	F	E	D	C	B	A
8	* 1.1316	* 1.4737	* 1.3523	* 1.4560	* 1.3096	* 1.3974	* 1.1349	* .6477
	* 1.7388	* 1.3493	* 1.4430	* 1.3220	* 1.4455	* 1.3455	* 1.6388	* 2.8265
9	* 1.4737	* 1.3506	* 1.4758	* 1.3447	* 1.4390	* 1.3091	* 1.3739	* .7889
	* 1.3493	* 1.4724	* 1.3164	* 1.4316	* 1.3292	* 1.4411	* 1.3687	* 2.3571
10	* 1.3523	* 1.4754	* 1.2443	* 1.4010	* 1.3597	* 1.3836	* 1.3142	* .7323
	* 1.4430	* 1.3182	* 1.5617	* 1.3860	* 1.4388	* 1.4024	* 1.4582	* 2.5603
11	* 1.4560	* 1.3422	* 1.3976	* 1.2909	* 1.4116	* 1.2671	* 1.3856	* .6612
	* 1.3220	* 1.4330	* 1.3894	* 1.5239	* 1.3637	* 1.5218	* 1.3958	* 2.9366
12	* 1.3096	* 1.4381	* 1.3588	* 1.4110	* 1.3579	* 1.3747	* .9707	*
	* 1.4455	* 1.3299	* 1.4398	* 1.3638	* 1.3958	* 1.3780	* 1.9626	*
13	* 1.3974	* 1.3088	* 1.3832	* 1.2669	* 1.3746	* 1.3845	* .6734	*
	* 1.3455	* 1.4414	* 1.4028	* 1.5220	* 1.3781	* 1.3493	* 2.7786	*
14	* 1.1349	* 1.3740	* 1.3142	* 1.3855	* .9703	* .6734	*	*
	* 1.6388	* 1.3686	* 1.4583	* 1.3959	* 1.9634	* 2.7786	*	*
15	* .6477	* .7891	* .7324	* .6612	* F-SUB-Q			
	* 2.8265	* 2.3566	* 2.5600	* 2.9368	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 219 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 20 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1463	* 1.5278	* 1.3900	* 1.5107	* 1.3647	* 1.4504	* 1.1672	* .6538 *
	* 1.7636	* 1.3322	* 1.4312	* 1.2973	* 1.4128	* 1.3199	* 1.6220	* 2.8513 *
9	* 1.5278	* 1.3863	* 1.5307	* 1.3814	* 1.4940	* 1.3524	* 1.4240	* .8006 *
	* 1.3322	* 1.4683	* 1.2928	* 1.4186	* 1.3038	* 1.4198	* 1.3434	* 2.3641 *
10	* 1.3900	* 1.5302	* 1.2684	* 1.4432	* 1.3982	* 1.4341	* 1.3642	* .7432 *
	* 1.4312	* 1.2947	* 1.5589	* 1.3702	* 1.4244	* 1.3771	* 1.4289	* 2.5676 *
11	* 1.5107	* 1.3803	* 1.4395	* 1.3408	* 1.4682	* 1.3131	* 1.4455	* .6716 *
	* 1.2973	* 1.4196	* 1.3738	* 1.4996	* 1.3398	* 1.5019	* 1.3667	* 2.9403 *
12	* 1.3647	* 1.4930	* 1.3972	* 1.4675	* 1.4069	* 1.4341	* 1.0054	*
	* 1.4128	* 1.3046	* 1.4255	* 1.3398	* 1.3812	* 1.3540	* 1.9401	*
13	* 1.4504	* 1.3520	* 1.4336	* 1.3128	* 1.4339	* 1.4557	* .6911	*
	* 1.3199	* 1.4201	* 1.3775	* 1.5021	* 1.3542	* 1.3160	* 2.7781	*
14	* 1.1672	* 1.4240	* 1.3640	* 1.4453	* 1.0049	* .6911	*	
	* 1.6220	* 1.3434	* 1.4291	* 1.3668	* 1.9410	* 2.7781	*	
15	* .6538	* .8007	* .7432	* .6715	* F-SUB-Q			
	* 2.8513	* 2.3637	* 2.5676	* 2.9407	* M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 19 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1550	* 1.5535	* 1.4092	* 1.5376	* 1.3868	* 1.4780	* 1.1814	* .6562 *
	* 1.7886	* 1.3352	* 1.4432	* 1.3016	* 1.4215	* 1.3235	* 1.6369	* 2.9029 *
9	* 1.5535	* 1.4017	* 1.5571	* 1.3993	* 1.5211	* 1.3762	* 1.4514	* .8067 *
	* 1.3352	* 1.4802	* 1.2990	* 1.4315	* 1.3081	* 1.4242	* 1.3455	* 2.3951 *
10	* 1.4092	* 1.5566	* 1.2851	* 1.4636	* 1.4189	* 1.4618	* 1.3930	* .7528 *
	* 1.4432	* 1.3009	* 1.5723	* 1.3799	* 1.4319	* 1.3779	* 1.4265	* 2.5865 *
11	* 1.5376	* 1.3983	* 1.4597	* 1.3633	* 1.4975	* 1.3402	* 1.4799	* .6798 *
	* 1.3016	* 1.4325	* 1.3836	* 1.5019	* 1.3398	* 1.5042	* 1.3597	* 2.9467 *
12	* 1.3868	* 1.5200	* 1.4178	* 1.4968	* 1.4378	* 1.4687	* 1.0291	*
	* 1.4215	* 1.3085	* 1.4331	* 1.3399	* 1.3843	* 1.3556	* 1.9397	*
13	* 1.4780	* 1.3758	* 1.4613	* 1.3399	* 1.4685	* 1.4981	* .7031	*
	* 1.3235	* 1.4246	* 1.3784	* 1.5045	* 1.3557	* 1.3148	* 2.8071	*
14	* 1.1814	* 1.4512	* 1.3928	* 1.4796	* 1.0287	* .7031	*	
	* 1.6369	* 1.3456	* 1.4267	* 1.3599	* 1.9405	* 2.8071	*	
15	* .6562	* .8068	* .7528	* .6797	* F-SUB-Q			
	* 2.9029	* 2.3949	* 2.5866	* 2.9472	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 220 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 18 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1675	* 1.5891	* 1.4346	* 1.5742	* 1.4131	* 1.5156	* 1.2012	* .6630 *
	* 1.8021	* 1.3200	* 1.4530	* 1.3038	* 1.4319	* 1.3241	* 1.6510	* 2.9474 *
9	* 1.5891	* 1.4236	* 1.5935	* 1.4240	* 1.5583	* 1.4082	* 1.4900	* .8190 *
	* 1.3200	* 1.4738	* 1.3011	* 1.4428	* 1.3091	* 1.4268	* 1.3429	* 2.4163 *
10	* 1.4346	* 1.5931	* 1.2991	* 1.4922	* 1.4479	* 1.5000	* 1.4300	* .7581 *
	* 1.4530	* 1.3031	* 1.5942	* 1.3860	* 1.4289	* 1.3729	* 1.4199	* 2.6284 *
11	* 1.5742	* 1.4230	* 1.4881	* 1.3908	* 1.5397	* 1.3747	* 1.5235	* .6865 *
	* 1.3038	* 1.4439	* 1.3899	* 1.4910	* 1.3342	* 1.4954	* 1.3402	* 2.9584 *
12	* 1.4131	* 1.5571	* 1.4467	* 1.5396	* 1.4757	* 1.5131	* 1.0477	*
	* 1.4319	* 1.3094	* 1.4301	* 1.3343	* 1.3814	* 1.3472	* 1.9514	*
13	* 1.5156	* 1.4078	* 1.4994	* 1.3743	* 1.5129	* 1.5482	* .7206	*
	* 1.3241	* 1.4271	* 1.3734	* 1.4958	* 1.3474	* 1.3020	* 2.8057	*
14	* 1.2012	* 1.4898	* 1.4297	* 1.5232	* 1.0470	* .7206	*	
	* 1.6510	* 1.3430	* 1.4202	* 1.3405	* 1.9525	* 2.8057	*	
15	* .6630	* .8190	* .7580	* .6864	* F-SUB-Q			
	* 2.9474	* 2.4161	* 2.6286	* 2.9591	* M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 17 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1647	* 1.6108	* 1.4517	* 1.5971	* 1.4312	* 1.5401	* 1.2150	* .6621 *
	* 1.8404	* 1.3324	* 1.4737	* 1.3228	* 1.4566	* 1.3419	* 1.6802	* 3.0384 *
9	* 1.6108	* 1.4375	* 1.6162	* 1.4407	* 1.5824	* 1.4301	* 1.5157	* .8228 *
	* 1.3324	* 1.4939	* 1.3186	* 1.4673	* 1.3264	* 1.4456	* 1.3568	* 2.4707 *
10	* 1.4517	* 1.6157	* 1.3097	* 1.5124	* 1.4687	* 1.5254	* 1.4549	* .7620 *
	* 1.4737	* 1.3207	* 1.6242	* 1.4017	* 1.4406	* 1.3786	* 1.4294	* 2.6832 *
11	* 1.5971	* 1.4397	* 1.5081	* 1.4115	* 1.5696	* 1.3987	* 1.5541	* .6898 *
	* 1.3228	* 1.4684	* 1.4057	* 1.5038	* 1.3331	* 1.4976	* 1.3400	* 3.0066 *
12	* 1.4312	* 1.5812	* 1.4675	* 1.5695	* 1.5045	* 1.5440	* 1.0637	*
	* 1.4566	* 1.3272	* 1.4418	* 1.3332	* 1.3825	* 1.3474	* 1.9540	*
13	* 1.5401	* 1.4297	* 1.5248	* 1.3983	* 1.5437	* 1.5840	* .7280	*
	* 1.3419	* 1.4459	* 1.3792	* 1.4980	* 1.3476	* 1.3028	* 2.8370	*
14	* 1.2150	* 1.5154	* 1.4546	* 1.5537	* 1.0630	* .7280	*	
	* 1.6802	* 1.3570	* 1.4298	* 1.3403	* 1.9552	* 2.8370	*	
15	* .6621	* .8228	* .7619	* .6896	* F-SUB-Q			
	* 3.0384	* 2.4707	* 2.6836	* 3.0073	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 221 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 16 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1748	* 1.6363	* 1.4705	* 1.6239	* 1.4512	* 1.5682	* 1.2303	* .6695 *
	* 1.8900	* 1.3515	* 1.4979	* 1.3447	* 1.4862	* 1.3629	* 1.7152	* 3.1082 *
9	* 1.6363	* 1.4535	* 1.6429	* 1.4597	* 1.6107	* 1.4540	* 1.5446	* .8314 *
	* 1.3515	* 1.5224	* 1.3375	* 1.4959	* 1.3460	* 1.4689	* 1.3733	* 2.5217 *
10	* 1.4705	* 1.6423	* 1.3215	* 1.5365	* 1.4924	* 1.5543	* 1.4821	* .7664 *
	* 1.4979	* 1.3382	* 1.6587	* 1.4207	* 1.4566	* 1.3897	* 1.4418	* 2.7471 *
11	* 1.6239	* 1.4586	* 1.5320	* 1.4346	* 1.6027	* 1.4246	* 1.5870	* .6946 *
	* 1.3447	* 1.4970	* 1.4249	* 1.5259	* 1.3476	* 1.5152	* 1.3511	* 3.0566 *
12	* 1.4512	* 1.6094	* 1.4911	* 1.6026	* 1.5351	* 1.5778	* 1.0781	*
	* 1.4862	* 1.3470	* 1.4578	* 1.3476	* 1.4007	* 1.3593	* 1.9840	*
13	* 1.5682	* 1.4536	* 1.5536	* 1.4242	* 1.5776	* 1.6213	* .7410	*
	* 1.3629	* 1.4693	* 1.3904	* 1.5156	* 1.3595	* 1.3092	* 2.8654	*
14	* 1.2303	* 1.5443	* 1.4817	* 1.5866	* 1.0774	* .7410	*	
	* 1.7152	* 1.3736	* 1.4421	* 1.3515	* 1.9853	* 2.8655	*	
15	* .6695	* .8313	* .7663	* .6944	* F-SUB-Q			
	* 3.1082	* 2.5217	* 2.7476	* 3.0574	* M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 15 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1609	* 1.6255	* 1.4667	* 1.6150	* 1.4489	* 1.5618	* 1.2287	* .6611 *
	* 1.9833	* 1.4057	* 1.5566	* 1.4037	* 1.5474	* 1.4217	* 1.7831	* 3.2635 *
9	* 1.6255	* 1.4477	* 1.6332	* 1.4566	* 1.6038	* 1.4517	* 1.5396	* .8308 *
	* 1.4057	* 1.5800	* 1.3941	* 1.5561	* 1.4027	* 1.5275	* 1.4260	* 2.6133 *
10	* 1.4667	* 1.6326	* 1.3314	* 1.5353	* 1.4926	* 1.5493	* 1.4789	* .7753 *
	* 1.5566	* 1.3948	* 1.7078	* 1.4742	* 1.5077	* 1.4421	* 1.4939	* 2.8088 *
11	* 1.6150	* 1.4555	* 1.5310	* 1.4355	* 1.6024	* 1.4235	* 1.5856	* .7027 *
	* 1.4037	* 1.5572	* 1.4784	* 1.5760	* 1.4021	* 1.5689	* 1.3927	* 3.1145 *
12	* 1.4489	* 1.6025	* 1.4913	* 1.6023	* 1.5402	* 1.5767	* 1.0903	*
	* 1.5474	* 1.4038	* 1.5091	* 1.4021	* 1.4535	* 1.4141	* 2.0345	*
13	* 1.5618	* 1.4512	* 1.5486	* 1.4231	* 1.5764	* 1.6236	* .7387	*
	* 1.4217	* 1.5279	* 1.4428	* 1.5694	* 1.4143	* 1.3578	* 2.9831	*
14	* 1.2287	* 1.5392	* 1.4785	* 1.5852	* 1.0897	* .7386	*	
	* 1.7831	* 1.4263	* 1.4943	* 1.3931	* 2.0356	* 2.9832	*	
15	* .6611	* .8307	* .7751	* .7025	* F-SUB-Q			
	* 3.2635	* 2.6134	* 2.8094	* 3.1154	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 222 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 14 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1751	* 1.6629	* 1.4914	* 1.6534	* 1.4750	* 1.6015	* 1.2487	* .6723 *
	* 1.9837	* 1.3951	* 1.5549	* 1.4016	* 1.5682	* 1.4438	* 1.8290	* 3.3468 *
9	* 1.6629	* 1.4694	* 1.6718	* 1.4814	* 1.6439	* 1.4844	* 1.5803	* .8397 *
	* 1.3951	* 1.5791	* 1.3867	* 1.5638	* 1.4094	* 1.5574	* 1.4467	* 2.6887 *
10	* 1.4914	* 1.6712	* 1.3392	* 1.5671	* 1.5240	* 1.5897	* 1.5162	* .7737 *
	* 1.5549	* 1.3872	* 1.7314	* 1.4786	* 1.5208	* 1.4583	* 1.5131	* 2.9242 *
11	* 1.6534	* 1.4803	* 1.5625	* 1.4664	* 1.6465	* 1.4582	* 1.6305	* .7020 *
	* 1.4016	* 1.5650	* 1.4830	* 1.5826	* 1.4149	* 1.5888	* 1.4046	* 3.2349 *
12	* 1.4750	* 1.6425	* 1.5226	* 1.6464	* 1.5786	* 1.6224	* 1.1016	*
	* 1.5682	* 1.4106	* 1.5222	* 1.4150	* 1.4728	* 1.4261	* 2.0834	*
13	* 1.6015	* 1.4839	* 1.5889	* 1.4576	* 1.6221	* 1.6730	* .7551	*
	* 1.4438	* 1.5578	* 1.4591	* 1.5893	* 1.4264	* 1.3697	* 3.0257	*
14	* 1.2487	* 1.5799	* 1.5156	* 1.6299	* 1.1008	* .7551	*	
	* 1.8290	* 1.4471	* 1.5136	* 1.4050	* 2.0849	* 3.0257	*	
15	* .6723	* .8397	* .7734	* .7017	* F-SUB-Q			
	* 3.3468	* 2.6888	* 2.9248	* 3.2359	* M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 13 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1714	* 1.6730	* 1.4989	* 1.6648	* 1.4841	* 1.6151	* 1.2557	* .6721 *
	* 2.0011	* 1.3957	* 1.5564	* 1.4000	* 1.5673	* 1.4392	* 1.8466	* 3.4386 *
9	* 1.6730	* 1.4744	* 1.6830	* 1.4891	* 1.6571	* 1.4969	* 1.5954	* .8426 *
	* 1.3957	* 1.5835	* 1.3858	* 1.5647	* 1.4064	* 1.5536	* 1.4578	* 2.7523 *
10	* 1.4989	* 1.6823	* 1.3458	* 1.5792	* 1.5367	* 1.6043	* 1.5306	* .7764 *
	* 1.5564	* 1.3865	* 1.7334	* 1.4772	* 1.5190	* 1.4547	* 1.5226	* 2.9927 *
11	* 1.6648	* 1.4880	* 1.5745	* 1.4786	* 1.6652	* 1.4725	* 1.6496	* .7050 *
	* 1.4000	* 1.5658	* 1.4816	* 1.5816	* 1.4145	* 1.5929	* 1.4193	* 3.3091 *
12	* 1.4841	* 1.6557	* 1.5352	* 1.6651	* 1.5975	* 1.6417	* 1.1117	*
	* 1.5673	* 1.4076	* 1.5204	* 1.4146	* 1.4770	* 1.4367	* 2.1139	*
13	* 1.6151	* 1.4964	* 1.6035	* 1.4719	* 1.6414	* 1.6962	* .7594	*
	* 1.4392	* 1.5541	* 1.4555	* 1.5935	* 1.4369	* 1.3921	* 3.1038	*
14	* 1.2557	* 1.5949	* 1.5301	* 1.6490	* 1.1109	* .7594	*	
	* 1.8466	* 1.4583	* 1.5232	* 1.4198	* 2.1155	* 3.1040	*	
15	* .6721	* .8425	* .7761	* .7047	* F-SUB-Q			
	* 3.4386	* 2.7526	* 2.9936	* 3.3104	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 223 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 12 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1603	* 1.6590	* 1.4909	* 1.6525	* 1.4777	* 1.6058	* 1.2514	* .6659 *
	* 2.0335	* 1.4170	* 1.5751	* 1.4193	* 1.5836	* 1.4560	* 1.8634	* 3.4896 *
9	* 1.6590	* 1.4647	* 1.6700	* 1.4816	* 1.6468	* 1.4913	* 1.5885	* .8399 *
	* 1.4170	* 1.6046	* 1.4057	* 1.5825	* 1.4239	* 1.5681	* 1.4718	* 2.7736 *
10	* 1.4909	* 1.6692	* 1.3492	* 1.5733	* 1.5324	* 1.5964	* 1.5262	* .7818 *
	* 1.5751	* 1.4064	* 1.7402	* 1.4927	* 1.5334	* 1.4709	* 1.5366	* 2.9840 *
11	* 1.6525	* 1.4806	* 1.5686	* 1.4729	* 1.6614	* 1.4686	* 1.6460	* .7097 *
	* 1.4193	* 1.5836	* 1.4972	* 1.5990	* 1.4292	* 1.6089	* 1.4323	* 3.3030 *
12	* 1.4777	* 1.6454	* 1.5310	* 1.6613	* 1.5982	* 1.6378	* 1.1195	* .7567 *
	* 1.5836	* 1.4251	* 1.5349	* 1.4293	* 1.4887	* 1.4520	* 2.1145	* .7567 *
13	* 1.6058	* 1.4907	* 1.5956	* 1.4680	* 1.6375	* 1.6961	* 1.4027	* 3.1381 *
	* 1.4560	* 1.5687	* 1.4717	* 1.6095	* 1.4523	* 1.4027	* 3.1381 *	
14	* 1.2514	* 1.5879	* 1.5256	* 1.6454	* 1.1188	* .7567		
	* 1.8634	* 1.4723	* 1.5372	* 1.4329	* 2.1159	* 3.1383		
15	* .6659	* .8398	* .7815	* .7094	* F-SUB-Q			
	* 3.4896	* 2.7740	* 2.9850	* 3.3043	* M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 11 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1666	* 1.6862	* 1.5064	* 1.6806	* 1.4948	* 1.6363	* 1.2648	* .6732 *
	* 2.0132	* 1.3884	* 1.5512	* 1.3891	* 1.5582	* 1.4232	* 1.8329	* 3.4167 *
9	* 1.6862	* 1.4775	* 1.6984	* 1.4971	* 1.6766	* 1.5154	* 1.6215	* .8484 *
	* 1.3884	* 1.5827	* 1.3763	* 1.5586	* 1.3939	* 1.5382	* 1.4385	* 2.7243 *
10	* 1.5064	* 1.6976	* 1.3496	* 1.5946	* 1.5546	* 1.6277	* 1.5574	* .7784 *
	* 1.5512	* 1.3770	* 1.7312	* 1.4696	* 1.5106	* 1.4401	* 1.5042	* 2.9739 *
11	* 1.6806	* 1.4960	* 1.5897	* 1.4945	* 1.6961	* 1.4947	* 1.6834	* .7082 *
	* 1.3891	* 1.5597	* 1.4739	* 1.5742	* 1.4068	* 1.5846	* 1.4042	* 3.2913 *
12	* 1.4948	* 1.6752	* 1.5534	* 1.6960	* 1.6274	* 1.6750	* 1.1254	* .7704 *
	* 1.5582	* 1.3950	* 1.5120	* 1.4069	* 1.4718	* 1.4270	* 2.1064	* .7704 *
13	* 1.6363	* 1.5148	* 1.6268	* 1.4941	* 1.6747	* 1.7385	* .7704	
	* 1.4232	* 1.5388	* 1.4409	* 1.5853	* 1.4273	* 1.3780	* 3.0859	
14	* 1.2648	* 1.6208	* 1.5568	* 1.6827	* 1.1245	* .7704		
	* 1.8329	* 1.4391	* 1.5049	* 1.4048	* 2.1080	* 3.0861		
15	* .6732	* .8483	* .7781	* .7079	* F-SUB-Q			
	* 3.4167	* 2.7247	* 2.9750	* 3.2928	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 224 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 10 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1572	* 1.6923	* 1.5085	* 1.6878	* 1.4984	* 1.6464	* 1.2680	* .6703 *
	* 1.9749	* 1.3463	* 1.5074	* 1.3464	* 1.5134	* 1.3775	* 1.7801	* 3.3395 *
9	* 1.6923	* 1.4774	* 1.7056	* 1.4993	* 1.6865	* 1.5238	* 1.6345	* .8482 *
	* 1.3463	* 1.5401	* 1.3339	* 1.5146	* 1.3498	* 1.4897	* 1.3899	* 2.6515 *
10	* 1.5085	* 1.7047	* 1.3467	* 1.6001	* 1.5620	* 1.6388	* 1.5705	* .7761 *
	* 1.5074	* 1.3346	* 1.6879	* 1.4252	* 1.4642	* 1.3927	* 1.4536	* 2.9017 *
11	* 1.6878	* 1.4982	* 1.5952	* 1.5008	* 1.7105	* 1.5049	* 1.7003	* .7064 *
	* 1.3464	* 1.5156	* 1.4295	* 1.5252	* 1.3599	* 1.5329	* 1.3534	* 3.2087 *
12	* 1.4984	* 1.6852	* 1.5607	* 1.7104	* 1.6407	* 1.6911	* 1.1292	*
	* 1.5134	* 1.3509	* 1.4656	* 1.3600	* 1.4259	* 1.3788	* 2.0413	*
13	* 1.6464	* 1.5232	* 1.6378	* 1.5044	* 1.6908	* 1.7598	* .7721	*
	* 1.3775	* 1.4903	* 1.3935	* 1.5335	* 1.3790	* 1.3298	* 2.9918	*
14	* 1.2680	* 1.6338	* 1.5698	* 1.6996	* 1.1283	* .7721	*	
	* 1.7801	* 1.3905	* 1.4542	* 1.3540	* 2.0430	* 2.9919	*	
15	* .6703	* .8481	* .7758	* .7061	* F-SUB-Q			
	* 3.3395	* 2.6519	* 2.9028	* 3.2101	* M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 9 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1493	* 1.6869	* 1.5026	* 1.6835	* 1.4940	* 1.6446	* 1.2647	* .6671 *
	* 1.9406	* 1.3179	* 1.4765	* 1.3172	* 1.4811	* 1.3458	* 1.7417	* 3.2761 *
9	* 1.6869	* 1.4702	* 1.7011	* 1.4945	* 1.6852	* 1.5222	* 1.6346	* .8454 *
	* 1.3179	* 1.5100	* 1.3051	* 1.4832	* 1.3190	* 1.4550	* 1.3560	* 2.5958 *
10	* 1.5026	* 1.7002	* 1.3441	* 1.5975	* 1.5608	* 1.6381	* 1.5719	* .7748 *
	* 1.4765	* 1.3057	* 1.6498	* 1.3922	* 1.4296	* 1.3589	* 1.4172	* 2.8359 *
11	* 1.6835	* 1.4927	* 1.5925	* 1.4983	* 1.7128	* 1.5060	* 1.7036	* .7052 *
	* 1.3172	* 1.4842	* 1.3964	* 1.4893	* 1.3229	* 1.4936	* 1.3159	* 3.1336 *
12	* 1.4940	* 1.6839	* 1.5595	* 1.7127	* 1.6440	* 1.6942	* 1.1309	*
	* 1.4811	* 1.3201	* 1.4310	* 1.3229	* 1.3859	* 1.3401	* 1.9847	*
13	* 1.6446	* 1.5216	* 1.6371	* 1.5055	* 1.6939	* 1.7663	* .7711	*
	* 1.3458	* 1.4555	* 1.3597	* 1.4942	* 1.3404	* 1.2890	* 2.9156	*
14	* 1.2647	* 1.6339	* 1.5712	* 1.7029	* 1.1300	* .7711	*	
	* 1.7417	* 1.3565	* 1.4179	* 1.3165	* 1.9863	* 2.9157	*	
15	* .6671	* .8452	* .7744	* .7049	* F-SUB-Q			
	* 3.2761	* 2.5963	* 2.8370	* 3.1351	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 225 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 8 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1341	* 1.6652	* 1.4866	* 1.6627	* 1.4791	* 1.6263	* 1.2534	* .6581
	* 1.9233	* 1.3060	* 1.4600	* 1.3050	* 1.4638	* 1.3316	* 1.7195	* 3.2512
9	* 1.6652	* 1.4535	* 1.6799	* 1.4797	* 1.6673	* 1.5079	* 1.6190	* .8403
	* 1.3060	* 1.4941	* 1.2929	* 1.4662	* 1.3046	* 1.4368	* 1.3389	* 2.5548
10	* 1.4866	* 1.6790	* 1.3410	* 1.5829	* 1.5479	* 1.6209	* 1.5583	* .7769
	* 1.4600	* 1.2936	* 1.6175	* 1.3739	* 1.4099	* 1.3428	* 1.3984	* 2.7662
11	* 1.6627	* 1.4777	* 1.5780	* 1.4850	* 1.6983	* 1.4942	* 1.6899	* .7073
	* 1.3050	* 1.4673	* 1.3780	* 1.4692	* 1.3014	* 1.4694	* 1.2951	* 3.0537
12	* 1.4791	* 1.6660	* 1.5466	* 1.6982	* 1.6341	* 1.6796	* 1.1308	*
	* 1.4638	* 1.3056	* 1.4112	* 1.3015	* 1.3592	* 1.3180	* 1.9367	*
13	* 1.6263	* 1.5073	* 1.6199	* 1.4937	* 1.6792	* 1.7548	* .7639	*
	* 1.3316	* 1.4373	* 1.3435	* 1.4701	* 1.3183	* 1.2638	* 2.8699	*
14	* 1.2534	* 1.6182	* 1.5576	* 1.6891	* 1.1300	* .7639	*	*
	* 1.7195	* 1.3395	* 1.3990	* 1.2957	* 1.9381	* 2.8700	*	*
15	* .6581	* .8401	* .7766	* .7069	* F-SUB-Q			
	* 3.2512	* 2.5553	* 2.7673	* 3.0552	* M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 7 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1380	* 1.6870	* 1.4956	* 1.6846	* 1.4889	* 1.6499	* 1.2603	* .6629
	* 1.8634	* 1.2558	* 1.4144	* 1.2565	* 1.4208	* 1.2840	* 1.6769	* 3.1663
9	* 1.6870	* 1.4605	* 1.7024	* 1.4892	* 1.6908	* 1.5249	* 1.6446	* .8423
	* 1.2558	* 1.4486	* 1.2438	* 1.4222	* 1.2562	* 1.3898	* 1.2908	* 2.4998
10	* 1.4956	* 1.7016	* 1.3354	* 1.5976	* 1.5625	* 1.6449	* 1.5813	* .7671
	* 1.4144	* 1.2444	* 1.5865	* 1.3274	* 1.3627	* 1.2928	* 1.3486	* 2.7473
11	* 1.6846	* 1.4871	* 1.5926	* 1.4988	* 1.7244	* 1.5126	* 1.7184	* .6991
	* 1.2565	* 1.4233	* 1.3315	* 1.4179	* 1.2460	* 1.4179	* 1.2441	* 3.0270
12	* 1.4889	* 1.6895	* 1.5612	* 1.7243	* 1.6541	* 1.7079	* 1.1276	*
	* 1.4208	* 1.2572	* 1.3638	* 1.2461	* 1.3027	* 1.2605	* 1.8956	*
13	* 1.6499	* 1.5243	* 1.6439	* 1.5121	* 1.7075	* 1.7869	* .7711	*
	* 1.2840	* 1.3903	* 1.2936	* 1.4184	* 1.2608	* 1.2076	* 2.7752	*
14	* 1.2603	* 1.6438	* 1.5805	* 1.7176	* 1.1265	* .7711	*	*
	* 1.6769	* 1.2914	* 1.3493	* 1.2447	* 1.8972	* 2.7754	*	*
15	* .6629	* .8421	* .7668	* .6987	* F-SUB-Q			
	* 3.1663	* 2.5002	* 2.7485	* 3.0285	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 226 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 6 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1300	* 1.6799	* 1.4878	* 1.6776	* 1.4819	* 1.6445	* 1.2540	* .6590 *
	* 1.8141	* 1.2227	* 1.3788	* 1.2243	* 1.3854	* 1.2505	* 1.6366	* 3.1038 *
9	* 1.6799	* 1.4523	* 1.6957	* 1.4828	* 1.6861	* 1.5196	* 1.6407	* .8382 *
	* 1.2227	* 1.4125	* 1.2112	* 1.3854	* 1.2219	* 1.3535	* 1.2558	* 2.4450 *
10	* 1.4878	* 1.6949	* 1.3304	* 1.5937	* 1.5587	* 1.6403	* 1.5765	* .7620 *
	* 1.3788	* 1.2118	* 1.5447	* 1.2901	* 1.3235	* 1.2576	* 1.3117	* 2.6913 *
11	* 1.6776	* 1.4808	* 1.5887	* 1.4935	* 1.7211	* 1.5081	* 1.7152	* .6944 *
	* 1.2242	* 1.3873	* 1.2941	* 1.3786	* 1.2063	* 1.3757	* 1.2076	* 2.9612 *
12	* 1.4819	* 1.6847	* 1.5573	* 1.7209	* 1.6520	* 1.7047	* 1.1218	*
	* 1.3854	* 1.2228	* 1.3246	* 1.2064	* 1.2578	* 1.2200	* 1.8451	*
13	* 1.6445	* 1.5190	* 1.6393	* 1.5076	* 1.7044	* 1.7846	* .7665	*
	* 1.2505	* 1.3541	* 1.2583	* 1.3762	* 1.2202	* 1.1682	* 2.7025	*
14	* 1.2540	* 1.6399	* 1.5757	* 1.7144	* 1.1208	* .7665	*	
	* 1.6366	* 1.2564	* 1.3123	* 1.2082	* 1.8467	* 2.7027	*	
15	* .6590	* .8380	* .7616	* .6940	F-SUB-Q			
	* 3.1038	* 2.4455	* 2.6925	* 2.9627	M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 5 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1070	* 1.6363	* 1.4593	* 1.6334	* 1.4537	* 1.6023	* 1.2313	* .6430 *
	* 1.8032	* 1.2231	* 1.3700	* 1.2258	* 1.3770	* 1.2516	* 1.6261	* 3.1056 *
9	* 1.6363	* 1.4253	* 1.6514	* 1.4561	* 1.6451	* 1.4861	* 1.5991	* .8252 *
	* 1.2231	* 1.4024	* 1.2122	* 1.3750	* 1.2204	* 1.3493	* 1.2562	* 2.4235 *
10	* 1.4593	* 1.6506	* 1.3234	* 1.5651	* 1.5317	* 1.5996	* 1.5363	* .7610 *
	* 1.3700	* 1.2127	* 1.5128	* 1.2799	* 1.3115	* 1.2568	* 1.3111	* 2.6295 *
11	* 1.6334	* 1.4542	* 1.5603	* 1.4655	* 1.6800	* 1.4750	* 1.6712	* .6931 *
	* 1.2258	* 1.3768	* 1.2838	* 1.3700	* 1.2015	* 1.3680	* 1.2065	* 2.8930 *
12	* 1.4537	* 1.6438	* 1.5304	* 1.6799	* 1.6220	* 1.6618	* 1.1112	*
	* 1.3770	* 1.2214	* 1.3126	* 1.2016	* 1.2446	* 1.2164	* 1.8128	*
13	* 1.6023	* 1.4855	* 1.5987	* 1.4744	* 1.6615	* 1.7375	* .7467	*
	* 1.2516	* 1.3499	* 1.2575	* 1.3685	* 1.2166	* 1.1655	* 2.6991	*
14	* 1.2313	* 1.5983	* 1.5356	* 1.6704	* 1.1103	* .7467	*	
	* 1.6261	* 1.2568	* 1.3117	* 1.2070	* 1.8142	* 2.6993	*	
15	* .6430	* .8251	* .7606	* .6927	F-SUB-Q			
	* 3.1056	* 2.4239	* 2.6307	* 2.8944	M-SUB-Q			

CNEI-0400-25
Appendix A, Rev. 19
Page 227 of 311

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

	H	G	F	E	D	C	B	A
8	* 1.1077	* 1.6295	* 1.4530	* 1.6236	* 1.4468	* 1.5952	* 1.2234	* .6397
	* 1.7653	* 1.2029	* 1.3479	* 1.2083	* 1.3559	* 1.2320	* 1.6043	* 3.0625
9	* 1.6295	* 1.4209	* 1.6425	* 1.4482	* 1.6370	* 1.4797	* 1.5935	* .8192
	* 1.2029	* 1.3779	* 1.1939	* 1.3546	* 1.2014	* 1.3277	* 1.2349	* 2.3941
10	* 1.4530	* 1.6419	* 1.3053	* 1.5571	* 1.5275	* 1.5950	* 1.5254	* .7462
	* 1.3479	* 1.1944	* 1.5027	* 1.2601	* 1.2875	* 1.2345	* 1.2929	* 2.6296
11	* 1.6236	* 1.4464	* 1.5524	* 1.4530	* 1.6715	* 1.4674	* 1.6596	* .6783
	* 1.2083	* 1.3563	* 1.2639	* 1.3552	* 1.1812	* 1.3450	* 1.1889	* 2.8969
12	* 1.4468	* 1.6358	* 1.5263	* 1.6714	* 1.6194	* 1.6557	* 1.0901	*
	* 1.3559	* 1.2023	* 1.2885	* 1.1813	* 1.2187	* 1.1938	* 1.8085	*
13	* 1.5952	* 1.4791	* 1.5941	* 1.4669	* 1.6554	* 1.7218	* .7413	*
	* 1.2320	* 1.3283	* 1.2352	* 1.3454	* 1.1941	* 1.1492	* 2.6608	*
14	* 1.2234	* 1.5927	* 1.5247	* 1.6588	* 1.0892	* .7412	*	
	* 1.6043	* 1.2355	* 1.2935	* 1.1894	* 1.8100	* 2.6610	*	
15	* .6397	* .8191	* .7458	* .6780	* F-SUB-Q			
	* 3.0625	* 2.3946	* 2.6308	* 2.8984	* M-SUB-Q			

	H	G	F	E	D	C	B	A
8	* 1.0898	* 1.5704	* 1.3969	* 1.5601	* 1.3826	* 1.5375	* 1.1803	* .6128
	* 1.7673	* 1.2289	* 1.3809	* 1.2382	* 1.3974	* 1.2588	* 1.6384	* 3.1528
9	* 1.5704	* 1.3785	* 1.5775	* 1.3886	* 1.5721	* 1.4266	* 1.5344	* .7931
	* 1.2289	* 1.3987	* 1.2239	* 1.3899	* 1.2316	* 1.3561	* 1.2627	* 2.4375
10	* 1.3969	* 1.5773	* 1.2537	* 1.4761	* 1.4661	* 1.5425	* 1.4831	* .7293
	* 1.3809	* 1.2240	* 1.5403	* 1.3092	* 1.3205	* 1.2567	* 1.3074	* 2.6523
11	* 1.5601	* 1.3874	* 1.4720	* 1.3857	* 1.6112	* 1.4144	* 1.5773	* .6566
	* 1.2382	* 1.3911	* 1.3127	* 1.3987	* 1.2054	* 1.3727	* 1.2304	* 2.9487
12	* 1.3826	* 1.5711	* 1.4650	* 1.6112	* 1.5733	* 1.5973	* 1.0419	*
	* 1.3974	* 1.2325	* 1.3215	* 1.2055	* 1.2337	* 1.2170	* 1.8624	*
13	* 1.5375	* 1.4260	* 1.5417	* 1.4139	* 1.5969	* 1.6395	* .7133	*
	* 1.2588	* 1.3567	* 1.2574	* 1.3732	* 1.2172	* 1.1864	* 2.7219	*
14	* 1.1803	* 1.5337	* 1.4824	* 1.5766	* 1.0411	* .7132	*	
	* 1.6384	* 1.2633	* 1.3080	* 1.2310	* 1.8638	* 2.7222	*	
15	* .6128	* .7929	* .7289	* .6563	* F-SUB-Q			
	* 3.1528	* 2.4380	* 2.6536	* 2.9502	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 228 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 100% POWER, 4 EFPD, THIS IS LEVEL 2 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9919	* 1.5219	* 1.1767	* 1.4795	* 1.1699	* 1.4497	* 1.0165	* .5315
	* 1.9226	* 1.2536	* 1.6222	* 1.2916	* 1.6348	* 1.3205	* 1.8828	* 3.6032
9	* 1.5219	* 1.1568	* 1.5257	* 1.1520	* 1.4947	* 1.2549	* 1.4363	* .6943
	* 1.2536	* 1.6497	* 1.2515	* 1.6590	* 1.2810	* 1.5257	* 1.3342	* 2.7580
10	* 1.1767	* 1.5254	* 1.1185	* 1.2469	* 1.2638	* 1.4500	* 1.4245	* .6580
	* 1.6222	* 1.2517	* 1.7064	* 1.5343	* 1.5165	* 1.3222	* 1.3459	* 2.9116
11	* 1.4795	* 1.1517	* 1.2441	* 1.1986	* 1.4968	* 1.2502	* 1.3719	* .5744
	* 1.2916	* 1.6595	* 1.5377	* 1.6000	* 1.2823	* 1.5359	* 1.3996	* 3.3387
12	* 1.1699	* 1.4939	* 1.2631	* 1.4965	* 1.3870	* 1.5454	* .9070	*
	* 1.6348	* 1.2816	* 1.5174	* 1.2825	* 1.3842	* 1.2435	* 2.1171	*
13	* 1.4497	* 1.2543	* 1.4493	* 1.2498	* 1.5451	* 1.4111	* .6270	*
	* 1.3205	* 1.5264	* 1.3228	* 1.5364	* 1.2437	* 1.3629	* 3.0655	*
14	* 1.0165	* 1.4357	* 1.4238	* 1.3713	* .9064	* .6269	*	*
	* 1.8828	* 1.3348	* 1.3465	* 1.4002	* 2.1185	* 3.0660	*	*
15	* .5315	* .6941	* .6576	* .5741	* F-SUB-Q			
	* 3.6032	* 2.7588	* 2.9131	* 3.3404	* M-SUB-Q			

AT 100% POWER, 4 EFPD, THIS IS LEVEL 1 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .7512	* .6436	* .5650	* .6386	* .5595	* .6249	* .4898	* .3768
	* 2.5251	* 2.9482	* 3.3600	* 2.9767	* 3.3995	* 3.0474	* 3.8899	* 5.0616
9	* .6436	* .5603	* .6386	* .5554	* .6425	* .5754	* .5652	* .3342
	* 2.9482	* 3.3879	* 2.9745	* 3.4215	* 2.9643	* 3.3088	* 3.3740	* 5.7090
10	* .5650	* .6389	* .5695	* .5425	* .5713	* .6356	* .5844	* .3257
	* 3.3600	* 2.9733	* 3.3354	* 3.5104	* 3.3388	* 3.0000	* 3.2641	* 5.8578
11	* .6386	* .5554	* .5421	* .5819	* .6541	* .5757	* .5362	* .2863
	* 2.9767	* 3.4213	* 3.5131	* 3.2788	* 2.9184	* 3.3172	* 3.5615	* 6.6726
12	* .5595	* .6422	* .5711	* .6540	* .6125	* .6128	* .4299	*
	* 3.3995	* 2.9657	* 3.3403	* 2.9188	* 3.1174	* 3.1191	* 4.4469	*
13	* .6249	* .5752	* .6353	* .5756	* .6127	* .5559	* .4466	*
	* 3.0474	* 3.3098	* 3.0014	* 3.3180	* 3.1197	* 3.4405	* 4.2845	*
14	* .4898	* .5649	* .5841	* .5359	* .4300	* .4465	*	*
	* 3.8899	* 3.3756	* 3.2657	* 3.5631	* 4.4459	* 4.2856	*	*
15	* .3768	* .3340	* .3256	* .2862	* F-SUB-Q			
	* 5.0616	* 5.7114	* 5.8606	* 6.6759	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 229 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 24 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .7829 *	* .6625 *	* .5957 *	* .6648 *	* .5883 *	* .6337 *	* .5161 *	* .4290 *
	* 2.7650 *	* 3.4309 *	* 3.6256 *	* 3.1756 *	* 3.5719 *	* 3.2694 *	* 3.9891 *	* 4.7324 *
9	* .6625 *	* .6046 *	* .6668 *	* .5912 *	* .6533 *	* .5879 *	* .5624 *	* .3622 *
	* 3.4309 *	* 3.6931 *	* 3.2473 *	* 3.6019 *	* 3.2160 *	* 3.5414 *	* 3.7125 *	* 5.6969 *
10	* .5957 *	* .6673 *	* .6106 *	* .5678 *	* .5776 *	* .6323 *	* .5765 *	* .3461 *
	* 3.6256 *	* 3.2472 *	* 3.5675 *	* 3.8042 *	* 3.7009 *	* 3.3999 *	* 3.6819 *	* 5.9977 *
11	* .6648 *	* .5913 *	* .5669 *	* .5379 *	* .6191 *	* .5670 *	* .5241 *	* .3060 *
	* 3.1756 *	* 3.6013 *	* 3.8106 *	* 4.0168 *	* 3.5984 *	* 4.0392 *	* 4.2252 *	* 7.0125 *
12	* .5883 *	* .6532 *	* .5775 *	* .6189 *	* .5462 *	* .5436 *	* .4208 *	
	* 3.5719 *	* 3.2166 *	* 3.7015 *	* 3.5987 *	* 3.8087 *	* 3.8502 *	* 5.3036 *	
13	* .6337 *	* .5879 *	* .6322 *	* .5669 *	* .5436 *	* .4899 *	* .4569 *	
	* 3.2694 *	* 3.5418 *	* 3.4003 *	* 4.0395 *	* 3.8504 *	* 4.2363 *	* 4.7565 *	
14	* .5161 *	* .5627 *	* .5766 *	* .5241 *	* .4210 *	* .4568 *		
	* 3.9891 *	* 3.7107 *	* 3.6815 *	* 4.2254 *	* 5.3009 *	* 4.7582 *		
15	* .4290 *	* .3623 *	* .3462 *	* .3060 *	F-SUB-Q			
	* 4.7324 *	* 5.6925 *	* 5.9954 *	* 7.0123 *	M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 23 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.0232 *	* 1.4742 *	* 1.1831 *	* 1.4361 *	* 1.1633 *	* 1.3729 *	* 1.0227 *	* .5778 *
	* 2.2022 *	* 1.6179 *	* 1.8802 *	* 1.5191 *	* 1.8535 *	* 1.5569 *	* 2.0784 *	* 3.6153 *
9	* 1.4742 *	* 1.1867 *	* 1.4859 *	* 1.1687 *	* 1.4148 *	* 1.2007 *	* 1.3360 *	* .7368 *
	* 1.6179 *	* 1.9160 *	* 1.5033 *	* 1.8778 *	* 1.5291 *	* 1.7872 *	* 1.6108 *	* 2.8727 *
10	* 1.1831 *	* 1.4856 *	* 1.1732 *	* 1.2135 *	* 1.2217 *	* 1.3508 *	* 1.3168 *	* .7037 *
	* 1.8802 *	* 1.5040 *	* 1.9028 *	* 1.8334 *	* 1.8211 *	* 1.6400 *	* 1.6568 *	* 3.0268 *
11	* 1.4361 *	* 1.1684 *	* 1.2109 *	* 1.1083 *	* 1.3410 *	* 1.1581 *	* 1.2449 *	* .6185 *
	* 1.5191 *	* 1.8785 *	* 1.8373 *	* 2.0698 *	* 1.7099 *	* 2.0015 *	* 1.8380 *	* 3.5685 *
12	* 1.1633 *	* 1.4144 *	* 1.2211 *	* 1.3407 *	* 1.1959 *	* 1.3379 *	* .8648 *	
	* 1.8535 *	* 1.5294 *	* 1.8217 *	* 1.7100 *	* 1.8188 *	* 1.6593 *	* 2.6500 *	
13	* 1.3729 *	* 1.2006 *	* 1.3506 *	* 1.1579 *	* 1.3378 *	* 1.2087 *	* .6125 *	
	* 1.5569 *	* 1.7872 *	* 1.6402 *	* 2.0016 *	* 1.6594 *	* 1.8185 *	* 3.6488 *	
14	* 1.0227 *	* 1.3364 *	* 1.3169 *	* 1.2448 *	* .8646 *	* .6125 *		
	* 2.0784 *	* 1.6103 *	* 1.6567 *	* 1.8382 *	* 2.6505 *	* 3.6491 *		
15	* .5778 *	* .7371 *	* .7039 *	* .6185 *	F-SUB-Q			
	* 3.6153 *	* 2.8713 *	* 3.0260 *	* 3.5685 *	M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 230 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 22 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1782	* 1.5190	* 1.3766	* 1.5025	* 1.3393	* 1.4463	* 1.1529	* .6561
	* 2.0467	* 1.5703	* 1.6509	* 1.4845	* 1.6385	* 1.5052	* 1.8736	* 3.2232
9	* 1.5190	* 1.3743	* 1.5221	* 1.3627	* 1.4821	* 1.3639	* 1.4241	* .8245
	* 1.5703	* 1.6985	* 1.4942	* 1.6406	* 1.4905	* 1.6031	* 1.5337	* 2.6078
10	* 1.3766	* 1.5218	* 1.3097	* 1.4438	* 1.4170	* 1.4388	* 1.3757	* .7800
	* 1.6509	* 1.4961	* 1.7313	* 1.5741	* 1.6071	* 1.5663	* 1.6163	* 2.7800
11	* 1.5025	* 1.3615	* 1.4401	* 1.3074	* 1.4489	* 1.3184	* 1.4259	* .7001
	* 1.4845	* 1.6415	* 1.5781	* 1.8130	* 1.6202	* 1.7983	* 1.6504	* 3.2246
12	* 1.3393	* 1.4813	* 1.4160	* 1.4489	* 1.4234	* 1.4217	* 1.0099	*
	* 1.6385	* 1.4908	* 1.6081	* 1.6202	* 1.6323	* 1.6329	* 2.3227	*
13	* 1.4463	* 1.3637	* 1.4384	* 1.3182	* 1.4216	* 1.4200	* .6927	*
	* 1.5052	* 1.6034	* 1.5667	* 1.7985	* 1.6330	* 1.6104	* 3.3115	*
14	* 1.1529	* 1.4243	* 1.3757	* 1.4258	* 1.0096	* .6927	*	*
	* 1.8736	* 1.5335	* 1.6163	* 1.6505	* 2.3232	* 3.3115	*	*
15	* .6561	* .8248	* .7802	* .7001	* F-SUB-Q			
	* 3.2232	* 2.6070	* 2.7796	* 3.2248	* M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 21 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2343	* 1.6369	* 1.4990	* 1.6184	* 1.4557	* 1.5555	* 1.2514	* .6959
	* 2.0229	* 1.4910	* 1.5484	* 1.4080	* 1.5385	* 1.4281	* 1.7515	* 3.0900
9	* 1.6369	* 1.4946	* 1.6415	* 1.4929	* 1.6029	* 1.4600	* 1.5322	* .8578
	* 1.4910	* 1.5955	* 1.4078	* 1.5324	* 1.4138	* 1.5268	* 1.4511	* 2.5569
10	* 1.4990	* 1.6410	* 1.3762	* 1.5636	* 1.5189	* 1.5429	* 1.4634	* .7951
	* 1.5484	* 1.4100	* 1.6827	* 1.4803	* 1.5356	* 1.4945	* 1.5538	* 2.7862
11	* 1.6184	* 1.4897	* 1.5593	* 1.4364	* 1.5766	* 1.4161	* 1.5563	* .7191
	* 1.4080	* 1.5341	* 1.4844	* 1.6796	* 1.5381	* 1.7163	* 1.5489	* 3.2066
12	* 1.4557	* 1.6017	* 1.5177	* 1.5757	* 1.5273	* 1.5432	* 1.0758	*
	* 1.5385	* 1.4142	* 1.5368	* 1.5382	* 1.5674	* 1.5496	* 2.2352	*
13	* 1.5555	* 1.4597	* 1.5423	* 1.4158	* 1.5431	* 1.5636	* .7385	*
	* 1.4281	* 1.5271	* 1.4950	* 1.7166	* 1.5498	* 1.5059	* 3.1926	*
14	* 1.2514	* 1.5322	* 1.4633	* 1.5561	* 1.0754	* .7385	*	*
	* 1.7515	* 1.4510	* 1.5540	* 1.5491	* 2.2361	* 3.1926	*	*
15	* .6959	* .8580	* .7952	* .7190	* F-SUB-Q			
	* 3.0900	* 2.5564	* 2.7860	* 3.2070	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 231 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 20 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2372	* 1.6787	* 1.5242	* 1.6618	* 1.5011	* 1.5987	* 1.2751	* .6969 *
	* 2.0826	* 1.4955	* 1.5657	* 1.4060	* 1.5305	* 1.4246	* 1.7639	* 3.1691 *
9	* 1.6787	* 1.5178	* 1.6845	* 1.5176	* 1.6474	* 1.4933	* 1.5742	* .8635 *
	* 1.4955	* 1.6198	* 1.4092	* 1.5482	* 1.4104	* 1.5294	* 1.4482	* 2.6031 *
10	* 1.5242	* 1.6839	* 1.3903	* 1.5940	* 1.5461	* 1.5838	* 1.5054	* .8005 *
	* 1.5657	* 1.4115	* 1.7093	* 1.4923	* 1.5482	* 1.4911	* 1.5455	* 2.8327 *
11	* 1.6618	* 1.5157	* 1.5893	* 1.4767	* 1.6237	* 1.4535	* 1.6088	* .7247 *
	* 1.4060	* 1.5494	* 1.4967	* 1.6807	* 1.5329	* 1.7183	* 1.5349	* 3.2574 *
12	* 1.5011	* 1.6462	* 1.5448	* 1.6233	* 1.5670	* 1.5947	* 1.1047	* .7518 *
	* 1.5305	* 1.4108	* 1.5495	* 1.5330	* 1.5738	* 1.5446	* 2.2394	* .7518 *
13	* 1.5987	* 1.4929	* 1.5832	* 1.4532	* 1.5945	* 1.6290	* 1.4894	* 3.2332 *
	* 1.4246	* 1.5298	* 1.4917	* 1.7185	* 1.5448	* 1.4894	* 3.2332 *	
14	* 1.2751	* 1.5741	* 1.5051	* 1.6085	* 1.1041	* .7518		
	* 1.7639	* 1.4483	* 1.5458	* 1.5352	* 2.2405	* 3.2332		
15	* .6969	* .8636	* .8005	* .7246	* F-SUB-Q			
	* 3.1691	* 2.6028	* 2.8328	* 3.2580	* M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 19 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2325	* 1.6869	* 1.5271	* 1.6719	* 1.5080	* 1.6113	* 1.2773	* .6930 *
	* 2.1455	* 1.5325	* 1.6067	* 1.4328	* 1.5645	* 1.4501	* 1.8021	* 3.2582 *
9	* 1.6869	* 1.5166	* 1.6935	* 1.5189	* 1.6583	* 1.5035	* 1.5888	* .8619 *
	* 1.5324	* 1.6703	* 1.4410	* 1.5871	* 1.4370	* 1.5584	* 1.4711	* 2.6737 *
10	* 1.5271	* 1.6929	* 1.3923	* 1.5974	* 1.5511	* 1.5969	* 1.5214	* .8034 *
	* 1.6067	* 1.4434	* 1.7549	* 1.5300	* 1.5862	* 1.5204	* 1.5717	* 2.8987 *
11	* 1.6719	* 1.5177	* 1.5926	* 1.4842	* 1.6434	* 1.4675	* 1.6296	* .7269 *
	* 1.4328	* 1.5877	* 1.5345	* 1.7183	* 1.5579	* 1.7488	* 1.5627	* 3.3498 *
12	* 1.5080	* 1.6569	* 1.5498	* 1.6433	* 1.5837	* 1.6158	* 1.1195	* .7578 *
	* 1.5645	* 1.4374	* 1.5875	* 1.5580	* 1.6036	* 1.5716	* 2.2739	* .7578 *
13	* 1.6113	* 1.5031	* 1.5962	* 1.4671	* 1.6155	* 1.6589	* 1.5129	* 3.3178 *
	* 1.4501	* 1.5588	* 1.5210	* 1.7492	* 1.5718	* 1.5129	* 3.3178 *	
14	* 1.2773	* 1.5886	* 1.5210	* 1.6292	* 1.1190	* .7578		
	* 1.8021	* 1.4713	* 1.5720	* 1.5630	* 2.2749	* 3.3179		
15	* .6930	* .8619	* .8034	* .7267	* F-SUB-Q			
	* 3.2582	* 2.6735	* 2.8989	* 3.3506	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 232 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 18 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2309	* 1.7045	* 1.5355	* 1.6909	* 1.5183	* 1.6331	* 1.2844	* .6942 *
	* 2.1978	* 1.5717	* 1.6573	* 1.4684	* 1.6125	* 1.4834	* 1.8561	* 3.3724 *
9	* 1.7045	* 1.5213	* 1.7119	* 1.5269	* 1.6785	* 1.5205	* 1.6121	* .8661 *
	* 1.5717	* 1.7267	* 1.4785	* 1.6375	* 1.4717	* 1.5978	* 1.5029	* 2.7576 *
10	* 1.5355	* 1.7113	* 1.3903	* 1.6083	* 1.5637	* 1.6199	* 1.5446	* .8009 *
	* 1.6573	* 1.4811	* 1.8241	* 1.5774	* 1.6348	* 1.5560	* 1.6063	* 3.0165 *
11	* 1.6909	* 1.5256	* 1.6034	* 1.4958	* 1.6710	* 1.4881	* 1.6589	* .7267 *
	* 1.4684	* 1.6381	* 1.5822	* 1.7721	* 1.5793	* 1.7742	* 1.5799	* 3.4845 *
12	* 1.5183	* 1.6771	* 1.5623	* 1.6709	* 1.6066	* 1.6458	* 1.1274	*
	* 1.6125	* 1.4721	* 1.6363	* 1.5793	* 1.6292	* 1.5898	* 2.3275	*
13	* 1.6331	* 1.5201	* 1.6191	* 1.4876	* 1.6456	* 1.6953	* .7687	*
	* 1.4834	* 1.5982	* 1.5567	* 1.7747	* 1.5900	* 1.5248	* 3.3713	*
14	* 1.2844	* 1.6118	* 1.5442	* 1.6585	* 1.1267	* .7687	*	
	* 1.8561	* 1.5031	* 1.6068	* 1.5803	* 2.3289	* 3.3714	*	
15	* .6942	* .8661	* .8008	* .7265	* F-SUB-Q			
	* 3.3724	* 2.7575	* 3.0169	* 3.4854	* M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 17 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2126	* 1.7054	* 1.5338	* 1.6936	* 1.5184	* 1.6392	* 1.2838	* .6866 *
	* 2.2884	* 1.6322	* 1.7389	* 1.5347	* 1.6897	* 1.5471	* 1.9421	* 3.5687 *
9	* 1.7054	* 1.5164	* 1.7138	* 1.5250	* 1.6830	* 1.5250	* 1.6201	* .8606 *
	* 1.6322	* 1.8156	* 1.5478	* 1.7176	* 1.5368	* 1.6678	* 1.5647	* 2.9022 *
10	* 1.5338	* 1.7132	* 1.3836	* 1.6087	* 1.5659	* 1.6271	* 1.5529	* .7963 *
	* 1.7389	* 1.5505	* 1.9230	* 1.6546	* 1.7127	* 1.6229	* 1.6726	* 3.1746 *
11	* 1.6936	* 1.5237	* 1.6036	* 1.4985	* 1.6825	* 1.4956	* 1.6717	* .7223 *
	* 1.5347	* 1.7183	* 1.6599	* 1.8334	* 1.6086	* 1.8089	* 1.6102	* 3.6743 *
12	* 1.5184	* 1.6816	* 1.5644	* 1.6824	* 1.6174	* 1.6591	* 1.1315	*
	* 1.6897	* 1.5373	* 1.7143	* 1.6087	* 1.6630	* 1.6212	* 2.3742	*
13	* 1.6392	* 1.5245	* 1.6263	* 1.4951	* 1.6588	* 1.7134	* .7681	*
	* 1.5471	* 1.6683	* 1.6236	* 1.8094	* 1.6215	* 1.5565	* 3.4739	*
14	* 1.2838	* 1.6197	* 1.5525	* 1.6712	* 1.1307	* .7681	*	
	* 1.9421	* 1.5650	* 1.6731	* 1.6107	* 2.3757	* 3.4739	*	
15	* .6866	* .8606	* .7962	* .7221	* F-SUB-Q			
	* 3.5687	* 2.9022	* 3.1752	* 3.6754	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 233 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 16 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2077	* 1.7098	* 1.5335	* 1.6999	* 1.5201	* 1.6483	* 1.2844	* .6868 *
	* 2.3999	* 1.6906	* 1.8395	* 1.6147	* 1.7842	* 1.6242	* 2.0471	* 3.7627 *
9	* 1.7098	* 1.5132	* 1.7194	* 1.5251	* 1.6912	* 1.5311	* 1.6301	* .8598 *
	* 1.6906	* 1.9107	* 1.6313	* 1.8157	* 1.6154	* 1.7537	* 1.6402	* 3.0621 *
10	* 1.5335	* 1.7187	* 1.3782	* 1.6128	* 1.5707	* 1.6374	* 1.5628	* .7920 *
	* 1.8395	* 1.6341	* 2.0443	* 1.7477	* 1.8071	* 1.7035	* 1.7537	* 3.3653 *
11	* 1.6999	* 1.5239	* 1.6077	* 1.5035	* 1.6966	* 1.5044	* 1.6859	* .7192 *
	* 1.6147	* 1.8164	* 1.7533	* 1.9018	* 1.6602	* 1.8674	* 1.6579	* 3.8520 *
12	* 1.5201	* 1.6897	* 1.5692	* 1.6965	* 1.6295	* 1.6744	* 1.1332	*
	* 1.7842	* 1.6159	* 1.8089	* 1.6603	* 1.7207	* 1.6697	* 2.4598	*
13	* 1.6483	* 1.5306	* 1.6366	* 1.5039	* 1.6741	* 1.7320	* .7729	*
	* 1.6242	* 1.7542	* 1.7043	* 1.8679	* 1.6699	* 1.5968	* 3.5774	*
14	* 1.2844	* 1.6297	* 1.5623	* 1.6854	* 1.1324	* .7729	*	
	* 2.0471	* 1.6405	* 1.7543	* 1.6584	* 2.4615	* 3.5775	*	
15	* .6868	* .8598	* .7919	* .7189	* F-SUB-Q			
	* 3.7627	* 3.0622	* 3.3660	* 3.8532	* M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 15 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1782	* 1.6759	* 1.5093	* 1.6682	* 1.4978	* 1.6203	* 1.2668	* .6708 *
	* 2.5650	* 1.7981	* 1.9929	* 1.7508	* 1.9292	* 1.7574	* 2.2052	* 4.0888 *
9	* 1.6759	* 1.4873	* 1.6865	* 1.5017	* 1.6618	* 1.5088	* 1.6052	* .8492 *
	* 1.7981	* 2.0258	* 1.7723	* 1.9649	* 1.7495	* 1.8936	* 1.7693	* 3.2903 *
10	* 1.5093	* 1.6858	* 1.3703	* 1.5900	* 1.5501	* 1.6113	* 1.5406	* .7920 *
	* 1.9929	* 1.7754	* 2.1883	* 1.8772	* 1.9140	* 1.8269	* 1.8895	* 3.5722 *
11	* 1.6682	* 1.5005	* 1.5850	* 1.4846	* 1.6742	* 1.4840	* 1.6626	* .7193 *
	* 1.7508	* 1.9656	* 1.8831	* 2.0092	* 1.7672	* 1.9839	* 1.7507	* 4.0084 *
12	* 1.4978	* 1.6605	* 1.5485	* 1.6742	* 1.6134	* 1.6517	* 1.1320	*
	* 1.9292	* 1.7500	* 1.9158	* 1.7673	* 1.8272	* 1.7769	* 2.5810	*
13	* 1.6203	* 1.5083	* 1.6104	* 1.4834	* 1.6514	* 1.7117	* .7615	*
	* 1.7574	* 1.8942	* 1.8278	* 1.9844	* 1.7772	* 1.6946	* 3.8055	*
14	* 1.2668	* 1.6048	* 1.5401	* 1.6621	* 1.1313	* .7614	*	
	* 2.2052	* 1.7698	* 1.8901	* 1.7512	* 2.5824	* 3.8056	*	
15	* .6708	* .8491	* .7918	* .7190	* F-SUB-Q			
	* 4.0888	* 3.2906	* 3.5731	* 4.0097	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 234 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 14 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1773	* 1.6917	* 1.5141	* 1.6854	* 1.5047	* 1.6402	* 1.2713	* .6741 *
	* 2.6016	* 1.8041	* 2.0128	* 1.8066	* 2.0200	* 1.8536	* 2.3441	* 4.3360 *
9	* 1.6917	* 1.4894	* 1.7036	* 1.5070	* 1.6817	* 1.5227	* 1.6255	* .8482 *
	* 1.8041	* 2.0482	* 1.7888	* 2.0194	* 1.8123	* 1.9977	* 1.8631	* 3.5082 *
10	* 1.5141	* 1.7026	* 1.3600	* 1.6009	* 1.5616	* 1.6320	* 1.5608	* .7811 *
	* 2.0128	* 1.7897	* 2.2417	* 1.9047	* 1.9560	* 1.8731	* 1.9590	* 3.8572 *
11	* 1.6854	* 1.5058	* 1.5958	* 1.4963	* 1.6981	* 1.5003	* 1.6875	* .7101 *
	* 1.8066	* 2.0211	* 1.9107	* 2.0457	* 1.8123	* 2.0452	* 1.8078	* 4.2582 *
12	* 1.5047	* 1.6804	* 1.5601	* 1.6980	* 1.6319	* 1.6776	* 1.1294	*
	* 2.0200	* 1.8140	* 1.9580	* 1.8124	* 1.8876	* 1.8358	* 2.7083	*
13	* 1.6402	* 1.5221	* 1.6311	* 1.4998	* 1.6773	* 1.7409	* .7691	*
	* 1.8536	* 1.9984	* 1.8742	* 2.0461	* 1.8362	* 1.7551	* 3.9596	*
14	* 1.2713	* 1.6249	* 1.5602	* 1.6869	* 1.1286	* .7691	*	
	* 2.3441	* 1.8636	* 1.9597	* 1.8084	* 2.7103	* 3.9597	*	
15	* .6741	* .8481	* .7808	* .7098	* F-SUB-Q			
	* 4.3360	* 3.5085	* 3.8582	* 4.2597	* M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 13 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1586	* 1.6791	* 1.5014	* 1.6744	* 1.4939	* 1.6325	* 1.2623	* .6661 *
	* 2.6670	* 1.8348	* 2.0493	* 1.8350	* 2.0518	* 1.8776	* 2.4249	* 4.5895 *
9	* 1.6791	* 1.4744	* 1.6920	* 1.4945	* 1.6740	* 1.5151	* 1.6198	* .8410 *
	* 1.8348	* 2.0886	* 1.8179	* 2.0546	* 1.8386	* 2.0244	* 1.8973	* 3.6478 *
10	* 1.5014	* 1.6911	* 1.3484	* 1.5912	* 1.5538	* 1.6256	* 1.5565	* .7746 *
	* 2.0493	* 1.8189	* 2.2824	* 1.9344	* 1.9842	* 1.8973	* 1.9847	* 3.9691 *
11	* 1.6744	* 1.4933	* 1.5861	* 1.4885	* 1.6947	* 1.4951	* 1.6848	* .7047 *
	* 1.8350	* 2.0562	* 1.9407	* 2.0739	* 1.8387	* 2.0751	* 1.8397	* 4.3866 *
12	* 1.4939	* 1.6727	* 1.5525	* 1.6946	* 1.6292	* 1.6753	* 1.1253	*
	* 2.0518	* 1.8402	* 1.9862	* 1.8388	* 1.9162	* 1.8641	* 2.7672	*
13	* 1.6325	* 1.5145	* 1.6246	* 1.4945	* 1.6749	* 1.7415	* .7642	*
	* 1.8776	* 2.0252	* 1.8984	* 2.0760	* 1.8644	* 1.7970	* 4.0907	*
14	* 1.2623	* 1.6192	* 1.5559	* 1.6841	* 1.1245	* .7641	*	
	* 2.4249	* 1.8980	* 1.9856	* 1.8405	* 2.7694	* 4.0910	*	
15	* .6661	* .8409	* .7743	* .7044	* F-SUB-Q			
	* 4.5895	* 3.6484	* 3.9704	* 4.3885	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 235 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 12 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1329	* 1.6427	* 1.4734	* 1.6398	* 1.4678	* 1.6018	* 1.2420	* .6527 *
	* 2.7536	* 1.8936	* 2.1075	* 1.8919	* 2.1079	* 1.9299	* 2.4783	* 4.6901 *
9	* 1.6427	* 1.4452	* 1.6564	* 1.4675	* 1.6433	* 1.4896	* 1.5925	* .8283 *
	* 1.8936	* 2.1506	* 1.8749	* 2.1133	* 1.8928	* 2.0788	* 1.9482	* 3.7317 *
10	* 1.4734	* 1.6555	* 1.3340	* 1.5638	* 1.5296	* 1.5965	* 1.5319	* .7707 *
	* 2.1075	* 1.8759	* 2.3291	* 1.9878	* 2.0369	* 1.9503	* 2.0362	* 4.0192 *
11	* 1.6398	* 1.4660	* 1.5588	* 1.4635	* 1.6684	* 1.4724	* 1.6587	* .7010 *
	* 1.8919	* 2.1149	* 1.9941	* 2.1320	* 1.8893	* 2.1315	* 1.8885	* 4.4485 *
12	* 1.4678	* 1.6419	* 1.5283	* 1.6683	* 1.6080	* 1.6492	* 1.1188	*
	* 2.1079	* 1.8944	* 2.0390	* 1.8894	* 1.9647	* 1.9162	* 2.8145	*
13	* 1.6018	* 1.4890	* 1.5955	* 1.4720	* 1.6488	* 1.7179	* .7522	*
	* 1.9299	* 2.0796	* 1.9514	* 2.1324	* 1.9166	* 1.8446	* 4.2048	*
14	* 1.2420	* 1.5919	* 1.5312	* 1.6580	* 1.1181	* .7521	*	
	* 2.4783	* 1.9489	* 2.0371	* 1.8893	* 2.8164	* 4.2051	*	
15	* .6527	* .8282	* .7704	* .7007	F-SUB-Q			
	* 4.6901	* 3.7324	* 4.0206	* 4.4505	M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 11 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1246	* 1.6475	* 1.4689	* 1.6456	* 1.4652	* 1.6110	* 1.2395	* .6520 *
	* 2.6766	* 1.8284	* 2.0448	* 1.8243	* 2.0436	* 1.8612	* 2.4057	* 4.5238 *
9	* 1.6475	* 1.4385	* 1.6622	* 1.4640	* 1.6517	* 1.4936	* 1.6035	* .8267 *
	* 1.8284	* 2.0888	* 1.8096	* 2.0504	* 1.8281	* 2.0118	* 1.8812	* 3.5946 *
10	* 1.4689	* 1.6613	* 1.3165	* 1.5633	* 1.5310	* 1.6065	* 1.5431	* .7582 *
	* 2.0448	* 1.8106	* 2.2819	* 1.9331	* 1.9843	* 1.8864	* 1.9676	* 3.9254 *
11	* 1.6456	* 1.4619	* 1.5582	* 1.4643	* 1.6807	* 1.4798	* 1.6740	* .6912 *
	* 1.8243	* 2.0519	* 1.9391	* 2.0748	* 1.8401	* 2.0733	* 1.8325	* 4.3480 *
12	* 1.4652	* 1.6503	* 1.5296	* 1.6806	* 1.6153	* 1.6645	* 1.1104	*
	* 2.0436	* 1.8297	* 1.9862	* 1.8402	* 1.9278	* 1.8627	* 2.7540	*
13	* 1.6110	* 1.4930	* 1.6056	* 1.4793	* 1.6642	* 1.7376	* .7564	*
	* 1.8612	* 2.0126	* 1.8875	* 2.0742	* 1.8631	* 1.7932	* 4.0398	*
14	* 1.2395	* 1.6028	* 1.5424	* 1.6733	* 1.1095	* .7564	*	
	* 2.4057	* 1.8819	* 1.9684	* 1.8333	* 2.7562	* 4.0400	*	
15	* .6520	* .8265	* .7579	* .6908	F-SUB-Q			
	* 4.5238	* 3.5952	* 3.9269	* 4.3499	M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 236 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 10 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1016	* 1.6317	* 1.4515	* 1.6310	* 1.4493	* 1.5999	* 1.2269	* .6415 *
	* 2.4983	* 1.6904	* 1.8951	* 1.6892	* 1.8991	* 1.7251	* 2.2345	* 4.2250 *
9	* 1.6317	* 1.4195	* 1.6472	* 1.4477	* 1.6397	* 1.4822	* 1.5951	* .8167 *
	* 1.6904	* 1.9376	* 1.6740	* 1.9032	* 1.6917	* 1.8651	* 1.7387	* 3.3492 *
10	* 1.4515	* 1.6463	* 1.2968	* 1.5476	* 1.5176	* 1.5964	* 1.5361	* .7471 *
	* 1.8951	* 1.6748	* 2.1229	* 1.7891	* 1.8349	* 1.7419	* 1.8172	* 3.6652 *
11	* 1.6310	* 1.4456	* 1.5425	* 1.4509	* 1.6726	* 1.4714	* 1.6685	* .6812 *
	* 1.6892	* 1.9046	* 1.7946	* 1.9154	* 1.6982	* 1.9167	* 1.6883	* 4.0497 *
12	* 1.4493	* 1.6384	* 1.5163	* 1.6725	* 1.6068	* 1.6585	* 1.1001	* .7489 *
	* 1.8991	* 1.6932	* 1.8367	* 1.6983	* 1.7795	* 1.7176	* 2.5552	* .7489 *
13	* 1.5999	* 1.4816	* 1.5954	* 1.4708	* 1.6581	* 1.7353	* .7489	* .7489 *
	* 1.7251	* 1.8658	* 1.7430	* 1.9176	* 1.7180	* 1.6491	* 3.7507	* .7489 *
14	* 1.2269	* 1.5944	* 1.5354	* 1.6678	* 1.0992	* .7489	* .7489	* .7489 *
	* 2.2345	* 1.7394	* 1.8180	* 1.6891	* 2.5573	* 3.7509	* .7489	* .7489 *
15	* .6415	* .8165	* .7468	* .6809	* F-SUB-Q			
	* 4.2250	* 3.3498	* 3.6667	* 4.0516	* M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 9 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.0809	* 1.6059	* 1.4277	* 1.6062	* 1.4270	* 1.5780	* 1.2088	* .6313 *
	* 2.3515	* 1.5873	* 1.7807	* 1.5861	* 1.7800	* 1.6135	* 2.0937	* 3.9677 *
9	* 1.6059	* 1.3948	* 1.6219	* 1.4249	* 1.6175	* 1.4619	* 1.5756	* .8045 *
	* 1.5873	* 1.8219	* 1.5718	* 1.7884	* 1.5875	* 1.7466	* 1.6297	* 3.1447 *
10	* 1.4277	* 1.6210	* 1.2789	* 1.5249	* 1.4970	* 1.5756	* 1.5182	* .7373 *
	* 1.7807	* 1.5726	* 1.9909	* 1.6773	* 1.7202	* 1.6333	* 1.7039	* 3.4439 *
11	* 1.6062	* 1.4229	* 1.5200	* 1.4326	* 1.6535	* 1.4537	* 1.6502	* .6722 *
	* 1.5861	* 1.7897	* 1.6825	* 1.7941	* 1.5849	* 1.7925	* 1.5772	* 3.8002 *
12	* 1.4270	* 1.6161	* 1.4956	* 1.6534	* 1.5890	* 1.6402	* 1.0883	* .7391 *
	* 1.7800	* 1.5888	* 1.7219	* 1.5850	* 1.6602	* 1.6041	* 2.3863	* .7391 *
13	* 1.5780	* 1.4613	* 1.5746	* 1.4532	* 1.6399	* 1.7189	* .7391	* .7391 *
	* 1.6135	* 1.7473	* 1.6343	* 1.7934	* 1.6045	* 1.5392	* 3.5161	* .7391 *
14	* 1.2088	* 1.5749	* 1.5175	* 1.6494	* 1.0874	* .7391	* .7391	* .7391 *
	* 2.0937	* 1.6304	* 1.7047	* 1.5779	* 2.3883	* 3.5163	* .7391	* .7391 *
15	* .6313	* .8044	* .7370	* .6719	* F-SUB-Q			
	* 3.9677	* 3.1453	* 3.4454	* 3.8021	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 237 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 8 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.0542	* 1.5656	* 1.3951	* 1.5668	* 1.3954	* 1.5413	* 1.1838	* .6158 *
	* 2.2421	* 1.5137	* 1.6918	* 1.5077	* 1.6892	* 1.5350	* 1.9882	* 3.7862 *
9	* 1.5656	* 1.3621	* 1.5817	* 1.3934	* 1.5803	* 1.4302	* 1.5417	* .7907 *
	* 1.5137	* 1.7339	* 1.4957	* 1.6956	* 1.5082	* 1.6573	* 1.5464	* 2.9735 *
10	* 1.3951	* 1.5809	* 1.2603	* 1.4919	* 1.4658	* 1.5398	* 1.4864	* .7310 *
	* 1.6918	* 1.4964	* 1.8744	* 1.5913	* 1.6344	* 1.5553	* 1.6195	* 3.2249 *
11	* 1.5668	* 1.3914	* 1.4871	* 1.4053	* 1.6188	* 1.4242	* 1.6160	* .6666 *
	* 1.5077	* 1.6968	* 1.5962	* 1.7065	* 1.5048	* 1.7028	* 1.5002	* 3.5766 *
12	* 1.3954	* 1.5790	* 1.4645	* 1.6187	* 1.5593	* 1.6055	* 1.0751	*
	* 1.6892	* 1.5095	* 1.6360	* 1.5048	* 1.5710	* 1.5229	* 2.2484	*
13	* 1.5413	* 1.4296	* 1.5388	* 1.4237	* 1.6052	* 1.6856	* .7237	*
	* 1.5350	* 1.6580	* 1.5562	* 1.7036	* 1.5233	* 1.4573	* 3.3406	*
14	* 1.1838	* 1.5410	* 1.4857	* 1.6152	* 1.0743	* .7236	*	
	* 1.9882	* 1.5471	* 1.6203	* 1.5009	* 2.2501	* 3.3408	*	
15	* .6158	* .7905	* .7307	* .6662	* F-SUB-Q			
	* 3.7862	* 2.9742	* 3.2263	* 3.5784	* M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 7 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.0458	* 1.5670	* 1.3865	* 1.5683	* 1.3877	* 1.5449	* 1.1763	* .6136 *
	* 2.1017	* 1.4097	* 1.5876	* 1.4077	* 1.5898	* 1.4347	* 1.8757	* 3.5659 *
9	* 1.5670	* 1.3523	* 1.5836	* 1.3851	* 1.5831	* 1.4287	* 1.5461	* .7838 *
	* 1.4097	* 1.6275	* 1.3945	* 1.5945	* 1.4072	* 1.5531	* 1.4425	* 2.8116 *
10	* 1.3865	* 1.5828	* 1.2399	* 1.4870	* 1.4613	* 1.5438	* 1.4902	* .7138 *
	* 1.5876	* 1.3952	* 1.7815	* 1.4888	* 1.5289	* 1.4483	* 1.5104	* 3.0928 *
11	* 1.5683	* 1.3832	* 1.4822	* 1.3995	* 1.6236	* 1.4240	* 1.6229	* .6515 *
	* 1.4077	* 1.5956	* 1.4935	* 1.5941	* 1.4024	* 1.5964	* 1.3971	* 3.4174 *
12	* 1.3877	* 1.5818	* 1.4600	* 1.6235	* 1.5587	* 1.6126	* 1.0593	*
	* 1.5898	* 1.4083	* 1.5305	* 1.4024	* 1.4657	* 1.4186	* 2.1389	*
13	* 1.5449	* 1.4281	* 1.5428	* 1.4235	* 1.6122	* 1.6948	* .7222	*
	* 1.4347	* 1.5537	* 1.4492	* 1.5969	* 1.4189	* 1.3567	* 3.1410	*
14	* 1.1763	* 1.5453	* 1.4895	* 1.6221	* 1.0583	* .7222	*	
	* 1.8757	* 1.4432	* 1.5112	* 1.3978	* 2.1408	* 3.1412	*	
15	* .6136	* .7836	* .7135	* .6512	* F-SUB-Q			
	* 3.5659	* 2.8121	* 3.0942	* 3.4192	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 238 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 6 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.0273	* 1.5427	* 1.3637	* 1.5440	* 1.3653	* 1.5222	* 1.1574	* .6036 *
	* 2.0090	* 1.3495	* 1.5222	* 1.3500	* 1.5268	* 1.3766	* 1.8035	* 3.4328 *
9	* 1.5427	* 1.3295	* 1.5593	* 1.3634	* 1.5604	* 1.4073	* 1.5245	* .7717 *
	* 1.3495	* 1.5601	* 1.3361	* 1.5286	* 1.3467	* 1.4899	* 1.3821	* 2.7017 *
10	* 1.3637	* 1.5585	* 1.2211	* 1.4661	* 1.4407	* 1.5218	* 1.4686	* .7016 *
	* 1.5222	* 1.3367	* 1.7071	* 1.4234	* 1.4607	* 1.3859	* 1.4462	* 2.9758 *
11	* 1.5440	* 1.3615	* 1.4613	* 1.3792	* 1.6015	* 1.4032	* 1.6007	* .6403 *
	* 1.3500	* 1.5306	* 1.4279	* 1.5230	* 1.3327	* 1.5203	* 1.3317	* 3.2794 *
12	* 1.3653	* 1.5592	* 1.4394	* 1.6014	* 1.5382	* 1.5907	* 1.0420	*
	* 1.5268	* 1.3478	* 1.4620	* 1.3328	* 1.3897	* 1.3484	* 2.0427	*
13	* 1.5222	* 1.4067	* 1.5208	* 1.4027	* 1.5903	* 1.6721	* .7101	*
	* 1.3766	* 1.4905	* 1.3868	* 1.5208	* 1.3487	* 1.2914	* 3.0021	*
14	* 1.1574	* 1.5237	* 1.4678	* 1.5999	* 1.0410	* .7100	*	
	* 1.8035	* 1.3827	* 1.4470	* 1.3323	* 2.0445	* 3.0023	*	
15	* .6036	* .7716	* .7013	* .6400	* F-SUB-Q			
	* 3.4328	* 2.7022	* 2.9771	* 3.2812	* M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 5 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9963	* 1.4864	* 1.3234	* 1.4872	* 1.3252	* 1.4671	* 1.1245	* .5833 *
	* 1.9721	* 1.3341	* 1.4947	* 1.3364	* 1.5007	* 1.3629	* 1.7722	* 3.3958 *
9	* 1.4864	* 1.2911	* 1.5022	* 1.3246	* 1.5059	* 1.3613	* 1.4704	* .7522 *
	* 1.3341	* 1.5306	* 1.3218	* 1.4996	* 1.3297	* 1.4690	* 1.3671	* 2.6471 *
10	* 1.3234	* 1.5014	* 1.2022	* 1.4242	* 1.4003	* 1.4679	* 1.4153	* .6938 *
	* 1.4947	* 1.3224	* 1.6516	* 1.3957	* 1.4298	* 1.3689	* 1.4281	* 2.8731 *
11	* 1.4872	* 1.3228	* 1.4198	* 1.3403	* 1.5459	* 1.3572	* 1.5418	* .6327 *
	* 1.3364	* 1.5016	* 1.3999	* 1.4948	* 1.3099	* 1.4916	* 1.3138	* 3.1631 *
12	* 1.3252	* 1.5046	* 1.3991	* 1.5458	* 1.4932	* 1.5333	* 1.0212	*
	* 1.5007	* 1.3307	* 1.4310	* 1.3100	* 1.3568	* 1.3262	* 1.9794	*
13	* 1.4671	* 1.3607	* 1.4670	* 1.3568	* 1.5329	* 1.6089	* .6846	*
	* 1.3629	* 1.4696	* 1.3697	* 1.4922	* 1.3265	* 1.2702	* 2.9539	*
14	* 1.1245	* 1.4696	* 1.4146	* 1.5410	* 1.0204	* .6846	*	
	* 1.7722	* 1.3677	* 1.4288	* 1.3145	* 1.9810	* 2.9541	*	
15	* .5833	* .7520	* .6934	* .6324	* F-SUB-Q			
	* 3.3958	* 2.6476	* 2.8744	* 3.1648	* M-SUB-Q			

CNEI-0400-25
Appendix A, Rev. 19
Page 239 of 311

F-SUB-O & M-SUB-O VALUES (F-SUB-O OP MARGIN) - POWER ESCALATION

	H	G	F	E	D	C	B	A
8	* .9874 *	* 1.4651 *	* 1.3042 *	* 1.4630 *	* 1.3052 *	* 1.4454 *	* 1.1060 *	* .5750 *
	* 1.9145 *	* 1.3018 *	* 1.4590 *	* 1.3072 *	* 1.4664 *	* 1.3315 *	* 1.7353 *	* 3.3224 *
9	* 1.4651 *	* 1.2740 *	* 1.4787 *	* 1.3039 *	* 1.4829 *	* 1.3412 *	* 1.4488 *	* .7396 *
	* 1.3018 *	* 1.4919 *	* 1.2917 *	* 1.4658 *	* 1.2987 *	* 1.4346 *	* 1.3339 *	* 2.5942 *
10	* 1.3042 *	* 1.4780 *	* 1.1739 *	* 1.4023 *	* 1.3819 *	* 1.4484 *	* 1.3904 *	* .6738 *
	* 1.4590 *	* 1.2923 *	* 1.6273 *	* 1.3634 *	* 1.3923 *	* 1.3341 *	* 1.3968 *	* 2.8500 *
11	* 1.4630 *	* 1.3022 *	* 1.3980 *	* 1.3165 *	* 1.5219 *	* 1.3359 *	* 1.5144 *	* .6133 *
	* 1.3072 *	* 1.4677 *	* 1.3675 *	* 1.4660 *	* 1.2768 *	* 1.4538 *	* 1.2840 *	* 3.1405 *
12	* 1.3052 *	* 1.4818 *	* 1.3808 *	* 1.5218 *	* 1.4748 *	* 1.5113 *	* .9915 *	
	* 1.4664 *	* 1.2997 *	* 1.3935 *	* 1.2769 *	* 1.3171 *	* 1.2901 *	* 1.9572 *	
13	* 1.4454 *	* 1.3406 *	* 1.4476 *	* 1.3355 *	* 1.5109 *	* 1.5767 *	* .6730 *	
	* 1.3315 *	* 1.4352 *	* 1.3349 *	* 1.4543 *	* 1.2904 *	* 1.2413 *	* 2.8843 *	
14	* 1.1060 *	* 1.4481 *	* 1.3897 *	* 1.5137 *	* .9907 *	* .6729 *		
	* 1.7353 *	* 1.3345 *	* 1.3975 *	* 1.2846 *	* 1.9589 *	* 2.8845 *		
15	* .5750 *	* .7395 *	* .6735 *	* .6130 *	F-SUB-Q			
	* 3.3224 *	* 2.5948 *	* 2.8513 *	* 3.1421 *	M-SUB-Q			

	H	G	F	E	D	C	B	A
8	* .9625	* 1.3975	* 1.2423	* 1.3914	* 1.2366	* 1.3787	* 1.0567	* .5460
	* 1.9069	* 1.3236	* 1.4876	* 1.3334	* 1.5043	* 1.3543	* 1.7642	* 3.4042
9	* 1.3975	* 1.2237	* 1.4056	* 1.2362	* 1.4096	* 1.2798	* 1.3811	* .7095
	* 1.3236	* 1.5072	* 1.3181	* 1.4973	* 1.3253	* 1.4587	* 1.3577	* 2.6286
10	* 1.2423	* 1.4052	* 1.1144	* 1.3160	* 1.3131	* 1.3864	* 1.3362	* .6524
	* 1.4876	* 1.3182	* 1.6602	* 1.4102	* 1.4214	* 1.3517	* 1.4056	* 2.8605
11	* 1.3914	* 1.2351	* 1.3123	* 1.2431	* 1.4517	* 1.2745	* 1.4239	* .5883
	* 1.3334	* 1.4986	* 1.4141	* 1.5055	* 1.2964	* 1.4763	* 1.3227	* 3.1804
12	* 1.2366	* 1.4086	* 1.3122	* 1.4516	* 1.4176	* 1.4426	* .9384	*
	* 1.5043	* 1.3262	* 1.4225	* 1.2965	* 1.3267	* 1.3085	* 2.0051	*
13	* 1.3787	* 1.2792	* 1.3856	* 1.2741	* 1.4423	* 1.4850	* .6415	*
	* 1.3543	* 1.4593	* 1.3524	* 1.4767	* 1.3088	* 1.2750	* 2.9343	*
14	* 1.0567	* 1.3804	* 1.3356	* 1.4232	* .9377	* .6414	*	*
	* 1.7642	* 1.3584	* 1.4063	* 1.3234	* 2.0067	* 2.9346	*	*
15	* .5460	* .7093	* .6521	* .5879	* F-SUB-Q			
	* 3.4042	* 2.6292	* 2.8619	* 3.1820	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 240 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 75% POWER, 4 EFPD, THIS IS LEVEL 2 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .8679 *	* 1.3388 *	* 1.0336 *	* 1.3068 *	* 1.0327 *	* 1.2863 *	* .9013 *	* .4692 *
	* 2.0702 *	* 1.3479 *	* 1.7452 *	* 1.3883 *	* 1.7576 *	* 1.4182 *	* 2.0241 *	* 3.8838 *
9	* 1.3388 *	* 1.0153 *	* 1.3444 *	* 1.0141 *	* 1.3260 *	* 1.1124 *	* 1.2781 *	* .6150 *
	* 1.3479 *	* 1.7751 *	* 1.3455 *	* 1.7846 *	* 1.3758 *	* 1.6391 *	* 1.4324 *	* 2.9692 *
10	* 1.0336 *	* 1.3441 *	* .9837 *	* 1.0991 *	* 1.1197 *	* 1.2898 *	* 1.2685 *	* .5829 *
	* 1.7452 *	* 1.3458 *	* 1.8363 *	* 1.6507 *	* 1.6299 *	* 1.4195 *	* 1.4446 *	* 3.1343 *
11	* 1.3068 *	* 1.0138 *	* 1.0966 *	* 1.0652 *	* 1.3327 *	* 1.1133 *	* 1.2235 *	* .5095 *
	* 1.3883 *	* 1.7851 *	* 1.6544 *	* 1.7191 *	* 1.3767 *	* 1.6493 *	* 1.5025 *	* 3.5946 *
12	* 1.0327 *	* 1.3254 *	* 1.1190 *	* 1.3324 *	* 1.2351 *	* 1.3805 *	* .8078 *	
	* 1.7576 *	* 1.3765 *	* 1.6310 *	* 1.3770 *	* 1.4861 *	* 1.3344 *	* 2.2756 *	
13	* 1.2863 *	* 1.1118 *	* 1.2892 *	* 1.1130 *	* 1.3802 *	* 1.2627 *	* .5581 *	
	* 1.4182 *	* 1.6398 *	* 1.4202 *	* 1.6499 *	* 1.3346 *	* 1.4624 *	* 3.2982 *	
14	* .9013 *	* 1.2775 *	* 1.2679 *	* 1.2229 *	* .8073 *	* .5580 *		
	* 2.0241 *	* 1.4331 *	* 1.4453 *	* 1.5032 *	* 2.2772 *	* 3.2988 *		
15	* .4692 *	* .6148 *	* .5826 *	* .5092 *	F-SUB-Q			
	* 3.8838 *	* 2.9701 *	* 3.1360 *	* 3.5965 *	M-SUB-Q			

AT 75% POWER, 4 EFPD, THIS IS LEVEL 1 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .6478 *	* .5544 *	* .4871 *	* .5523 *	* .4846 *	* .5430 *	* .4259 *	* .3274 *
	* 2.7247 *	* 3.1797 *	* 3.6255 *	* 3.2092 *	* 3.6660 *	* 3.2827 *	* 4.1938 *	* 5.4676 *
9	* .5544 *	* .4830 *	* .5510 *	* .4803 *	* .5582 *	* .4998 *	* .4924 *	* .2908 *
	* 3.1797 *	* 3.6557 *	* 3.2076 *	* 3.6913 *	* 3.1933 *	* 3.5660 *	* 3.6337 *	* 6.1615 *
10	* .4871 *	* .5512 *	* .4915 *	* .4703 *	* .4978 *	* .5534 *	* .5097 *	* .2835 *
	* 3.6255 *	* 3.2062 *	* 3.5998 *	* 3.7859 *	* 3.5971 *	* 3.2304 *	* 3.5143 *	* 6.3223 *
11	* .5523 *	* .4803 *	* .4699 *	* .5069 *	* .5701 *	* .5029 *	* .4682 *	* .2495 *
	* 3.2092 *	* 3.6911 *	* 3.7888 *	* 3.5330 *	* 3.1425 *	* 3.5725 *	* 3.8349 *	* 7.2021 *
12	* .4846 *	* .5579 *	* .4976 *	* .5700 *	* .5344 *	* .5359 *	* .3755 *	
	* 3.6660 *	* 3.1948 *	* 3.5988 *	* 3.1430 *	* 3.3570 *	* 3.3571 *	* 4.7932 *	
13	* .5430 *	* .4997 *	* .5531 *	* .5028 *	* .5358 *	* .4869 *	* .3907 *	
	* 3.2827 *	* 3.5671 *	* 3.2320 *	* 3.5733 *	* 3.3578 *	* 3.7029 *	* 4.6205 *	
14	* .4259 *	* .4921 *	* .5094 *	* .4680 *	* .3756 *	* .3906 *		
	* 4.1938 *	* 3.6355 *	* 3.5160 *	* 3.8366 *	* 4.7921 *	* 4.6217 *		
15	* .3274 *	* .2907 *	* .2833 *	* .2493 *	F-SUB-Q			
	* 5.4676 *	* 6.1642 *	* 6.3253 *	* 7.2057 *	M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 241 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 24 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .8244 *	* .7037 *	* .6293 *	* .7065 *	* .6230 *	* .6756 *	* .5461 *	* .4468 *
	* 3.1911 *	* 3.9753 *	* 4.2121 *	* 3.6657 *	* 4.1425 *	* 3.7658 *	* 4.6386 *	* 5.6099 *
9	* .7037 *	* .6387 *	* .7089 *	* .6250 *	* .6961 *	* .6245 *	* .6009 *	* .3789 *
	* 3.9754 *	* 4.2991 *	* 3.7483 *	* 4.1793 *	* 3.7089 *	* 4.0975 *	* 4.2790 *	* 6.7342 *
10	* .6293 *	* .7094 *	* .6435 *	* .6019 *	* .6141 *	* .6752 *	* .6159 *	* .3619 *
	* 4.2121 *	* 3.7485 *	* 4.1614 *	* 4.4187 *	* 4.3015 *	* 3.9360 *	* 4.2624 *	* 7.0924 *
11	* .7065 *	* .6251 *	* .6007 *	* .5720 *	* .6622 *	* .6041 *	* .5611 *	* .3201 *
	* 3.6657 *	* 4.1787 *	* 4.4270 *	* 4.5339 *	* 4.0368 *	* 4.5294 *	* 4.9063 *	* 8.3438 *
12	* .6230 *	* .6959 *	* .6140 *	* .6620 *	* .5840 *	* .5854 *	* .4468 *	
	* 4.1425 *	* 3.7096 *	* 4.3024 *	* 4.0371 *	* 4.2593 *	* 4.2832 *	* 5.9979 *	
13	* .6756 *	* .6244 *	* .6750 *	* .6039 *	* .5854 *	* .5284 *	* .4825 *	
	* 3.7658 *	* 4.0980 *	* 3.9366 *	* 4.5298 *	* 4.2835 *	* 4.7019 *	* 5.3963 *	
14	* .5461 *	* .6011 *	* .6160 *	* .5611 *	* .4470 *	* .4823 *		
	* 4.6386 *	* 4.2771 *	* 4.2620 *	* 4.9067 *	* 5.9950 *	* 5.3983 *		
15	* .4468 *	* .3790 *	* .3620 *	* .3201 *	F-SUB-Q			
	* 5.6099 *	* 6.7289 *	* 7.0898 *	* 8.3439 *	M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 23 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1039 *	* 1.6091 *	* 1.2868 *	* 1.5706 *	* 1.2677 *	* 1.5043 *	* 1.1117 *	* .6143 *
	* 2.5143 *	* 1.8239 *	* 2.1394 *	* 1.7192 *	* 2.1089 *	* 1.7598 *	* 2.3710 *	* 4.2258 *
9	* 1.6091 *	* 1.2895 *	* 1.6252 *	* 1.2716 *	* 1.5506 *	* 1.3141 *	* 1.4671 *	* .7886 *
	* 1.8239 *	* 2.1874 *	* 1.7022 *	* 2.1343 *	* 1.7308 *	* 2.0302 *	* 1.8223 *	* 3.3384 *
10	* 1.2868 *	* 1.6249 *	* 1.2720 *	* 1.3235 *	* 1.3365 *	* 1.4822 *	* 1.4442 *	* .7529 *
	* 2.1394 *	* 1.7031 *	* 2.1771 *	* 2.0860 *	* 2.0747 *	* 1.8633 *	* 1.8830 *	* 3.5308 *
11	* 1.5706 *	* 1.2712 *	* 1.3203 *	* 1.2123 *	* 1.4742 *	* 1.2679 *	* 1.3724 *	* .6620 *
	* 1.7192 *	* 2.1353 *	* 2.0910 *	* 2.2995 *	* 1.8895 *	* 2.2101 *	* 2.0887 *	* 4.1804 *
12	* 1.2677 *	* 1.5500 *	* 1.3357 *	* 1.4739 *	* 1.3210 *	* 1.4815 *	* .9425 *	
	* 2.1089 *	* 1.7312 *	* 2.0755 *	* 1.8898 *	* 2.0001 *	* 1.8176 *	* 2.9552 *	
13	* 1.5043 *	* 1.3139 *	* 1.4819 *	* 1.2676 *	* 1.4814 *	* 1.3411 *	* .6614 *	
	* 1.7598 *	* 2.0305 *	* 1.8637 *	* 2.2103 *	* 1.8177 *	* 1.9886 *	* 4.0913 *	
14	* 1.1117 *	* 1.4675 *	* 1.4442 *	* 1.3723 *	* .9423 *	* .6614 *		
	* 2.3710 *	* 1.8218 *	* 1.8829 *	* 2.0889 *	* 2.9558 *	* 4.0916 *		
15	* .6143 *	* .7890 *	* .7531 *	* .6620 *	F-SUB-Q			
	* 4.2257 *	* 3.3368 *	* 3.5300 *	* 4.1805 *	M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 242 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 22 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2640	* 1.6573	* 1.4994	* 1.6413	* 1.4643	* 1.5844	* 1.2562	* .6992
	* 2.3575	* 1.7967	* 1.8883	* 1.6928	* 1.8699	* 1.7150	* 2.1529	* 3.8033
9	* 1.6573	* 1.4948	* 1.6630	* 1.4865	* 1.6255	* 1.4966	* 1.5653	* .8846
	* 1.7967	* 1.9457	* 1.7026	* 1.8757	* 1.6985	* 1.8248	* 1.7457	* 3.0476
10	* 1.4994	* 1.6626	* 1.4248	* 1.5802	* 1.5543	* 1.5789	* 1.5090	* .8361
	* 1.8883	* 1.7050	* 1.9842	* 1.7942	* 1.8353	* 1.7882	* 1.8475	* 3.2556
11	* 1.6413	* 1.4850	* 1.5758	* 1.4283	* 1.5975	* 1.4503	* 1.5750	* .7514
	* 1.6928	* 1.8769	* 1.7992	* 2.0663	* 1.8024	* 2.0005	* 1.8697	* 3.7885
12	* 1.4643	* 1.6245	* 1.5531	* 1.5974	* 1.5743	* 1.5713	* 1.1034	*
	* 1.8699	* 1.6989	* 1.8366	* 1.8024	* 1.8060	* 1.8083	* 2.6057	*
13	* 1.5844	* 1.4963	* 1.5784	* 1.4500	* 1.5712	* 1.5784	* .7495	*
	* 1.7150	* 1.8252	* 1.7887	* 2.0008	* 1.8084	* 1.7683	* 3.7355	*
14	* 1.2562	* 1.5655	* 1.5089	* 1.5748	* 1.1031	* .7495	*	*
	* 2.1529	* 1.7456	* 1.8476	* 1.8700	* 2.6063	* 3.7355	*	*
15	* .6992	* .8849	* .8362	* .7513	* F-SUB-Q			
	* 3.8033	* 3.0468	* 3.2552	* 3.7888	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 21 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.3156	* 1.7742	* 1.6214	* 1.7568	* 1.5814	* 1.6944	* 1.3524	* .7366
	* 2.3707	* 1.7320	* 1.7972	* 1.6269	* 1.7794	* 1.6486	* 2.0395	* 3.6856
9	* 1.7742	* 1.6141	* 1.7819	* 1.6180	* 1.7449	* 1.5933	* 1.6751	* .9166
	* 1.7320	* 1.8575	* 1.6291	* 1.7772	* 1.6324	* 1.7601	* 1.6745	* 3.0223
10	* 1.6214	* 1.7813	* 1.4860	* 1.7022	* 1.6572	* 1.6841	* 1.5971	* .8488
	* 1.7972	* 1.6319	* 1.9591	* 1.7114	* 1.7750	* 1.7279	* 1.7987	* 3.3006
11	* 1.7568	* 1.6142	* 1.6970	* 1.5605	* 1.7232	* 1.5494	* 1.7120	* .7690
	* 1.6269	* 1.7781	* 1.7166	* 1.9531	* 1.7384	* 1.9390	* 1.7742	* 3.8125
12	* 1.5814	* 1.7435	* 1.6557	* 1.7231	* 1.6798	* 1.6965	* 1.1699	*
	* 1.7794	* 1.6329	* 1.7765	* 1.7384	* 1.7615	* 1.7433	* 2.5454	*
13	* 1.6944	* 1.5929	* 1.6835	* 1.5490	* 1.6963	* 1.7294	* .7959	*
	* 1.6486	* 1.7605	* 1.7285	* 1.9393	* 1.7435	* 1.6787	* 3.6527	*
14	* 1.3524	* 1.6751	* 1.5969	* 1.7117	* 1.1694	* .7959	*	*
	* 2.0395	* 1.6744	* 1.7990	* 1.7745	* 2.5466	* 3.6527	*	*
15	* .7366	* .9168	* .8488	* .7689	* F-SUB-Q			
	* 3.6856	* 3.0218	* 3.3004	* 3.8131	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 243 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 20 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.3078	* 1.8042	* 1.6345	* 1.7892	* 1.6171	* 1.7280	* 1.3681	* .7341 *
	* 2.4973	* 1.7687	* 1.8507	* 1.6562	* 1.8051	* 1.6757	* 2.0911	* 3.8405 *
9	* 1.8042	* 1.6253	* 1.8132	* 1.6309	* 1.7792	* 1.6169	* 1.7092	* .9170 *
	* 1.7687	* 1.9205	* 1.6603	* 1.8281	* 1.6598	* 1.7965	* 1.7009	* 3.1299 *
10	* 1.6345	* 1.8125	* 1.4912	* 1.7209	* 1.6734	* 1.7157	* 1.6314	* .8495 *
	* 1.8507	* 1.6633	* 2.0242	* 1.7565	* 1.8239	* 1.7559	* 1.8211	* 3.4125 *
11	* 1.7892	* 1.6285	* 1.7154	* 1.5910	* 1.7667	* 1.5781	* 1.7570	* .7705 *
	* 1.6562	* 1.8297	* 1.7621	* 1.9889	* 1.7702	* 1.9834	* 1.7994	* 3.9315 *
12	* 1.6171	* 1.7777	* 1.6718	* 1.7666	* 1.7101	* 1.7400	* 1.1931	*
	* 1.8051	* 1.6603	* 1.8255	* 1.7702	* 1.8074	* 1.7750	* 2.6035	*
13	* 1.7280	* 1.6164	* 1.7149	* 1.5777	* 1.7397	* 1.7889	* .8053	*
	* 1.6757	* 1.7970	* 1.7566	* 1.9838	* 1.7752	* 1.6952	* 3.7731	*
14	* 1.3681	* 1.7090	* 1.6310	* 1.7566	* 1.1925	* .8053	*	*
	* 2.0911	* 1.7010	* 1.8215	* 1.7998	* 2.6049	* 3.7732	*	*
15	* .7341	* .9171	* .8494	* .7704	* F-SUB-Q			
	* 3.8405	* 3.1296	* 3.4126	* 3.9324	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 19 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2911	* 1.7959	* 1.6223	* 1.7833	* 1.6097	* 1.7263	* 1.3592	* .7256 *
	* 2.6375	* 1.8565	* 1.9450	* 1.7249	* 1.8859	* 1.7426	* 2.1820	* 4.0313 *
9	* 1.7959	* 1.6086	* 1.8057	* 1.6169	* 1.7745	* 1.6134	* 1.7103	* .9086 *
	* 1.8565	* 2.0287	* 1.7385	* 1.9167	* 1.7280	* 1.8705	* 1.7645	* 3.2791 *
10	* 1.6223	* 1.8051	* 1.4795	* 1.7080	* 1.6632	* 1.7150	* 1.6351	* .8464 *
	* 1.9450	* 1.7416	* 2.1281	* 1.8440	* 1.9095	* 1.8286	* 1.8908	* 3.5612 *
11	* 1.7833	* 1.6154	* 1.7025	* 1.5842	* 1.7728	* 1.5794	* 1.7646	* .7673 *
	* 1.7249	* 1.9175	* 1.8500	* 2.0815	* 1.8497	* 2.0759	* 1.8675	* 4.1224 *
12	* 1.6097	* 1.7729	* 1.6615	* 1.7727	* 1.7128	* 1.7478	* 1.1995	*
	* 1.8859	* 1.7285	* 1.9113	* 1.8498	* 1.8949	* 1.8582	* 2.7180	*
13	* 1.7263	* 1.6129	* 1.7141	* 1.5789	* 1.7476	* 1.8061	* .8057	*
	* 1.7426	* 1.8710	* 1.8295	* 2.0764	* 1.8584	* 1.7695	* 3.9789	*
14	* 1.3592	* 1.7100	* 1.6347	* 1.7641	* 1.1989	* .8057	*	*
	* 2.1820	* 1.7647	* 1.8913	* 1.8679	* 2.7193	* 3.9790	*	*
15	* .7256	* .9086	* .8463	* .7671	* F-SUB-Q			
	* 4.0313	* 3.2790	* 3.5616	* 4.1235	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 244 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 18 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2771	* 1.7964	* 1.6148	* 1.7858	* 1.6047	* 1.7331	* 1.3543	* .7212
	* 2.7712	* 1.9544	* 2.0598	* 1.8146	* 1.9954	* 1.8293	* 2.3051	* 4.2745
9	* 1.7964	* 1.5973	* 1.8071	* 1.6091	* 1.7789	* 1.6160	* 1.7193	* .9055
	* 1.9544	* 2.1530	* 1.8313	* 2.0302	* 1.8164	* 1.9682	* 1.8492	* 3.4651
10	* 1.6148	* 1.8064	* 1.4625	* 1.7021	* 1.6600	* 1.7232	* 1.6453	* .8369
	* 2.0598	* 1.8347	* 2.2711	* 1.9523	* 2.0203	* 1.9199	* 1.9817	* 3.7966
11	* 1.7858	* 1.6076	* 1.6965	* 1.5806	* 1.7855	* 1.5864	* 1.7796	* .7609
	* 1.8146	* 2.0311	* 1.9588	* 2.2036	* 1.9336	* 2.1744	* 1.9306	* 4.3923
12	* 1.6047	* 1.7775	* 1.6583	* 1.7854	* 1.7209	* 1.7637	* 1.1972	*
	* 1.9954	* 1.8170	* 2.0223	* 1.9338	* 1.9853	* 1.9376	* 2.8670	*
13	* 1.7331	* 1.6154	* 1.7222	* 1.5858	* 1.7634	* 1.8286	* .8106	*
	* 1.8293	* 1.9688	* 1.9208	* 2.1749	* 1.9379	* 1.8421	* 4.1689	*
14	* 1.3543	* 1.7190	* 1.6448	* 1.7791	* 1.1964	* .8105	*	*
	* 2.3051	* 1.8495	* 1.9823	* 1.9311	* 2.8688	* 4.1690	*	*
15	* .7212	* .9055	* .8367	* .7607	* F-SUB-Q			
	* 4.2745	* 3.4651	* 3.7971	* 4.3936	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 17 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2453	* 1.7785	* 1.5960	* 1.7699	* 1.5882	* 1.7219	* 1.3406	* .7069
	* 2.9895	* 2.1059	* 2.2309	* 1.9570	* 2.1579	* 1.9656	* 2.4808	* 4.6362
9	* 1.7785	* 1.5753	* 1.7900	* 1.5901	* 1.7666	* 1.6041	* 1.7106	* .8917
	* 2.1059	* 2.3366	* 1.9788	* 2.1979	* 1.9559	* 2.1154	* 1.9793	* 3.7360
10	* 1.5960	* 1.7893	* 1.4401	* 1.6842	* 1.6447	* 1.7135	* 1.6396	* .8247
	* 2.2309	* 1.9825	* 2.4715	* 2.1144	* 2.1844	* 2.0600	* 2.1178	* 4.0865
11	* 1.7699	* 1.5887	* 1.6785	* 1.5668	* 1.7795	* 1.5782	* 1.7752	* .7496
	* 1.9570	* 2.1989	* 2.1216	* 2.3491	* 2.0396	* 2.2941	* 2.0345	* 4.7185
12	* 1.5882	* 1.7651	* 1.6430	* 1.7794	* 1.7145	* 1.7600	* 1.1901	*
	* 2.1579	* 1.9565	* 2.1866	* 2.0397	* 2.1013	* 2.0491	* 3.0301	*
13	* 1.7218	* 1.6035	* 1.7125	* 1.5776	* 1.7597	* 1.8295	* .8026	*
	* 1.9656	* 2.1161	* 2.0610	* 2.2947	* 2.0495	* 1.9542	* 4.4618	*
14	* 1.3406	* 1.7102	* 1.6390	* 1.7746	* 1.1892	* .8026	*	*
	* 2.4808	* 1.9798	* 2.1185	* 2.0352	* 3.0322	* 4.4620	*	*
15	* .7069	* .8917	* .8245	* .7494	* F-SUB-Q			
	* 4.6362	* 3.7361	* 4.0873	* 4.7201	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 245 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 16 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2277	* 1.7641	* 1.5786	* 1.7577	* 1.5733	* 1.7135	* 1.3279	* .7006 *
	* 3.2734	* 2.2645	* 2.4101	* 2.0943	* 2.3151	* 2.0958	* 2.6509	* 4.9420 *
9	* 1.7641	* 1.5554	* 1.7770	* 1.5735	* 1.7578	* 1.5937	* 1.7035	* .8826 *
	* 2.2645	* 2.5373	* 2.1291	* 2.3641	* 2.0884	* 2.2601	* 2.1066	* 3.9960 *
10	* 1.5786	* 1.7759	* 1.4193	* 1.6702	* 1.6322	* 1.7065	* 1.6347	* .8127 *
	* 2.4101	* 2.1331	* 2.6805	* 2.2783	* 2.3456	* 2.1998	* 2.2582	* 4.3958 *
11	* 1.7577	* 1.5720	* 1.6646	* 1.5553	* 1.7757	* 1.5710	* 1.7717	* .7395 *
	* 2.0943	* 2.3650	* 2.2860	* 2.5328	* 2.1915	* 2.4636	* 2.1792	* 5.0813 *
12	* 1.5733	* 1.7563	* 1.6304	* 1.7756	* 1.7091	* 1.7579	* 1.1801	* .8127 *
	* 2.3151	* 2.0890	* 2.3480	* 2.1917	* 2.2646	* 2.1953	* 3.2625	* .8127 *
13	* 1.7135	* 1.5931	* 1.7055	* 1.5704	* 1.7575	* 1.8300	* .8001	* .8001 *
	* 2.0958	* 2.2608	* 2.2009	* 2.4643	* 2.1957	* 2.0839	* 4.7691	* .8001 *
14	* 1.3279	* 1.7030	* 1.6341	* 1.7711	* 1.1792	* .8000	* .8000	* .8000 *
	* 2.6509	* 2.1072	* 2.2590	* 2.1799	* 3.2648	* 4.7692	* 4.7692	* .8000 *
15	* .7006	* .8825	* .8125	* .7392	* F-SUB-Q			
	* 4.9420	* 3.9962	* 4.3968	* 5.0831	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 15 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1853	* 1.7102	* 1.5369	* 1.7063	* 1.5337	* 1.6665	* 1.2963	* .6778 *
	* 3.6684	* 2.5274	* 2.6746	* 2.3186	* 2.5525	* 2.3093	* 2.9072	* 5.4601 *
9	* 1.7102	* 1.5122	* 1.7241	* 1.5325	* 1.7105	* 1.5536	* 1.6595	* .8633 *
	* 2.5274	* 2.8195	* 2.3702	* 2.6138	* 2.3048	* 2.4838	* 2.3107	* 4.3520 *
10	* 1.5369	* 1.7231	* 1.3961	* 1.6284	* 1.5932	* 1.6613	* 1.5946	* .8049 *
	* 2.6746	* 2.3745	* 2.9484	* 2.5292	* 2.5864	* 2.4186	* 2.4708	* 4.7202 *
11	* 1.7063	* 1.5311	* 1.6230	* 1.5192	* 1.7333	* 1.5341	* 1.7281	* .7325 *
	* 2.3186	* 2.6147	* 2.5377	* 2.8093	* 2.4455	* 2.7419	* 2.4087	* 5.4480 *
12	* 1.5337	* 1.7090	* 1.5918	* 1.7332	* 1.6736	* 1.7153	* 1.1667	* .7325 *
	* 2.5525	* 2.3055	* 2.5889	* 2.4456	* 2.5215	* 2.4475	* 3.5816	* .7325 *
13	* 1.6665	* 1.5530	* 1.6604	* 1.5336	* 1.7149	* 1.7885	* .7804	* .7804 *
	* 2.3093	* 2.4846	* 2.4198	* 2.7427	* 2.4480	* 2.3157	* 5.3021	* .7804 *
14	* 1.2963	* 1.6590	* 1.5940	* 1.7274	* 1.1660	* .7804	* .7804	* .7804 *
	* 2.9072	* 2.3114	* 2.4717	* 2.4095	* 3.5837	* 5.3023	* 5.3023	* .7804 *
15	* .6778	* .8632	* .8047	* .7322	* F-SUB-Q			
	* 5.4601	* 4.3524	* 4.7214	* 5.4500	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 246 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 14 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1720	* 1.7074	* 1.5249	* 1.7050	* 1.5238	* 1.6687	* 1.2871	* .6744 *
	* 3.8477	* 2.6359	* 2.8913	* 2.4821	* 2.7481	* 2.4647	* 3.1153	* 5.8145 *
9	* 1.7074	* 1.4977	* 1.7224	* 1.5216	* 1.7120	* 1.5506	* 1.6622	* .8537 *
	* 2.6359	* 3.0025	* 2.5431	* 2.8196	* 2.4646	* 2.6602	* 2.4614	* 4.6833 *
10	* 1.5249	* 1.7214	* 1.3704	* 1.6212	* 1.5881	* 1.6644	* 1.5982	* .7859 *
	* 2.8913	* 2.5476	* 3.2229	* 2.7243	* 2.7887	* 2.5875	* 2.6402	* 5.1553 *
11	* 1.7050	* 1.5196	* 1.6157	* 1.5142	* 1.7388	* 1.5344	* 1.7348	* .7159 *
	* 2.4821	* 2.8205	* 2.7334	* 2.9866	* 2.6308	* 2.9759	* 2.6143	* 5.9660 *
12	* 1.5238	* 1.7105	* 1.5866	* 1.7387	* 1.6741	* 1.7233	* 1.1517	*
	* 2.7481	* 2.4653	* 2.7914	* 2.6310	* 2.7363	* 2.6600	* 3.9548	*
13	* 1.6687	* 1.5500	* 1.6634	* 1.5339	* 1.7229	* 1.7989	* .7802	*
	* 2.4647	* 2.6611	* 2.5888	* 2.9772	* 2.6606	* 2.5294	* 5.8127	*
14	* 1.2871	* 1.6616	* 1.5975	* 1.7340	* 1.1508	* .7802	*	*
	* 3.1153	* 2.4621	* 2.6412	* 2.6153	* 3.9578	* 5.8129	*	*
15	* .6744	* .8536	* .7856	* .7156	* F-SUB-Q			
	* 5.8144	* 4.6837	* 5.1567	* 5.9682	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 13 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1411	* 1.6758	* 1.4954	* 1.6750	* 1.4962	* 1.6426	* 1.2644	* .6598 *
	* 4.0100	* 2.7247	* 2.9400	* 2.5560	* 2.8405	* 2.5760	* 3.3195	* 6.3123 *
9	* 1.6758	* 1.4664	* 1.6916	* 1.4934	* 1.6852	* 1.5259	* 1.6381	* .8378 *
	* 2.7247	* 3.1101	* 2.5949	* 2.8975	* 2.5595	* 2.7942	* 2.6284	* 5.0887 *
10	* 1.4954	* 1.6907	* 1.3438	* 1.5931	* 1.5631	* 1.6396	* 1.5764	* .7715 *
	* 2.9400	* 2.5996	* 3.2899	* 2.7956	* 2.9002	* 2.7283	* 2.8297	* 5.6109 *
11	* 1.6750	* 1.4911	* 1.5876	* 1.4894	* 1.7160	* 1.5133	* 1.7123	* .7033 *
	* 2.5560	* 2.8986	* 2.8050	* 3.0798	* 2.7073	* 3.0623	* 2.7033	* 6.5368 *
12	* 1.4962	* 1.6837	* 1.5616	* 1.7159	* 1.6522	* 1.7016	* 1.1353	*
	* 2.8405	* 2.5604	* 2.9033	* 2.7075	* 2.8181	* 2.7403	* 4.1004	*
13	* 1.6426	* 1.5252	* 1.6386	* 1.5127	* 1.7012	* 1.7789	* .7673	*
	* 2.5760	* 2.7953	* 2.7300	* 3.0637	* 2.7410	* 2.6315	* 6.0952	*
14	* 1.2644	* 1.6375	* 1.5757	* 1.7115	* 1.1344	* .7672	*	*
	* 3.3195	* 2.6294	* 2.8310	* 2.7045	* 4.1038	* 6.0956	*	*
15	* .6598	* .8377	* .7713	* .7030	* F-SUB-Q			
	* 6.3123	* 5.0897	* 5.6131	* 6.5393	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 247 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 12 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1042 *	* 1.6213 *	* 1.4513 *	* 1.6223 *	* 1.4539 *	* 1.5939 *	* 1.2307 *	* .6400 *
	* 4.1717 *	* 2.8013 *	* 2.9556 *	* 2.5774 *	* 2.8582 *	* 2.5961 *	* 3.3327 *	* 6.3583 *
9	* 1.6213 *	* 1.4215 *	* 1.6376 *	* 1.4510 *	* 1.6357 *	* 1.4835 *	* 1.5925 *	* .8168 *
	* 2.8013 *	* 3.1261 *	* 2.6153 *	* 2.9153 *	* 2.5806 *	* 2.8117 *	* 2.6466 *	* 5.1032 *
10	* 1.4513 *	* 1.6367 *	* 1.3149 *	* 1.5480 *	* 1.5213 *	* 1.5924 *	* 1.5342 *	* .7600 *
	* 2.9556 *	* 2.6200 *	* 3.2819 *	* 2.8099 *	* 2.9161 *	* 2.7493 *	* 2.8476 *	* 5.5725 *
11	* 1.6223 *	* 1.4489 *	* 1.5428 *	* 1.4536 *	* 1.6703 *	* 1.4742 *	* 1.6666 *	* .6925 *
	* 2.5774 *	* 2.9164 *	* 2.8193 *	* 3.1902 *	* 2.8231 *	* 3.1838 *	* 2.8094 *	* 6.5408 *
12	* 1.4539 *	* 1.6343 *	* 1.5199 *	* 1.6702 *	* 1.6122 *	* 1.6562 *	* 1.1165 *	
	* 2.8582 *	* 2.5815 *	* 2.9192 *	* 2.8233 *	* 2.9383 *	* 2.8620 *	* 4.2235 *	
13	* 1.5939 *	* 1.4828 *	* 1.5914 *	* 1.4736 *	* 1.6558 *	* 1.7345 *	* .7473 *	
	* 2.5961 *	* 2.8129 *	* 2.7510 *	* 3.1853 *	* 2.8627 *	* 2.7494 *	* 6.3508 *	
14	* 1.2307 *	* 1.5918 *	* 1.5335 *	* 1.6658 *	* 1.1157 *	* .7473 *		
	* 3.3327 *	* 2.6478 *	* 2.8491 *	* 2.8108 *	* 4.2265 *	* 6.3513 *		
15	* .6400 *	* .8166 *	* .7597 *	* .6922 *	F-SUB-Q			
	* 6.3583 *	* 5.1044 *	* 5.5749 *	* 6.5444 *	M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 11 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.0845 *	* 1.6080 *	* 1.4307 *	* 1.6099 *	* 1.4350 *	* 1.5852 *	* 1.2149 *	* .6328 *
	* 3.9861 *	* 2.6918 *	* 2.8899 *	* 2.5092 *	* 2.7996 *	* 2.5275 *	* 3.2679 *	* 6.2104 *
9	* 1.6080 *	* 1.3992 *	* 1.6250 *	* 1.4311 *	* 1.6256 *	* 1.4708 *	* 1.5857 *	* .8068 *
	* 2.6918 *	* 3.0565 *	* 2.5440 *	* 2.8555 *	* 2.5129 *	* 2.7476 *	* 2.5769 *	* 4.9995 *
10	* 1.4307 *	* 1.6240 *	* 1.2834 *	* 1.5296 *	* 1.5053 *	* 1.5846 *	* 1.5284 *	* .7400 *
	* 2.8899 *	* 2.5485 *	* 3.2446 *	* 2.7497 *	* 2.8578 *	* 2.6795 *	* 2.7779 *	* 5.5404 *
11	* 1.6099 *	* 1.4291 *	* 1.5245 *	* 1.4386 *	* 1.6637 *	* 1.4648 *	* 1.6628 *	* .6757 *
	* 2.5092 *	* 2.8566 *	* 2.7588 *	* 3.0486 *	* 2.6808 *	* 3.0286 *	* 2.6648 *	* 6.4349 *
12	* 1.4350 *	* 1.6242 *	* 1.5040 *	* 1.6636 *	* 1.6009 *	* 1.6528 *	* 1.0961 *	
	* 2.7996 *	* 2.5137 *	* 2.8609 *	* 2.6810 *	* 2.8045 *	* 2.7082 *	* 4.0381 *	
13	* 1.5852 *	* 1.4702 *	* 1.5836 *	* 1.4642 *	* 1.6524 *	* 1.7341 *	* .7436 *	
	* 2.5275 *	* 2.7488 *	* 2.6812 *	* 3.0300 *	* 2.7088 *	* 2.5943 *	* 5.9540 *	
14	* 1.2149 *	* 1.5849 *	* 1.5276 *	* 1.6620 *	* 1.0951 *	* .7436 *		
	* 3.2679 *	* 2.5781 *	* 2.7793 *	* 2.6660 *	* 4.0416 *	* 5.9544 *		
15	* .6328 *	* .8066 *	* .7397 *	* .6754 *	F-SUB-Q			
	* 6.2104 *	* 5.0007 *	* 5.5429 *	* 6.4381 *	M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 248 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 10 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.0511	* 1.5750	* 1.3982	* 1.5779	* 1.4037	* 1.5568	* 1.1895	* .6163
	* 3.6724	* 2.4546	* 2.6763	* 2.3273	* 2.6047	* 2.3477	* 3.0448	* 5.8039
9	* 1.5750	* 1.3656	* 1.5923	* 1.3993	* 1.5957	* 1.4433	* 1.5597	* .7888
	* 2.4546	* 2.8228	* 2.3525	* 2.6525	* 2.3318	* 2.5547	* 2.3909	* 4.6466
10	* 1.3982	* 1.5914	* 1.2511	* 1.4970	* 1.4752	* 1.5570	* 1.5045	* .7216
	* 2.6763	* 2.3566	* 3.0120	* 2.5470	* 2.6466	* 2.4773	* 2.5668	* 5.1517
11	* 1.5779	* 1.3975	* 1.4919	* 1.4118	* 1.6370	* 1.4398	* 1.6385	* .6591
	* 2.3273	* 2.6533	* 2.5553	* 2.7813	* 2.4396	* 2.7614	* 2.4230	* 5.9229
12	* 1.4037	* 1.5943	* 1.4738	* 1.6369	* 1.5743	* 1.6280	* 1.0740	*
	* 2.6047	* 2.3326	* 2.6493	* 2.4398	* 2.5547	* 2.4656	* 3.6955	*
13	* 1.5568	* 1.4427	* 1.5560	* 1.4393	* 1.6277	* 1.7119	* .7285	*
	* 2.3477	* 2.5558	* 2.4789	* 2.7627	* 2.4662	* 2.3611	* 5.4594	*
14	* 1.1895	* 1.5589	* 1.5038	* 1.6377	* 1.0731	* .7285	*	*
	* 3.0448	* 2.3920	* 2.5681	* 2.4242	* 3.6987	* 5.4598	*	*
15	* .6163	* .7887	* .7213	* .6588	* F-SUB-Q			
	* 5.8039	* 4.6476	* 5.1541	* 5.9260	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 9 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.0211	* 1.5336	* 1.3607	* 1.5374	* 1.3673	* 1.5191	* 1.1597	* .6005
	* 3.3878	* 2.2574	* 2.4305	* 2.1147	* 2.3686	* 2.1344	* 2.7738	* 5.2987
9	* 1.5336	* 1.3277	* 1.5511	* 1.3626	* 1.5570	* 1.4080	* 1.5239	* .7692
	* 2.2574	* 2.5633	* 2.1346	* 2.4106	* 2.1186	* 2.3218	* 2.1727	* 4.2337
10	* 1.3607	* 1.5502	* 1.2207	* 1.4590	* 1.4393	* 1.5202	* 1.4708	* .7050
	* 2.4305	* 2.1383	* 2.7287	* 2.3075	* 2.3978	* 2.2470	* 2.3283	* 4.6830
11	* 1.5374	* 1.3608	* 1.4541	* 1.3789	* 1.6005	* 1.4070	* 1.6023	* .6439
	* 2.1147	* 2.4113	* 2.3150	* 2.5575	* 2.2471	* 2.5475	* 2.2337	* 5.4464
12	* 1.3673	* 1.5557	* 1.4380	* 1.6004	* 1.5394	* 1.5924	* 1.0512	*
	* 2.3686	* 2.1195	* 2.4004	* 2.2473	* 2.3522	* 2.2721	* 3.4053	*
13	* 1.5191	* 1.4074	* 1.5192	* 1.4065	* 1.5920	* 1.6763	* .7116	*
	* 2.1344	* 2.3228	* 2.2484	* 2.5488	* 2.2727	* 2.1745	* 5.0450	*
14	* 1.1597	* 1.5231	* 1.4701	* 1.6015	* 1.0503	* .7115	*	*
	* 2.7738	* 2.1738	* 2.3295	* 2.2348	* 3.4083	* 5.0453	*	*
15	* .6005	* .7691	* .7047	* .6435	* F-SUB-Q			
	* 5.2987	* 4.2347	* 4.6852	* 5.4496	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 249 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 8 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9860	* 1.4794	* 1.3159	* 1.4844	* 1.3230	* 1.4679	* 1.1239	* .5800
	* 3.1389	* 2.0931	* 2.2438	* 1.9593	* 2.1903	* 1.9789	* 2.5669	* 4.9288
9	* 1.4794	* 1.2831	* 1.4967	* 1.3186	* 1.5049	* 1.3628	* 1.4748	* .7485
	* 2.0931	* 2.3645	* 1.9747	* 2.2270	* 1.9628	* 2.1480	* 2.0130	* 3.9035
10	* 1.3159	* 1.4959	* 1.1904	* 1.4122	* 1.3941	* 1.4697	* 1.4245	* .6922
	* 2.2438	* 1.9780	* 2.4960	* 2.1256	* 2.2082	* 2.0772	* 2.1508	* 4.2758
11	* 1.4844	* 1.3168	* 1.4075	* 1.3382	* 1.5499	* 1.3635	* 1.5517	* .6321
	* 1.9593	* 2.2277	* 2.1324	* 2.3654	* 2.0895	* 2.3606	* 2.0712	* 4.9528
12	* 1.3230	* 1.5036	* 1.3928	* 1.5498	* 1.4940	* 1.5416	* 1.0275	*
	* 2.1903	* 1.9636	* 2.2106	* 2.0896	* 2.1840	* 2.1187	* 3.1402	*
13	* 1.4679	* 1.3622	* 1.4687	* 1.3629	* 1.5412	* 1.6252	* .6896	*
	* 1.9789	* 2.1489	* 2.0785	* 2.3618	* 2.1192	* 2.0274	* 4.7118	*
14	* 1.1239	* 1.4740	* 1.4237	* 1.5509	* 1.0267	* .6895	*	*
	* 2.5669	* 2.0140	* 2.1519	* 2.0722	* 3.1427	* 4.7122	*	*
15	* .5800	* .7483	* .6918	* .6318	* F-SUB-Q			
	* 4.9288	* 3.9046	* 4.2779	* 4.9557	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 7 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9690	* 1.4655	* 1.2943	* 1.4709	* 1.3019	* 1.4560	* 1.1052	* .5723
	* 2.8797	* 1.8860	* 2.0565	* 1.7875	* 2.0116	* 1.8058	* 2.3649	* 4.5319
9	* 1.4655	* 1.2608	* 1.4830	* 1.2968	* 1.4917	* 1.3468	* 1.4633	* .7346
	* 1.8860	* 2.1647	* 1.7966	* 2.0439	* 1.7902	* 1.9651	* 1.8334	* 3.6031
10	* 1.2943	* 1.4822	* 1.1589	* 1.3925	* 1.3750	* 1.4580	* 1.4130	* .6692
	* 2.0565	* 1.7997	* 2.3126	* 1.9392	* 2.0142	* 1.8883	* 1.9576	* 4.0018
11	* 1.4709	* 1.2952	* 1.3878	* 1.3186	* 1.5378	* 1.3485	* 1.5413	* .6117
	* 1.7875	* 2.0445	* 1.9455	* 2.1393	* 1.9011	* 2.1572	* 1.8721	* 4.6064
12	* 1.3019	* 1.4904	* 1.3737	* 1.5377	* 1.4771	* 1.5317	* 1.0018	*
	* 2.0116	* 1.7909	* 2.0164	* 1.9012	* 1.9863	* 1.9228	* 2.9183	*
13	* 1.4560	* 1.3462	* 1.4571	* 1.3480	* 1.5313	* 1.6159	* .6812	*
	* 1.8058	* 1.9660	* 1.8895	* 2.1583	* 1.9232	* 1.8393	* 4.3093	*
14	* 1.1052	* 1.4625	* 1.4122	* 1.5405	* 1.0009	* .6812	*	*
	* 2.3649	* 1.8344	* 1.9587	* 1.8731	* 2.9211	* 4.3096	*	*
15	* .5723	* .7344	* .6689	* .6113	* F-SUB-Q			
	* 4.5319	* 3.6040	* 4.0038	* 4.6091	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 250 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 6 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9430	* 1.4285	* 1.2604	* 1.4340	* 1.2682	* 1.4202	* 1.0767	* .5578
	* 2.6513	* 1.7581	* 1.9245	* 1.6766	* 1.8887	* 1.6954	* 2.2256	* 4.2691
9	* 1.4285	* 1.2275	* 1.4457	* 1.2637	* 1.4554	* 1.3131	* 1.4278	* .7164
	* 1.7581	* 2.0187	* 1.6795	* 1.9165	* 1.6788	* 1.8439	* 1.7184	* 3.3856
10	* 1.2604	* 1.4449	* 1.1301	* 1.3590	* 1.3417	* 1.4226	* 1.3781	* .6515
	* 1.9245	* 1.6823	* 2.1609	* 1.8070	* 1.8751	* 1.7635	* 1.8306	* 3.7615
11	* 1.4340	* 1.2621	* 1.3545	* 1.2863	* 1.5013	* 1.3150	* 1.5040	* .5954
	* 1.6766	* 1.9170	* 1.8128	* 1.9952	* 1.7531	* 1.9990	* 1.7428	* 4.2950
12	* 1.2682	* 1.4542	* 1.3405	* 1.5012	* 1.4424	* 1.4950	* .9755	*
	* 1.8887	* 1.6794	* 1.8771	* 1.7532	* 1.8315	* 1.7779	* 2.7009	*
13	* 1.4202	* 1.3125	* 1.4217	* 1.3145	* 1.4947	* 1.5770	* .6632	*
	* 1.6954	* 1.8447	* 1.7646	* 2.0001	* 1.7783	* 1.7076	* 4.0094	*
14	* 1.0767	* 1.4271	* 1.3773	* 1.5032	* .9745	* .6631	*	*
	* 2.2256	* 1.7193	* 1.8316	* 1.7437	* 2.7035	* 4.0097	*	*
15	* .5578	* .7163	* .6512	* .5951	* F-SUB-Q			
	* 4.2691	* 3.3864	* 3.7634	* 4.2976	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 5 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9061	* 1.3635	* 1.2119	* 1.3685	* 1.2194	* 1.3555	* 1.0362	* .5342
	* 2.5491	* 1.6754	* 1.8459	* 1.6272	* 1.8200	* 1.6473	* 2.1477	* 4.1463
9	* 1.3635	* 1.1811	* 1.3799	* 1.2163	* 1.3909	* 1.2579	* 1.3634	* .6919
	* 1.6754	* 1.9228	* 1.6236	* 1.8403	* 1.6291	* 1.7832	* 1.6677	* 3.2530
10	* 1.2119	* 1.3788	* 1.1025	* 1.3078	* 1.2916	* 1.3589	* 1.3147	* .6383
	* 1.8459	* 1.6263	* 2.0423	* 1.7289	* 1.7895	* 1.7020	* 1.7692	* 3.5569
11	* 1.3685	* 1.2147	* 1.3036	* 1.2380	* 1.4348	* 1.2594	* 1.4337	* .5829
	* 1.6272	* 1.8416	* 1.7344	* 1.8960	* 1.6877	* 1.9250	* 1.6775	* 4.0285
12	* 1.2194	* 1.3898	* 1.2904	* 1.4347	* 1.3861	* 1.4266	* .9468	*
	* 1.8200	* 1.6297	* 1.7914	* 1.6878	* 1.7498	* 1.7114	* 2.5668	*
13	* 1.3555	* 1.2573	* 1.3580	* 1.2589	* 1.4262	* 1.5013	* .6334	*
	* 1.6473	* 1.7840	* 1.7031	* 1.9259	* 1.7118	* 1.6427	* 3.8576	*
14	* 1.0362	* 1.3626	* 1.3140	* 1.4330	* .9460	* .6333	*	*
	* 2.1477	* 1.6686	* 1.7702	* 1.6784	* 2.5689	* 3.8579	*	*
15	* .5342	* .6917	* .6380	* .5826	* F-SUB-Q			
	* 4.1463	* 3.2538	* 3.5587	* 4.0308	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 251 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 4 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .8902	* 1.3314	* 1.1832	* 1.3334	* 1.1897	* 1.3226	* 1.0096	* .5220
	* 2.3760	* 1.5906	* 1.7642	* 1.5657	* 1.7491	* 1.5847	* 2.0716	* 3.9962
9	* 1.3314	* 1.1548	* 1.3453	* 1.1862	* 1.3567	* 1.2274	* 1.3295	* .6742
	* 1.5906	* 1.8252	* 1.5568	* 1.7651	* 1.5666	* 1.7134	* 1.6004	* 3.1362
10	* 1.1832	* 1.3447	* 1.0669	* 1.2757	* 1.2626	* 1.3280	* 1.2789	* .6143
	* 1.7642	* 1.5592	* 1.9713	* 1.6531	* 1.7024	* 1.6225	* 1.6956	* 3.4657
11	* 1.3334	* 1.1846	* 1.2717	* 1.2046	* 1.3988	* 1.2275	* 1.3941	* .5599
	* 1.5657	* 1.7662	* 1.6582	* 1.8152	* 1.6123	* 1.8191	* 1.5969	* 3.9130
12	* 1.1897	* 1.3557	* 1.2615	* 1.3987	* 1.3555	* 1.3922	* .9105	*
	* 1.7491	* 1.5672	* 1.7041	* 1.6115	* 1.6713	* 1.6395	* 2.4781	*
13	* 1.3226	* 1.2268	* 1.3272	* 1.2270	* 1.3918	* 1.4561	* .6168	*
	* 1.5847	* 1.7142	* 1.6235	* 1.8200	* 1.6399	* 1.5862	* 3.7186	*
14	* 1.0096	* 1.3288	* 1.2782	* 1.3933	* .9097	* .6167	*	*
	* 2.0716	* 1.6013	* 1.6966	* 1.5978	* 2.4804	* 3.7190	*	*
15	* .5220	* .6740	* .6140	* .5596	* F-SUB-Q			
	* 3.9962	* 3.1369	* 3.4674	* 3.9153	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 3 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .8604	* 1.2581	* 1.1177	* 1.2568	* 1.1181	* 1.2495	* .9556	* .4915
	* 2.3086	* 1.5810	* 1.7637	* 1.5779	* 1.7736	* 1.5948	* 2.0854	* 4.0545
9	* 1.2581	* 1.0991	* 1.2668	* 1.1133	* 1.2775	* 1.1600	* 1.2554	* .6409
	* 1.5810	* 1.8027	* 1.5638	* 1.7734	* 1.5769	* 1.7239	* 1.6134	* 3.1426
10	* 1.1177	* 1.2664	* 1.0036	* 1.1864	* 1.1888	* 1.2590	* 1.2157	* .5895
	* 1.7637	* 1.5643	* 1.9794	* 1.6841	* 1.7087	* 1.6180	* 1.6816	* 3.4356
11	* 1.2568	* 1.1122	* 1.1830	* 1.1271	* 1.3214	* 1.1598	* 1.2975	* .5322
	* 1.5779	* 1.7749	* 1.6889	* 1.8445	* 1.5932	* 1.8115	* 1.6174	* 3.8940
12	* 1.1181	* 1.2766	* 1.1878	* 1.3213	* 1.2903	* 1.3158	* .8536	*
	* 1.7736	* 1.5773	* 1.7103	* 1.5933	* 1.6355	* 1.6167	* 2.4831	*
13	* 1.2495	* 1.1595	* 1.2583	* 1.1594	* 1.3156	* 1.3573	* .5826	*
	* 1.5948	* 1.7247	* 1.6190	* 1.8124	* 1.6170	* 1.5888	* 3.6825	*
14	* .9556	* 1.2547	* 1.2151	* 1.2968	* .8529	* .5826	*	*
	* 2.0854	* 1.6142	* 1.6825	* 1.6182	* 2.4851	* 3.6830	*	*
15	* .4915	* .6408	* .5892	* .5319	* F-SUB-Q			
	* 4.0545	* 3.1434	* 3.4374	* 3.8962	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 252 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 50% POWER, 4 EFPD, THIS IS LEVEL 2 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .7691	* 1.1925	* .9192	* 1.1688	* .9224	* 1.1541	* .8081	* .4184
	* 2.4647	* 1.5925	* 2.0584	* 1.6280	* 2.0620	* 1.6619	* 2.3817	* 4.6060
9	* 1.1925	* .9022	* 1.1992	* .9039	* 1.1900	* .9971	* 1.1490	* .5501
	* 1.5925	* 2.0984	* 1.5830	* 2.0991	* 1.6214	* 1.9278	* 1.6937	* 3.5319
10	* .9192	* 1.1990	* .8764	* .9806	* 1.0034	* 1.1599	* 1.1411	* .5216
	* 2.0584	* 1.5833	* 2.1661	* 1.9569	* 1.9449	* 1.6906	* 1.7196	* 3.7505
11	* 1.1688	* .9037	* .9783	* .9577	* 1.1997	* 1.0021	* 1.1020	* .4564
	* 1.6280	* 2.0997	* 1.9614	* 2.0904	* 1.6728	* 2.0120	* 1.8235	* 4.3602
12	* .9224	* 1.1894	* 1.0027	* 1.1995	* 1.1117	* 1.2460	* .7270	*
	* 2.0620	* 1.6220	* 1.9464	* 1.6732	* 1.8121	* 1.6333	* 2.7923	*
13	* 1.1541	* .9966	* 1.1593	* 1.0017	* 1.2457	* 1.1409	* .5018	*
	* 1.6619	* 1.9287	* 1.6915	* 2.0127	* 1.6336	* 1.8010	* 4.0893	*
14	* .8081	* 1.1484	* 1.1405	* 1.1014	* .7265	* .5017	*	*
	* 2.3817	* 1.6946	* 1.7205	* 1.8244	* 2.7943	* 4.0900	*	*
15	* .4184	* .5500	* .5213	* .4561	* F-SUB-Q			
	* 4.6060	* 3.5330	* 3.7525	* 4.3627	* M-SUB-Q			

AT 50% POWER, 4 EFPD, THIS IS LEVEL 1 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .5666	* .4842	* .4259	* .4840	* .4256	* .4776	* .3749	* .2876
	* 3.2243	* 3.7571	* 4.2774	* 3.7707	* 4.3126	* 3.8609	* 4.9497	* 6.4943
9	* .4842	* .4223	* .4818	* .4216	* .4911	* .4399	* .4338	* .2559
	* 3.7571	* 4.3139	* 3.7809	* 4.3477	* 3.7712	* 4.1982	* 4.3110	* 7.3610
10	* .4259	* .4820	* .4302	* .4132	* .4392	* .4877	* .4495	* .2495
	* 4.2774	* 3.7792	* 4.2495	* 4.4926	* 4.2784	* 3.8510	* 4.1938	* 7.5585
11	* .4840	* .4216	* .4129	* .4473	* .5030	* .4447	* .4135	* .2198
	* 3.7708	* 4.3476	* 4.4962	* 4.3062	* 3.8305	* 4.3283	* 4.6329	* 8.7312
12	* .4256	* .4908	* .4390	* .5029	* .4719	* .4739	* .3318	*
	* 4.3126	* 3.7726	* 4.2807	* 3.8311	* 4.1022	* 4.1195	* 5.8928	*
13	* .4776	* .4397	* .4874	* .4446	* .4739	* .4312	* .3456	*
	* 3.8609	* 4.1996	* 3.8530	* 4.3304	* 4.1203	* 4.5606	* 5.7276	*
14	* .3749	* .4336	* .4493	* .4133	* .3319	* .3455	*	*
	* 4.9497	* 4.3133	* 4.1960	* 4.6352	* 5.8917	* 5.7292	*	*
15	* .2876	* .2558	* .2494	* .2197	* F-SUB-Q			
	* 6.4943	* 7.3646	* 7.5624	* 8.7360	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 253 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 24 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .8491 *	* .7292 *	* .6492 *	* .7330 *	* .6446 *	* .7034 *	* .5653 *	* .4572 *
	* 3.1911 *	* 3.9753 *	* 4.2121 *	* 3.6657 *	* 4.1425 *	* 3.7658 *	* 4.6386 *	* 5.6099 *
9	* .7292 *	* .6589 *	* .7352 *	* .6455 *	* .7240 *	* .6481 *	* .6270 *	* .3891 *
	* 3.9754 *	* 4.2991 *	* 3.7483 *	* 4.1793 *	* 3.7089 *	* 4.0975 *	* 4.2790 *	* 6.7342 *
10	* .6492 *	* .7357 *	* .6630 *	* .6229 *	* .6379 *	* .7041 *	* .6429 *	* .3715 *
	* 4.2121 *	* 3.7485 *	* 4.1614 *	* 4.4187 *	* 4.3015 *	* 3.9360 *	* 4.2624 *	* 7.0924 *
11	* .7330 *	* .6455 *	* .6216 *	* .5955 *	* .6916 *	* .6289 *	* .5868 *	* .3288 *
	* 3.6657 *	* 4.1787 *	* 4.4270 *	* 4.5339 *	* 4.0368 *	* 4.5294 *	* 4.9063 *	* 8.3438 *
12	* .6446 *	* .7238 *	* .6377 *	* .6915 *	* .6100 *	* .6153 *	* .4643 *	
	* 4.1425 *	* 3.7096 *	* 4.3024 *	* 4.0371 *	* 4.2593 *	* 4.2832 *	* 5.9979 *	
13	* .7034 *	* .6480 *	* .7040 *	* .6287 *	* .6152 *	* .5564 *	* .4996 *	
	* 3.7658 *	* 4.0980 *	* 3.9366 *	* 4.5298 *	* 4.2835 *	* 4.7019 *	* 5.3963 *	
14	* .5653 *	* .6272 *	* .6429 *	* .5868 *	* .4645 *	* .4994 *		
	* 4.6386 *	* 4.2771 *	* 4.2620 *	* 4.9067 *	* 5.9950 *	* 5.3983 *		
15	* .4572 *	* .3892 *	* .3716 *	* .3288 *	F-SUB-Q			
	* 5.6099 *	* 6.7289 *	* 7.0898 *	* 8.3439 *	M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 23 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1627 *	* 1.7103 *	* 1.3641 *	* 1.6734 *	* 1.3475 *	* 1.6073 *	* 1.1808 *	* .6412 *
	* 2.5143 *	* 1.8239 *	* 2.1394 *	* 1.7192 *	* 2.1089 *	* 1.7598 *	* 2.3710 *	* 4.2258 *
9	* 1.7103 *	* 1.3660 *	* 1.7307 *	* 1.3491 *	* 1.6561 *	* 1.4024 *	* 1.5711 *	* .8277 *
	* 1.8239 *	* 2.1874 *	* 1.7022 *	* 2.1343 *	* 1.7308 *	* 2.0302 *	* 1.8223 *	* 3.3384 *
10	* 1.3641 *	* 1.7303 *	* 1.3455 *	* 1.4068 *	* 1.4251 *	* 1.5863 *	* 1.5454 *	* .7901 *
	* 2.1394 *	* 1.7031 *	* 2.1771 *	* 2.0860 *	* 2.0747 *	* 1.8633 *	* 1.8830 *	* 3.5308 *
11	* 1.6734 *	* 1.3487 *	* 1.4042 *	* 1.2934 *	* 1.5802 *	* 1.3562 *	* 1.4750 *	* .6951 *
	* 1.7192 *	* 2.1353 *	* 2.0910 *	* 2.2995 *	* 1.8895 *	* 2.2101 *	* 2.0887 *	* 4.1804 *
12	* 1.3475 *	* 1.6554 *	* 1.4243 *	* 1.5797 *	* 1.4214 *	* 1.5984 *	* 1.0042 *	
	* 2.1089 *	* 1.7312 *	* 2.0755 *	* 1.8898 *	* 2.0001 *	* 1.8176 *	* 2.9552 *	
13	* 1.6073 *	* 1.4022 *	* 1.5860 *	* 1.3559 *	* 1.5982 *	* 1.4495 *	* .6998 *	
	* 1.7598 *	* 2.0305 *	* 1.8637 *	* 2.2103 *	* 1.8177 *	* 1.9886 *	* 4.0913 *	
14	* 1.1808 *	* 1.5715 *	* 1.5455 *	* 1.4748 *	* 1.0040 *	* .6998 *		
	* 2.3710 *	* 1.8218 *	* 1.8829 *	* 2.0889 *	* 2.9558 *	* 4.0916 *		
15	* .6412 *	* .8281 *	* .7903 *	* .6950 *	F-SUB-Q			
	* 4.2257 *	* 3.3368 *	* 3.5300 *	* 4.1805 *	M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 254 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 22 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.3277	* 1.7648	* 1.5944	* 1.7505	* 1.5637	* 1.6959	* 1.3395	* .7325 *
	* 2.3575	* 1.7967	* 1.8883	* 1.6928	* 1.8699	* 1.7150	* 2.1529	* 3.8033 *
9	* 1.7648	* 1.5876	* 1.7732	* 1.5834	* 1.7416	* 1.6039	* 1.6810	* .9320 *
	* 1.7967	* 1.9457	* 1.7026	* 1.8757	* 1.6985	* 1.8248	* 1.7457	* 3.0476 *
10	* 1.5944	* 1.7727	* 1.5143	* 1.6876	* 1.6641	* 1.6932	* 1.6183	* .8804 *
	* 1.8883	* 1.7050	* 1.9842	* 1.7942	* 1.8353	* 1.7882	* 1.8475	* 3.2556 *
11	* 1.7505	* 1.5817	* 1.6825	* 1.5236	* 1.7197	* 1.5586	* 1.6990	* .7922 *
	* 1.6928	* 1.8769	* 1.7992	* 2.0663	* 1.8024	* 2.0005	* 1.8697	* 3.7885 *
12	* 1.5637	* 1.7404	* 1.6627	* 1.7197	* 1.6987	* 1.6958	* 1.1803	* .7959 *
	* 1.8699	* 1.6989	* 1.8366	* 1.8024	* 1.8060	* 1.8083	* 2.6057	* 3.7355 *
13	* 1.6959	* 1.6036	* 1.6925	* 1.5582	* 1.6956	* 1.7121	* .7959	* 3.7355 *
	* 1.7150	* 1.8252	* 1.7887	* 2.0008	* 1.8084	* 1.7683	* 3.7355	* 3.7355 *
14	* 1.3395	* 1.6812	* 1.6181	* 1.6987	* 1.1800	* .7959	* 3.7355	* 3.7355 *
	* 2.1529	* 1.7456	* 1.8476	* 1.8700	* 2.6063	* 3.7355	* 3.7355	* 3.7355 *
15	* .7325	* .9322	* .8805	* .7922	* F-SUB-Q			
	* 3.8033	* 3.0468	* 3.2552	* 3.7888	* M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 21 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.3766	* 1.8822	* 1.7169	* 1.8672	* 1.6826	* 1.8083	* 1.4349	* .7704 *
	* 2.3707	* 1.7320	* 1.7972	* 1.6269	* 1.7794	* 1.6486	* 2.0395	* 3.6856 *
9	* 1.8822	* 1.7070	* 1.8930	* 1.7166	* 1.8631	* 1.7026	* 1.7945	* .9640 *
	* 1.7320	* 1.8575	* 1.6291	* 1.7772	* 1.6324	* 1.7601	* 1.6745	* 3.0223 *
10	* 1.7169	* 1.8923	* 1.5726	* 1.8126	* 1.7691	* 1.8010	* 1.7086	* .8922 *
	* 1.7972	* 1.6319	* 1.9591	* 1.7114	* 1.7750	* 1.7279	* 1.7987	* 3.3006 *
11	* 1.8672	* 1.7123	* 1.8066	* 1.6594	* 1.8497	* 1.6602	* 1.8436	* .8098 *
	* 1.6269	* 1.7781	* 1.7166	* 1.9531	* 1.7384	* 1.9390	* 1.7742	* 3.8125 *
12	* 1.6826	* 1.8612	* 1.7675	* 1.8496	* 1.8072	* 1.8259	* 1.2487	* .8437 *
	* 1.7794	* 1.6329	* 1.7765	* 1.7384	* 1.7615	* 1.7433	* 2.5454	* 3.6527 *
13	* 1.8083	* 1.7021	* 1.8002	* 1.6597	* 1.8256	* 1.8715	* .8437	* 3.6527 *
	* 1.6486	* 1.7605	* 1.7285	* 1.9393	* 1.7435	* 1.6787	* 3.6527	* 3.6527 *
14	* 1.4349	* 1.7944	* 1.7083	* 1.8432	* 1.2480	* .8437	* 3.6527	* 3.6527 *
	* 2.0395	* 1.6744	* 1.7990	* 1.7745	* 2.5466	* 3.6527	* 3.6527	* 3.6527 *
15	* .7704	* .9642	* .8922	* .8096	* F-SUB-Q			
	* 3.6856	* 3.0218	* 3.3004	* 3.8131	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 255 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 20 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.3611	* 1.9035	* 1.7212	* 1.8914	* 1.7111	* 1.8350	* 1.4448	* .7649 *
	* 2.4973	* 1.7687	* 1.8507	* 1.6562	* 1.8051	* 1.6757	* 2.0911	* 3.8405 *
9	* 1.9035	* 1.7093	* 1.9158	* 1.7209	* 1.8888	* 1.7191	* 1.8226	* .9609 *
	* 1.7687	* 1.9205	* 1.6603	* 1.8281	* 1.6598	* 1.7965	* 1.7009	* 3.1299 *
10	* 1.7212	* 1.9150	* 1.5710	* 1.8225	* 1.7771	* 1.8260	* 1.7377	* .8897 *
	* 1.8507	* 1.6633	* 2.0242	* 1.7565	* 1.8239	* 1.7559	* 1.8211	* 3.4125 *
11	* 1.8914	* 1.7182	* 1.8162	* 1.6827	* 1.8873	* 1.6828	* 1.8837	* .8086 *
	* 1.6562	* 1.8297	* 1.7621	* 1.9889	* 1.7702	* 1.9834	* 1.7994	* 3.9315 *
12	* 1.7111	* 1.8868	* 1.7753	* 1.8872	* 1.8305	* 1.8639	* 1.2682	*
	* 1.8051	* 1.6603	* 1.8255	* 1.7702	* 1.8074	* 1.7750	* 2.6035	*
13	* 1.8350	* 1.7185	* 1.8251	* 1.6822	* 1.8636	* 1.9272	* .8506	*
	* 1.6757	* 1.7970	* 1.7566	* 1.9838	* 1.7752	* 1.6952	* 3.7731	*
14	* 1.4448	* 1.8224	* 1.7372	* 1.8832	* 1.2674	* .8506	*	
	* 2.0911	* 1.7010	* 1.8215	* 1.7998	* 2.6049	* 3.7732	*	
15	* .7649	* .9610	* .8896	* .8084	F-SUB-Q			
	* 3.8405	* 3.1296	* 3.4126	* 3.9324	M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 19 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.3355	* 1.8825	* 1.6973	* 1.8732	* 1.6927	* 1.8221	* 1.4273	* .7523 *
	* 2.6375	* 1.8565	* 1.9450	* 1.7249	* 1.8859	* 1.7426	* 2.1820	* 4.0313 *
9	* 1.8825	* 1.6809	* 1.8956	* 1.6952	* 1.8734	* 1.7050	* 1.8133	* .9473 *
	* 1.8565	* 2.0287	* 1.7385	* 1.9167	* 1.7280	* 1.8705	* 1.7645	* 3.2791 *
10	* 1.6973	* 1.8947	* 1.5488	* 1.7969	* 1.7550	* 1.8143	* 1.7332	* .8822 *
	* 1.9450	* 1.7416	* 2.1281	* 1.8440	* 1.9095	* 1.8286	* 1.8908	* 3.5612 *
11	* 1.8732	* 1.6936	* 1.7906	* 1.6648	* 1.8824	* 1.6741	* 1.8806	* .8014 *
	* 1.7249	* 1.9175	* 1.8500	* 2.0815	* 1.8497	* 2.0759	* 1.8675	* 4.1224 *
12	* 1.6927	* 1.8718	* 1.7532	* 1.8823	* 1.8223	* 1.8613	* 1.2681	*
	* 1.8859	* 1.7285	* 1.9113	* 1.8498	* 1.8949	* 1.8582	* 2.7180	*
13	* 1.8221	* 1.7044	* 1.8133	* 1.6735	* 1.8610	* 1.9345	* .8469	*
	* 1.7426	* 1.8710	* 1.8295	* 2.0764	* 1.8584	* 1.7695	* 3.9789	*
14	* 1.4273	* 1.8129	* 1.7327	* 1.8801	* 1.2674	* .8468	*	
	* 2.1820	* 1.7647	* 1.8913	* 1.8679	* 2.7193	* 3.9790	*	
15	* .7523	* .9473	* .8821	* .8012	F-SUB-Q			
	* 4.0313	* 3.2790	* 3.5616	* 4.1235	M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 256 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 18 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.3120	* 1.8696	* 1.6774	* 1.8626	* 1.6756	* 1.8168	* 1.4130	* .7433 *
	* 2.7712	* 1.9544	* 2.0598	* 1.8146	* 1.9954	* 1.8293	* 2.3051	* 4.2745 *
9	* 1.8696	* 1.6570	* 1.8838	* 1.6750	* 1.8663	* 1.6959	* 1.8107	* .9386 *
	* 1.9544	* 2.1530	* 1.8313	* 2.0302	* 1.8164	* 1.9682	* 1.8492	* 3.4651 *
10	* 1.6774	* 1.8826	* 1.5201	* 1.7775	* 1.7392	* 1.8105	* 1.7347	* .8672 *
	* 2.0598	* 1.8347	* 2.2711	* 1.9523	* 2.0203	* 1.9199	* 1.9817	* 3.7966 *
11	* 1.8626	* 1.6733	* 1.7713	* 1.6491	* 1.8831	* 1.6700	* 1.8841	* .7900 *
	* 1.8146	* 2.0311	* 1.9588	* 2.2036	* 1.9336	* 2.1744	* 1.9306	* 4.3923 *
12	* 1.6756	* 1.8647	* 1.7373	* 1.8829	* 1.8182	* 1.8656	* 1.2577	*
	* 1.9954	* 1.8170	* 2.0223	* 1.9338	* 1.9853	* 1.9376	* 2.8670	*
13	* 1.8168	* 1.6952	* 1.8095	* 1.6694	* 1.8653	* 1.9455	* .8469	*
	* 1.8293	* 1.9688	* 1.9208	* 2.1749	* 1.9379	* 1.8421	* 4.1689	*
14	* 1.4130	* 1.8103	* 1.7341	* 1.8834	* 1.2568	* .8469	*	
	* 2.3051	* 1.8495	* 1.9823	* 1.9311	* 2.8688	* 4.1690	*	
15	* .7433	* .9386	* .8670	* .7898	* F-SUB-Q			
	* 4.2745	* 3.4651	* 3.7971	* 4.3936	* M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 17 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2698	* 1.8365	* 1.6450	* 1.8318	* 1.6457	* 1.7914	* 1.3886	* .7237 *
	* 2.9895	* 2.1059	* 2.2309	* 1.9570	* 2.1579	* 1.9656	* 2.4808	* 4.6362 *
9	* 1.8365	* 1.6216	* 1.8516	* 1.6425	* 1.8391	* 1.6705	* 1.7880	* .9180 *
	* 2.1059	* 2.3366	* 1.9788	* 2.1979	* 1.9559	* 2.1154	* 1.9793	* 3.7360 *
10	* 1.6450	* 1.8504	* 1.4852	* 1.7447	* 1.7097	* 1.7868	* 1.7160	* .8489 *
	* 2.2309	* 1.9825	* 2.4715	* 2.1144	* 2.1844	* 2.0600	* 2.1178	* 4.0865 *
11	* 1.8318	* 1.6408	* 1.7385	* 1.6220	* 1.8625	* 1.6499	* 1.8651	* .7732 *
	* 1.9570	* 2.1989	* 2.1216	* 2.3491	* 2.0396	* 2.2941	* 2.0345	* 4.7185 *
12	* 1.6457	* 1.8375	* 1.7078	* 1.8624	* 1.7976	* 1.8477	* 1.2412	*
	* 2.1579	* 1.9565	* 2.1866	* 2.0397	* 2.1013	* 2.0491	* 3.0301	*
13	* 1.7914	* 1.6699	* 1.7858	* 1.6494	* 1.8473	* 1.9316	* .8330	*
	* 1.9656	* 2.1161	* 2.0610	* 2.2947	* 2.0495	* 1.9542	* 4.4618	*
14	* 1.3886	* 1.7875	* 1.7154	* 1.8644	* 1.2403	* .8329	*	
	* 2.4808	* 1.9798	* 2.1185	* 2.0352	* 3.0322	* 4.4620	*	
15	* .7237	* .9180	* .8487	* .7729	* F-SUB-Q			
	* 4.6362	* 3.7361	* 4.0873	* 4.7201	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 257 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 16 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.2423	* 1.8070	* 1.6141	* 1.8046	* 1.6172	* 1.7687	* 1.3648	* .7121 *
	* 3.2734	* 2.2645	* 2.4101	* 2.0943	* 2.3151	* 2.0958	* 2.6509	* 4.9420 *
9	* 1.8070	* 1.5883	* 1.8232	* 1.6128	* 1.8153	* 1.6466	* 1.7665	* .9021 *
	* 2.2645	* 2.5373	* 2.1291	* 2.3641	* 2.0884	* 2.2601	* 2.1066	* 3.9960 *
10	* 1.6141	* 1.8221	* 1.4522	* 1.7162	* 1.6831	* 1.7655	* 1.6976	* .8305 *
	* 2.4101	* 2.1331	* 2.6805	* 2.2783	* 2.3456	* 2.1998	* 2.2582	* 4.3958 *
11	* 1.8046	* 1.6107	* 1.7101	* 1.5973	* 1.8438	* 1.6303	* 1.8465	* .7572 *
	* 2.0943	* 2.3650	* 2.2860	* 2.5328	* 2.1915	* 2.4636	* 2.1792	* 5.0813 *
12	* 1.6172	* 1.8137	* 1.6815	* 1.8437	* 1.7775	* 1.8308	* 1.2215	*
	* 2.3151	* 2.0890	* 2.3480	* 2.1917	* 2.2646	* 2.1953	* 3.2625	*
13	* 1.7687	* 1.6459	* 1.7644	* 1.6297	* 1.8305	* 1.9165	* .8242	*
	* 2.0958	* 2.2608	* 2.2009	* 2.4643	* 2.1957	* 2.0839	* 4.7691	*
14	* 1.3648	* 1.7659	* 1.6969	* 1.8457	* 1.2205	* .8242	*	
	* 2.6509	* 2.1072	* 2.2590	* 2.1799	* 3.2648	* 4.7692	*	
15	* .7121	* .9020	* .8303	* .7569	* F-SUB-Q			
	* 4.9420	* 3.9962	* 4.3968	* 5.0831	* M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 15 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1897	* 1.7372	* 1.5586	* 1.7372	* 1.5635	* 1.7058	* 1.3216	* .6837 *
	* 3.6684	* 2.5274	* 2.6746	* 2.3186	* 2.5525	* 2.3093	* 2.9072	* 5.4601 *
9	* 1.7372	* 1.5314	* 1.7541	* 1.5592	* 1.7516	* 1.5917	* 1.7063	* .8755 *
	* 2.5274	* 2.8195	* 2.3702	* 2.6138	* 2.3048	* 2.4838	* 2.3107	* 4.3520 *
10	* 1.5586	* 1.7530	* 1.4168	* 1.6592	* 1.6306	* 1.7044	* 1.6420	* .8163 *
	* 2.6746	* 2.3745	* 2.9484	* 2.5292	* 2.5864	* 2.4186	* 2.4708	* 4.7202 *
11	* 1.7372	* 1.5570	* 1.6533	* 1.5519	* 1.7846	* 1.5798	* 1.7854	* .7443 *
	* 2.3186	* 2.6147	* 2.5377	* 2.8093	* 2.4455	* 2.7419	* 2.4087	* 5.4480 *
12	* 1.5635	* 1.7500	* 1.6291	* 1.7845	* 1.7258	* 1.7714	* 1.1979	*
	* 2.5525	* 2.3055	* 2.5889	* 2.4456	* 2.5215	* 2.4475	* 3.5816	*
13	* 1.7058	* 1.5910	* 1.7034	* 1.5793	* 1.7710	* 1.8566	* .7977	*
	* 2.3093	* 2.4846	* 2.4198	* 2.7427	* 2.4480	* 2.3157	* 5.3021	*
14	* 1.3216	* 1.7057	* 1.6413	* 1.7847	* 1.1971	* .7977	*	
	* 2.9072	* 2.3114	* 2.4717	* 2.4095	* 3.5837	* 5.3023	*	
15	* .6837	* .8753	* .8160	* .7440	* F-SUB-Q			
	* 5.4601	* 4.3524	* 4.7214	* 5.4500	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 258 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 14 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1666	* 1.7192	* 1.5328	* 1.7208	* 1.5399	* 1.6932	* 1.3010	* .6749 *
	* 3.8477	* 2.6359	* 2.8913	* 2.4821	* 2.7481	* 2.4647	* 3.1153	* 5.8145 *
9	* 1.7192	* 1.5035	* 1.7371	* 1.5352	* 1.7379	* 1.5748	* 1.6942	* .8587 *
	* 2.6359	* 3.0025	* 2.5431	* 2.8196	* 2.4646	* 2.6602	* 2.4614	* 4.6833 *
10	* 1.5328	* 1.7361	* 1.3786	* 1.6371	* 1.6109	* 1.6928	* 1.6315	* .7905 *
	* 2.8913	* 2.5476	* 3.2229	* 2.7243	* 2.7887	* 2.5875	* 2.6402	* 5.1553 *
11	* 1.7208	* 1.5330	* 1.6313	* 1.5335	* 1.7747	* 1.5662	* 1.7764	* .7215 *
	* 2.4821	* 2.8205	* 2.7334	* 2.9866	* 2.6308	* 2.9759	* 2.6143	* 5.9660 *
12	* 1.5399	* 1.7363	* 1.6094	* 1.7746	* 1.7109	* 1.7640	* 1.1724	*
	* 2.7481	* 2.4653	* 2.7914	* 2.6310	* 2.7363	* 2.6600	* 3.9548	*
13	* 1.6932	* 1.5741	* 1.6917	* 1.5657	* 1.7636	* 1.8508	* .7909	*
	* 2.4647	* 2.6611	* 2.5888	* 2.9772	* 2.6606	* 2.5294	* 5.8127	*
14	* 1.3010	* 1.6935	* 1.6308	* 1.7756	* 1.1714	* .7909	*	*
	* 3.1153	* 2.4621	* 2.6412	* 2.6153	* 3.9578	* 5.8129	*	*
15	* .6749	* .8586	* .7902	* .7211	* F-SUB-Q			
	* 5.8144	* 4.6837	* 5.1567	* 5.9682	* M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 13 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.1263	* 1.6724	* 1.4898	* 1.6755	* 1.4985	* 1.6518	* 1.2668	* .6547 *
	* 4.0100	* 2.7247	* 2.9400	* 2.5560	* 2.8405	* 2.5760	* 3.3195	* 6.3123 *
9	* 1.6724	* 1.4590	* 1.6908	* 1.4933	* 1.6952	* 1.5356	* 1.6544	* .8356 *
	* 2.7247	* 3.1101	* 2.5949	* 2.8975	* 2.5595	* 2.7942	* 2.6284	* 5.0887 *
10	* 1.4898	* 1.6898	* 1.3399	* 1.5941	* 1.5712	* 1.6526	* 1.5947	* .7696 *
	* 2.9400	* 2.5996	* 3.2899	* 2.7956	* 2.9002	* 2.7283	* 2.8297	* 5.6109 *
11	* 1.6755	* 1.4912	* 1.5884	* 1.4983	* 1.7354	* 1.5305	* 1.7372	* .7028 *
	* 2.5560	* 2.8986	* 2.8050	* 3.0798	* 2.7073	* 3.0623	* 2.7033	* 6.5368 *
12	* 1.4985	* 1.6936	* 1.5697	* 1.7353	* 1.6731	* 1.7259	* 1.1454	*
	* 2.8405	* 2.5604	* 2.9033	* 2.7075	* 2.8181	* 2.7403	* 4.1004	*
13	* 1.6518	* 1.5349	* 1.6515	* 1.5300	* 1.7255	* 1.8130	* .7711	*
	* 2.5760	* 2.7953	* 2.7300	* 3.0637	* 2.7410	* 2.6315	* 6.0952	*
14	* 1.2668	* 1.6537	* 1.5939	* 1.7363	* 1.1445	* .7711	*	*
	* 3.3195	* 2.6294	* 2.8310	* 2.7045	* 4.1038	* 6.0956	*	*
15	* .6547	* .8355	* .7693	* .7025	* F-SUB-Q			
	* 6.3123	* 5.0897	* 5.6131	* 6.5393	* M-SUB-Q			

CNEI-0400-25
Appendix A, Rev. 19
Page 259 of 311

F-SUB-O & M-SUB-O VALUES (F-SUB-O OP MARGIN) - POWER ESCALATION

	H	G	F	E	D	C	B	A
8	* 1.0804	* 1.6033	* 1.4331	* 1.6089	* 1.4429	* 1.5881	* 1.2220	* .6296
	* 4.1717	* 2.8013	* 2.9556	* 2.5774	* 2.8582	* 2.5961	* 3.3327	* 6.3583
9	* 1.6033	* 1.4018	* 1.6218	* 1.4378	* 1.6302	* 1.4791	* 1.5932	* .8075
	* 2.8013	* 3.1261	* 2.6153	* 2.9153	* 2.5806	* 2.8117	* 2.6466	* 5.1032
10	* 1.4331	* 1.6208	* 1.2994	* 1.5347	* 1.5151	* 1.5900	* 1.5375	* .7514
	* 2.9556	* 2.6200	* 3.2819	* 2.8099	* 2.9161	* 2.7493	* 2.8476	* 5.5725
11	* 1.6089	* 1.4358	* 1.5293	* 1.4490	* 1.6735	* 1.4770	* 1.6745	* .6860
	* 2.5774	* 2.9164	* 2.8193	* 3.1902	* 2.8231	* 3.1838	* 2.8094	* 6.5408
12	* 1.4429	* 1.6287	* 1.5136	* 1.6733	* 1.6171	* 1.6639	* 1.1162	*
	* 2.8582	* 2.5815	* 2.9192	* 2.8233	* 2.9383	* 2.8620	* 4.2235	*
13	* 1.5881	* 1.4784	* 1.5890	* 1.4765	* 1.6635	* 1.7505	* .7444	*
	* 2.5961	* 2.8129	* 2.7510	* 3.1853	* 2.8627	* 2.7494	* 6.3508	*
14	* 1.2220	* 1.5924	* 1.5367	* 1.6737	* 1.1154	* .7443	*	
	* 3.3327	* 2.6478	* 2.8491	* 2.8108	* 4.2265	* 6.3513	*	
15	* .6296	* .8073	* .7511	* .6856	* F-SUB-Q			
	* 6.3583	* 5.1044	* 5.5749	* 6.5444	* M-SUB-Q			

	H	G	F	E	D	C	B	A
8	* 1.0519	* 1.5753	* 1.3995	* 1.5828	* 1.4107	* 1.5645	* 1.1949	* .6169
	* 3.9861	* 2.6918	* 2.8899	* 2.5092	* 2.7996	* 2.5275	* 3.2679	* 6.2104
9	* 1.5753	* 1.3669	* 1.5942	* 1.4047	* 1.6048	* 1.4525	* 1.5712	* .7904
	* 2.6918	* 3.0565	* 2.5440	* 2.8555	* 2.5129	* 2.7476	* 2.5769	* 4.9995
10	* 1.3995	* 1.5933	* 1.2575	* 1.5020	* 1.4848	* 1.5673	* 1.5171	* .7251
	* 2.8899	* 2.5485	* 3.2446	* 2.7497	* 2.8578	* 2.6795	* 2.7779	* 5.5404
11	* 1.5828	* 1.4027	* 1.4967	* 1.4204	* 1.6509	* 1.4535	* 1.6545	* .6633
	* 2.5092	* 2.8566	* 2.7588	* 3.0486	* 2.6808	* 3.0286	* 2.6648	* 6.4349
12	* 1.4107	* 1.6033	* 1.4834	* 1.6508	* 1.5902	* 1.6445	* 1.0854	*
	* 2.7996	* 2.5137	* 2.8609	* 2.6810	* 2.8045	* 2.7082	* 4.0381	*
13	* 1.5645	* 1.4519	* 1.5663	* 1.4529	* 1.6441	* 1.7329	* .7340	*
	* 2.5275	* 2.7488	* 2.6812	* 3.0300	* 2.7088	* 2.5943	* 5.9540	*
14	* 1.1949	* 1.5704	* 1.5163	* 1.6537	* 1.0845	* .7339	*	*
	* 3.2679	* 2.5781	* 2.7793	* 2.6660	* 4.0416	* 5.9544	*	*
15	* .6169	* .7902	* .7247	* .6629	* F-SUB-Q			
	* 6.2104	* 5.0007	* 5.5429	* 6.4381	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 260 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 10 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* 1.0109	* 1.5284	* 1.3549	* 1.5375	* 1.3668	* 1.5218	* 1.1589	* .5954 *
	* 3.6724	* 2.4546	* 2.6763	* 2.3273	* 2.6047	* 2.3477	* 3.0448	* 5.8039 *
9	* 1.5284	* 1.3215	* 1.5474	* 1.3604	* 1.5601	* 1.4115	* 1.5304	* .7657 *
	* 2.4546	* 2.8228	* 2.3525	* 2.6525	* 2.3318	* 2.5547	* 2.3909	* 4.6466 *
10	* 1.3549	* 1.5464	* 1.2142	* 1.4557	* 1.4409	* 1.5252	* 1.4790	* .7006 *
	* 2.6763	* 2.3566	* 3.0120	* 2.5470	* 2.6466	* 2.4773	* 2.5668	* 5.1517 *
11	* 1.5375	* 1.3586	* 1.4505	* 1.3806	* 1.6087	* 1.4147	* 1.6141	* .6411 *
	* 2.3273	* 2.6533	* 2.5553	* 2.7813	* 2.4396	* 2.7614	* 2.4230	* 5.9229 *
12	* 1.3668	* 1.5587	* 1.4395	* 1.6086	* 1.5483	* 1.6041	* 1.0534	*
	* 2.6047	* 2.3326	* 2.6493	* 2.4398	* 2.5547	* 2.4656	* 3.6955	*
13	* 1.5218	* 1.4109	* 1.5242	* 1.4142	* 1.6037	* 1.6936	* .7123	*
	* 2.3477	* 2.5558	* 2.4789	* 2.7627	* 2.4662	* 2.3611	* 5.4594	*
14	* 1.1589	* 1.5296	* 1.4782	* 1.6133	* 1.0525	* .7123	*	
	* 3.0448	* 2.3920	* 2.5681	* 2.4242	* 3.6987	* 5.4598	*	
15	* .5954	* .7656	* .7003	* .6407	* F-SUB-Q			
	* 5.8039	* 4.6476	* 5.1541	* 5.9260	* M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 9 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9734	* 1.4743	* 1.3063	* 1.4848	* 1.3189	* 1.4708	* 1.1192	* .5749 *
	* 3.3878	* 2.2574	* 2.4305	* 2.1147	* 2.3686	* 2.1344	* 2.7738	* 5.2987 *
9	* 1.4743	* 1.2730	* 1.4932	* 1.3123	* 1.5077	* 1.3639	* 1.4807	* .7399 *
	* 2.2574	* 2.5633	* 2.1346	* 2.4106	* 2.1186	* 2.3218	* 2.1727	* 4.2337 *
10	* 1.3063	* 1.4923	* 1.1737	* 1.4053	* 1.3924	* 1.4749	* 1.4318	* .6783 *
	* 2.4305	* 2.1383	* 2.7287	* 2.3075	* 2.3978	* 2.2470	* 2.3283	* 4.6830 *
11	* 1.4848	* 1.3105	* 1.4004	* 1.3356	* 1.5576	* 1.3691	* 1.5628	* .6205 *
	* 2.1147	* 2.4113	* 2.3150	* 2.5575	* 2.2471	* 2.5475	* 2.2337	* 5.4464 *
12	* 1.3189	* 1.5063	* 1.3911	* 1.5574	* 1.4993	* 1.5536	* 1.0213	*
	* 2.3686	* 2.1195	* 2.4004	* 2.2473	* 2.3522	* 2.2721	* 3.4053	*
13	* 1.4708	* 1.3632	* 1.4739	* 1.3685	* 1.5532	* 1.6416	* .6893	*
	* 2.1344	* 2.3228	* 2.2484	* 2.5488	* 2.2727	* 2.1745	* 5.0450	*
14	* 1.1192	* 1.4799	* 1.4310	* 1.5620	* 1.0203	* .6892	*	
	* 2.7738	* 2.1738	* 2.3295	* 2.2348	* 3.4083	* 5.0453	*	
15	* .5749	* .7397	* .6780	* .6202	* F-SUB-Q			
	* 5.2987	* 4.2347	* 4.6852	* 5.4496	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 261 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 8 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9315	* 1.4090	* 1.2518	* 1.4203	* 1.2643	* 1.4077	* 1.0744	* .5503
	* 3.1389	* 2.0931	* 2.2438	* 1.9593	* 2.1903	* 1.9789	* 2.5669	* 4.9288
9	* 1.4090	* 1.2191	* 1.4277	* 1.2581	* 1.4433	* 1.3074	* 1.4189	* .7133
	* 2.0931	* 2.3645	* 1.9747	* 2.2270	* 1.9628	* 2.1480	* 2.0130	* 3.9035
10	* 1.2518	* 1.4266	* 1.1341	* 1.3474	* 1.3359	* 1.4124	* 1.3731	* .6598
	* 2.2438	* 1.9780	* 2.4960	* 2.1256	* 2.2082	* 2.0772	* 2.1508	* 4.2758
11	* 1.4203	* 1.2564	* 1.3428	* 1.2840	* 1.4937	* 1.3138	* 1.4983	* .6035
	* 1.9593	* 2.2277	* 2.1324	* 2.3654	* 2.0895	* 2.3606	* 2.0712	* 4.9528
12	* 1.2643	* 1.4420	* 1.3346	* 1.4936	* 1.4408	* 1.4892	* .9887	*
	* 2.1903	* 1.9636	* 2.2106	* 2.0896	* 2.1840	* 2.1187	* 3.1402	*
13	* 1.4077	* 1.3068	* 1.4115	* 1.3133	* 1.4889	* 1.5753	* .6617	*
	* 1.9789	* 2.1489	* 2.0785	* 2.3618	* 2.1192	* 2.0274	* 4.7118	*
14	* 1.0744	* 1.4182	* 1.3723	* 1.4974	* .9879	* .6616	*	*
	* 2.5669	* 2.0140	* 2.1519	* 2.0722	* 3.1427	* 4.7122	*	*
15	* .5503	* .7131	* .6595	* .6032	* F-SUB-Q			
	* 4.9288	* 3.9046	* 4.2779	* 4.9557	* M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 7 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .9075	* 1.3828	* 1.2195	* 1.3941	* 1.2323	* 1.3829	* 1.0465	* .5380
	* 2.8797	* 1.8860	* 2.0565	* 1.7875	* 2.0116	* 1.8058	* 2.3649	* 4.5319
9	* 1.3828	* 1.1868	* 1.4014	* 1.2256	* 1.4170	* 1.2795	* 1.3941	* .6935
	* 1.8860	* 2.1647	* 1.7966	* 2.0439	* 1.7902	* 1.9651	* 1.8334	* 3.6031
10	* 1.2195	* 1.4003	* 1.0937	* 1.3159	* 1.3048	* 1.3880	* 1.3487	* .6320
	* 2.0565	* 1.7997	* 2.3126	* 1.9392	* 2.0142	* 1.8883	* 1.9576	* 4.0018
11	* 1.3941	* 1.2240	* 1.3113	* 1.2529	* 1.4677	* 1.2866	* 1.4734	* .5786
	* 1.7875	* 2.0445	* 1.9455	* 2.1393	* 1.9011	* 2.1572	* 1.8721	* 4.6064
12	* 1.2323	* 1.4157	* 1.3035	* 1.4676	* 1.4104	* 1.4651	* .9546	*
	* 2.0116	* 1.7909	* 2.0164	* 1.9012	* 1.9863	* 1.9228	* 2.9183	*
13	* 1.3829	* 1.2789	* 1.3871	* 1.2861	* 1.4648	* 1.5505	* .6475	*
	* 1.8058	* 1.9660	* 1.8895	* 2.1583	* 1.9232	* 1.8393	* 4.3093	*
14	* 1.0465	* 1.3934	* 1.3479	* 1.4725	* .9537	* .6474	*	*
	* 2.3649	* 1.8344	* 1.9587	* 1.8731	* 2.9211	* 4.3096	*	*
15	* .5380	* .6933	* .6317	* .5782	* F-SUB-Q			
	* 4.5319	* 3.6040	* 4.0038	* 4.6091	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 262 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 6 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .8755 *	* 1.3357 *	* 1.1770 *	* 1.3466 *	* 1.1894 *	* 1.3363 *	* 1.0100 *	* .5196 *
	* 2.6513 *	* 1.7581 *	* 1.9245 *	* 1.6766 *	* 1.8887 *	* 1.6954 *	* 2.2256 *	* 4.2691 *
9	* 1.3357 *	* 1.1450 *	* 1.3541 *	* 1.1834 *	* 1.3696 *	* 1.2358 *	* 1.3472 *	* .6702 *
	* 1.7581 *	* 2.0187 *	* 1.6795 *	* 1.9165 *	* 1.6788 *	* 1.8439 *	* 1.7184 *	* 3.3856 *
10	* 1.1770 *	* 1.3527 *	* 1.0569 *	* 1.2725 *	* 1.2613 *	* 1.3417 *	* 1.3027 *	* .6096 *
	* 1.9245 *	* 1.6823 *	* 2.1609 *	* 1.8070 *	* 1.8751 *	* 1.7635 *	* 1.8306 *	* 3.7615 *
11	* 1.3466 *	* 1.1819 *	* 1.2681 *	* 1.2108 *	* 1.4192 *	* 1.2425 *	* 1.4236 *	* .5580 *
	* 1.6766 *	* 1.9170 *	* 1.8128 *	* 1.9952 *	* 1.7531 *	* 1.9990 *	* 1.7428 *	* 4.2950 *
12	* 1.1894 *	* 1.3684 *	* 1.2601 *	* 1.4191 *	* 1.3641 *	* 1.4163 *	* .9207 *	
	* 1.8887 *	* 1.6794 *	* 1.8771 *	* 1.7532 *	* 1.8315 *	* 1.7779 *	* 2.7009 *	
13	* 1.3363 *	* 1.2352 *	* 1.3409 *	* 1.2420 *	* 1.4159 *	* 1.4980 *	* .6245 *	
	* 1.6954 *	* 1.8447 *	* 1.7646 *	* 2.0001 *	* 1.7783 *	* 1.7076 *	* 4.0094 *	
14	* 1.0100 *	* 1.3464 *	* 1.3020 *	* 1.4227 *	* .9198 *	* .6244 *		
	* 2.2256 *	* 1.7193 *	* 1.8316 *	* 1.7437 *	* 2.7035 *	* 4.0097 *		
15	* .5196 *	* .6700 *	* .6093 *	* .5576 *	F-SUB-Q			
	* 4.2691 *	* 3.3864 *	* 3.7634 *	* 4.2976 *	M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 5 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .8343 *	* 1.2637 *	* 1.1219 *	* 1.2736 *	* 1.1335 *	* 1.2639 *	* .9633 *	* .4932 *
	* 2.5491 *	* 1.6754 *	* 1.8459 *	* 1.6272 *	* 1.8200 *	* 1.6473 *	* 2.1477 *	* 4.1463 *
9	* 1.2637 *	* 1.0924 *	* 1.2811 *	* 1.1291 *	* 1.2971 *	* 1.1731 *	* 1.2742 *	* .6413 *
	* 1.6754 *	* 1.9228 *	* 1.6236 *	* 1.8403 *	* 1.6291 *	* 1.7832 *	* 1.6677 *	* 3.2530 *
10	* 1.1219 *	* 1.2795 *	* 1.0225 *	* 1.2139 *	* 1.2035 *	* 1.2696 *	* 1.2310 *	* .5919 *
	* 1.8459 *	* 1.6263 *	* 2.0423 *	* 1.7289 *	* 1.7895 *	* 1.7020 *	* 1.7692 *	* 3.5569 *
11	* 1.2736 *	* 1.1277 *	* 1.2099 *	* 1.1551 *	* 1.3438 *	* 1.1790 *	* 1.3438 *	* .5413 *
	* 1.6272 *	* 1.8416 *	* 1.7344 *	* 1.8960 *	* 1.6877 *	* 1.9250 *	* 1.6775 *	* 4.0285 *
12	* 1.1335 *	* 1.2960 *	* 1.2023 *	* 1.3437 *	* 1.2986 *	* 1.3386 *	* .8853 *	
	* 1.8200 *	* 1.6297 *	* 1.7914 *	* 1.6878 *	* 1.7498 *	* 1.7114 *	* 2.5668 *	
13	* 1.2639 *	* 1.1725 *	* 1.2689 *	* 1.1785 *	* 1.3383 *	* 1.4119 *	* .5909 *	
	* 1.6473 *	* 1.7840 *	* 1.7031 *	* 1.9259 *	* 1.7118 *	* 1.6427 *	* 3.8576 *	
14	* .9633 *	* 1.2734 *	* 1.2303 *	* 1.3430 *	* .8846 *	* .5909 *		
	* 2.1477 *	* 1.6686 *	* 1.7702 *	* 1.6784 *	* 2.5689 *	* 3.8579 *		
15	* .4932 *	* .6412 *	* .5916 *	* .5410 *	F-SUB-Q			
	* 4.1463 *	* 3.2538 *	* 3.5587 *	* 4.0308 *	M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 263 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 4 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .8124	* 1.2233	* 1.0859	* 1.2300	* 1.0962	* 1.2222	* .9301	* .4778
	* 2.3760	* 1.5906	* 1.7642	* 1.5657	* 1.7491	* 1.5847	* 2.0716	* 3.9962
9	* 1.2233	* 1.0588	* 1.2375	* 1.0915	* 1.2540	* 1.1343	* 1.2305	* .6194
	* 1.5906	* 1.8252	* 1.5568	* 1.7651	* 1.5666	* 1.7134	* 1.6004	* 3.1362
10	* 1.0859	* 1.2369	* .9812	* 1.1739	* 1.1660	* 1.2293	* 1.1862	* .5646
	* 1.7642	* 1.5592	* 1.9713	* 1.6531	* 1.7024	* 1.6225	* 1.6956	* 3.4657
11	* 1.2300	* 1.0902	* 1.1702	* 1.1140	* 1.2983	* 1.1385	* 1.2941	* .5152
	* 1.5657	* 1.7662	* 1.6582	* 1.8152	* 1.6123	* 1.8191	* 1.5969	* 3.9130
12	* 1.0962	* 1.2530	* 1.1650	* 1.2982	* 1.2583	* 1.2942	* .8435	*
	* 1.7491	* 1.5672	* 1.7041	* 1.6115	* 1.6713	* 1.6395	* 2.4781	*
13	* 1.2222	* 1.1338	* 1.2285	* 1.1381	* 1.2938	* 1.3561	* .5702	*
	* 1.5847	* 1.7142	* 1.6235	* 1.8200	* 1.6399	* 1.5862	* 3.7186	*
14	* .9301	* 1.2299	* 1.1855	* 1.2934	* .8427	* .5701	*	*
	* 2.0716	* 1.6013	* 1.6966	* 1.5978	* 2.4804	* 3.7190	*	*
15	* .4778	* .6192	* .5643	* .5149	* F-SUB-Q			
	* 3.9962	* 3.1369	* 3.4674	* 3.9153	* M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 3 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .7786	* 1.1457	* 1.0176	* 1.1489	* 1.0220	* 1.1440	* .8725	* .4460
	* 2.3086	* 1.5810	* 1.7637	* 1.5779	* 1.7736	* 1.5948	* 2.0854	* 4.0545
9	* 1.1457	* .9991	* 1.1549	* 1.0157	* 1.1705	* 1.0624	* 1.1515	* .5837
	* 1.5810	* 1.8027	* 1.5638	* 1.7734	* 1.5769	* 1.7239	* 1.6134	* 3.1426
10	* 1.0176	* 1.1545	* .9147	* 1.0823	* 1.0883	* 1.1548	* 1.1159	* .5371
	* 1.7637	* 1.5643	* 1.9794	* 1.6841	* 1.7087	* 1.6180	* 1.6816	* 3.4356
11	* 1.1489	* 1.0147	* 1.0791	* 1.0333	* 1.2152	* 1.0660	* 1.1929	* .4854
	* 1.5779	* 1.7749	* 1.6889	* 1.8445	* 1.5932	* 1.8115	* 1.6174	* 3.8940
12	* 1.0220	* 1.1697	* 1.0874	* 1.2151	* 1.1867	* 1.2118	* .7836	*
	* 1.7736	* 1.5773	* 1.7103	* 1.5933	* 1.6355	* 1.6167	* 2.4831	*
13	* 1.1440	* 1.0619	* 1.1541	* 1.0656	* 1.2115	* 1.2517	* .5338	*
	* 1.5948	* 1.7247	* 1.6190	* 1.8124	* 1.6170	* 1.5888	* 3.6825	*
14	* .8725	* 1.1509	* 1.1153	* 1.1922	* .7830	* .5337	*	*
	* 2.0854	* 1.6142	* 1.6825	* 1.6182	* 2.4851	* 3.6830	*	*
15	* .4460	* .5835	* .5368	* .4851	* F-SUB-Q			
	* 4.0545	* 3.1434	* 3.4374	* 3.8962	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 264 of 311

TABLE 5 (CONTINUED)

F-SUB-Q & M-SUB-Q VALUES (F-SUB-Q OP MARGIN) - POWER ESCALATION

AT 30% POWER, 4 EFPD, THIS IS LEVEL 2 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .6903	* 1.0753	* .8278	* 1.0579	* .8339	* 1.0468	* .7319	* .3762
	* 2.4647	* 1.5925	* 2.0584	* 1.6280	* 2.0620	* 1.6619	* 2.3817	* 4.6060
9	* 1.0753	* .8120	* 1.0830	* .8163	* 1.0800	* .9036	* 1.0428	* .4962
	* 1.5925	* 2.0984	* 1.5830	* 2.0991	* 1.6214	* 1.9278	* 1.6937	* 3.5319
10	* .8278	* 1.0827	* .7906	* .8855	* .9097	* 1.0541	* 1.0363	* .4707
	* 2.0584	* 1.5833	* 2.1661	* 1.9569	* 1.9449	* 1.6906	* 1.7196	* 3.7505
11	* 1.0579	* .8162	* .8834	* .8709	* 1.0926	* .9115	* 1.0018	* .4122
	* 1.6280	* 2.0997	* 1.9614	* 2.0904	* 1.6728	* 2.0120	* 1.8235	* 4.3602
12	* .8339	* 1.0794	* .9090	* 1.0923	* 1.0118	* 1.1360	* .6605	*
	* 2.0620	* 1.6220	* 1.9464	* 1.6732	* 1.8121	* 1.6333	* 2.7923	*
13	* 1.0468	* .9031	* 1.0536	* .9112	* 1.1357	* 1.0407	* .4552	*
	* 1.6619	* 1.9287	* 1.6915	* 2.0127	* 1.6336	* 1.8010	* 4.0893	*
14	* .7319	* 1.0422	* 1.0358	* 1.0013	* .6601	* .4551	*	*
	* 2.3817	* 1.6946	* 1.7205	* 1.8244	* 2.7943	* 4.0900	*	*
15	* .3762	* .4960	* .4704	* .4120	* F-SUB-Q			
	* 4.6060	* 3.5330	* 3.7525	* 4.3627	* M-SUB-Q			

AT 30% POWER, 4 EFPD, THIS IS LEVEL 1 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
8	* .5021	* .4286	* .3773	* .4297	* .3790	* .4250	* .3336	* .2548
	* 3.2243	* 3.7571	* 4.2774	* 3.7707	* 4.3126	* 3.8609	* 4.9497	* 6.4943
9	* .4286	* .3741	* .4269	* .3747	* .4373	* .3917	* .3862	* .2272
	* 3.7571	* 4.3139	* 3.7809	* 4.3477	* 3.7712	* 4.1982	* 4.3110	* 7.3610
10	* .3773	* .4270	* .3815	* .3675	* .3921	* .4347	* .4006	* .2215
	* 4.2774	* 3.7792	* 4.2495	* 4.4926	* 4.2784	* 3.8510	* 4.1938	* 7.5585
11	* .4297	* .3748	* .3672	* .3995	* .4491	* .3977	* .3690	* .1953
	* 3.7708	* 4.3476	* 4.4962	* 4.3062	* 3.8305	* 4.3283	* 4.6329	* 8.7312
12	* .3790	* .4370	* .3919	* .4490	* .4216	* .4238	* .2961	*
	* 4.3126	* 3.7726	* 4.2807	* 3.8311	* 4.1022	* 4.1195	* 5.8928	*
13	* .4250	* .3915	* .4345	* .3976	* .4237	* .3860	* .3084	*
	* 3.8609	* 4.1996	* 3.8530	* 4.3304	* 4.1203	* 4.5606	* 5.7276	*
14	* .3336	* .3860	* .4004	* .3688	* .2962	* .3084	*	*
	* 4.9497	* 4.3133	* 4.1960	* 4.6352	* 5.8917	* 5.7292	*	*
15	* .2548	* .2271	* .2214	* .1952	* F-SUB-Q			
	* 6.4943	* 7.3646	* 7.5624	* 8.7360	* M-SUB-Q			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 289 of 311

TABLE 7

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 24 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.6250	2.9773	3.6395	3.1160	3.7638	3.2559	4.2264	5.1450
9*	2.9773	3.5743	3.0712	3.7389	3.1545	3.7448	3.6116	5.9795
10*	3.6395	3.0673	3.6792	3.8250	3.7243	3.1934	3.4860	6.3572
11*	3.1161	3.7379	3.8276	3.6791	3.0838	3.6857	3.7707	7.0425
12*	3.7638	3.1551	3.7249	3.0840	3.4738	3.3030	4.7968	
13*	3.2559	3.7451	3.1937	3.6859	3.3031	3.6321	4.4097	
14*	4.2264	3.6099	3.4854	3.7707	4.7942	4.4111		
15 *	5.1450	5.9767	6.3547	7.0420				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 23 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.0940	1.4330	1.9301	1.5155	1.9887	1.5719	2.2296	3.8985
9*	1.4330	1.9074	1.4573	1.9768	1.5276	1.9090	1.5816	3.0614
10*	1.9301	1.4573	1.9981	1.8775	1.8509	1.5621	1.5857	3.1678
11*	1.5155	1.9777	1.8792	1.9509	1.5062	1.8822	1.6469	3.5369
12*	1.9887	1.5279	1.8512	1.5063	1.7115	1.4570	2.4619	
13*	1.5719	1.9093	1.5622	1.8823	1.4571	1.5949	3.4025	
14*	2.2296	1.5811	1.5855	1.6469	2.4622	3.4027		
15 *	3.8985	3.0600	3.1669	3.5368				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 290 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 22 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	1.9405	1.4479	1.7142	1.4765	1.7716	1.5219	2.0252	3.4525
9*	1.4479	1.7067	1.4542	1.7416	1.4790	1.7162	1.5187	2.7750
10*	1.7142	1.4540	1.8126	1.6191	1.6420	1.5020	1.5520	2.8449
11*	1.4765	1.7429	1.6228	1.7525	1.4332	1.7033	1.4697	3.1153
12*	1.7716	1.4796	1.6427	1.4332	1.5454	1.4386	2.1834	
13*	1.5219	1.7165	1.5023	1.7034	1.4387	1.4147	3.0532	
14*	2.0252	1.5184	1.5520	1.4697	2.1838	3.0531		
15 *	3.4525	2.7741	2.8443	3.1153				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 21 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	1.8966	1.3882	1.6247	1.4103	1.6700	1.4456	1.9030	3.2934
9*	1.3882	1.6228	1.3907	1.6278	1.4090	1.6441	1.4454	2.6961
10*	1.6247	1.3911	1.7259	1.5307	1.5701	1.4365	1.4851	2.7682
11*	1.4103	1.6311	1.5347	1.6583	1.3667	1.6329	1.3807	3.0107
12*	1.6700	1.4097	1.5709	1.3667	1.4844	1.3707	2.1147	
13*	1.4456	1.6446	1.4368	1.6331	1.3708	1.3230	2.8935	
14*	1.9030	1.4454	1.4853	1.3808	2.1156	2.8934		
15 *	3.2934	2.6958	2.7679	3.0109				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 291 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 20 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	1.9446	1.3951	1.6472	1.4075	1.6571	1.4392	1.9124	3.3436
9*	1.3951	1.6529	1.3900	1.6417	1.4060	1.6420	1.4355	2.7161
10*	1.6472	1.3904	1.7409	1.5389	1.5857	1.4384	1.4815	2.7569
11*	1.4075	1.6450	1.5432	1.6611	1.3649	1.6370	1.3732	3.0141
12*	1.6571	1.4067	1.5867	1.3649	1.4890	1.3683	2.1240	
13*	1.4392	1.6426	1.4389	1.6372	1.3684	1.3081	2.8975	
14*	1.9124	1.4356	1.4817	1.3733	2.1251	2.8975		
15 *	3.3436	2.7159	2.7567	3.0144				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 19 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.0121	1.4262	1.6924	1.4397	1.7002	1.4712	1.9667	3.4635
9*	1.4262	1.7025	1.4217	1.6906	1.4341	1.6810	1.4618	2.7930
10*	1.6924	1.4221	1.7887	1.5793	1.6213	1.4668	1.5035	2.8074
11*	1.4397	1.6942	1.5839	1.6972	1.3952	1.6744	1.3946	3.0627
12*	1.7002	1.4350	1.6224	1.3952	1.5239	1.4002	2.1696	
13*	1.4712	1.6817	1.4674	1.6747	1.4004	1.3303	2.9738	
14*	1.9667	1.4620	1.5037	1.3948	2.1706	2.9739		
15 *	3.4635	2.7930	2.8073	3.0632				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 292 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 18 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
*****	*****	*****	*****	*****	*****	*****	*****	*****
8*	2.0921	1.4680	1.7533	1.4808	1.7579	1.5105	2.0316	3.5796
9*	1.4680	1.7685	1.4629	1.7520	1.4696	1.7285	1.4956	2.8813
10*	1.7533	1.4634	1.8566	1.6317	1.6688	1.5002	1.5339	2.9102
11*	1.4808	1.7541	1.6365	1.7487	1.4226	1.7081	1.4190	3.1613
12*	1.7579	1.4706	1.6700	1.4227	1.5533	1.4239	2.2312	
13*	1.5105	1.7291	1.5007	1.7084	1.4241	1.3504	3.0333	
14*	2.0316	1.4958	1.5342	1.4192	2.2327	3.0334		
15 *	3.5796	2.8814	2.9102	3.1619				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 17 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
*****	*****	*****	*****	*****	*****	*****	*****	*****
8*	2.2303	1.5400	1.8405	1.5454	1.8332	1.5679	2.1124	3.7556
9*	1.5400	1.8636	1.5297	1.8347	1.5324	1.7951	1.5505	3.0044
10*	1.8405	1.5310	1.9545	1.7099	1.7506	1.5676	1.5978	3.0320
11*	1.5454	1.8371	1.7152	1.8305	1.4848	1.7827	1.4752	3.3138
12*	1.8332	1.5334	1.7519	1.4849	1.6221	1.4851	2.3322	
13*	1.5679	1.7956	1.5681	1.7831	1.4853	1.4015	3.1625	
14*	2.1124	1.5508	1.5981	1.4756	2.3339	3.1626		
15 *	3.7556	3.0046	3.0321	3.3146				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 293 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 16 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.3711	1.6184	1.9414	1.6208	1.9285	1.6382	2.2170	3.9471
9*	1.6184	1.9699	1.6052	1.9309	1.6009	1.8780	1.6158	3.1497
10*	1.9414	1.6076	2.0596	1.7964	1.8341	1.6372	1.6648	3.1874
11*	1.6208	1.9334	1.8020	1.9252	1.5617	1.8747	1.5388	3.4728
12*	1.9285	1.6020	1.8355	1.5618	1.7148	1.5648	2.4600	
13*	1.6382	1.8786	1.6379	1.8751	1.5650	1.4750	3.3320	
14*	2.2170	1.6162	1.6652	1.5391	2.4618	3.3321		
15 *	3.9471	3.1500	3.1876	3.4737				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 15 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.5596	1.7601	2.1030	1.7572	2.0813	1.7692	2.3779	4.2649
9*	1.7601	2.1331	1.7430	2.0856	1.7294	2.0214	1.7355	3.3841
10*	2.1030	1.7461	2.2148	1.9404	1.9738	1.7645	1.7856	3.3933
11*	1.7572	2.0883	1.9464	2.0667	1.6825	2.0121	1.6490	3.6951
12*	2.0813	1.7307	1.9754	1.6826	1.8414	1.6832	2.6054	
13*	1.7692	2.0221	1.7651	2.0126	1.6834	1.5797	3.6007	
14*	2.3779	1.7359	1.7861	1.6494	2.6070	3.6009		
15 *	4.2649	3.3846	3.3936	3.6960				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 294 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 14 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.6954	1.8339	2.2049	1.8361	2.1982	1.8535	2.5108	4.4632
9*	1.8339	2.2428	1.8204	2.2090	1.8219	2.1268	1.8192	3.5663
10*	2.2049	1.8212	2.3525	2.0559	2.0992	1.8578	1.8836	3.6133
11*	1.8361	2.2121	2.0617	2.2056	1.7808	2.1341	1.7388	3.9493
12*	2.1982	1.8232	2.1009	1.7808	1.9562	1.7757	2.7965	
13*	1.8535	2.1275	1.8586	2.1346	1.7760	1.6646	3.7913	
14*	2.5108	1.8196	1.8841	1.7393	2.7987	3.7915		
15 *	4.4632	3.5668	3.6136	3.9503				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 13 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.7581	1.8754	2.2541	1.8838	2.2584	1.9174	2.6389	4.6922
9*	1.8754	2.2942	1.8646	2.2676	1.8807	2.2105	1.9205	3.7632
10*	2.2541	1.8653	2.4134	2.1039	2.1680	1.9332	1.9965	3.8096
11*	1.8838	2.2706	2.1105	2.2679	1.8747	2.2615	1.8516	4.1791
12*	2.2584	1.8822	2.1701	1.8748	2.0739	1.8951	2.9909	
13*	1.9174	2.2113	1.9342	2.2624	1.8954	1.7828	4.0662	
14*	2.6389	1.9211	1.9972	1.8521	2.9933	4.0664		
15 *	4.6922	3.7637	3.8099	4.1801				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 295 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 12 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.7730	1.8790	2.2496	1.8847	2.2663	1.9394	2.6626	4.7952
9*	1.8790	2.2931	1.8665	2.2660	1.8950	2.2356	1.9397	3.8361
10*	2.2496	1.8674	2.3953	2.1128	2.1890	1.9588	2.0170	3.8523
11*	1.8847	2.2673	2.1187	2.2816	1.8981	2.2875	1.8744	4.2501
12*	2.2663	1.8965	2.1909	1.8982	2.0934	1.9187	3.0019	
13*	1.9394	2.2364	1.9599	2.2884	1.9191	1.8257	4.1916	
14*	2.6626	1.9403	2.0178	1.8750	3.0041	4.1919		
15 *	4.7952	3.8370	3.8529	4.2515				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 11 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.7293	1.8315	2.2044	1.8313	2.2125	1.8777	2.6008	4.6470
9*	1.8315	2.2524	1.8157	2.2174	1.8404	2.1800	1.8929	3.7268
10*	2.2044	1.8165	2.3628	2.0671	2.1437	1.9073	1.9733	3.7901
11*	1.8313	2.2186	2.0728	2.2356	1.8593	2.2558	1.8435	4.1922
12*	2.2125	1.8418	2.1457	1.8594	2.0674	1.8866	3.0001	
13*	1.8777	2.1808	1.9083	2.2567	1.8869	1.7979	4.1006	
14*	2.6008	1.8935	1.9740	1.8442	3.0027	4.1009		
15 *	4.6470	3.7277	3.7908	4.1937				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 296 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 10 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
*****	*****	*****	*****	*****	*****	*****	*****	*****
8*	2.5969	1.7353	2.0932	1.7365	2.1051	1.7813	2.4648	4.4153
9*	1.7353	2.1403	1.7212	2.1082	1.7459	2.0614	1.7821	3.5389
10*	2.0932	1.7220	2.2477	1.9640	2.0342	1.7999	1.8546	3.6035
11*	1.7365	2.1093	1.9694	2.1201	1.7599	2.1244	1.7302	3.9612
12*	2.1051	1.7472	2.0362	1.7600	1.9589	1.7756	2.8171	
13*	1.7813	2.0622	1.8009	2.1253	1.7759	1.6924	3.8363	
14*	2.4648	1.7827	1.8553	1.7308	2.8196	3.8366		
15 *	4.4153	3.5398	3.6041	3.9628				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 9 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
*****	*****	*****	*****	*****	*****	*****	*****	*****
8*	2.4698	1.6404	1.9801	1.6410	1.9896	1.6801	2.3297	4.1975
9*	1.6404	2.0268	1.6266	1.9939	1.6478	1.9430	1.6768	3.3481
10*	1.9801	1.6273	2.1225	1.8521	1.9167	1.6957	1.7453	3.4052
11*	1.6410	1.9950	1.8572	1.9977	1.6506	1.9955	1.6210	3.7359
12*	1.9896	1.6490	1.9185	1.6507	1.8353	1.6644	2.6436	
13*	1.6801	1.9438	1.6967	1.9964	1.6647	1.5809	3.6136	
14*	2.3297	1.6774	1.7460	1.6216	2.6461	3.6139		
15 *	4.1975	3.3491	3.4060	3.7375				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 297 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 8 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
*****	*****	*****	*****	*****	*****	*****	*****	*****
8*	2.3738	1.5716	1.8918	1.5724	1.9016	1.6088	2.2259	4.0486
9*	1.5716	1.9381	1.5578	1.9053	1.5770	1.8552	1.5981	3.1990
10*	1.8918	1.5585	2.0168	1.7651	1.8253	1.6198	1.6622	3.2305
11*	1.5724	1.9063	1.7700	1.9035	1.5689	1.8975	1.5402	3.5414
12*	1.9016	1.5783	1.8270	1.5690	1.7369	1.5814	2.4934	
13*	1.6088	1.8560	1.6207	1.8984	1.5817	1.4947	3.4610	
14*	2.2259	1.5988	1.6629	1.5408	2.4955	3.4613		
15 *	4.0486	3.2000	3.2313	3.5429				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 7 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
*****	*****	*****	*****	*****	*****	*****	*****	*****
8*	2.2374	1.4745	1.7898	1.4765	1.7995	1.5088	2.1094	3.8258
9*	1.4745	1.8356	1.4618	1.8036	1.4791	1.7461	1.4972	3.0295
10*	1.7898	1.4625	1.9215	1.6621	1.7166	1.5165	1.5546	3.0940
11*	1.4765	1.8046	1.6669	1.7898	1.4586	1.7754	1.4359	3.3799
12*	1.7995	1.4803	1.7180	1.4587	1.6161	1.4675	2.3706	
13*	1.5088	1.7468	1.5174	1.7761	1.4678	1.3856	3.2241	
14*	2.1094	1.4978	1.5552	1.4365	2.3729	3.2244		
15 *	3.8258	3.0304	3.0947	3.3814				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 298 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 6 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
*****	*****	*****	*****	*****	*****	*****	*****	*****
8*	2.1354	1.4026	1.7055	1.4072	1.7194	1.4433	2.0287	3.6939
9*	1.4026	1.7492	1.3915	1.7200	1.4093	1.6752	1.4328	2.9165
10*	1.7055	1.3921	1.8320	1.5791	1.6356	1.4518	1.4864	2.9857
11*	1.4072	1.7218	1.5837	1.6997	1.3880	1.6929	1.3687	3.2566
12*	1.7194	1.4104	1.6369	1.3881	1.5333	1.3959	2.2683	
13*	1.4433	1.6759	1.4526	1.6935	1.3962	1.3152	3.0907	
14*	2.0287	1.4334	1.4870	1.3693	2.2706	3.0910		
15 *	3.6939	2.9174	2.9864	3.2580				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 5 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A
*****	*****	*****	*****	*****	*****	*****	*****	*****
8*	2.0910	1.3741	1.6568	1.3797	1.6703	1.4103	1.9784	3.6537
9*	1.3741	1.6983	1.3636	1.6689	1.3783	1.6342	1.4074	2.8608
10*	1.6568	1.3642	1.7674	1.5312	1.5839	1.4165	1.4585	2.9022
11*	1.3797	1.6711	1.5356	1.6534	1.3595	1.6539	1.3410	3.1743
12*	1.6703	1.3793	1.5851	1.3595	1.4909	1.3685	2.1902	
13*	1.4103	1.6349	1.4172	1.6544	1.3687	1.2867	3.0709	
14*	1.9784	1.4080	1.4592	1.3416	2.1922	3.0712		
15 *	3.6537	2.8617	2.9029	3.1758				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 299 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 4 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.0180	1.3259	1.5987	1.3346	1.6127	1.3611	1.9151	3.5516
9*	1.3259	1.6369	1.3187	1.6126	1.3320	1.5764	1.3602	2.7856
10*	1.5987	1.3192	1.7297	1.4781	1.5245	1.3646	1.4147	2.8741
11*	1.3346	1.6144	1.4823	1.6049	1.3115	1.5995	1.2991	3.1517
12*	1.6127	1.3330	1.5257	1.3115	1.4360	1.3208	2.1509	
13*	1.3611	1.5770	1.3653	1.6000	1.3211	1.2470	2.9984	
14*	1.9151	1.3607	1.4153	1.2996	2.1530	2.9987		
15 *	3.5516	2.7865	2.8748	3.1531				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 3 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.0098	1.3284	1.6061	1.3404	1.6287	1.3634	1.9174	3.6390
9*	1.3284	1.6282	1.3264	1.6201	1.3386	1.5770	1.3632	2.8222
10*	1.6061	1.3264	1.7667	1.5055	1.5315	1.3629	1.4072	2.9346
11*	1.3404	1.6214	1.5095	1.6262	1.3122	1.6022	1.3194	3.2509
12*	1.6287	1.3394	1.5326	1.3122	1.4256	1.3221	2.1769	
13*	1.3634	1.5777	1.3636	1.6028	1.3223	1.2623	3.0772	
14*	1.9174	1.3637	1.4078	1.3199	2.1788	3.0775		
15 *	3.6390	2.8232	2.9355	3.2524				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 300 of 311

TABLE 7 (CONTINUED)

M-SUB-C VALUES (F-SUB-Q RPS MARGIN) POWER ESCALATION

AT 118% POWER, 4 EFPD, THIS IS LEVEL 2 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.2035	1.3324	1.8469	1.3760	1.8665	1.4076	2.1592	4.1572
9*	1.3324	1.8806	1.3325	1.8941	1.3702	1.7355	1.4110	3.1835
10*	1.8469	1.3327	1.9647	1.7298	1.7216	1.4140	1.4244	3.3007
11*	1.3760	1.8947	1.7336	1.8232	1.3742	1.7527	1.4731	3.7727
12*	1.8665	1.3708	1.7226	1.3744	1.5673	1.3278	2.4308	
13*	1.4076	1.7363	1.4146	1.7533	1.3281	1.4248	3.5233	
14*	2.1592	1.4116	1.4250	1.4738	2.4325	3.5238		
15 *	4.1572	3.1844	3.3021	3.7745				

AT 118% POWER, 4 EFPD, THIS IS LEVEL 1 OF 24
(LEVEL 24 = TOP OF CORE, LEVEL 1 = BOTTOM)

	H	G	F	E	D	C	B	A

8*	2.8806	3.0220	3.7006	3.0598	3.7553	3.1434	4.3123	5.8148
9*	3.0220	3.7336	3.0536	3.7757	3.0573	3.6491	3.4815	6.5251
10*	3.7006	3.0523	3.7738	3.8480	3.6845	3.0986	3.3709	6.7642
11*	3.0598	3.7754	3.8508	3.6259	3.0149	3.6701	3.6772	7.7074
12*	3.7553	3.0585	3.6861	3.0153	3.4267	3.2257	4.9389	
13*	3.1434	3.6503	3.1000	3.6709	3.2263	3.5559	4.9251	
14*	4.3123	3.4831	3.3724	3.6788	4.9378	4.9263		
15 *	5.8148	6.5273	6.7672	7.7110				

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 310 of 311

TABLE 9

F-DEL-H & M-DEL-H VALUES - POWER ESCALATION

AT 100% POWER, 4 EFPD								
	H	G	F	E	D	C	B	A
8	* .9900	* 1.3879	* 1.2419	* 1.3798	* 1.2282	* 1.3413	* 1.0430	* .5744
	* 1.5508	* 1.1701	* 1.2834	* 1.1500	* 1.2673	* 1.1657	* 1.4465	* 2.4989
9	* 1.3879	* 1.2247	* 1.3946	* 1.2324	* 1.3721	* 1.2449	* 1.3264	* .7117
	* 1.1701	* 1.3115	* 1.1489	* 1.2752	* 1.1560	* 1.2498	* 1.1659	* 2.0419
10	* 1.2419	* 1.3943	* 1.1286	* 1.3051	* 1.2760	* 1.3320	* 1.2749	* .6597
	* 1.2834	* 1.1506	* 1.3762	* 1.2199	* 1.2576	* 1.2269	* 1.2685	* 2.2229
11	* 1.3798	* 1.2316	* 1.3015	* 1.2130	* 1.3753	* 1.2216	* 1.3585	* .5962
	* 1.1500	* 1.2760	* 1.2232	* 1.3201	* 1.1681	* 1.3042	* 1.1750	* 2.5144
12	* 1.2282	* 1.3712	* 1.2749	* 1.3752	* 1.3190	* 1.3568	* .9240	*
	* 1.2673	* 1.1563	* 1.2585	* 1.1682	* 1.1976	* 1.1757	* 1.6877	*
13	* 1.3413	* 1.2444	* 1.3314	* 1.2212	* 1.3566	* 1.3909	* .6446	*
	* 1.1657	* 1.2501	* 1.2274	* 1.3044	* 1.1759	* 1.1317	* 2.3586	*
14	* 1.0430	* 1.3261	* 1.2745	* 1.3581	* .9234	* .6445	*	*
	* 1.4465	* 1.1660	* 1.2688	* 1.1752	* 1.6885	* 2.3587	*	*
15	* .5744	* .7117	* .6595	* .5960	F-DEL-H			
	* 2.4989	* 2.0417	* 2.2229	* 2.5149	M-DEL-H			

AT 75% POWER, 4 EFPD								
	H	G	F	E	D	C	B	A
8	* .9756	* 1.3835	* 1.2365	* 1.3776	* 1.2276	* 1.3438	* 1.0407	* .5666
	* 1.9908	* 1.4678	* 1.5467	* 1.3803	* 1.5166	* 1.4052	* 1.7330	* 3.0748
9	* 1.3835	* 1.2184	* 1.3920	* 1.2292	* 1.3763	* 1.2490	* 1.3342	* .7057
	* 1.4678	* 1.6054	* 1.3881	* 1.5278	* 1.3849	* 1.4892	* 1.3963	* 2.5036
10	* 1.2365	* 1.3915	* 1.1246	* 1.3052	* 1.2793	* 1.3372	* 1.2813	* .6540
	* 1.5467	* 1.3902	* 1.6844	* 1.4716	* 1.5171	* 1.4527	* 1.4877	* 2.7161
11	* 1.3776	* 1.2282	* 1.3013	* 1.2125	* 1.3845	* 1.2284	* 1.3720	* .5919
	* 1.3803	* 1.5283	* 1.4758	* 1.6502	* 1.4649	* 1.6173	* 1.4703	* 3.0996
12	* 1.2276	* 1.3753	* 1.2781	* 1.3845	* 1.3296	* 1.3690	* .9267	*
	* 1.5166	* 1.3851	* 1.5182	* 1.4649	* 1.4799	* 1.4714	* 2.1143	*
13	* 1.3438	* 1.2486	* 1.3365	* 1.2279	* 1.3687	* 1.4099	* .6427	*
	* 1.4052	* 1.4895	* 1.4532	* 1.6177	* 1.4716	* 1.4164	* 3.0038	*
14	* 1.0407	* 1.3338	* 1.2809	* 1.3715	* .9261	* .6426	*	*
	* 1.7330	* 1.3964	* 1.4881	* 1.4707	* 2.1153	* 3.0039	*	*
15	* .5666	* .7056	* .6539	* .5917	F-DEL-H			
	* 3.0748	* 2.5034	* 2.7163	* 3.1002	M-DEL-H			

Catawba 2 Cycle 12 Core Operating Limits Report

CNEI-0400-25
Appendix A, Rev. 19
Page 311 of 311

TABLE 9 (CONTINUED)

F-DEL-H & M-DEL-H VALUES - POWER ESCALATION

AT 50% POWER, 4 EFPD

	H	G	F	E	D	C	B	A
8	* .9616	* 1.3777	* 1.2296	* 1.3743	* 1.2261	* 1.3463	* 1.0385	* .5594
	* 1.9362	* 1.5488	* 1.6617	* 1.4859	* 1.6270	* 1.5049	* 1.8677	* 3.3350
9	* 1.3777	* 1.2105	* 1.3881	* 1.2245	* 1.3797	* 1.2526	* 1.3419	* .7004
	* 1.5488	* 1.7302	* 1.4960	* 1.6357	* 1.4919	* 1.5983	* 1.5061	* 2.7178
10	* 1.2296	* 1.3875	* 1.1194	* 1.3032	* 1.2811	* 1.3422	* 1.2881	* .6492
	* 1.6617	* 1.4984	* 1.7916	* 1.5794	* 1.6334	* 1.5418	* 1.6221	* 2.9180
11	* 1.3743	* 1.2235	* 1.2991	* 1.2147	* 1.3937	* 1.2350	* 1.3854	* .5884
	* 1.4859	* 1.6364	* 1.5842	* 1.7826	* 1.5652	* 1.7397	* 1.5802	* 3.4060
12	* 1.2261	* 1.3786	* 1.2799	* 1.3936	* 1.3399	* 1.3815	* .9300	*
	* 1.6269	* 1.4921	* 1.6348	* 1.5662	* 1.4366	* 1.5749	* 2.2718	*
13	* 1.3463	* 1.2521	* 1.3415	* 1.2346	* 1.3813	* 1.4292	* .6416	*
	* 1.5049	* 1.5986	* 1.5423	* 1.7400	* 1.5751	* 1.4960	* 3.2324	*
14	* 1.0385	* 1.3415	* 1.2876	* 1.3849	* .9294	* .6415	*	*
	* 1.8677	* 1.5062	* 1.6224	* 1.5806	* 2.2728	* 3.2325	*	*
15	* .5594	* .7003	* .6490	* .5882	* F-DEL-H			
	* 3.3350	* 2.7174	* 2.9179	* 3.4067	* M-DEL-H			

AT 30% POWER, 4 EFPD

	H	G	F	E	D	C	B	A
8	* .9489	* 1.3716	* 1.2228	* 1.3708	* 1.2246	* 1.3483	* 1.0366	* .5530
	* 1.9362	* 1.5488	* 1.6617	* 1.4859	* 1.6270	* 1.5049	* 1.8677	* 3.3350
9	* 1.3716	* 1.2029	* 1.3840	* 1.2200	* 1.3826	* 1.2556	* 1.3484	* .6956
	* 1.5488	* 1.7302	* 1.4960	* 1.6357	* 1.4919	* 1.5983	* 1.5061	* 2.7178
10	* 1.2228	* 1.3832	* 1.1144	* 1.3008	* 1.2832	* 1.3468	* 1.2948	* .6448
	* 1.6617	* 1.4984	* 1.7916	* 1.5794	* 1.6334	* 1.5418	* 1.6221	* 2.9180
11	* 1.3708	* 1.2189	* 1.2964	* 1.2169	* 1.4022	* 1.2429	* 1.3976	* .5854
	* 1.4859	* 1.6364	* 1.5842	* 1.7826	* 1.5652	* 1.7397	* 1.5802	* 3.4060
12	* 1.2246	* 1.3815	* 1.2820	* 1.4021	* 1.3494	* 1.3933	* .9335	*
	* 1.6269	* 1.4921	* 1.6348	* 1.5662	* 1.4366	* 1.5749	* 2.2718	*
13	* 1.3483	* 1.2551	* 1.3460	* 1.2425	* 1.3930	* 1.4471	* .6410	*
	* 1.5049	* 1.5986	* 1.5423	* 1.7400	* 1.5751	* 1.4960	* 3.2324	*
14	* 1.0366	* 1.3480	* 1.2942	* 1.3970	* .9329	* .6410	*	*
	* 1.8677	* 1.5062	* 1.6224	* 1.5806	* 2.2728	* 3.2325	*	*
15	* .5530	* .6955	* .6446	* .5851	* F-DEL-H			
	* 3.3350	* 2.7174	* 2.9179	* 3.4067	* M-DEL-H			