

SURVEILLANCE REQUIREMENTS

SURVEILLANCE		FREQUENCY
SR 3.7.5.1	Verify each AFW manual, power operated, and automatic valve in each water flow path and in both steam supply flow paths to the steam turbine driven pump, that is not locked, sealed, or otherwise secured in position, is in the correct position.	31 days
SR 3.7.5.2	<p>-----NOTE----- Not required to be performed for the turbine driven AFW pump until 72 hours after reaching 800 psig in the steam generators. -----</p> <p>Verify the developed head of each AFW pump at the flow test point is greater than or equal to the required developed head.</p>	In accordance with the Inservice Testing Program
SR 3.7.5.3	<p>-----NOTE----- Not required to be performed for the turbine driven AFW pump until 72 hours after reaching 800 psig in the steam generators. -----</p> <p>Verify each AFW automatic valve actuates to the correct position on an actual or simulated actuation signal, except valves HV-8200 and HV-8201.</p>	24 months

(continued)

SURVEILLANCE REQUIREMENTS

SURVEILLANCE	FREQUENCY
<p>SR 3.7.5.1 Verify each AFW manual, power operated, and automatic valve in each water flow path and in both steam supply flow paths to the steam turbine driven pump, that is not locked, sealed, or otherwise secured in position, is in the correct position.</p>	<p>31 days</p>
<p>SR 3.7.5.2 -----NOTE----- Not required to be performed for the turbine driven AFW pump until 72 hours after reaching 800 psig in the steam generators. ----- Verify the developed head of each AFW pump at the flow test point is greater than or equal to the required developed head.</p>	<p>In accordance with the Inservice Testing Program</p>
<p>SR 3.7.5.3 -----NOTE----- Not required to be performed for the turbine driven AFW pump until 72 hours after reaching 800 psig in the steam generators. ----- Verify each AFW automatic valve actuates to the correct position on an actual or simulated actuation signal, except valves HV-8200 and HV-8201.</p>	<p>24 months</p>

(continued)