



RECEIVED
REGION 1

2006 MAR 15 PM 1: 24

Manuel Serrano
Vice President, Operations

Global Chemicals
1 Reagent Lane
Fair Lawn, NJ 07410
Tel: 201-703-3141

Serrano@Fisherchem.com

March 9, 2006

Q-9

Ms. Elizabeth Ullrich
Licensing Assistance Team
Nuclear Materials Safety Branch
US Nuclear Regulatory Commission, Region I
475 Allendale Road
King of Prussia, PA 19406-1415

Re: Byproduct Material License Termination Request; License Number 29-10211-01
Survey Results Follow-Up

Mail Control No.: 138080; Docket No.: 03005379

Dear Ms. Ullrich:

You should have received our response dated 25 January 2006. Our response did not include the residual radiation levels and the levels of residual removable contamination. In our response, we did confirm that results would follow. This letter is to confirm that we conducted the required surveys. Attached is a copy of the Residual Radiation Levels as well as the swipe sample results indicating levels of residual removable contamination originally requested in your letter dated 5 January 2006.

I believe the above information fulfills your request. In the event, you need additional information, please contact me directly.

Sincerely,

Manuel Serrano
Vice President, Operations

138080

NUCLEAR MATERIALS-002

| Residual Radiation Levels-Completed 2/6/06 | | |
|--|---|------------------------|
| Sample Area | Area to Geiger & Swipe with Filter Paper | Geiger Reading (mR/hr) |
| 1 | Radioactive Materials Storage Cabinet Shelf | 0.04 |
| 2 | Lab bench top underneath the radioactive materials storage cabinet shelf | 0.04 |
| 3 | Floor directly in front of the bench-top | 0.04 |
| 4 | Inside the scintillation counter | 0.04 |
| 5 | Lab bench top the scintillation counter sits on | 0.04 |
| 6 | Floor directly in front of the bench-top the scintillation counter sits on | 0.04 |
| 7 | Floor of doorway in Lab 3 heading out to hallway | 0.03 |
| 8 | Floor of doorway heading into Lab 2 | 0.04 |
| 9 | Floor of doorway heading into Lab 1 | 0.03 |
| 10 | Benchtop where solutions are made | 0.03 |
| 11 | Floor directly in front of bench top where solutions are made | 0.04 |
| 12 | Hood area where solutions are made | 0.02 |
| 13 | Floor directly in front of the hood where solutions are made | 0.02 |
| 14 | Benchtop where solutions are made | 0.03 |
| 15 | Floor directly in front of bench top where solutions are made | 0.03 |
| 16 | Floor of doorway between Lab 1 and 2 | 0.05 |
| 17 | Floor in pathway | 0.04 |
| 18 | Floor in pathway | 0.00 |
| 19 | Floor in doorway between Lab 2 and 3 | 0.04 |
| 20 | Blank | 0.00 |
| 21 | Blank | 0.00 |
| 22 | Yellow waste storage cabinet shelf | 0.02 |
| 23 | Floor in front of yellow waste storage cabinet | 0.04 |
| 24 | Floor of doorway into waste storage room | 0.04 |
| 25 | Floor in waste sink room | 0.02 |
| | | |
| | *Background Avg=0.03mR/hr | |
| | **Instrument Information: Wm. B. Johnson & Association Inc. Model GSM-110, Serial No. 8267 | |
| | Includes pancake wand Model HP-265, Serial No. 6891 Last Calibrated 10/10/05, +-5% accuracy | |



**Antkowiak and Mahoney
Enterprises, Inc.**

3 Valley Court
Chester, NY 10918

845 406-1917

Jeanette DeGennaro
Fisher Scientific
1 Reagent Lane
Fair Lawn, NJ 07410

The following samples have been analyzed by liquid scintillation counting. Channel 1 is set for optimum tritium efficiency (0-19 KeV). Channel 2 is set for optimum carbon-14 efficiency (19-156 KeV). Analysis has been made to NIST traceable standards.

Results by Liquid Scintillation Counting

| Sample ID | Channel 1 dpm/sample | Channel 2 dpm/sample | Channel 3 dpm/sample |
|-----------|-------------------------|-------------------------|-------------------------|
| 1 | <MDA | <MDA | <MDA |
| 2 | <MDA | <MDA | <MDA |
| 3 | <MDA | <MDA | <MDA |
| 4 | <MDA | <MDA | <MDA |
| 5 | <MDA | <MDA | <MDA |
| 6 | <MDA | <MDA | <MDA |
| 7 | <MDA | <MDA | <MDA |
| 8 | <MDA | <MDA | <MDA |
| 9 | <MDA | <MDA | <MDA |
| 10 | <MDA | <MDA | <MDA |
| 11 | <MDA | <MDA | <MDA |
| 12 | <MDA | <MDA | <MDA |
| 13 | <MDA | <MDA | <MDA |
| 14 | <MDA | <MDA | <MDA |
| 15 | <MDA | <MDA | <MDA |
| 16 | <MDA | <MDA | <MDA |
| 17 | <MDA | <MDA | <MDA |
| 18 | <MDA | <MDA | <MDA |
| 19 | <MDA | <MDA | <MDA |



**Antkowiak and Mahoney
Enterprises, Inc.**

3 Valley Court
Chester, NY 10918

845 406-1917

| Sample ID | Channel 1 dpm/sample | Channel 2 dpm/sample | Channel 3 dpm/sample |
|-----------|-------------------------|-------------------------|-------------------------|
| 20 | <MDA | <MDA | <MDA |
| 21 | <MDA | <MDA | <MDA |
| 22 | <MDA | <MDA | <MDA |
| 23 | <MDA | <MDA | <MDA |
| 24 | <MDA | <MDA | <MDA |
| 25 | <MDA | <MDA | <MDA |

Analytical Equipment: Packard Model 1900TR

serial#: 401071

Positive results are reported with the 2 sigma counting error. Minimum Detectable Activity (MDA) is the smallest amount of radioactivity that can be detected at the 95% confidence level. Based on the efficiency, background, and count time, the following MDA's have been calculated for this procedure:

^3H = 102 dpm/sample

^{14}C = 43 dpm/sample

Higher energy emitters = 33 dpm/sample

Joel Antkowiak

Digitally signed by Joel Antkowiak
DN: CN = Joel Antkowiak, C = US,
O = AME Inc.
Date: 2006.02.20 15:19:56 -05'00'

Reviewed and Approved by: _____

Date: _____