

MANUAL HARD COPY DISTRIBUTION
DOCUMENT TRANSMITTAL 2006-12371

USER INFORMATION:

GERLACH*ROSE M EMPL#:028401 CA#: 0363
Address: NUCSA2
Phone#: 254-3194

TRANSMITTAL INFORMATION:

TO: GERLACH*ROSE M 03/17/2006
LOCATION: USNRC
FROM: NUCLEAR RECORDS DOCUMENT CONTROL CENTER (NUCSA-2)
THE FOLLOWING CHANGES HAVE OCCURRED TO THE HARDCOPY OR ELECTRONIC MANUAL ASSIGNED
TO YOU. HARDCOPY USERS MUST ENSURE THE DOCUMENTS PROVIDED MATCH THE INFORMATION ON
THIS TRANSMITTAL. WHEN REPLACING THIS MATERIAL IN YOUR HARDCOPY MANUAL, ENSURE THE
UPDATE DOCUMENT ID IS THE SAME DOCUMENT ID YOU'RE REMOVING FROM YOUR MANUAL. TOOLS
FROM THE HUMAN PERFORMANCE TOOL BAG SHOULD BE UTILIZED TO ELIMINATE THE CHANCE OF
ERRORS.
ATTENTION: "REPLACE" directions do not affect the Table of Contents, Therefore no
TOC will be issued with the updated material.

TSB1 - TECHNICAL SPECIFICATION BASES UNIT 1 MANUAL

REMOVE MANUAL TABLE OF CONTENTS DATE: 02/01/2006

ADD MANUAL TABLE OF CONTENTS DATE: 03/16/2006

CATEGORY: DOCUMENTS TYPE: TSB1

A001

ID: TEXT 3.6.4.1

REMOVE: REV:4

ADD: REV: 5

CATEGORY: DOCUMENTS TYPE: TSB1

ID: TEXT LOES

REMOVE: REV:68

ADD: REV: 69

ANY DISCREPANCIES WITH THE MATERIAL PROVIDED, CONTACT DCS @ X3107 OR X3136 FOR ASSISTANCE. UPDATES FOR HARDCOPY MANUALS WILL BE DISTRIBUTED WITHIN 5 DAYS IN ACCORDANCE WITH DEPARTMENT PROCEDURES. PLEASE MAKE ALL CHANGES AND ACKNOWLEDGE COMPLETE IN YOUR NIMS INBOX UPON COMPLETION OF UPDATES. FOR ELECTRONIC MANUAL USERS, ELECTRONICALLY REVIEW THE APPROPRIATE DOCUMENTS AND ACKNOWLEDGE COMPLETE IN YOUR NIMS INBOX.

SSES MANUAL

Manual Name: TSB1

Manual Title: TECHNICAL SPECIFICATION BASES UNIT 1 MANUAL

Table Of Contents

Issue Date: 03/16/2006

| <u>Procedure Name</u> | <u>Rev</u> | <u>Issue Date</u> | <u>Change ID</u> | <u>Change Number</u> |
|---|------------|-------------------|------------------|----------------------|
| TEXT LOES | 69 | 03/16/2006 | | |
| Title: LIST OF EFFECTIVE SECTIONS | | | | |
| TEXT TOC | 7 | 04/18/2005 | | |
| Title: TABLE OF CONTENTS | | | | |
| TEXT 2.1.1 | 1 | 04/27/2004 | | |
| Title: SAFETY LIMITS (SLS) REACTOR CORE SLS | | | | |
| TEXT 2.1.2 | 0 | 11/15/2002 | | |
| Title: SAFETY LIMITS (SLS) REACTOR COOLANT SYSTEM (RCS) PRESSURE SL | | | | |
| TEXT 3.0 | 1 | 04/18/2005 | | |
| Title: LIMITING CONDITION FOR OPERATION (LCO) APPLICABILITY | | | | |
| TEXT 3.1.1 | 0 | 11/15/2002 | | |
| Title: REACTIVITY CONTROL SYSTEMS SHUTDOWN MARGIN (SDM) | | | | |
| TEXT 3.1.2 | 0 | 11/15/2002 | | |
| Title: REACTIVITY CONTROL SYSTEMS REACTIVITY ANOMALIES | | | | |
| TEXT 3.1.3 | 1 | 07/06/2005 | | |
| Title: REACTIVITY CONTROL SYSTEMS CONTROL ROD OPERABILITY | | | | |
| TEXT 3.1.4 | 1 | 07/06/2005 | | |
| Title: REACTIVITY CONTROL SYSTEMS CONTROL ROD SCRAM TIMES | | | | |
| TEXT 3.1.5 | 1 | 07/06/2005 | | |
| Title: REACTIVITY CONTROL SYSTEMS CONTROL ROD SCRAM ACCUMULATORS | | | | |
| TEXT 3.1.6 | 1 | 02/17/2005 | | |
| Title: REACTIVITY CONTROL SYSTEMS ROD PATTERN CONTROL | | | | |

SSES MANUAL

Manual Name: TSB1

Manual Title: TECHNICAL SPECIFICATION BASES UNIT 1 MANUAL

TEXT 3.1.7 1 08/30/2005
Title: REACTIVITY CONTROL SYSTEMS STANDBY LIQUID CONTROL (SLC) SYSTEM

TEXT 3.1.8 1 10/19/2005
Title: REACTIVITY CONTROL SYSTEMS SCRAM DISCHARGE VOLUME (SDV) VENT AND DRAIN VALVES

TEXT 3.2.1 0 11/15/2002
Title: POWER DISTRIBUTION LIMITS AVERAGE PLANAR LINEAR HEAT GENERATION RATE (APLHGR)

TEXT 3.2.2 0 11/15/2002
Title: POWER DISTRIBUTION LIMITS MINIMUM CRITICAL POWER RATIO (MCPR)

TEXT 3.2.3 0 11/15/2002
Title: POWER DISTRIBUTION LIMITS LINEAR HEAT GENERATION RATE (LHGR)

TEXT 3.2.4 1 07/06/2005
Title: POWER DISTRIBUTION LIMITS AVERAGE POWER RANGE MONITOR (APRM) GAIN AND SETPOINTS

TEXT 3.3.1.1 2 07/06/2005
Title: INSTRUMENTATION REACTOR PROTECTION SYSTEM (RPS) INSTRUMENTATION

TEXT 3.3.1.2 0 11/15/2002
Title: INSTRUMENTATION SOURCE RANGE MONITOR (SRM) INSTRUMENTATION

TEXT 3.3.1.3 0 11/22/2004
Title: OPRM INSTRUMENTATION

TEXT 3.3.2.1 1 02/17/2005
Title: INSTRUMENTATION CONTROL ROD BLOCK INSTRUMENTATION

TEXT 3.3.2.2 0 11/15/2002
Title: INSTRUMENTATION FEEDWATER - MAIN TURBINE HIGH WATER LEVEL TRIP INSTRUMENTATION

TEXT 3.3.3.1 2 07/06/2005
Title: INSTRUMENTATION POST ACCIDENT MONITORING (PAM) INSTRUMENTATION

SSSES MANUAL

Manual Name: TSB1

Manual Title: TECHNICAL SPECIFICATION BASES UNIT 1 MANUAL

TEXT 3.3.3.2 1 04/18/2005

Title: INSTRUMENTATION REMOTE SHUTDOWN SYSTEM

TEXT 3.3.4.1 0 11/15/2002

Title: INSTRUMENTATION END OF CYCLE RECIRCULATION PUMP TRIP (EOC-RPT) INSTRUMENTATION

TEXT 3.3.4.2 0 11/15/2002

Title: INSTRUMENTATION ANTICIPATED TRANSIENT WITHOUT SCRAM RECIRCULATION PUMP TRIP (ATWS-RPT) INSTRUMENTATION

TEXT 3.3.5.1 2 07/06/2005

Title: INSTRUMENTATION EMERGENCY CORE COOLING SYSTEM (ECCS) INSTRUMENTATION

TEXT 3.3.5.2 0 11/15/2002

Title: INSTRUMENTATION REACTOR CORE ISOLATION COOLING (RCIC) SYSTEM INSTRUMENTATION

TEXT 3.3.6.1 1 11/09/2004

Title: INSTRUMENTATION PRIMARY CONTAINMENT ISOLATION INSTRUMENTATION

TEXT 3.3.6.2 1 11/09/2004

Title: INSTRUMENTATION SECONDARY CONTAINMENT ISOLATION INSTRUMENTATION

TEXT 3.3.7.1 0 11/15/2002

Title: INSTRUMENTATION CONTROL ROOM EMERGENCY OUTSIDE AIR SUPPLY (CREOAS) SYSTEM INSTRUMENTATION

TEXT 3.3.8.1 1 09/02/2004

Title: INSTRUMENTATION LOSS OF POWER (LOP) INSTRUMENTATION

TEXT 3.3.8.2 0 11/15/2002

Title: INSTRUMENTATION REACTOR PROTECTION SYSTEM (RPS) ELECTRIC POWER MONITORING

TEXT 3.4.1 2 11/22/2004

Title: REACTOR COOLANT SYSTEM (RCS) RECIRCULATION LOOPS OPERATING

TEXT 3.4.2 0 11/15/2002

Title: REACTOR COOLANT SYSTEM (RCS) JET PUMPS

1

3

SSES MANUAL

Manual Name: TSB1

Manual Title: TECHNICAL SPECIFICATION BASES UNIT 1 MANUAL

TEXT 3.6.1.1 0 11/15/2002

Title: CONTAINMENT SYSTEMS PRIMARY CONTAINMENT

TEXT 3.6.1.2 0 11/15/2002

Title: CONTAINMENT SYSTEMS PRIMARY CONTAINMENT AIR LOCK

TEXT 3.6.1.3 3 12/08/2005

Title: CONTAINMENT SYSTEMS PRIMARY CONTAINMENT ISOLATION VALVES (PCIVS)

TEXT 3.6.1.4 0 11/15/2002

Title: CONTAINMENT SYSTEMS CONTAINMENT PRESSURE

TEXT 3.6.1.5 1 10/05/2005

Title: CONTAINMENT SYSTEMS DRYWELL AIR TEMPERATURE

TEXT 3.6.1.6 0 11/15/2002

Title: CONTAINMENT SYSTEMS SUPPRESSION CHAMBER-TO-DRYWELL VACUUM BREAKERS

TEXT 3.6.2.1 0 11/15/2002

Title: CONTAINMENT SYSTEMS SUPPRESSION POOL AVERAGE TEMPERATURE

TEXT 3.6.2.2 0 11/15/2002

Title: CONTAINMENT SYSTEMS SUPPRESSION POOL WATER LEVEL

TEXT 3.6.2.3 1 01/16/2006

Title: CONTAINMENT SYSTEMS RESIDUAL HEAT REMOVAL (RHR) SUPPRESSION POOL COOLING

TEXT 3.6.2.4 0 11/15/2002

Title: CONTAINMENT SYSTEMS RESIDUAL HEAT REMOVAL (RHR) SUPPRESSION POOL SPRAY

TEXT 3.6.3.1 1 04/18/2005

Title: CONTAINMENT SYSTEMS PRIMARY CONTAINMENT HYDROGEN RECOMBINERS

TEXT 3.6.3.2 1 04/18/2005

Title: CONTAINMENT SYSTEMS DRYWELL AIR FLOW SYSTEM

5

Manual Title: TECHNICAL SPECIFICATION BASES UNIT 1 MANUAL

TEXT 3.6.4.1 5 03/16/2006
Title: CONTAINMENT SYSTEMS SECONDARY CONTAINMENT

TEXT 3.6.4.2 2 01/03/2005

Title: CONTAINMENT SYSTEMS SECONDARY CONTAINMENT ISOLATION VALVES (SCIVS)

TEXT 3.6.4.3 3 10/24/2005

Title: CONTAINMENT SYSTEMS STANDBY GAS TREATMENT (SGT) SYSTEM

TEXT 3.7.1 0 11/15/2002

Title: PLANT SYSTEMS RESIDUAL HEAT REMOVAL SERVICE WATER (RHRSW) SYSTEM AND THE
ULTIMATE HEAT SINK (UHS)

TEXT 3.7.2 1 11/09/2004
Title: PLANT SYSTEMS EMERGENCY SERVICE WATER (ESW) SYSTEM

TEXT 3.7.3 0 11/15/2002

Title: PLANT SYSTEMS CONTROL ROOM EMERGENCY OUTSIDE AIR SUPPLY (CREOAS) SYSTEM

TEXT 3.7.4 0 11/15/2002

Title: PLANT SYSTEMS CONTROL ROOM FLOOR COOLING SYSTEM

TEXT 3.7.5 0 11/15/2002

Title: PLANT SYSTEMS MAIN CONDENSER OFFGAS

TEXT 3.7.6 1 01/17/2005

Title: PLANT SYSTEMS MAIN TURBINE BYPASS SYSTEM

TEXT 3.7.7 0 11/15/2002

Title: PLANT SYSTEMS SPENT FUEL STORAGE POOL WATER LEVEL

TEXT 3.8.1 3 10/05/2005

Title: ELECTRICAL POWER SYSTEMS AC SOURCES - OPERATING

SSES MANUAL

Manual Name: TSB1

Manual Title: TECHNICAL SPECIFICATION BASES UNIT 1 MANUAL

TEXT 3.8.2 0 11/15/2002

Title: ELECTRICAL POWER SYSTEMS AC SOURCES - SHUTDOWN

TEXT 3.8.3 0 11/15/2002

Title: ELECTRICAL POWER SYSTEMS DIESEL FUEL OIL, LUBE OIL, AND STARTING AIR

TEXT 3.8.4 0 11/15/2002

Title: ELECTRICAL POWER SYSTEMS DC SOURCES - OPERATING

TEXT 3.8.5 0 11/15/2002

Title: ELECTRICAL POWER SYSTEMS DC SOURCES - SHUTDOWN

TEXT 3.8.6 0 11/15/2002

Title: ELECTRICAL POWER SYSTEMS BATTERY CELL PARAMETERS

TEXT 3.8.7 1 10/05/2005

Title: ELECTRICAL POWER SYSTEMS DISTRIBUTION SYSTEMS - OPERATING

TEXT 3.8.8 0 11/15/2002.

Title: ELECTRICAL POWER SYSTEMS DISTRIBUTION SYSTEMS - SHUTDOWN

TEXT 3.9.1 0 11/15/2002

Title: REFUELING OPERATIONS REFUELING EQUIPMENT INTERLOCKS

TEXT 3.9.2 0 11/15/2002

Title: REFUELING OPERATIONS REFUEL POSITION ONE-ROD-OUT INTERLOCK

TEXT 3.9.3 0 11/15/2002

Title: REFUELING OPERATIONS CONTROL ROD POSITION

TEXT 3.9.4 0 11/15/2002

Title: REFUELING OPERATIONS CONTROL ROD POSITION INDICATION

TEXT 3.9.5 0 11/15/2002

Title: REFUELING OPERATIONS CONTROL ROD OPERABILITY - REFUELING

1.

Manual Title: TECHNICAL SPECIFICATION BASES UNIT 1 MANUAL

TEXT 3.9.7 0 11/15/2002

Title: REFUELING OPERATIONS RESIDUAL HEAT REMOVAL (RHR) - HIGH WATER LEVEL

TEXT 3.9.8 0 11/15/2002

Title: REFUELING OPERATIONS RESIDUAL HEAT REMOVAL (RHR) - LOW WATER LEVEL

TEXT 3.10.1 0 11/15/2002

Title: SPECIAL OPERATIONS INSERVICE LEAK AND HYDROSTATIC TESTING OPERATION

TEXT 3.10.2 0 11/15/2002

Title: SPECIAL OPERATIONS REACTOR MODE SWITCH INTERLOCK TESTING

TEXT 3.10.3 0 11/15/2002
Title: SPECIAL OPERATIONS SINGLE CONTROL ROD WITHDRAWAL - HOT SHUTDOWN

TEXT 3.10.4 0 11/15/2002.
Title: SPECIAL OPERATIONS SINGLE CONTROL ROD WITHDRAWAL - COLD SHUTDOWN

TEXT 3.10.5 0 11/15/2002

Title: SPECIAL OPERATIONS SINGLE CONTROL ROD DRIVE (CRD) REMOVAL - REFUELING

TEXT 3.10.6 0 11/15/2002

Title: SPECIAL OPERATIONS MULTIPLE CONTROL ROD WITHDRAWAL - REFUELING

TEXT 3.10.7 0 11/15/2002
Title: SPECIAL OPERATIONS CONTROL ROD TESTING - OPERATING

TEXT 3.10.8 0 11/15/2002
Title: SPECIAL OPERATIONS SHUTDOWN MARGIN (SDM) TEST - REFUELING

SUSQUEHANNA STEAM ELECTRIC STATION
LIST OF EFFECTIVE SECTIONS (TECHNICAL SPECIFICATIONS BASES)

| <u>Section</u> | <u>Title</u> | <u>Revision</u> |
|----------------|---|-----------------|
| TOC | Table of Contents | 7 |
| B 2.0 | SAFETY LIMITS BASES | |
| | Page B 2.0-1 | 0 |
| | Page TS / B 2.0-2 | 2 |
| | Page TS / B 2.0-3 | 3 |
| | Pages TS/ B 2.0-4 and TS / B 2.0-5 | 2 |
| | Page TS / B 2.0-6 | 1 |
| | Pages B 2.0-7 through B 2.0-9 | 0 |
| B 3.0 | LCO AND SR APPLICABILITY BASES | |
| | Pages B 3.0-1 through B 3.0-4 | 0 |
| | Pages TS / B 3.0-5 through TS / B 3.0-7 | 1 |
| | Pages TS / B 3.0-8 through TS / B 3.0-9 | 2 |
| | Pages TS / B 3.0-10 through TS / B 3.0-12 | 1 |
| | Pages TS / B 3.0-13 through TS / B 3.0-15 | 2 |
| | Pages TS / B 3.0-16 and TS / B 3.0-17 | 0 |
| B 3.1 | REACTIVITY CONTROL BASES | |
| | Pages B 3.1-1 through B 3.1-5 | 0 |
| | Pages TS / B 3.1-6 and TS / B 3.1-7 | 1 |
| | Pages B 3.1-8 through B 3.1-13 | 0 |
| | Page TS / B 3.1-14 | 1 |
| | Pages B 3.1-15 through B 3.1-22 | 0 |
| | Page TS / B 3.1-23 | 1 |
| | Pages B 3.1-24 through B 3.1-27 | 0 |
| | Page TS / B 3.1-28 | 1 |
| | Page TS / B 3.1-29 | 1 |
| | Pages B 3.1-30 through B 3.1-33 | 0 |
| | Pages TS / B 3.3-34 through TS / B 3.3-36 | 1 |
| | Page TS / B 3.1-37 | 2 |
| | Page TS / B 3.1-38 | 1 |
| | Pages B 3.1-39 through B 3.1-44 | 0 |
| | Page TS / B 3.1-45 | 1 |
| | Pages B 3.1-46 and B 3.1-47 | 0 |
| | Pages TS / B 3.1-48 and TS / B 3.1-49 | 1 |
| | Page B 3.1-50 | 0 |
| | Page TS / B 3.1-51 | 1 |
| B 3.2 | POWER DISTRIBUTION LIMITS BASES | |
| | Page TS / B 3.2-1 | 1 |
| | Page TS / B 3.2-2 | 2 |
| | Page TS / B 3.2-3 | 1 |
| | Page TS / B 3.2-4 | 2 |
| | Pages TS / B 3.2-5 and TS / B 3.2-6 | 1 |

SUSQUEHANNA STEAM ELECTRIC STATION
LIST OF EFFECTIVE SECTIONS (TECHNICAL SPECIFICATIONS BASES)

| <u>Section</u> | <u>Title</u> | <u>Revision</u> |
|----------------|---|-----------------|
| | Page B 3.2-7 | 0 |
| | Pages TS / B 3.2-8 through TS / B 3.2-10 | 1 |
| | Page TS / B 3.2-11 | 2 |
| | Page B 3.2-12 | 0 |
| | Page TS / B 3.2-13 | 2 |
| | Pages B 3.2-14 and B 3.2-15 | 0 |
| | Page TS / B 3.2-16 | 2 |
| | Pages B 3.2-17 and B 3.2-18 | 0 |
| | Page TS / B 3.2-19 | 3 |
| B 3.3 | INSTRUMENTATION | |
| | Pages TS / B 3.3-1 through TS / B 3.3-4 | 1 |
| | Page TS / B 3.3-5 | 2 |
| | Page TS / B 3.3-6 | 1 |
| | Pages TS / B 3.3-7 through TS / B 3.3-11 | 2 |
| | Page TS / B 3.3-12 | 2 |
| | Page TS / B 3.3-13 | 1 |
| | Page TS / B 3.3-14 | 2 |
| | Pages TS / B 3.3-15 and TS / B 3.3-16 | 1 |
| | Pages TS / B 3.3-17 and TS / B 3.3-18 | 2 |
| | Pages TS / B 3.3-19 through TS / B 3.3-27 | 1 |
| | Pages TS / B 3.3-28 through TS / B 3.3-31 | 2 |
| | Pages TS / B 3.3-32 and TS / B 3.3-33 | 4 |
| | Pages TS / B 3.3-34 through TS / B 3.3-43 | 1 |
| | Pages TS / B 3.3-43a through TS / B 3.3-43i | 0 |
| | Pages TS / B 3.3-44 through TS / B 3.3-50 | 2 |
| | Pages TS / B 3.3-51 through TS / B 3.3-53 | 1 |
| | Page TS / B 3.3-54 | 2 |
| | Pages B 3.3-55 through B 3.3-63 | 0 |
| | Pages TS / B 3.3-64 and TS / B 3.3-65 | 2 |
| | Page TS / B 3.3-66 | 4 |
| | Page TS / B 3.3-67 | 3 |
| | Page TS / B 3.3-68 | 4 |
| | Pages TS / B 3.3-69 and TS / B 3.3-70 | 3 |
| | Page TS / B 3.3-71 | 3 |
| | Pages TS / 3.3-72 through TS / 3.3-75 | 2 |
| | Page TS / B 3.3-75a | 4 |
| | Pages TS / B 3.3-75b and TS / B 3.3-75c | 4 |
| | Pages B 3.3-76 through 3.3-77 | 0 |
| | Page TS / B 3.3-78 | 1 |
| | Pages B 3.3-79 through B 3.3-89 | 0 |
| | Page TS / B 3.3-90 | 1 |
| | Page B 3.3-91 | 0 |
| | Page TS / B 3.3-92 through TS / B 3.3-100 | 1 |
| | Pages B 3.3-101 through B 3.3-103 | 0 |

SUSQUEHANNA STEAM ELECTRIC STATION
LIST OF EFFECTIVE SECTIONS (TECHNICAL SPECIFICATIONS BASES)

| <u>Section</u> | <u>Title</u> | <u>Revision</u> |
|----------------|---|-----------------|
| | Page TS / B 3.3-104 | 1 |
| | Pages B 3.3-105 and B 3.3-106 | 0 |
| | Page TS / B 3.3-107 | 1 |
| | Page B 3.3-108 | 0 |
| | Page TS / B 3.3-109 | 1 |
| | Pages B 3.3-110 and B 3.3-111 | 0 |
| | Pages TS / B 3.3-112 and TS / B 3.3-112a | 1 |
| | Pages TS / B 3.3-113 and TS / B 3.3-114 | 1 |
| | Page TS / B 3.3-115 | 1 |
| | Page TS / B 3.3-116 | 2 |
| | Page TS / B 3.3-117 | 1 |
| | Pages B 3.3-118 through B 3.3-122 | 0 |
| | Pages TS / B 3.3-123 and TS / B 3.3-124 | 1 |
| | Page TS / B 3.3-124a | 0 |
| | Page B 3.3-125 | 0 |
| | Page TS / B 3.3-126 | 1 |
| | Page TS / B 3.3-127 | 1 |
| | Pages B 3.3-128 through B 3.3-130 | 0 |
| | Page TS / B 3.3-131 | 1 |
| | Pages B 3.3-132 through B 3.3-137 | 0 |
| | Page TS / B 3.3-138 | 1 |
| | Pages B 3.3-139 through B 3.3-149 | 0 |
| | Page TS / B 3.3-150 through TS / B 3.3-162 | 1 |
| | Page TS / B 3.3-163 | 2 |
| | Pages TS / B 3.3-164 through TS / B 3.3-177 | 1 |
| | Pages TS / B 3.3-178 and TS / B 3.3-179 | 2 |
| | Page TS / B 3.3-179a | 2 |
| | Page TS / B 3.3-179b | 0 |
| | Page TS / B 3.3-179c | 0 |
| | Page TS / B 3.3-180 | 1 |
| | Page TS / B 3.3-181 | 2 |
| | Pages TS / B 3.3-182 through TS / B 3.3-186 | 1 |
| | Pages TS / B 3.3-187 and TS / B 3.3-188 | 2 |
| | Pages TS / B 3.3-189 through TS / B 3.3-191 | 1 |
| | Pages B 3.3-192 through B 3.3-204 | 0 |
| | Page TS / B 3.3-205 | 1 |
| | Pages B 3.3-206 through B 3.3-219 | 0 |
| B 3.4 | REACTOR COOLANT SYSTEM BASES | |
| | Pages B 3.4-1 and B 3.4-2 | 0 |
| | Page TS / B 3.4-3 and Page TS / B 3.4-4 | 3 |
| | Pages TS / B 3.4-5 through TS / B 3.4-9 | 2 |
| | Pages B 3.4-10 through B 3.4-14 | 0 |
| | Page TS / B 3.4-15 | 1 |
| | Pages TS / B 3.4-16 through TS / B 3.4-18 | 2 |

SUSQUEHANNA STEAM ELECTRIC STATION
LIST OF EFFECTIVE SECTIONS (TECHNICAL SPECIFICATIONS BASES)

| <u>Section</u> | <u>Title</u> | <u>Revision</u> |
|----------------|---|-----------------|
| | Pages B 3.4-19 through B 3.4-27 | 0 |
| | Pages TS / B 3.4-28 and TS / B 3.4-29 | 1 |
| | Pages B 3.4-30 and B 3.4-31 | 0 |
| | Page TS / B 3.4-32 | 1 |
| | Pages B 3.4-33 through B 3.4-36 | 0 |
| | Page TS / B 3.4-37 | 1 |
| | Pages B 3.4-38 through B 3.4-40 | 0 |
| | Page TS / B 3.4-41 | 1 |
| | Pages B 3.4-42 through B 3.4-48 | 0 |
| | Page TS / B 3.4-49 | 2 |
| | Page TS / B 3.4-50 | 1 |
| | Page TS / B 3.4-51 | 2 |
| | Pages TS / B 3.4-52 and TS / B 3.4-53 | 1 |
| | Page TS / B 3.4-54 | 2 |
| | Page TS / B 3.4-55 | 2 |
| | Page TS / B 3.4-56 | 1 |
| | Page TS / B 3.4-57 | 2 |
| | Pages TS / B 3.4-58 through TS / B 3.4-60 | 1 |
| B 3.5 | ECCS AND RCIC BASES | |
| | Pages B 3.5-1 and B 3.5-2 | 0 |
| | Page TS / B 3.5-3 | 2 |
| | Page TS / B 3.5-4 | 1 |
| | Page TS / B 3.5-5 | 2 |
| | Page TS / B 3.5-6 | 1 |
| | Pages B 3.5-7 through B 3.5-10 | 0 |
| | Page TS / B 3.5-11 | 1 |
| | Page TS / B 3.5-12 | 0 |
| | Page TS / B 3.5-13 | 1 |
| | Page TS / B 3.5-14 and TS / B 3.5-15 | 0 |
| | Pages TS / B 3.5-16 through TS / B 3.5-18 | 1 |
| | Pages B 3.5-19 through B 3.5-24 | 0 |
| | Page TS / B 3.5-25 | 1 |
| | Pages TS / B 3.5-26 and TS / B 3.5-27 | 1 |
| | Pages B 3.5-28 through B 3.5-31 | 0 |
| B 3.6 | CONTAINMENT SYSTEMS BASES | |
| | Page TS / B 3.6-1 | 2 |
| | Page TS / B 3.6-1a | 3 |
| | Pages TS / B 3.6-2 through TS / B 3.6-5 | 2 |
| | Page TS / B 3.6-6 | 3 |
| | Pages TS / B 3.6-6a and TS / B 3.6-6b | 2 |
| | Page TS / B 3.6-6c | 0 |
| | Pages B 3.6-7 through B 3.6-14 | 0 |
| | Page TS / B 3.6-15 | 2 |

SUSQUEHANNA STEAM ELECTRIC STATION
LIST OF EFFECTIVE SECTIONS (TECHNICAL SPECIFICATIONS BASES)

| <u>Section</u> | <u>Title</u> | <u>Revision</u> |
|----------------|---|-----------------|
| | Pages TS / B 3.6-15a and TS / B 3.6-15b | 0 |
| | Page B 3.6-16 | 0 |
| | Page TS / B 3.6-17 | 1 |
| | Page TS / B 3.6-17a | 0 |
| | Pages TS / B 3.6-18 and TS / B 3.6-19 | 0 |
| | Page TS / B 3.6-20 | 1 |
| | Page TS / B 3.6-21 | 2 |
| | Page TS / B 3.6-22 | 1 |
| | Page TS / B 3.6-22a | 0 |
| | Page TS / B 3.6-23 | 1 |
| | Pages TS / B 3.6-24 through TS / B 3.6-25 | 0 |
| | Page TS / B 3.6-26 | 1 |
| | Page TS / B 3.6-27 | 2 |
| | Page TS / B 3.6-28 | 5 |
| | Page TS / B 3.6-29 | 1 |
| | Page TS / B 3.6-30 | 1 |
| | Page TS / B 3.6-31 | 3 |
| | Page B 3.6-32 | 0 |
| | Page TS / B 3.6-33 | 1 |
| | Pages B 3.6-34 and B 3.6-35 | 0 |
| | Page TS / B 3.6-36 | 1 |
| | Page B 3.6-37 | 0 |
| | Page TS / B 3.6-38 | 1 |
| | Page B 3.6-39 | 0 |
| | Page TS / B 3.6-40 | 4 |
| | Pages B 3.6-41 through B 3.6-43 | 3 |
| | Pages TS / B 3.6-44 and TS / B 3.6-45 | 1 |
| | Page TS / B 3.6-46 | 2 |
| | Pages TS / B 3.6-47 through TS / B 3.6-51 | 1 |
| | Page TS / B 3.6-52 | 2 |
| | Pages B 3.6-53 through B 3.6-63 | 0 |
| | Pages TS / B 3.6-64 and TS / B 3.6-65 | 1 |
| | Pages B 3.6-66 through B 3.6-72 | 0 |
| | Page TS / B 3.6-73 | 1 |
| | Pages B 3.6-74 through B 3.6-77 | 0 |
| | Page TS / B 3.6-78 | 1 |
| | Pages B 3.6-79 through B 3.3.6-83 | 0 |
| | Page TS / B 3.6-84 | 3 |
| | Page TS / B 3.6-85 | 2 |
| | Page TS / B 3.6-86 | 3 |
| | Page TS / B 3.6-87 | 1 |
| | Pages TS / B 3.6-88 and TS / B 3.6-88a | 2 |
| | Page TS / B 3.6-89 | 3 |
| | Page TS / B 3.6-90 | 2 |
| | Page TS / B 3.6-91 | 3 |

SUSQUEHANNA STEAM ELECTRIC STATION
LIST OF EFFECTIVE SECTIONS (TECHNICAL SPECIFICATIONS BASES)

| <u>Section</u> | <u>Title</u> | <u>Revision</u> |
|----------------|---|-----------------|
| | Pages TS / B 3.6-92 through TS / B 3.6-96 | 1 |
| | Page TS / B 3.6-97 | 2 |
| | Pages TS / B 3.6-98 and TS / B 3.6-99 | 1 |
| | Page TS / B 3.6-100 | 2 |
| | Pages TS / B 3.6-101 and TS / B 3.6-102 | 1 |
| | Pages TS / B 3.6-103 and TS / B 3.6-104 | 2 |
| | Page TS / B 3.6-105 | 3 |
| | Pages TS / B 3.6-106 and TS / B 3.6-107 | 2 |
| B 3.7 | PLANT SYSTEMS BASES | |
| | Pages TS / B 3.7-1 through TS / B 3.7-6 | 2 |
| | Page TS / B 3.7-6a | 2 |
| | Pages TS / B 3.7-6b and TS / B 3.7-6c | 0 |
| | Page TS / B 3.7-7 | 2 |
| | Pages TS / B 3.7-8 through TS / B 3.7-11 | 1 |
| | Pages TS / B 3.7-12 and TS / B 3.7-13 | 1 |
| | Pages TS / B 3.7-14 through TS / B 3.7-18 | 2 |
| | Page TS / B 3.7-18a | 0 |
| | Pages TS / B 3.7-19 through TS / B 3.7-23 | 1 |
| | Pages B 3.7-24 through B 3.7-26 | 0 |
| | Pages TS / B 3.7-27 through TS / B 3.7-29 | 4 |
| | Page TS / B 3.7-30 | 2 |
| | Pages B 3.7-31 through B 3.7-33 | 0 |
| B 3.8 | ELECTRICAL POWER SYSTEMS BASES | |
| | Pages TS / B 3.8-1 through TS / B 3.8-4 | 2 |
| | Page TS / B 3.8-5 | 4 |
| | Page TS / B 3.8-6 | 3 |
| | Pages TS / B 3.8-7 through TS/B 3.8-8 | 2 |
| | Page TS / B 3.8-9 | 4 |
| | Page TS / B 3.8-10 | 3 |
| | Pages TS / B 3.8-11 and TS / B 3.8-17 | 2 |
| | Page TS / B 3.8-18 | 3 |
| | Pages TS / B 3.8-19 through TS / B 3.8-21 | 2 |
| | Pages TS / B 3.8-22 and TS / B 3.8-23 | 3 |
| | Pages TS / B 3.8-24 through TS / B 3.8-37 | 2 |
| | Pages B 3.8-38 through B 3.8-53 | 0 |
| | Pages TS / B 3.8-54 through TS / B 3.8-61 | 1 |
| | Page TS / B 3.8-62 | 2 |
| | Page TS / B 3.8-63 | 2 |
| | Page TS / B 3.8-64 | 1 |
| | Page TS / B 3.8-65 | 2 |
| | Pages B 3.8-66 through B 3.8-80 | 0 |
| | Page TS / B 3.8-81 | 1 |
| | Pages B 3.8-82 through B 3.8-90 | 0 |

SUSQUEHANNA STEAM ELECTRIC STATION
LIST OF EFFECTIVE SECTIONS (TECHNICAL SPECIFICATIONS BASES)

| <u>Section</u> | <u>Title</u> | <u>Revision</u> |
|----------------|---|-----------------|
| B 3.9 | REFUELING OPERATIONS BASES | |
| | Pages TS / B 3.9-1 and TS / B 3.9-1a | 1 |
| | Pages TS / B 3.9-2 through TS / B 3.9-4 | 1 |
| | Pages B 3.9-5 through B 3.9-30 | 0 |
| B 3.10 | SPECIAL OPERATIONS BASES | |
| | Page TS / B 3.10-1 | 1 |
| | Pages B 3.10-2 through B 3.10-31 | 0 |
| | Page TS / B 3.10-32 | 1 |
| | Pages B 3.10-33 through B 3.10-37 | 0 |
| | Page TS / B 3.10-38 | 1 |

TSB1 text LOES
3/1/06

B 3.6 CONTAINMENT SYSTEMS

B 3.6.4.1 Secondary Containment

BASES

BACKGROUND

The secondary containment structure completely encloses the primary containment structure such that a dual-containment design is utilized to limit the spread of radioactivity to the environment to within limits. The function of the secondary containment is to contain, dilute, and hold up fission products that may leak from primary containment into secondary containment following a Design Basis Accident (DBA). In conjunction with operation of the Standby Gas Treatment (SGT) System and closure of certain valves whose lines penetrate the secondary containment, the secondary containment is designed to reduce the activity level of the fission products prior to release to the environment and to isolate and contain fission products that are released during certain operations that take place inside primary containment, when primary containment is not required to be OPERABLE, or that take place outside primary containment (Ref. 1).

The secondary containment is a structure that completely encloses the primary containment and reactor coolant pressure boundary components. This structure forms a control volume that serves to hold up and dilute the fission products. It is possible for the pressure in the control volume to rise relative to the environmental pressure (e.g., due to pump and motor heat load additions).

The secondary containment boundary consists of the reactor building structure and associated removable walls and panels, hatches, doors, dampers, sealed penetrations and valves. The secondary containment is divided into Zone I, Zone II and Zone III, each of which must be OPERABLE depending on plant status and the alignment of the secondary containment boundary. Specifically, the Unit 1 secondary containment boundary can be modified to exclude Zone II. Similarly, the Unit 2 secondary containment boundary can be modified to exclude Zone I. Secondary containment may consist of only Zone III when in MODE 4 or 5 during CORE ALTERATIONS, or during handling of irradiated fuel within the Zone III secondary containment boundary.

(continued)

BASES

BACKGROUND
(continued)

To prevent ground level exfiltration while allowing the secondary containment to be designed as a conventional structure, the secondary containment requires support systems to maintain the control volume pressure at less than the external pressure. Requirements for the safety related systems are specified separately in LCO 3.6.4.2, "Secondary Containment Isolation Valves (SCIVs)," and LCO 3.6.4.3, "Standby Gas Treatment (SGT) System." When one or more zones are excluded from secondary containment, the specific requirements for support systems will also change (e.g., required secondary containment isolation valves).

APPLICABLE
SAFETY
ANALYSES

There are two principal accidents for which credit is taken for secondary containment OPERABILITY. These are a loss of coolant accident (LOCA) (Ref. 2) and a fuel handling accident inside secondary containment (Ref. 3). The secondary containment performs no active function in response to either of these limiting events; however, its leak tightness is required to ensure that the release of radioactive materials from the primary containment is restricted to those leakage paths and associated leakage rates assumed in the accident analysis and that fission products entrapped within the secondary containment structure will be treated by the SGT System prior to discharge to the environment.

Secondary containment satisfies Criterion 3 of the NRC Policy Statement (Ref. 4).

LCO

An OPERABLE secondary containment provides a control volume into which fission products that bypass or leak from primary containment, or are released from the reactor coolant pressure boundary components located in secondary containment, can be diluted and processed prior to release to the environment. For the secondary containment to be considered OPERABLE, it must have adequate leak tightness to ensure that the required vacuum can be established and maintained. The leak tightness of secondary containment must also ensure that the release of radioactive materials to the environment is restricted to those leakage paths and associated leakage rates assumed in the accident analysis. For example, secondary containment bypass leakage must be restricted to the leakage rate required by LCO 3.6.1.3. The secondary containment boundary required to be OPERABLE is dependent on the operating status of both units, as well as the configuration of walls, doors, hatches, SCIVs, and available flow paths to the SGT System.

(continued)

BASES (continued)

APPLICABILITY In MODES 1, 2, and 3, a LOCA could lead to a fission product release to primary containment that leaks to secondary containment. Therefore, secondary containment OPERABILITY is required during the same operating conditions that require primary containment OPERABILITY.

In MODES 4 and 5, the probability and consequences of the LOCA are reduced due to the pressure and temperature limitations in these MODES. Therefore, maintaining secondary containment OPERABLE is not required in MODE 4 or 5 to ensure a control volume, except for other situations for which significant releases of radioactive material can be postulated, such as during operations with a potential for draining the reactor vessel (OPDRVs), during CORE ALTERATIONS, or during movement of irradiated fuel assemblies in the secondary containment.

ACTIONS

A.1

If secondary containment is inoperable, it must be restored to OPERABLE status within 4 hours. The 4 hour Completion Time provides a period of time to correct the problem that is commensurate with the importance of maintaining secondary containment during MODES 1, 2, and 3. This time period also ensures that the probability of an accident (requiring secondary containment OPERABILITY) occurring during periods where secondary containment is inoperable is minimal.

A temporary (one-time) Completion Time is connected to the Completion Time Requirements above (4 hours) with an "OR" connector. The Temporary Completion Time is 48 hours and applies to the replacement of the Reactor Building Recirculating Fan Damper Motors. The Temporary Completion Time of 48 hours may only be used once, and expires on December 31, 2005.

(continued)

BASES

ACTIONS
(continued)

B.1 and B.2

If secondary containment cannot be restored to OPERABLE status within the required Completion Time, the plant must be brought to a MODE in which the LCO does not apply. To achieve this status, the plant must be brought to at least MODE 3 within 12 hours and to MODE 4 within 36 hours. The allowed Completion Times are reasonable, based on operating experience, to reach the required plant conditions from full power conditions in an orderly manner and without challenging plant systems.

C.1, C.2, and C.3

Movement of irradiated fuel assemblies in the secondary containment, CORE ALTERATIONS, and OPDRVs can be postulated to cause fission product release to the secondary containment. In such cases, the secondary containment is the only barrier to release of fission products to the environment. CORE ALTERATIONS and movement of irradiated fuel assemblies must be immediately suspended if the secondary containment is inoperable.

Suspension of these activities shall not preclude completing an action that involves moving a component to a safe position. Also, action must be immediately initiated to suspend OPDRVs to minimize the probability of a vessel draindown and subsequent potential for fission product release. Actions must continue until OPDRVs are suspended.

Required Action C.1 has been modified by a Note stating that LCO 3.0.3 is not applicable. If moving irradiated fuel assemblies while in MODE 4 or 5, LCO 3.0.3 would not specify any action. If moving irradiated fuel assemblies while in MODE 1, 2, or 3, the fuel movement is independent of reactor operations. Therefore, in either case, inability to suspend movement of irradiated fuel assemblies would not be a sufficient reason to require a reactor shutdown.

SURVEILLANCE
REQUIREMENTS

SR 3.6.4.1.1

This SR ensures that the secondary containment boundary is sufficiently leak tight to preclude exfiltration.

(continued)

BASES

**SURVEILLANCE
REQUIREMENTS**

SR 3.6.4.1.1 (continued)

The 24 hour Frequency of this SR was developed based on operating experience related to secondary containment vacuum variations during the applicable MODES and the low probability of a DBA occurring between surveillances.

Furthermore, the 24 hour Frequency is considered adequate in view of other indications available in the control room, including alarms, to alert the operator to an abnormal secondary containment vacuum condition.

SR 3.6.4.1.2 and SR 3.6.4.1.3

Verifying that secondary containment equipment hatches, removable walls and one access door in each access opening required to be closed are closed ensures that the infiltration of outside air of such a magnitude as to prevent maintaining the desired negative pressure does not occur.

Verifying that all such openings are closed also provides adequate assurance that exfiltration from the secondary containment will not occur. In this application, the term "sealed" has no connotation of leak tightness.

An access opening typically contains one inner and one outer door. Maintaining secondary containment OPERABILITY requires verifying one door in each access opening to secondary containment zones is closed. In some cases (e.g., railroad bay), secondary containment access openings are shared such that a secondary containment barrier may have multiple inner or multiple outer doors. The intent is to maintain the secondary containment barrier intact, which is achieved by maintaining the inner or outer portion of the barrier closed at all times. However, all secondary containment access doors are normally kept closed, except when the access opening is being used for entry and exit or when maintenance is being performed on an access opening.

When the railroad bay door (No. 101) is closed; all Zone I and III hatches, removable walls, dampers, and one door in each access opening connected to the railroad access bay are closed; or, only Zone I removable walls and/or doors are open to the railroad access shaft; or, only Zone III hatches and/or dampers are open to the railroad access shaft. When the railroad bay door (No. 101) is open; all Zone I and III hatches, removable walls, dampers, and one door in each access opening connected to the railroad access bay are closed. The truck bay hatch is closed and the truck bay door (No. 102) is closed unless Zone II is isolated from Zones I and III.

(continued)

BASES

**SURVEILLANCE
REQUIREMENTS**

SR 3.6.4.1.2 and SR 3.6.4.1.3 (continued)

When an access opening between required secondary containment zones is being used for exit and entry, then at least one door (where two doors are provided) must remain closed. The access openings between secondary containment zones which are not provided with two doors are administratively controlled to maintain secondary containment integrity during exit and entry. This Surveillance is modified by a Note that allows access openings with a single door (i.e., no airlock) within the secondary containment boundary (i.e., between required secondary containment zones) to be opened for entry and exit. Opening of an access door for entry and exit allows sufficient administrative control by individual personnel making the entries and exits to assure the secondary containment function is not degraded. When one of the zones is not a zone required for secondary containment OPERABILITY, the Note allowance would not apply.

The 31 day Frequency for these SRs has been shown to be adequate, based on operating experience, and is considered adequate in view of the other indications of door and hatch status that are available to the operator.

(continued)

BASIS

SURVEILLANCE
REQUIREMENTS
(continued)

SR 3.6.4.1.4 and SR 3.6.4.1.5

The SGT System exhausts the secondary containment atmosphere to the environment through appropriate treatment equipment. To ensure that all fission products are treated, SR 3.6.4.1.4 verifies that the SGT System will rapidly establish and maintain a pressure in the secondary containment that is less than the pressure external to the secondary containment boundary. This is confirmed by demonstrating that one SGT subsystem will draw down the secondary containment to ≥ 0.25 inches of vacuum water gauge in less than or equal to the maximum time allowed. This cannot be accomplished if the secondary containment boundary is not intact. SR 3.6.4.1.5 demonstrates that one SGT subsystem can maintain ≥ 0.25 inches of vacuum water gauge for at least 1 hour at less than or equal to the maximum flow rate permitted for the secondary containment configuration that is operable. The 1 hour test period allows secondary containment to be in thermal equilibrium at steady state conditions. As noted, both SR 3.6.4.1.4 and SR 3.6.4.1.5 acceptance limits are dependent upon the secondary containment configuration when testing is being performed. The acceptance criteria for the SRs based on secondary containment configuration is defined as follows:

| SECONDARY CONTAINMENT TEST CONFIGURATION | MAXIMUM DRAWDOWN TIME(SEC) (SR 3.6.4.1.4 ACCEPTANCE CRITERIA) | MAXIMUM FLOW RATE (CFM) (SR 3.6.4.1.5 ACCEPTANCE CRITERIA) |
|--|---|--|
| | | |
| Zones I, II and III. | ≤ 125 Seconds (Zones I, II, and III) | ≤ 4000 CFM (From Zones I, II, and III) |
| Zones I and III. | ≤ 117 Seconds (Zones I and III) | ≤ 2885 CFM (From Zones I and III) |

(continued)

BASES

SURVEILLANCE REQUIREMENTS SR 3.6.4.1.4 and SR 3.6.4.1.5 (continued)

Only one of the above listed configurations needs to be tested to confirm secondary containment OPERABILITY.

A Note also modifies the Frequency for each SR. This Note identifies that each configuration is to be tested every 60 months. Testing each configuration every 60 months assures that the most limiting configuration is tested every 60 months. The 60 month Frequency is acceptable because operating experience has shown that these components usually pass the Surveillance and all active components are tested more frequently. Therefore, these tests are used to ensure secondary containment boundary integrity.

Since these SRs are secondary containment tests, they need not be performed with each SGT subsystem. The SGT subsystems are tested on a STAGGERED TEST BASIS, however, to ensure that in addition to the requirements of LCO 3.6.4.3, either SGT subsystem will perform SR 3.6.4.1.4 and SR 3.6.4.1.5. Operating experience has shown these components usually pass the Surveillance when performed at the 24 month Frequency. Therefore, the Frequency was concluded to be acceptable from a reliability standpoint.

-
- | | |
|------------|--|
| REFERENCES | <ol style="list-style-type: none">1. FSAR, Section 6.2.3.2. FSAR, Section 15.6.3. FSAR, Section 15.7.4.4. Final Policy Statement on Technical Specifications Improvements, July 22, 1993 (58 FR 39132). |
|------------|--|
-