

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9233	8	71-9233	USA/9233/B(U)	1 OF	3

## 2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

## 3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- a. ISSUED TO (*Name and Address*)  
qTransnuclear, Inc  
Four Skyline Drive  
Hawthorne, NY 10532-2120
- b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION  
Transnuclear, Inc. application  
dated March 8, 2005, as supplemented.

## 4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

## 5.

## (a) Packaging

- (1) Model No.: TN-RAM
- (2) Description

The package is a steel encased lead shielded cask with wood impact limiters attached at both ends. The cask is a right circular cylinder. The overall dimensions of the packaging are approximately 178 inches long and 92 inches diameter with the impact limiters installed. The cask body is approximately 129 inches long with an outer diameter of 51 inches. The cask cavity has a length of approximately 111 inches and an inside diameter of 35 inches. The cask body is made of a 0.75-inch stainless steel inner shell, a 5.88-inch thick lead annulus, a 1.5-inch thick stainless steel outer shell, a 0.5-inch thick inner bottom plate and a 2.5-inch thick outside bottom plate. The lead shielding is 6 inches thick in the bottom end of the cask. The outer shell of the cask body is covered with a stainless steel thermal shield. The closure lid consists of a 2.5-inch thick outer stainless steel plate and a 0.5-inch thick inner stainless steel plate separated by 6 inches of lead shielding. The lid is secured by sixteen 1.5-inch diameter closure bolts. Two concentric silicone O-rings are installed in grooves on the underside of the lid. The cask is equipped with a sealed leak test port between the O-rings, a vent port in the closure lid and a sealed drain port in the bottom of the cask.

Each impact limiter is attached to the cask by eight 1.75-inch diameter bolts. The cask is equipped with 6 trunnions, four at the top and two at the bottom.

The gross weight of the package is approximately 80,000 pounds, including maximum contents of 9,500 pounds.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9233	8	71-9233	USA/9233/B(U)	2 OF	3

## 5.(a) Packaging (continued)

## (3) Drawings

The packaging is constructed in accordance with Transnuclear, Inc. Drawing Nos. 990-701, Rev. 6; 990-702, Rev. 6; 990-703, Rev. 7; 990-704, Rev. 3; 990-705, Rev. 5; 990-706, Rev. 3; 990-707, Rev. 3; 990-708, Rev. 6; and 990-709, Rev. 1.

## (b) Contents

## (1) Type and Form of Material

Dry irradiated and contaminated non-fuel-bearing solid materials contained within a secondary container.

## (2) Maximum quantity of material per package

Greater than Type A quantities of radioactive material which may include fissile material provided that the fissile material does not exceed the mass limits of 10 CFR 71.15. The contents may not exceed 2,000 times an A<sub>2</sub> quantity. The decay heat of the contents may not exceed 300 watts. The maximum gross weight of the contents, secondary container, and shoring is limited to 9,500 pounds.

6. As appropriate, shoring must be used in the secondary container sufficient to prevent significant movement of the contents under accident conditions.
7. Both the inner cask cavity and the secondary container must be free of water when the package is delivered to a carrier for transport.
8. In addition to the requirements of Subpart G of 10 CFR Part 71:
  - (a) Prior to each shipment, the lid seals must be inspected. The seals must be replaced with new seals if inspection shows any defects or every 12 months, whichever occurs first;
  - (b) The package shall be prepared for shipment and operated in accordance with the Operating Procedures of Section 7.0 of the application; and
  - (c) The package must meet the Acceptance Tests and Maintenance Program of Section 8.0 of the application.
9. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.
10. Expiration date: April 30, 2010.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9233	8	71-9233	USA/9233/B(U)	3 OF	3

REFERENCES

Transnuclear, Inc., application dated March 8, 2005.

Supplement dated: May 4, 2007.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

/RA/

Robert A. Nelson, Chief  
Licensing Branch  
Division of Spent Fuel Storage  
and Transportation  
Office of Nuclear Material Safety  
and Safeguards

Date: May 7, 2007

