

Facility:		Date of Exam:															
Tier	Group	RO K/A Category Points											SRO-Only Points				
		K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G *	Total	A2	G*	Total	
1. Emergency & Abnormal Plant Evolutions	1	3	4	4	N/A			3	3	N/A			3	20			
	2	1	1	1				2	1				1	7			
	Tier Totals	4	5	5				5	4				4	27			
2. Plant Systems	1	2	2	2	2	2	3	2	3	3	2	3	26				
	2	2	1	1	1	1	1	1	1	1	1	1	12				
	Tier Totals	4	3	3	3	3	4	3	4	4	3	4	38				
3. Generic Knowledge and Abilities Categories					1		2		3		4		10	1	2	3	4
					3		3		2		2						
<p>Note:</p> <ol style="list-style-type: none"> Ensure that at least two topics from every applicable K/A category are sampled within each tier of the RO and SRO-only outlines (i.e., except for one category in Tier 3 of the SRO-only outline, the "Tier Totals" in each K/A category shall not be less than two). The point total for each group and tier in the proposed outline must match that specified in the table. The final point total for each group and tier may deviate by ± 1 from that specified in the table based on NRC revisions. The final RO exam must total 75 points and the SRO-only exam must total 25 points. Systems/evolutions within each group are identified on the associated outline; systems or evolutions that do not apply at the facility should be deleted and justified; operationally important, site-specific systems/evolutions that are not included on the outline should be added. Refer to Section D.1.b of ES-401 for guidance regarding the elimination of inappropriate K/A statements. Select topics from as many systems and evolutions as possible; sample every system or evolution in the group before selecting a second topic for any system or evolution. Absent a plant-specific priority, only those K/As having an importance rating (IR) of 2.5 or higher shall be selected. Use the RO and SRO ratings for the RO and SRO-only portions, respectively. Select SRO topics for Tiers 1 and 2 from the shaded systems and K/A categories. * The generic (G) K/As in Tiers 1 and 2 shall be selected from Section 2 of the K/A Catalog, but the topics must be relevant to the applicable evolution or system. Refer to Section D.1.b of ES-401 for the applicable K/As. On the following pages, enter the K/A numbers, a brief description of each topic, the topics' importance ratings (IRs) for the applicable license level, and the point totals (#) for each system and category. Enter the group and tier totals for each category in the table above; if fuel handling equipment is sampled in other than Category A2 or G* on the SRO-only exam, enter it on the left side of Column A2 for Tier 2, Group 2 (Note #1 does not apply). Use duplicate pages for RO and SRO-only exams. For Tier 3, select topics from Section 2 of the K/A catalog, and enter the K/A numbers, descriptions, IRs, and point totals (#) on Form ES-401-3. Limit SRO selections to K/As that are linked to 10 CFR 55.43. 																	

ES-401		BWR Examination Outline Emergency and Abnormal Plant Evolutions - Tier 1/Group 1 (RO / SRO)						Form ES-401-1	
E/APE # / Name / Safety Function	K 1	K 2	K 3	A 1	A 2	G	K/A Topic(s)	IR	#
295001 Partial or Complete Loss of Forced Core Flow Circulation / 1 & 4		X					K2.06 – knowledge of the interrelationships between PARTIAL OR COMPLETE LOSS OF FORCED CORE FLOW CIRCULATION: Reactor Power. (41.7)	3.8	1
295003 Partial or Complete Loss of AC / 6			X				K3.02 – Knowledge of the reasons for the following responses as they apply to PARTIAL OR COMPLETE LOSS OF A.C. POWER: Selective tripping. (41.5)	2.9	2
295004 Partial or Total Loss of DC Pwr / 6				X			A1.01 – Ability to operate and/or monitor the following as they apply to PARTIAL OR COMPLETE LOSS OF D.C. POWER: D.C. Electrical distribution systems. (41.7)	3.3	3
295005 Main Turbine Generator Trip / 3					X		A.2.01 – Ability to determine and/or interpret the following as they apply to MAIN TURBINE GENERATOR TRIP: Turbine speed. (41.10)	2.6	4
295006 SCRAM / 1						X	2.4.46 – Ability to verify that the alarms are consistent with the plant conditions. SCRAM (41.10)	4.2	5
295016 Control Room Abandonment / 7		X					K2.03 – Knowledge of the interrelations between the CONTROL ROOM ABANDONMENT and the following: Control Room HVAC. (41.5)	2.9	6
295018 Partial or Total Loss of CCW / 8	X						K1.01 – Knowledge of the operational implications of the following concepts as they apply to PARTIAL OR COMPLETE LOSS OF COMPONENT COOLING WATER: Effects on component/system operation. (41.8)	3.5	7
295019 Partial or Total Loss of Inst. Air / 8			X				K3.02 – Knowledge of the reasons for the following responses as they apply to PARTIAL OR COMPLETE LOSS OF INSTRUMENT AIR: Standby air compressor operation. (41.5)	3.5	8
295021 Loss of Shutdown Cooling / 4		X					K2.03 – Knowledge of the interrelations between LOSS OF SHUTDOWN COOLING and RHR Shutdown Cooling (41.7)	3.6	9
295023 Refueling Acc / 8				X			A.1.02 – Ability to operate and/or monitor the following as they apply to REFUELING ACCIDENTS: Fuel pool cooling and cleanup system. (41.7)	2.9	10
295024 High Drywell Pressure / 5					X		A2.06 – Ability to determine and/or interpret the following as they apply to HIGH DRYWELL PRESSURE: Suppression pool temperature. (41.10)	4.1	11
295025 High Reactor Pressure / 3						X	2.1.32 – Ability to explain and apply system limits and precautions: High Reactor Pressure. (41.10)	3.8	12
295026 Suppression Pool High Water Temp. / 5	X						K1.02 – Knowledge of the operational implications of the following concepts as they apply to SUPPRESSION POOL HIGH WATER TEMPERATURE: Steam Condensation. (41.8)	3.5	13
295027 High Containment Temperature / 5							Mark III only		
295028 High Drywell Temperature / 5			X				K3.01 – Knowledge of the reasons for the following responses as they apply to HIGH DRYWELL TEMPERATURE: Emergency Depressurization (41.5)	3.6	14
295030 Low Suppression Pool Wtr Lvl / 5				X			A1.03 – Ability to operate and/or monitor the following as they apply to LOW SUPPRESSION POOL WATER LEVEL: HPCS (41.7)	3.4	15

295031 Reactor Low Water Level / 2					X		A2.03 – Ability to determine and/or interpret the following as they apply to REACTOR LOW WATER LEVEL: Reactor Pressure. (41.10)	4.2	16
295037 SCRAM Condition Present and Reactor Power Above APRM Downscale or Unknown / 1						X	2.2.37 – Ability to determine operability and/or availability of safety related equipment: (41.7)	3.6	17
295038 High Off-site Release Rate / 9	X						K1.01 – Knowledge of the operational implications of the following concepts as they apply to HIGH OFF-SITE RELEASE RATE: Biological effects of radioisotope injection. (41.8).	2.5	18
600000 Plant Fire On Site / 8		X					K2.04 – Knowledge of the interrelations between Plant Fire on Site and the following: Breakers, relays and disconnects.	2.5	19
700000 Generator Voltage and Electric Grid Disturbances / 6			X				K3.01 – Knowledge of the reasons for the following responses as they apply to GENERATOR VOLTAGE AND ELECTRIC GRID DISTURBANCES: Reactor and turbine trip criteria. (41.4,5 or 7)	3.9	20
K/A Category Totals:	3	4	4	3	3	3	Group Point Total:	20	

BWR Examination Outline								Form ES-401-1	
Emergency and Abnormal Plant Evolutions - Tier 1/Group 2 (RO / SRO)									
E/APE # / Name / Safety Function	K 1	K 2	K 3	A 1	A 2	G	K/A Topic(s)	IR	#
295002 Loss of Main Condenser Vac / 3									
295007 High Reactor Pressure / 3				X			A1.05 - Ability to operate and/or monitor the following as they apply to HIGH REACTOR PRESSURE: Reactor/turbine pressure regulating system (41.7)	3.7	21
295008 High Reactor Water Level / 2									
295009 Low Reactor Water Level / 2					X		A2.02 - Ability to determine and/or interpret the following as they apply to LOW REACTOR WATER LEVEL : Steam flow/feed flow mismatch (41.10)	3.6	22
295010 High Drywell Pressure / 5									
295011 High Containment Temp / 5									
295012 High Drywell Temperature / 5									
295013 High Suppression Pool Temp. / 5		X					K2.01: Knowledge of the interrelations between HIGH SUPPRESSION POOL TEMPERATURE and the following: Suppression pool cooling (41.7)	3.6	23
295014 Inadvertent Reactivity Addition / 1									
295015 Incomplete SCRAM / 1			X				K3.01 - Knowledge of the reasons for the following responses as they apply to INCOMPLETE SCRAM : Bypassing rod insertion blocks (41.5)	3.4	24
295017 High Off-site Release Rate / 9									
295020 Inadvertent Cont. Isolation / 5 & 7									
295022 Loss of CRD Pumps / 1						X	2.1.28 - Knowledge of the purpose and function of major system components and controls. (41.7)	4.1	25
295029 High Suppression Pool Wtr Lvl / 5									
295032 High Secondary Containment Area Temperature / 5				X			A1.03 - Ability to operate and/or monitor the following as they apply to HIGH SECONDARY CONTAINMENT AREA TEMPERATURE : Secondary containment ventilation (41.7)	3.7	26
295033 High Secondary Containment Area Radiation Levels / 9									
295034 Secondary Containment Ventilation High Radiation / 9									
295035 Secondary Containment High Differential Pressure / 5	X						K1-01 - Knowledge of the operational implications of the following concepts as they apply to SECONDARY CONTAINMENT HIGH DIFFERENTIAL PRESSURE :Secondary Containment Integrity (41.8 to 41.10)	3.9	27
295036 Secondary Containment High Sump/Area Water Level / 5									
500000 High CTMT Hydrogen Conc. / 5									

K/A Category Point Totals:	1	1	1	2	1	1	Group Point Total:			7

ES-401		BWR Examination Outline Plant Systems - Tier 2/Group 1 (RO / SRO)											Form ES-401-1	
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
203000 RHR/LPCI: Injection Mode								X				A2.09 - Ability to (a) predict the impacts of the following on the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) ; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: Inadequate system flow (41.5)	3.3	28
205000 Shutdown Cooling									X			A3.03 - Ability to monitor automatic operations of the SHUTDOWN COOLING SYSTEM (RHR SHUTDOWN COOLING MODE) including: Lights and alarms (41.7)	3.5	29
206000 HPCI												Suppressed K/A		
207000 Isolation (Emergency) Condenser												Suppressed K/A		
209001 LPCS										X		A4.03 - Ability to manually operate and/or monitor in the control room: Injection valves (41.7)	3.7	30
209002 HPCS											X	2.2.22 Knowledge of limiting conditions for operations and safety limits. (41.5)	4.0	31
211000 SLC	X											K1.07 - Knowledge of the physical connections and/or cause/effect relationships between STANDBY LIQUID CONTROL SYSTEM and the following: Jet pump differential pressure indication: Plant-Specific (41.2 to 41.9)	2.6	32
212000 RPS		X										K2.01 - Knowledge of electrical power supplies to the following: RPS motor-generator sets (41.7)	3.2	33
215003 IRM			X									K3.01 - Knowledge of the effect that a loss or malfunction of the INTERMEDIATE RANGE MONITOR (IRM) SYSTEM will have on following: RPS (41.7)	3.9	34
215004 Source Range Monitor				X								K4.05 - Knowledge of SOURCE RANGE MONITOR (SRM) SYSTEM design feature(s) and/or interlocks which provide for the following: Alarm seal-in (41.7)	2.5	35
215005 APRM / LPRM					X							K5.05 - Knowledge of the operational implications of the following concepts as they apply to AVERAGE POWER RANGE MONITOR/LOCAL POWER RANGE MONITOR SYSTEM : Core flow effects on APRM trip setpoints (41.5)	3.6	36
217000 RCIC						X						K6.03 - Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) : Suppression pool water supply (41.7)	3.5	37
218000 ADS							X					A1.04 - Ability to predict and/or monitor changes in parameters associated with operating the AUTOMATIC DEPRESSURIZATION SYSTEM controls including: Reactor pressure (41.5)	4.1	38

223002 PCIS/Nuclear Steam Supply Shutoff									X				A2.09 - Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT ISOLATION SYSTEM/NUCLEAR STEAM SUPPLY SHUT-OFF ; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: System initiation (41.5)	3.6	39
239002 SRVs										X			A3.06 - Ability to monitor automatic operations of the RELIEF/SAFETY VALVES including: Reactor pressure (41.7)	4.1	40
259002 Reactor Water Level Control											X		A4.01 - Ability to manually operate and/or monitor in the control room: All individual component controllers in the manual mode (41.7)	3.8	41
261000 SGTS												X	2.4.2 - Knowledge of system setpoints, interlocks and automatic actions associated with EOP entry. (41.7)	4.5	42
262001 AC Electrical Distribution	X												K1.03 - Knowledge of the physical connections and/or cause/effect relationships between A.C. ELECTRICAL DISTRIBUTION and the following: Off-site power sources (41.2 to 41.9)	3.4	43
262002 UPS (AC/DC)			X										K3.01. Knowledge of the effect that a loss or malfunction of the Uninterruptible Power Supply (AC/DC) will have on Water Level Control	3.1	44
263000 DC Electrical Distribution		X											K2.01 - Knowledge of electrical power supplies to the following: Major D.C. loads (CFR: 41.7)	3.1	45
264000 EDGs				X									K4.04 - Knowledge of EMERGENCY GENERATORS (DIESEL/JET) design feature(s) and/or interlocks which provide for the following: Field flashing (CFR: 41.7)	2.6	46
300000 Instrument Air					X								K5.01 - Knowledge of the operational implications of the following concepts as they apply to the INSTRUMENT AIR SYSTEM: Air compressors (41.5)	2.5	47
400000 Component Cooling Water						X							K6.05 - Knowledge of the effect that a loss or malfunction of the following will have on the CCWS: Motors (41.7)	2.8	48
203000 RHR/LPCI: Injection Mode							X						A1.01 - Ability to predict and/or monitor changes in parameters associated with operating the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) controls including: Reactor water level (41.5)	4.2	49
212000 RPS								X					A2.06 - Ability to (a) predict the impacts of the following on the REACTOR PROTECTION SYSTEM ; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: High reactor power (41.5)	4.1	50
262001 AC Electrical Distribution										X			A3.03 - Ability to monitor automatic operations of the A.C. ELECTRICAL DISTRIBUTION including: Load shedding (41.7)	3.4	51
262002 UPS (AC/DC)						X							K6.02 Knowledge of the effect that a loss or malfunction of the following will have on the Uninterruptible Power Supply (AC/DC) DC electrical power (41.7)	2.8	52
400000 Component Cooling Water												X	2.1.7 - Ability to evaluate plant performance and make operational judgments based on operating characteristics, reactor behavior, and instrument interpretation. +(41.5)	4.4	53
K/A Category Point Totals:	2	2	2	2	2	3	2	3	3	2	3		Group Point Total:		26

ES-401 1		BWR Examination Outline											Form ES-401-	
Plant Systems - Tier 2/Group 2 (RO / SRO)														
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
201001 CRD Hydraulic	X											K1.01 - Knowledge of the physical connections and/or cause/effect relationships between CONTROL ROD DRIVEHYDRAULIC SYSTEM and the following: Condensate system (41.2 to 41.9)	3.1	54
201002 RMCS												Suppressed K/A		
201003 Control Rod and Drive Mechanism			X									K3.01 - Knowledge of the effect that a loss or malfunction of the CONTROL ROD AND DRIVE MECHANISM will have on following: Reactor power (41.7)	3.2	55
201004 RSCS												Suppressed K/A		
201005 RCIS														
201006 RWM												Suppressed K/A		
202001 Recirculation														
202002 Recirculation Flow Control		X										K2.02 - Knowledge of electrical power supplies to the following: Hydraulic power unit: Plant-Specific (CFR: 41.7)	2.6	56
204000 RWCU														
214000 RPIS												Suppressed K/A		
215001 Traversing In-core Probe														
215002 RBM												Suppressed K/A		
216000 Nuclear Boiler Inst.				X								K4.09 - Knowledge of NUCLEAR BOILER INSTRUMENTATION design feature(s) and/or interlocks which provide for the following: Protection against filling the main steam lines from the feed system (41.7)	3.3	57
219000 RHR/LPCI: Torus/Pool Cooling Mode					X							K5.04 - Knowledge of the operational implications of the following concepts as they apply to RHR/LPCI: TORUS/SUPPRESSION POOL COOLING MODE : Heat exchanger operation (41.5)	2.9	58
223001 Primary CTMT and Aux.						X						K6.13 - Knowledge of the effect that a loss or malfunction of the following will have on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES : Applicable plant air system/ nitrogen make-up system (41.7)	3.2	59
226001 RHR/LPCI: CTMT Spray Mode												Suppressed K/A		
230000 RHR/LPCI: Torus/Pool Spray Mode												Suppressed K/A		
233000 Fuel Pool Cooling/Cleanup														
234000 Fuel Handling Equipment														
239001 Main and Reheat Steam														
239003 MSIV Leakage Control														
241000 Reactor/Turbine Pressure Regulator														

245000 Main Turbine Gen. / Aux.													A1.01 - Ability to predict and/or monitor changes in parameters associated with operating the REACTOR CONDENSATE SYSTEM controls including: System flow (41.5)	2.9	60
256000 Reactor Condensate							X								
259001 Reactor Feedwater															
268000 Radwaste															
271000 Offgas								X					A2.03 - Ability to (a) predict the impacts of the following on the OFFGAS SYSTEM ; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: Main steamline high radiation (41.5)	3.5	61
272000 Radiation Monitoring									X				A3.10 - Ability to monitor automatic operations of the RADIATION MONITORING SYSTEM including: Lights and alarms (41.7)	3.3	62
286000 Fire Protection										X			A4.04 - Ability to manually operate and/or monitor in the control room: Fire main pressure: Plant-Specific (41.7)	2.8	63
288000 Plant Ventilation											X		2.4.11 Knowledge of abnormal condition procedures. (41.10)	4.0	64
290001 Secondary CTMT	X												K1.06 - Knowledge of the physical connections and/or cause/effect relationships between SECONDARY CONTAINMENT and the following: Auxiliary building isolation: BWR-6 (41.2 to 41.9)	3.4	65
290003 Control Room HVAC															
290002 Reactor Vessel Internals															
K/A Category Point Totals:	2	1	1	1	1	1	1	1	1	1	1	1	Group Point Total:		12

Facility:		Date of Exam:				
Category	K/A #	Topic	RO		SRO-Only	
			IR	#	IR	#
1. Conduct of Operations	2.1.20	Ability to interpret and execute procedure steps.(41.10)	4.6	66		
	2.1.25	Ability to interpret reference materials, such as graphs, curves, tables, etc. (41.10)	3.9	67		
	2.1.30	Ability to locate and operate components, including local controls. (41.7)	4.4	68		
	Subtotal			3		
2. Equipment Control	2.2.36	Ability to analyze the effect of maintenance activities, such as degraded power sources, on the status of limiting conditions for operations. (41.10)	3.1	69		
	2.2.40	Ability to apply Technical Specifications for a system. (41.10)	3.4	70		
	2.2.44	Ability to interpret control room indications to verify the status and operation of a system, and understand how operator actions and directives affect plant and system conditions. (41.5)	4.2	71		
	Subtotal			3		
3. Radiation Control	2.3.4	Knowledge of radiation exposure limits under normal or emergency conditions. (41.12)	3.2	72		
	2.3.14	Knowledge of radiation or contamination hazards that may arise during normal, abnormal, or emergency conditions or activities. (41.12)	3.4	73		
	Subtotal			2		
4. Emergency Procedures / Plan	2.4.1	Knowledge of EOP entry conditions and immediate action steps. (41.10)	4.6	74		
	2.4.45	Ability to prioritize and interpret the significance of each annunciator or alarm. (41.10)	4.1	75		
	Subtotal			2		
Tier 3 Point Total				10		

[illegible]

Facility:		Date of Exam:																
Tier	Group	RO K/A Category Points											SRO-Only Points					
		K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G *	Total	A2	G*	Total		
1. Emergency & Abnormal Plant Evolutions	1													4	3	7		
	2													1	2	3		
	Tier Totals													5	5	10		
2. Plant Systems	1													3	2	5		
	2													1	2	3		
	Tier Totals													4	4	8		
3. Generic Knowledge and Abilities Categories		1		2		3		4						1	2	3	4	7
														2	2	1	2	
<p>Note:</p> <ol style="list-style-type: none"> 1. Ensure that at least two topics from every applicable K/A category are sampled within each tier of the RO and SRO-only outlines (i.e., except for one category in Tier 3 of the SRO-only outline, the "Tier Totals" in each K/A category shall not be less than two). 2. The point total for each group and tier in the proposed outline must match that specified in the table. The final point total for each group and tier may deviate by ± 1 from that specified in the table based on NRC revisions. The final RO exam must total 75 points and the SRO-only exam must total 25 points. 3. Systems/evolutions within each group are identified on the associated outline; systems or evolutions that do not apply at the facility should be deleted and justified; operationally important, site-specific systems/evolutions that are not included on the outline should be added. Refer to Section D.1.b of ES-401 for guidance regarding the elimination of inappropriate K/A statements. 4. Select topics from as many systems and evolutions as possible; sample every system or evolution in the group before selecting a second topic for any system or evolution. 5. Absent a plant-specific priority, only those K/As having an importance rating (IR) of 2.5 or higher shall be selected. Use the RO and SRO ratings for the RO and SRO-only portions, respectively. 6. Select SRO topics for Tiers 1 and 2 from the shaded systems and K/A categories. 7.* The generic (G) K/As in Tiers 1 and 2 shall be selected from Section 2 of the K/A Catalog, but the topics must be relevant to the applicable evolution or system. Refer to Section D.1.b of ES-401 for the applicable K/As. 8. On the following pages, enter the K/A numbers, a brief description of each topic, the topics' importance ratings (IRs) for the applicable license level, and the point totals (#) for each system and category. Enter the group and tier totals for each category in the table above; if fuel handling equipment is sampled in other than Category A2 or G* on the SRO-only exam, enter it on the left side of Column A2 for Tier 2, Group 2 (Note #1 does not apply). Use duplicate pages for RO and SRO-only exams. 9. For Tier 3, select topics from Section 2 of the K/A catalog, and enter the K/A numbers, descriptions, IRs, and point totals (#) on Form ES-401-3. Limit SRO selections to K/As that are linked to 10 CFR 55.43. 																		

[illegible]

K/A Category Totals:						4	3	Group Point Total:		7

[illegible]

K/A Category Point Totals:					1	2	Group Point Total:	3
----------------------------	--	--	--	--	---	---	--------------------	---

ES-401												BWR Examination Outline												Form ES-401-1			
Plant Systems - Tier 2/Group 1 (RO / SRO)																											
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)												IR	#		
203000 RHR/LPCI: Injection Mode																											
205000 Shutdown Cooling																											
206000 HPCI												Suppressed K/A															
207000 Isolation (Emergency) Condenser												Suppressed K/A															
209001 LPCS									X			A2.03 - Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM ; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: A.C. failures(45.6)												3.6	86		
209002 HPCS																											
211000 SLC											X	2.1.7 Ability to evaluate plant performance and make operational judgments based on operating characteristics, reactor behavior, and instrument interpretation. (43.5)												4.7	87		
212000 RPS																											
215003 IRM																											
215004 Source Range Monitor									X			A2.05 - Ability to (a) predict the impacts of the following on the SOURCE RANGE MONITOR (SRM) SYSTEM ; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: Faulty or erratic operation of detectors/system (45.6)												3.5	88		
215005 APRM / LPRM																											
217000 RCIC											X	2.4.8 Knowledge of how abnormal operating procedures are used in conjunction with EOPs. (43.5)												4.5	89		
218000 ADS																											
223002 PCIS/Nuclear Steam Supply Shutoff																											
239002 SRVs																											
259002 Reactor Water Level Control																											
261000 SGTS																											
262001 AC Electrical Distribution																											
262002 UPS (AC/DC)																											

[illegible]

ES-401 401-1		BWR Examination Outline											Form ES-	
Plant Systems - Tier 2/Group 2 (RO / SRO)														
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
201001 CRD Hydraulic														
201002 RMCS												Suppressed K/A		
201003 Control Rod and Drive Mechanism														
201004 RSCS												Suppressed K/A		
201005 RCIS														
201006 RWM												Suppressed K/A		
202001 Recirculation														
202002 Recirculation Flow Control														
204000 RWCU														
214000 RPIS												Suppressed K/A		
215001 Traversing In-core Probe														
215002 RBM												Suppressed K/A		
216000 Nuclear Boiler Inst.														
219000 RHR/LPCI: Torus/Pool Cooling Mode														
223001 Primary CTMT and Aux.											X	2.2.36 Ability to analyze the effect of maintenance activities, such as degraded power sources, on the status of limiting conditions for operations. (43.2)	4.2	91
226001 RHR/LPCI: CTMT Spray Mode												Suppressed K/A		
230000 RHR/LPCI: Torus/Pool Spray Mode												Suppressed K/A		
233000 Fuel Pool Cooling/Cleanup														
234000 Fuel Handling Equipment														
239001 Main and Reheat Steam														
239003 MSIV Leakage Control								X				A2.02 - Ability to (a) predict the impacts of the following on the MSIV LEAKAGE CONTROL SYSTEM ; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (41.5) Outboard MSIV valves leakage.	3.3	92
241000 Reactor/Turbine Pressure Regulator														
245000 Main Turbine Gen. / Aux.														
256000 Reactor Condensate											X	2.2.38 Knowledge of conditions and limitations in the facility license. (43.1)	4.5	93
259001 Reactor Feedwater														
268000 Radwaste														

271000 Offgas													
272000 Radiation Monitoring													
286000 Fire Protection													
288000 Plant Ventilation													
290001 Secondary CTMT													
290003 Control Room HVAC													
290002 Reactor Vessel Internals													
K/A Category Point Totals:								1			2	Group Point Total:	3

Facility:		Date of Exam:				
Category	K/A #	Topic	RO		SRO-Only	
			IR	#	IR	#
1. Conduct of Operations	2.1.25	Ability to interpret reference materials, such as graphs, curves, tables, etc. (43.5)			4.2	94
	2.1.36	Knowledge of procedures and limitations involved in core alterations. (43.6)			4.1	95
	2.1.					
	2.1.					
	2.1.					
	2.1.					
	Subtotal					
2. Equipment Control	2.2.12	Knowledge of surveillance procedures. (45.13)			4.1	96
	2.2.40	Ability to apply Technical Specifications for a system. (43.2 / 43.5)			4.7	97
	2.2.					
	2.2.					
	2.2.					
	2.2.					
	Subtotal					
3. Radiation Control	2.3.6	Ability to approve release permits. (43.4)			3.8	98
	2.3.					
	2.3.					
	2.3.					
	2.3.					
	2.3.					
	Subtotal					
4. Emergency Procedures / Plan	2.4.18	Knowledge of the specific bases for EOPs. (43.1)			4.0	99
	2.4.40	Knowledge of SRO responsibilities in emergency plan implementation. (43.5)			4.5	100
	2.4.					
	2.4.					
	2.4.					
	2.4.					
	Subtotal					
Tier 3 Point Total						7

[illegible]

NRC

ES-301

Administrative Topics Outline

Form ES-301-1

Facility: <u>River Bend Station</u>		Date of Examination: 11/12/2012
Examination Level: RO <input checked="" type="checkbox"/> SRO <input type="checkbox"/>		Operating Test Number: _____
Administrative Topic (see Note)	Type Code*	Describe activity to be performed
Conduct of Operations	R,M	(A1) Determine when Hot Shutdown Boron has been injected into the core. KA 2.1.25; IR 3.9
Conduct of Operations	R,N	(A2) Determine maintenance requirements of an active license. KA 2.1.4; IR 3.3
Equipment Control	R,M	(A3) Use plant drawings to determine the effect of removing a fuse. KA 2.2.15; IR 3.9
Radiation Control	R,N	(A4) Obtain radiological information from a survey map. KA 2.3.7; IR 3.5
Emergency Procedures/Plan		
NOTE: All items (5 total) are required for SROs. RO applicants require only 4 items unless they are retaking only the administrative topics, when all 5 are required.		
* Type Codes & Criteria: <div style="display: inline-block; vertical-align: top; margin-left: 20px;"> (C)ontrol room, (S)imulator, or Class(R)oom (D)irect from bank (≤ 3 for ROs; ≤ 4 for SROs & RO retakes) (N)ew or (M)odified from bank (≥ 1) (P)revious 2 exams (≤ 1; randomly selected) </div>		

NRC

ES-301

Administrative Topics Outline

Form ES-301-1

Facility: <u>River Bend Station</u>		Date of Examination: 11/12/2012
Examination Level: RO <input type="checkbox"/> SRO <input checked="" type="checkbox"/>		Operating Test Number: _____
Administrative Topic (see Note)	Type Code*	Describe activity to be performed
Conduct of Operations	R,M	(A5) Generate a manual LCO tracking sheet. KA 2.1.18; IR 3.8
Conduct of Operations	R,M	(A6) Determine Plant Safety Index during shutdown conditions KA 2.1.23; IR 4.4
Equipment Control	R,M	(A7) Review and Approve a Completed Surveillance Test Procedure. KA 2.2.12; IR 4.1
Radiation Control	R,M	(A8) Calculate Maximum Permissible Stay Time KA 2.3.7; IR 3.6
Emergency Procedures/Plan	R,M	(A9) Classify an Emergency. KA 2.4.41; IR 4.6
NOTE: All items (5 total) are required for SROs. RO applicants require only 4 items unless they are retaking only the administrative topics, when all 5 are required.		
* Type Codes & Criteria: <div style="margin-left: 20px;"> (C)ontrol room, (S)imulator, or Class(R)oom (D)irect from bank (≤ 3 for ROs; ≤ 4 for SROs & RO retakes) 1 (N)ew or (M)odified from bank (≥ 1) 4 (P)revious 2 exams (≤ 1; randomly selected) 0 </div>		

NRC

ES-301

Control Room/In-Plant Systems Outline

Form ES-301-2

Facility: <u>River Bend Station</u>		Date of Examination: <u>11/12/2012</u>	
Exam Level: RO <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>		Operating Test No.: _____	
Control Room Systems [@] (8 for RO); (7 for SRO-I); (2 or 3 for SRO-U, including 1 ESF)			
System / JPM Title	Type Code*	Safety Function	
a. (S1) Respond to High Radiation levels in the Auxiliary Building	A,S,EN,N	5	
b. (S2) Transfer Reactor Recirculation Pumps from Fast to Slow Speed	A,S,D	1	
c. (S3) Manual Isolation of a Main Steam Line During Power Operation	S,D	3	
d. (S4) Shift Divisions of Control Building Chilled Water	A,S,D,EN	9	
e. (S5) Secure High Pressure Core Spray Following Spurious Initiation	A,S,D,EN	2	
f. (S6) Start Residual Heat Removal in the Shutdown Cooling Mode	S,D,L	4	
g. (C1) Respond to a loss of Control Room Annunciators	C,N	6	
h. (C2) Perform APRM Setdown Channel Functional Test for APRM B	C,N	7	
In-Plant Systems [@] (3 for RO); (3 for SRO-I); (3 or 2 for SRO-U)			
i. (P1) Transfer RCIC Steam Supply Isolation Valve to Alternate Power	E,L,N,R	2	
j. (P2) Start of Fire Protection Water Pump	A,D,E	8	
k. (P3) Initiate Full Scram and NSSSS Isolation from the Electrical Protection Assembly (EPA) breakers	D,E,EN	7	
@ All RO and SRO-I control room (and in-plant) systems must be different and serve different safety functions; all 5 SRO-U systems must serve different safety functions; in-plant systems and functions may overlap those tested in the control room.			
* Type Codes	Criteria for RO / SRO-I / SRO-U		
(A)lternate path (C)ontrol room (D)irect from bank (E)mergency or abnormal in-plant (EN)gineered safety feature (L)ow-Power / Shutdown (N)ew or (M)odified from bank including 1(A) (P)revious 2 exams (R)CA (S)imulator	4-6 / 4-6 / 2-3 5 <input checked="" type="checkbox"/> $\leq 9 / \leq 8 / \leq 4$ 8 <input checked="" type="checkbox"/> $\geq 1 / \geq 1 / \geq 1$ 2 <input checked="" type="checkbox"/> - / - / ≥ 1 (control room system) - $\geq 1 / \geq 1 / \geq 1$ 3 <input checked="" type="checkbox"/> $\geq 2 / \geq 2 / \geq 1$ 4; 1(A) <input checked="" type="checkbox"/> $\leq 3 / \leq 3 / \leq 2$ (randomly selected) 0 $\geq 1 / \geq 1 / \geq 1$ 1 <input checked="" type="checkbox"/>		

Facility: River Bend Station			Date of Exam: 11/12/2012			Operating Test No.:											
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M(*)		
		1			2			3			4				R	I	U
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P				
		U1	R2	R3	U2	R3	R2										
RO <input type="checkbox"/>	RX	-												0	1	1	0
SRO-I <input type="checkbox"/>	NOR	1,2												2	1	1	1
SRO-U <input type="checkbox"/>	I/C	4,5,6, 8,9												5	4	4	2
<input checked="" type="checkbox"/> U1	MAJ	7												1	2	2	1
	TS	4,5												2	0	2	2
RO <input checked="" type="checkbox"/> R2	RX		3				-							1	1	1	0
SRO-I <input type="checkbox"/>	NOR		2				2							2	1	1	1
SRO-U <input type="checkbox"/>	I/C		4,8				4,6,8							5	4	4	2
	MAJ		7				7							2	2	2	1
	TS		-				-							0	0	2	2
RO <input checked="" type="checkbox"/> R3	RX			-		3								1	1	1	0
SRO-I <input type="checkbox"/>	NOR			1		1								2	1	1	1
SRO-U <input type="checkbox"/>	I/C			6,9		5,6								4	4	4	2
	MAJ			7		7								2	2	2	1
	TS			-		-								0	0	2	2
RO <input type="checkbox"/>	RX				-									0	1	1	0
SRO-I <input type="checkbox"/>	NOR				1,2									2	1	1	1
SRO-U <input type="checkbox"/>	I/C				3,4,5, 6,8									5	4	4	2
<input checked="" type="checkbox"/> U2	MAJ				7									1	2	2	1
	TS				3,4									2	0	2	2

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls (ATC)" and "balance-of-plant (BOP)" positions; Instant SROs must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an Instant SRO *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.

Facility: River Bend Station				Date of Exam: 11/12/2012				Operating Test No.:										
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M (*)			
		1			2			3			4							
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N							
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P					
		U3	I2	R1	I2	I1	R1	I1	R1	I2						R	I	U
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input checked="" type="checkbox"/> U3	RX	-												0	1	1	0	
	NOR	1,2												2	1	1	1	
	I/C	4,5,6,8,9												5	4	4	2	
	MAJ	7												1	2	2	1	
	TS	4,5												2	0	2	2	
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> I2 SRO-U <input type="checkbox"/>	RX		3		-					-				1	1	1	0	
	NOR		2		1,2					2				4	1	1	1	
	I/C		4,8		3,4,5,6,8					4, 6, 8				10	4	4	2	
	MAJ		7		7					7				3	2	2	1	
	TS		-		3,4					-				2	0	2	2	
RO <input checked="" type="checkbox"/> R1 SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX			-			-		3					1	1	1	0	
	NOR			1			2		1					3	1	1	1	
	I/C			6,9			4,6,8		5,9					7	4	4	2	
	MAJ			7			7		7					3	2	2	1	
	TS			-			-		-					0	0	2	2	
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> I1 SRO-U <input type="checkbox"/>	RX					3		-						1	1	1	0	
	NOR					1		1,2						3	1	1	1	
	I/C					5,6		4,5,6,8,9						7	4	4	2	
	MAJ					7		7						2	2	2	1	
	TS					-		4,6						2	0	2	2	

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls (ATC)" and "balance-of-plant (BOP)" positions; Instant SROs must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an Instant SRO *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.

NRC

Appendix D

Scenario Outline

Form ES-D-1

Facility: <u>River Bend Station</u>	Scenario No.: <u>A</u>	Op-Test No.: _____	
Examiners: _____ Operators: _____ _____ _____			
Initial Conditions:			
<p><u>Mode 1, Reactor power 68%. Power ascension in progress following downpower for Feedwater pump 'C' seal replacement. APRM B in bypass due to downscale failure. FWS-P1A & B in service.</u></p> <p>Turnover: Shift priorities: 1) Start lube oil system for FWS-P1C in preparation for pump start. 2) Place 3rd Feed Reg Valve in service. 3) Raise reactor power in accordance with Reactivity Control Plan Step 20, then await further guidance from reactor engineering.</p>			
Event No.	Malf. No.	Event Type*	Event Description
1	NA	N (CRS,BOP)	Start Feedwater pump "C" lube oil system per SOP-0009.
2	NA	N (CRS,ATC)	Place 3 rd Feedwater Regulating Valve in service per SOP-0009.
3	NA	R (ATC)	Raise reactor power in accordance with the reactivity control plan Step 20.
4	NMS015F	I (CRS,ATC)	(Tech Spec) APRM F Upscale failure due to flow converter downscale failure and half scram.
5	MSC011	C(CRS)	(Tech Spec) 171' airlock inner door seal failure.
6	p870_54a: g_5 FAIL ON	C(CRS,BOP)	Steam Packing Exhauster failure requiring equipment rotation.
7	EHC001 RPS001A	M (ALL)	Main Turbine Trip/Anticipated Transient Without Scram with MSIVs open due to failure of RPS to completely de-energize.
8	FWS004B	C (CRS,ATC)	Feedwater Master Level Controller output fails high.
9	EHC002B	C (CRS,BOP)	Main Turbine Bypass Valves fail closed.
* (N)ormal, (R)eactivity, (I)nstrument, (C)omponent, (M)ajor			

Total Malfunctions (5-8) **(7)**APRM F, 171' airlock, Stm Packing Exh.,Turb trip, ATWS, Master Controller, Turb Bypass Valves.

Malfunctions after EOP entry (1-2) **(2)** Feedwater Master Controller, Turbine Bypass Valves

Abnormal Events (2-4) **(2)** AOP-2,AOP-3

Major Transients (1-2) **(1)** ATWS

EOPs entered (1-2) **(2)** EOP-1, EOP-2

EOP contingencies (0-2) **(1)** EOP-1A

Critical Tasks (2-3) **(2)** Terminate injection to <-56", Begin control rod insertion

NRC

Appendix D

Scenario Outline

Form ES-D-1

Facility: <u>River Bend Station</u>	Scenario No.: <u>B</u>	Op-Test No.: _____
Examiners: _____ Operators: _____ _____ _____		
Initial Conditions: <u>Mode 1, 100% power, Division 1 work week, Div 1 DG tagged out</u>		
Turnover: <u>Shift Priorities: 1) Alternate HDL Pumps from A to B due to report of seal leakage on A. 2) Run STP-402-0201 for scheduled surveillance.</u>		

Event No.	Malf. No.	Event Type*	Event Description
1	NA	N (CRS,ATC)	Alternate HDL Pumps from A to B due to reported seal leakage.
2	NA	N (CRS,BOP)	Run STP-402-0201 for scheduled surveillance.
3	CRDM2809 Uncoupled	R(ATC) C(CRS)	(Tech Spec) Control Rod Drop – Control Rod 28-09
4	CRD001A	C (CRS,BOP)	(Tech Spec) CRD pump trip
5	FWS001A	C (CRS, ATC)	Feedwater A pump trip
6	ED004F	C (ALL)	Trip of NJS-LDC1F/Loss of Feed/Reactor Scram
7	RCS007 E22MOV F004 BREAKER TRIP RCIC001	M (ALL)	Coolant leak in the drywell with loss of power to E22-F004 and trip of RCIC
8	ED003H RHR002B RHR001C	C (CRS,BOP)	ENS-SWG1A bus loss, RHR B fails to auto start, E12-F042C injection valve fails.

* (N)ormal, (R)eactivity, (I)nstrument, (C)omponent, (M)ajor

Total Malfunctions (5-8) **(6)** Rod drop, CRD trip, Feedpump trip, NJS Bus, Leak, E12-F042C

Malfunctions after EOP entry (1-2) **(2)** Leak, E12-F042C

Abnormal Events (2-4) **(3)**AOP-0061, AOP-0006, AOP-0003

Major Transients (1-2) **(1)** Leak

EOPs entered (1-2) **(2)** EOP-1, EOP-2

EOP contingencies (0-2) **(2)** Alternate Level Control, Emergency Depressurization

Critical Tasks (2-3) **(3)** Insert control rod 28-09, Open SRVs to depressurize vessel, manually start RHR B.

NRC

Appendix D

Scenario Outline

Form ES-D-1

Facility: <u>River Bend Station</u>	Scenario No.: <u>C</u>	Op-Test No.: _____	
Examiners: _____		Operators: _____	
_____		_____	
_____		_____	
<p>Initial Conditions: <u>Mode 1, 100% power. Startup Feed Reg Valve in Augmentation Mode per SOP-0009 to support maintenance on Feed Reg Valve "C". Feed Reg Valve "C" has been returned to service. Downpower for sequence exchange this shift.</u></p> <p>Turnover: <u>Shift Priorities: 1)Remove Startup Feed Reg Valve from Augmentation Mode. 2)Start RHR B for STP-204-6302and notify IST personnel when the pump is running at reference conditions. 3)Lower reactor power for sequence exchange per the reactivity control plan while field personnel gather data following RHR B pump start.</u></p>			
Event No.	Malf. No.	Event Type*	Event Description
1	NA	N (CRS,ATC)	Remove Startup Feedwater Regulating Valve from Augmentation Mode and place in standby
2	NA	N (CRS,BOP)	Perform STP-204-6302 Section 7.1, RHR B Quarterly Surveillance.
3	NA	R(ATC)	Lower reactor power with Reactor Recirculation flow in accordance with the Reactivity Control Plan Step 1.
4	RHR002B	C(CRS,BOP)	(Tech Spec) RHR B trips
5	DI-CNM-HA68A-CAM	C(CRS,ATC)	Feedwater Pump "A" minimum flow valve fails open.
6	RCIC005	I(CRS,BOP)	(Tech Spec) Inadvertent RCIC initiation.
7	RCIC004 RCIC006 RPS001B	M(ALL)	RCIC steam supply line break in the RCIC Room and Main Steam Tunnel with failure of RCIC Steam Supply Valves fail to isolate. Auto scram signals fail.
8	MSS008G MSS008D MSS008I	C(CRS,BOP)	Three Safety Relief Valves fail to energize when required for emergency depressurization.
9	FWS005A	C(CRS,ATC)	Startup Feedwater Regulating Valve fails closed.
<p>* (N)ormal, (R)eactivity, (I)nstrument, (C)omponent, (M)ajor</p>			

Total Malfunctions (5-8) **(6)** RHR B trip, A min flow, RCIC initiation, RCIC steam leak, SRV failure, Startup Reg Valve Failure

Malfunctions after EOP entry (1-2) **(2)** SRV failure, Startup Reg Valve

Abnormal Events (2-4) **(2)** AOP-0006-Min flow failure, AOP-0003-Steam Leak

Major Transients (1-2) **(1)** Steam leak with failure to isolate affecting multiple areas

EOPs entered (1-2) **(2)** EOP-1, EOP-3

EOP contingencies (0-2) **(1)** Emergency Depressurization

NRC

Appendix D

Scenario Outline

Form ES-D-1

Facility: <u>River Bend Station</u>	Scenario No.: <u>D</u>	Op-Test No.: _____
Examiners: _____ Operators: _____ _____ _____		
Initial Conditions: <u>Mode 1, 75% power.</u>		
Turnover: <u>Shift Priorities: 1) Start Feedwater Pump "A" 2) Continue power ascension with recirc flow per reactivity control plan. 3) Transfer Steam Seal Evaporator to Extraction Steam.</u>		

Event No.	Malfunction No.	Event Type*	Event Description
1	NA	N (SRO, ATC)	Start a Reactor Feedwater Pump "A"
2	NA	R (ATC)	Raise reactor power with reactor recirculation flow
3	NA	N (SRO-BOP)	Transfer Steam Seal Evaporator to Extraction Steam
4	RMS016A	I(SRO)	(Technical Specification) Failure of RMS-RE16A Drywell Radiation Monitor
5	ED004Q	C (SRO, BOP)	(Technical Specification) Loss of EJS-LDC2B
6	FWS016A	I(SRO,ATC)	Feedwater flow input to Feedwater Level Control failure
7	ED001	M (ALL)	Loss of offsite power
8	RCIC003A	C(SRO,BOP)	RCIC Flow controller fails low
9	SWP-P2A BKR TRIP	C(SRO,ATC)	SWP-P2A pump breaker trip

* (N)ormal, (R)eactivity, (I)nstrument, (C)omponent, (M)ajor

Total Malfunctions (5-8) **(6)** EJS-LDC2B, RMS-RE16A, FWLC input, Loss of Offsite power, RCIC controller, SWP-P2A
 Malfunctions after EOP entry (1-2) **(2)** RCIC controller, SWP-P2A
 Abnormal Events (2-4) **(2)** AOP-0006, AOP-0001
 Major Transients (1-2) **(1)** Loss of offsite power
 EOPs entered (1-2) **(1)** EOP-0001
 EOP contingencies (0-2) **(1 potential)** Alternate Level Control
 Critical Tasks (2-3) **(2)** Take manual control of FW, Maintain reactor water level >-162" with RCIC