

GPU Nuclear Update - 5

Oyster Creek 12/90

Envelope of Doppler Coefficient Versus Temperature, E=200 MWd/t

Fig. 4.3-1



GPU Nuclear

Oyster Creek

Update - 5

12/90

Envelope of Doppler Coefficient Versus Temperature, E=15,000 MWd/t

Fig. 4.3-2



GPU Nuclear

Oyster Creek

Update - 5

12/90

Doppler Coefficient of Reactivity — Unirradiated Fuel

Fig. 4.3-3



GPU Nuclear

Update - 5

Oyster Creek

12/90

Core Average Doppler Defect Versus Core Power Level

Fig. 4.3-4



GPU Nuclear

Oyster Creek

Update - 5

12/90

Doppler Defect Versus Fuel Temperature

Fig. 4.3-5



GPU Nuclear

Update - 5

Oyster Creek

12/90

Envelope of Delta-k - Infinity (From 0.4 Void to Other Voids) Versus Exposure

Fig. 4.3-6



GPU Nuclear — Update - 5

Oyster Creek — 12/90

Moderator Void Coefficients of Reactivity

Fig. 4.3-7



GPU Nuclear

Update - 5

Oyster Creek

12/90

Moderator Temperature Coefficients of Reactivity

Fig. 4.3-8



GPU Nuclear Update - 5

Oyster Creek 12/90

Xenon Reactivity as a Function of Exposure at Rated Power Density with 35 Percent Voids

Fig. 4.3-9





GPU Nuclear Update - 5

Oyster Creek 12/90

Xenon Reactivity Buildup After Shutdown and Burnout on Return to Full Power from Maximum Shutdown Xenon Buildup at EOL and BOL

Fig. 4.3-10



GPU Nuclear

Oyster Creek

Control Rod Drop Accident Determination of Allowable Rod Worths Versus Rod Drop Velocity

Update - 5
12/90

Fig. 4.3-11



GPU Nuclear
Oyster Creek

Peak Fuel Enthalpy — Rod Drop Accident at Hot Standby Condition

Update - 5
12/90

Fig. 4.3-12



NOTE:

The maximum rod worth is determined by the Rod Drop Analysis, and the RWM is programmed to assure the 280 cal/gm limit is met. These groups may be subdivided to assure compliance with this limit.

GPU Nuclear — Update - 5

Oyster Creek — 12/90

Control Rod Withdrawal Sequences

Fig. 4.3-13



GPU Nuclear Update - 5

Oyster Creek 12/90

Relative Xenon Stability with No Flux Flattening

Fig. 4.3-14



GPU Nuclear — Update - 5

Oyster Creek — 12/90

Effect of Power Density on Axial Xenon Stability Including Void Transport

Fig. 4.3-15



Azimuthal Xenon Stability

Fig. 4.3-16



GPU Nuclear

Update - 5

Oyster Creek

12/90

Cladding Temperature Versus Heat Flux at Beginning of Life (BOL) P8x8R Fuel

Fig. 4.4-1



GPU Nuclear

Oyster Creek

Update - 5

12/90

Cladding Temperature Versus Heat Flux at End of Life (EOL) P8x8R Fuel

Fig. 4.4-2



GPU Nuclear Update - 5

Oyster Creek 12/90

Schematic of Reactor Assembly Showing the Bypass Flow Paths

Fig. 4.4-3

OCNGS
FSAR Update

Oyster Creek Power Operations Curve



Rev. 14 10/05

OYSTER CREEK NUCLEAR GENERATING STATION

Reactor Power-Flow Relationship

FIGURE 4.4-4



GPU Nuclear
Oyster Creek
Reactor Vessel Isometric

Update - 5
12/90

Fig. 4.5-1



GPU Nuclear
Oyster Creek
Control Rod Drive System — Simplified Component Illustration
Update - 5
12/90
Fig. 4.6-1



GPU Nuclear
Oyster Creek

Update - 5
12/90

Control Rod Drive — Cutaway

Fig. 4.6-2



GPU Nuclear

Oyster Creek

Update - 5

12/90

Oyster Creek Control Rod Drive Hydraulic Control Units, Scram Discharge Volumes and Scram Air Valving — Simplified Sketch

Fig. 4.6-3



GPU Nuclear — Update - 5

Oyster Creek — 12/90

Control-Rod-To-Drive Coupling — Isometric

Fig. 4.6-4

Figure 4.6-5

Deleted

1. ACCUMULATOR CHARGING WATER RISER
2. DRIVE - WITHDRAW RISER
3. ISOLATION VALVE — DRIVE-WITHDRAW RISER (EP 102)
4. DRIVE WATER RISER
5. ISOLATION VALVE — DRIVE WATER RISER (EP 103)
6. ISOLATION VALVE — SCRAM DISCHARGE RISER (EP 108 OR EP 112)
7. SCRAM PILOT VALVE ASSEMBLY (EP 117, 118)
8. OUTLET SCRAM VALVE AND ACTUATOR (EP 127)
9. TYPICAL ELECTRICAL CONNECTION
10. WIRING TROUGH ASSEMBLY
11. MANIFOLD (PART OF PIPING ASSEMBLY)
12. DIRECTIONAL CONTROL VALVES (4 EACH) (EP 120, 121, 122, 123)
13. ISOLATION VALVE —ACCUMULATOR CHARGING WATER RISER (EP 106
14. SCRAM ACCUMULATOR — NITROGEN CYLINDER (EP 128)
15. ACCUMULATOR GAS PRESSURE INDICATOR (EP 131)
16. ACCUMULATOR INSTRUMENTATION ASSEMBLY
17. NEEDLE VALVE — ACCUMULATOR GAS CHARGING (EP 111)
18. FRAME
19. SCRAM ACCUMULATOR — WATER CYLINDER (EP 125)
20. NEEDLE VALVE — ACCUMULATOR WATER CYLINDER DRAIN (EP 107)
21. COOLING CHECK VALVE (IN MANIFOLD)
22. SPEED CONTROL VALVES (2 EACH)
23. INLET SCRAM VALVE AND ACTUATOR (EP 126)
24. ISOLATION VALVE — COOLING WATER RISER (EP 104)
25. ISOLATION VALVE — DRIVE-INSERT RISER (EP 101)
26. ISOLATION VALVE — EXHAUST WATER RISER (EP 105)
27. EXHAUST WATER RISER
28. DRIVE-INSERT RISER
29. COOLING WATER RISER
30. SCRAM DISCHARGE RISER



GPU Nuclear — Update - 5

Oyster Creek — 12/90

Control Rod Drive Hydraulic Control Unit— Isometric

Fig. 4.6-6



GPU Nuclear

Update - 5

Oyster Creek

12/90

Control Rod — Isometric

Fig. 4.6-7



GPU Nuclear

Update - 5

Oyster Creek

12/90

Control Rod -- Isometric

Fig. 4.6-8



GPU Nuclear

Oyster Creek

Update-8
8/93

Illustration of Typical Marathon Control Rod (BWR/2-4 D-Lattice)

S3B.SKM.00.0570.001-.0001

Fig.4.6-9