

30-269/270/287
FILE NUMBER

NRC DISTRIBUTION FOR PART 50 DOCKET MATERIAL

TO: Mr Rusche

FROM: Duke Power Company
Charlotte, NC
W O Parker JrDATE OF DOCUMENT
12-28-76DATE RECEIVED
12-30-76☒ LETTER
☒ ORIGINAL
☐ COPY☐ NOTORIZED
☒ UNCLASSIFIED

PROP

INPUT FORM

NUMBER OF COPIES RECEIVED

one signed

DESCRIPTION

Ltr re their 9-5-76 ltr.....& our 11-23-76
ltr.....furnishing info concerning Appendix
J.....

PLANT NAME: Oconee 1-3

ENCLOSURE

ACKNOWLEDGED

DO NOT REMOVE

SAFETY

FOR ACTION/INFORMATION

ENVIRO

1-4-76 ehf

ASSIGNED AD:

BRANCH CHIEF:

PROJECT MANAGER:

LIC. ASST. :

ASSIGNED AD:

BRANCH CHIEF:

PROJECT MANAGER:

LIC. ASST. :

INTERNAL DISTRIBUTION

REG FILE

NRC PDR

I & E (2)

OELD

GOSSICK & STAFF

MIPC

CASE

HANAUER

HARLESS

SYSTEMS SAFETY

HEINEMAN

SCHROEDER

ENGINEERING

MACARRY

KNIGHT

SIHWEIL

PAWLICKI

PLANT SYSTEMS

TEDESCO

BENAROYA

LAINAS

IPPOLITO

KIRKWOOD

OPERATING REACTORS

STELLO

SITE SAFETY &

ENVIRO ANALYSIS

DENTON & MULLER

ENVIRO TECH.

ERNST

BALLARD

SPANGLER

SITE TECH.

CAMMILL

STAPP

HULMAN

SITE ANALYSIS

VOLLMER

BUNCH

J. COLLINS

KREGER

PROJECT MANAGEMENT

BOYD

P. COLLINS

HOUSTON

PETERSON

MELTZ

HELTEMES

SKOVHOLT

REACTOR SAFETY

ROSS

NOVAK

ROSZTOCZY

CHECK

AT & I

SALTZMAN

RUTBERG

OPERATING TECH.

EISENHUT

SHAO

BAER

BUTLER

GRIMES

EXTERNAL DISTRIBUTION

LPDR: Waikalla, SC

TIC:

NSIC:

ASLB:

ACRS 16 CYS HOLDING/SENT AS CAT B 1-4-76

NAT. LAB:

REG V. IE

LA PDR

CONSULTANTS:

BROOKHAVEN NAT. LAB.

ULRIKSON (ORNL)

CONTROL NUMBER

13085

DUKE POWER COMPANY

POWER BUILDING

422 SOUTH CHURCH STREET, CHARLOTTE, N. C. 28242

WILLIAM O. PARKER, JR.
VICE PRESIDENT
STEAM PRODUCTION

Regulatory Docket File

TELEPHONE: AREA 704
373-4083

December 28, 1976

Mr. Benard C. Rusche
Director of Nuclear Reactor Regulation
U. S. Nuclear Regulatory Commission
Washington, D. C. 20555

Attention: Mr. A. Schwencer, Chief
Operating Reactors Branch #1



Re: Oconee Nuclear Station
Docket Nos. 50-269, -270, -287

Dear Mr. Rusche:

Our September 5, 1975 letter requested an exemption from the provisions of 10CFR50, Appendix J concerning the testing of containment airlocks. It was our interpretation that Section III.D.2 of Appendix J to 10CFR50 requires a Type B test to be performed at six-month intervals; however, those airlocks which are opened during such intervals were to be tested after each opening. Our letter described the design features of the Oconee containment airlocks which made this requirement impractical.

In your letter dated November 23, 1976, an acceptable approach to meeting the objectives of Appendix J was described. This requires, at six-month intervals, that the entire airlock assembly shall be leak tested at the peak pressure, Pa. Additionally, should the airlock be opened during the interval between the six-month tests, the airlock door seals shall be tested within 72 hours of every first opening of a series of openings. This leak test may be performed at a lower pressure (e.g., manufacturer's recommended pressure) and the results conservatively extrapolated to a leakage rate at the accident pressure, Pa.

It is our conclusion that your interpretation of the intent of 10CFR50, Appendix J provides a suitable alternative for testing the Oconee containment airlocks. In the case of the Oconee design, however, only the outer door in each airlock has a double seal and is therefore testable. The inner door only has one seal and cannot be tested. Proposed Technical



13085


Mr. Benard C. Rusche

Page 2

December 28, 1976

Specifications will be submitted by February 15, 1977 which incorporate these considerations into the testing of the Oconee containment airlocks.

Very truly yours,

A handwritten signature in dark ink, appearing to read "William O. Parker, Jr.", with a long, sweeping horizontal line extending to the right.

William O. Parker, Jr.

MST:vr