

**Allen, William**

---

**From:** Tom Szymanski (Generation - 6) <tom.szymanski@dom.com>  
**Sent:** Monday, May 23, 2016 3:35 PM  
**To:** Allen, William  
**Subject:** [External\_Sender] 15 vs 18 inches question

Chris,

We have verified that our TN-32 transporter (CTT125 Transporter) is designed to lift a cask no higher than 15 inches (including tire deflection). Mechanical stops prevent a higher lift. The SAR reflects this limit. The TN-32 TSAR specifies an 18 inch bottom end drop which is reflected in NAPS ISFSI Technical Specifications (and procedures) as a maximum lift height. As the transporter cannot physically lift the cask 18 inches, the Tech Spec and procedures cannot be violated.

Tom Szymanski  
804-273-3065  
tom.szymanski@dom.com  
Corporate Nuclear Licensing

---

**CONFIDENTIALITY NOTICE:** This electronic message contains information which may be legally confidential and or privileged and does not in any case represent a firm ENERGY COMMODITY bid or offer relating thereto which binds the sender without an additional express written confirmation to that effect. The information is intended solely for the individual or entity named above and access by anyone else is unauthorized. If you are not the intended recipient, any disclosure, copying, distribution, or use of the contents of this information is prohibited and may be unlawful. If you have received this electronic transmission in error, please reply immediately to the sender that you have received the message in error, and delete it. Thank you.