

Facility: <u>Dresden Generating Station</u>		Date of Examination: <u>08/08/2016</u>
Exam Level: RO X SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	Operating Test No.: <u>2016-301</u>	

Control Room Systems: * 8 for RO; 7 for SRO-I; 2 or 3 for SRO-U		
System / JPM Title	Type Code*	Safety Function
a. 211000.A4.08 4.2/4.2 SBLC – Injection with Pump and RWCU Failures	A, D, EN, P, S	1
b. 259002.A4.03 3.8/3.6 FW - Transfer FWLC to Main FRV during SU	D, L, S	2
c. 241000.A4.06 3.9/3.9 DEHC – Establish RPV Cooldown with Bypass Valves	D, L, S	3
d. 203000.A1.04 3.6/3.6 LPCI – Mitigate high Suction Pressure While Lining Up CST Suction For Injection	A, D, P, S	4
e. 223001.A4.07 4.2/4.1 Containment – Vent Containment with APCV	A, L, N, S	5
f. 262001.A4.01 3.4/3.7 AUX POWER - Restore Normal Feed to 28-7/29-7 from Bus 29	D, S	6
g. 215004.A4.04 3.2/3.2 SRM – Withdraw SRM Detectors with Stuck Detector	A, D, L, S	7
h. 261000.A4.09 2.7/2.7 SBTG - Start SBTG with RB Vent Failure to Isolate	A, EN, M, S	9

In-Plant Systems * (3 for RO); (3 for SRO-I); (3 or 2 for SRO-U)		
i. 295019.AA.1.02 3.3/3.1 Inst. Air – Lineup IACs to Unit 2 Instrument Air Header	N, R	8
j. 295028.EA1.03 3.9/3.9 Containment - Bypass Drywell Cooler Trip	D, E	5
k. 201001.A4.03 2.9/2.8 CRD - Swap CRD FCVs	D, R	1

* All RO and SRO-I control room (and in-plant) systems must be different and serve different safety functions; all five SRO-U systems must serve different safety functions; in-plant systems and functions may overlap those tested in the control room.

* Type Codes	Criteria for RO / SRO-I / SRO-U
A)lternate path (C)ontrol room (D)irect from bank (E)mergency or abnormal in-plant (EN)gineered safety feature (L)ow-Power / Shutdown (N)ew or (M)odified from bank including 1(A) (P)revious 2 exams (R)CA (S)imulator	4-6 / 4-6 / 2-3 $\leq 9 / \leq 8 / \leq 4$ $\geq 1 / \geq 1 / \geq 1$ $\geq 1 / \geq 1 / \geq 1$ (control room system) $\geq 1 / \geq 1 / \geq 1$ $\geq 2 / \geq 2 / \geq 1$ $\leq 3 / \leq 3 / \leq 2$ (randomly selected) $\geq 1 / \geq 1 / \geq 1$

Facility: Dresden Generating Station Date of Examination: 08/08/2016Exam Level: RO ☐ SRO-I ☒ SRO-U ☐ Operating Test No.: 2016-301

Control Room Systems: * 8 for RO; 7 for SRO-I; 2 or 3 for SRO-U

System / JPM Title	Type Code*	Safety Function
a. 211000.A4.08 4.2/4.2 SBLC – Injection with Pump and RWCU Failures	A, D, EN, P, S	1
b.		
c. 241000.A4.06 3.9/3.9 DEHC – Establish RPV Cooldown with Bypass Valves	D, L, S	3
d. 203000.A1.04 3.6/3.6 LPCI – Mitigate high Suction Pressure While Lining Up CST Suction For Injection	A, D, P, S	4
e. 223001.A4.07 4.2/4.1 Containment – Vent Containment with APCV	A, L, N, S	5
f. 262001.A4.01 3.4/3.7 AUX POWER - Restore Normal Feed to 28-7/29-7 from Bus 29	D, S	6
g. 215004.A4.04 3.2/3.2 SRM – Withdraw SRM Detectors with Stuck Detector	A, D, L, S	7
h. 261000.A4.09 2.7/2.7 SBTG - Start SBTG with RB Vent Failure to Isolate	A, EN, M, S	9

In-Plant Systems * (3 for RO); (3 for SRO-I); (3 or 2 for SRO-U)

i. 295019.AA.1.02 3.3/3.1 Inst. Air – Lineup IACs to Unit 2 Instrument Air Header	N, R	8
j. 295028.EA1.03 3.9/3.9 Containment - Bypass Drywell Cooler Trip	D, E	5
k. 201001.A4.03 2.9/2.8 CRD - Swap CRD FCVs	D, R	1

* All RO and SRO-I control room (and in-plant) systems must be different and serve different safety functions; all five SRO-U systems must serve different safety functions; in-plant systems and functions may overlap those tested in the control room.

* Type Codes	Criteria for RO / SRO-I / SRO-U
A)lternate path	4-6 / 4-6 / 2-3
(C)ontrol room	
(D)irect from bank	$\leq 9 / \leq 8 / \leq 4$
(E)mergency or abnormal in-plant	$\geq 1 / \geq 1 / \geq 1$
(EN)gineered safety feature	$\geq 1 / \geq 1 / \geq 1$ (control room system)
(L)ow-Power / Shutdown	$\geq 1 / \geq 1 / \geq 1$
(N)ew or (M)odified from bank including 1(A)	$\geq 2 / \geq 2 / \geq 1$
(P)revious 2 exams	$\leq 3 / \leq 3 / \leq 2$ (randomly selected)
(R)CA	$\geq 1 / \geq 1 / \geq 1$
(S)imulator	