

REGULATORY INFORMATION DISTRIBUTION SYSTEM (RIDS)

ACCESSION NBR: 8308250157 DOC. DATE: 83/08/19 NOTARIZED: NO DOCKET #
 FACIL: 50-315 Donald C. Cook Nuclear Power Plant, Unit 1, Indiana & 05000315
 50-316 Donald C. Cook Nuclear Power Plant, Unit 2, Indiana & 05000316

AUTH. NAME AUTHOR AFFILIATION
 ALEXICH, M. P. Indiana & Michigan Electric Co.
 RECIP. NAME RECIPIENT AFFILIATION
 DENTON, H. R. Office of Nuclear Reactor Regulation, Director

SUBJECT: Suppl to 810814 Tech Spec change request re Mode 6
 surveillance requirement, proposing frequency of 24 h to
 determine RHR operation & circulating reactor coolant flow
 rate.

DISTRIBUTION CODE: A001S COPIES RECEIVED: LTR 1 ENCL 0 SIZE: 2
 TITLE: OR Submittal: General Distribution

NOTES:

	RECIPIENT ID CODE/NAME		COPIES LTTR ENCL		RECIPIENT ID CODE/NAME		COPIES LTTR ENCL
	NRR ORB1 BC 01.		7				
INTERNAL:	ELD/HDS3		1		NRR/DE/MTEB		1
	NRR/DL DIR		1		NRR/DL/ORAB		1
	NRR/DSI/METB		1		NRR/DSI/RAB		1
	<u>REG FILE</u> 04		1		RGN3		1
EXTERNAL:	ACRS 09	6			LPDR 03	2	
	NRC PDR 02	1			NSIC 05	1	
	NTIS	1					

TOTAL NUMBER OF COPIES REQUIRED: LTTR 26 ENCL 0
4

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200

201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300

301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400

401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500

501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600

INDIANA & MICHIGAN ELECTRIC COMPANY

P. O. BOX 18
BOWLING GREEN STATION
NEW YORK, N. Y. 10004

August 19, 1983
AEP:NRC:0420C

Donald C. Cook Nuclear Plant Unit Nos. 1 and 2
Docket Nos. 50-315 and 50-316
License Nos. DPR-58 and DPR-74
FURTHER INFORMATION ON TECHNICAL SPECIFICATION CHANGE REQUEST
SUBMITTED IN LETTER NO. AEP:NRC:0420A, DATED AUGUST 14, 1981

Mr. Harold R. Denton, Director
Office of Nuclear Reactor Regulation
U. S. Nuclear Regulatory Commission
Washington, D. C. 20555

Dear Mr. Denton:

In the above-referenced application, under Technical Specification (T/S) No. 4.9.8.1, we proposed a 24-hour interval as the appropriate frequency to determine that a residual heat removal (RHR) loop is in operation and circulating reactor coolant at a flow rate of 3,000 gpm. This surveillance requirement applies in Mode 6. This letter provides additional information in support of our 24-hour request.

All four RHR pumps at the Cook Plant are provided with low flow alarms set at 2,000 gpm. The RHR flow dissipates the core's decay heat to the component cooling water (CCW) in the RHR heat exchangers. We have estimated that one RHR train with degraded flow of 2,000 gpm and maximum CCW inlet temperature of 95°F could remove heat at a rate of 33 MBTU/hr from the reactor coolant system. More realistic assumptions for the CCW inlet temperature (65°F) would permit a heat removal rate of 55 MBTU/hr.

We have also estimated on the basis of the data presented in Reference (1), that the decay heat rate would become less than 33.10 MBTU/hr approximately 204 hours after shutdown, and less than 39.43 MBTU/hr approximately 110 hours after shutdown. The time at which the decay heat rate reaches 33 MBTU/hr is estimated to be 206.2 hrs. These calculations correspond to the decay heat rate of a 3,411 MW(t) reactor with all 193 assemblies inserted in the reactor vessel.


8308250157 830819
PDR ADOCK 05000315
P PDR

A001
1/0

During the actual refueling experience at the Donald C. Cook Nuclear Plant, the shortest time recorded from shutdown to entry into Mode 6 is approximately 214 hours (8 days and 22 hours) which corresponds to a decay heat rate of 32.66 MBTU/hr. We feel, therefore, justified in our Technical Specification change request, mentioned at the beginning of this letter, in that a frequency of surveillance higher than 24 hours does not seem justified because of the existence of the low flow alarm. We also feel that this alarm is set at a sufficiently high flow level that the RHR system could be capable of removing the decay heat generated by the core if one makes reasonable assumptions both about the time needed to reach Mode 6 and the CCW inlet temperature. Furthermore, the reactor coolant temperature/RHR temperature is monitored and logged during each shift while the plant is in Mode 6 and the vessel head is unbolted or lifted. Any abnormal increase in reactor coolant temperature would be detected and remedial actions taken. Such actions are discussed in Section 9.3.3 of the updated FSAR.

This letter has been prepared following Corporate Procedures which incorporate a reasonable set of controls to insure its accuracy and completeness prior to signature by the undersigned.

Very truly yours,


M. P. Alexich
Vice President

Reference (1): ANS-5.1. - "Proposed ANS Standard Decay Energy Release Rates Following Shutdown of Uranium Fueled Thermal Reactors." October, 1971.

MPA:cam

cc: John E. Dolan
W. G. Smith, Jr. - Bridgman
R. C. Callen
G. Charnoff
E. R. Swanson, NRC Resident Inspector - Bridgman

