

ATTACHMENT 3

PROPOSED TECHNICAL SPECIFICATION

Marked-up Technical Specifications Pages,

3/4 7-12 (no change, for reference only)

3/4 7-13

9107030302 910621
PDR ADOCK 05000250
PDR

PLANT SYSTEMS

3/4.7.2 COMPONENT COOLING WATER SYSTEM

LIMITING CONDITION FOR OPERATION

3.7.2 The Component Cooling Water System (CCW) shall be OPERABLE with:

- a. Three CCW pumps, and
- b. Two CCW heat exchangers.

APPLICABILITY: MODES 1, 2, 3, and 4.

ACTION:

- a. With only two CCW pumps with independent power supplies OPERABLE, restore the inoperable CCW pump to OPERABLE status within 30 days or be in HOT STANDBY within the next 6 hours and in COLD SHUTDOWN within the following 30 hours. The provisions of Specification 3.0.4 are not applicable.
- b. With only one CCW pump OPERABLE or with two CCW pumps OPERABLE but not from independent power supplies, restore two pumps from independent power supplies to OPERABLE status within 72 hours or be in HOT STANDBY within the next 6 hours and in COLD SHUTDOWN within the following 30 hours.
- c. With less than two CCW heat exchangers OPERABLE, restore two heat exchangers to OPERABLE status within 1 hour or be in HOT STANDBY within the next 6 hours and in COLD SHUTDOWN within the following 30 hours.

SURVEILLANCE REQUIREMENTS

4.7.2 The Component Cooling Water System (CCW) shall be demonstrated OPERABLE:

- a. At least once per 12 hours, by verifying that two heat exchangers and one pump are capable of removing design basis heat loads.

SURVEILLANCE REQUIREMENTS (Continued)

- b. At least once per 31 days by: (1) verifying that each valve (manual, power-operated, or automatic) servicing safety-related equipment that is not locked, sealed, or otherwise secured in position is in its correct position, and (2) verifying by a performance test the heat exchanger surveillance curves.*
- c. At least once per 18 months during shutdown, by verifying that:
 - 1) Each automatic valve servicing safety-related equipment actuates to its correct position on a SI test signal, and
 - 2) Each Component Cooling Water System pump starts automatically on a SI test signal.
 - 3) Interlocks required for CCW operability are OPERABLE.

* Technical specification 4.7.2.b (2) is not applicable for entry into MODE 4 or MODE 3, provided that:

- 1) surveillance 4.7.2.b (2) is performed no later than 72 hours after reaching a Reactor Coolant System T_{avg} of 547°F , and
- 2) MODE 2 shall not be entered prior to satisfactory performance of this surveillance.

11-11-61

1. The first part of the report deals with the general situation in the country. It is a very interesting and informative study of the country's development and progress. The author has done a great deal of research and has gathered a wealth of material. The report is well written and is easy to read. It is a valuable contribution to the study of the country's development.

2. The second part of the report deals with the economic situation. It is a very detailed and thorough study of the country's economy. The author has done a great deal of research and has gathered a wealth of material. The report is well written and is easy to read. It is a valuable contribution to the study of the country's economy.

3. The third part of the report deals with the social situation. It is a very detailed and thorough study of the country's social conditions. The author has done a great deal of research and has gathered a wealth of material. The report is well written and is easy to read. It is a valuable contribution to the study of the country's social conditions.

4. The fourth part of the report deals with the political situation. It is a very detailed and thorough study of the country's political conditions. The author has done a great deal of research and has gathered a wealth of material. The report is well written and is easy to read. It is a valuable contribution to the study of the country's political conditions.