

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9319	9	71-9319	USA/9319/B(U)F-96	1 OF	6

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.
3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION
- a. ISSUED TO (*Name and Address*)  
Framatome Inc.  
2101 Horn Rapids Road  
Richland, WA 99354
- b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION  
TN Americas LLC, application dated November 8, 2017.

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

(a) Packaging

- (1) Model Nos.: MAP-12 and MAP-13
- (2) Description

The MAP package is designed to transport unirradiated uranium fuel assemblies with enrichment up to 5.0 weight percent. The package is designed to carry two fuel assemblies with core components. The package consists of two components: a base and lid. The containment system of the MAP package is the fuel rod cladding.

The base consists of a fixed stainless steel strong-back which supports the fuel assemblies. A series of inner stiffeners are secured to the underside of the strong-back to support the fuel assemblies. A neutron moderator and absorber are positioned directly beneath the strong-back between each inner stiffener. The base inner stiffeners are retained by a stainless steel cover. Exterior to the cover is a layer of rigid polyurethane foam and an outer shell of 11 gauge stainless steel. A 12-gauge stainless steel sheet is provided between the two middle stiffeners. Four stainless steel outer stiffeners support the package base. The payload rests on the "W" shaped strong-back (referred to as a W-plate) and is held in place with hinged and latched aluminum doors. The lid is very similar to that of the base – a "W" shaped stainless steel inner shell is fitted with a series of inner stiffeners, neutron moderator and absorbers, and a stainless steel cover is fitted over the stiffeners. The lid is fitted with trapezoidal impact limiters at each end. The impact limiters are constructed from rigid polyurethane foam encased by the package outer stainless shell skin. The base and lid include end plates with interlocking, interfacing angles.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9319	9	71-9319	USA/9319/B(U)F-96	2 OF	6

5.(a) (2) Description (continued)

There are two models of the MAP package, the MAP-12 and MAP-13. The weights and dimensions of the package are as follows:

MAP-12 (for 144-in Maximum Nominal Active Fuel Length):

Maximum Gross Weight	8,630 lbs
Maximum Payload Weight	3,400 lbs
Outer Dimensions	
Length	208 in
Width	45 in
Height	31 in

MAP-13 (for 150-in Maximum Nominal Active Fuel Length):

Maximum Gross Weight	8,630 lbs
Maximum Payload Weight	3,400 lbs
Outer Dimensions	
Length	221 in
Width	45 in
Height	31 in

(3) Drawings

The MAP-12 and MAP-13 packages are fabricated and assembled in accordance with the following AREVA NP, Inc. Drawing Nos.:

9045393, Rev. 6;	9045402, Rev. 4;
9045397, Rev. 1;	9045403, Rev. 3;
9045399, Rev. 2;	9045404, Rev. 3;
9045401, Rev. 3;	9045405, Rev. 3.

(b) Contents

(1) Type and Form of Material

Enriched commercial grade uranium or enriched reprocessed uranium, as defined in ASTM C996-04, oxide fuel rods enriched to no more than 5.0 weight percent in the U-235 isotope, with limits specified in Table 1 below.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**


1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9319	9	71-9319	USA/9319/B(U)F-96	3 OF	6

5.(b) Contents (continued)

(2) Maximum Quantity of Material per Package

Table 1: Maximum Authorized Concentrations

Isotope	Maximum Content
U-232	$2.00 \times 10^{-9}$ g/g U
U-234	$2.00 \times 10^{-3}$ g/g U
U-235	$5.00 \times 10^{-2}$ g/g U
U-236	$2.50 \times 10^{-2}$ g/g U
U-238	Balance of Uranium
Np-237	$1.66 \times 10^{-6}$ g/g U
Pu-238	$6.20 \times 10^{-11}$ g/g U
Pu-239	$3.04 \times 10^{-9}$ g/g U
Pu-240	$3.04 \times 10^{-9}$ g/g U
Gamma Emitters	$5.18 \times 10^5$ MeV – Bq/kg U



**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9319	9	71-9319	USA/9319/B(U)F-96	4 OF	6

5.(b) Contents (continued)

(3) Fuel Assembly

- (i) The parameters of the fuel assemblies that are permitted are specified in the table below.

Fuel Rod Array	14x14		15x15					16x16	17x17	
Assembly Type	1	2	1			2	3	1	1	2
No. of Fuel Rods	176	179	208			216	204	236	264	264
No. of Non-Fuel Cells	20	17	17			9	21	20	25	25
Nominal Fuel Rod Pitch (in)	0.580	0.556	0.568			0.550	0.563	0.506	0.502	0.496
Maximum Pellet Outer Diameter (in)	0.3812	0.3682	0.3622	0.3707	0.3742	0.3617	0.3682	0.3282	0.3252	0.3232
Minimum Fuel Rod Outer Diameter (in)	0.438	0.422	0.414	0.428	0.428	0.414	0.422	0.380	0.377	0.372
Minimum Clad Wall Thickness (in)	0.0245	0.0230	0.0220	0.0245	0.0230	0.0220	0.0230	0.0220	0.0220	0.0205
Minimum Guide Tube Wall Thickness (in)	N/A	N/A	0.0140	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Minimum Guide Tube Outer Diameter (in)	N/A	N/A	0.528	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Number of Guide Tubes	N/A	N/A	16	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Minimum Instrument Tube Wall Thickness (in)	N/A	N/A	0.0240	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Minimum Instrument Tube Outer Diameter (in)	N/A	N/A	0.491	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Number of Instrument Tubes	N/A	N/A	1	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Clad/Tube Material Type	Zr Alloy	Zr Alloy	Zr Alloy			Zr Alloy	Zr Alloy	Zr Alloy	Zr Alloy	Zr Alloy
Maximum Active Fuel Length (in)	160	160	160			160	160	160	160	160

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9319	9	71-9319	USA/9319/B(U)F-96	5 OF	6

5.(b) Contents (continued)

(3) Fuel Assembly (continued)

- (ii) Non-fissile base-plate mounted and spider body core components are permitted.
- (iii) Fuel rods assembled into the fuel assemblies are those loaded with sintered pellets of uranium oxides and/or with sintered pellets of uranium oxides mixed with various additives (e.g., Chromium, Boron, Gadolinium, and Europium).

(c) Criticality Safety Index: 2.8

6. In addition to the requirements of Subpart G of 10 CFR Part 71:

- (a) The package shall be prepared for shipment and operated in accordance with the Package Operations in Section 7 of the application, as supplemented.
- (b) Each package must meet the Acceptance Tests and Maintenance Program of Section 8 of the application, as supplemented.
- (c) Each fuel assembly must be unsheathed or must be enclosed in an unsealed, polyethylene or polypropylene sheath, which may not extend beyond the ends of the fuel assembly. The ends of the sheath may not be folded or taped in any manner that would prevent the flow of liquids into or out of the sheathed fuel assembly.
- (d) The fuel rods must be leak tested after fabrication to ensure that the leakage rate of the containment boundary is less than 1E-7 ref cc/sec.

7. Transport by air of fissile material is not authorized.

8. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.

9. Expiration date: February 28, 2023.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9319	9	71-9319	USA/9319/B(U)F-96	6 OF	6

REFERENCES

TN Americas LLC, application dated November 8, 2017.

Framatome Inc., name change request dated January 17, 2018.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

/RA/

John McKirgan, Chief  
Spent Fuel Licensing Branch  
Division of Spent Fuel Management  
Office of Nuclear Material Safety  
and Safeguards

Date: 03/01/18

