

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9228	27	71-9228	USA/9228/B(U)-96	1	OF 4

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- |   |   |
|---|---|
| <p>a. ISSUED TO <i>(Name and Address)</i><br/>GE-Hitachi Nuclear Energy Americas, LLC<br/>3901 Castle Hayne Road<br/>Wilmington, NC 28401</p> | <p>b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION<br/>GE Hitachi Nuclear Energy consolidated application<br/>dated April 28, 2016, as supplemented.</p> |
|---|---|

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

(a) Packaging

- (1) Model No.: 2000
- (2) Description

The cask body is constructed of two concentric 1-inch thick 304 stainless steel cylindrical shells (ASTM A240) joined at the bottom end to a 6-inch thick 304 stainless steel forging (ASTM A182). The overall packaging dimensions are approximately 131.5 inches in height and 72 inches in diameter, and its gross weight is approximately 33,550 lbs. The cavity of the packaging is approximately 26.5 inches in diameter and 54.0 inches deep.

The cask lid is fully recessed into the cask top flange and secured to the cask body by 15, 1.25-inch diameter socket head screws. The packaging is equipped with a seal test port on the side of the body, a vent port in the lid, and a drain port near the bottom of the packaging. The cask lid utilizes four O-rings in a metal retainer.

The overpack is constructed from two 0.5-inch thick concentric 304 stainless steel cylindrical shells (ASTM A240), separated radially by eight equally spaced tubes and horizontally by two tube sections. A 304 stainless steel toroidal shell impact limiter is attached to each end of the overpack. The overpack opens just above the lower impact limiter for access to the packaging. The top of the overpack is joined to the base by 15, 1-3/8-inch diameter shoulder screws. Gussets on the top and bottom impact limiters provide tie-down points for the package. The lifting devices are detached during transport.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9228	27	71-9228	USA/9228/B(U)-96	2	OF 4

5.(a) (2) Description (Continued)

A high performance insert (HPI) is fabricated from two concentric stainless steel cylindrical shells. The annulus between the cylindrical shells is filled with depleted uranium. The HPI is positioned within the cask cavity by support disks arranged axially to provide uniform support. Vertical lifting arms connect the support disks and also serve as the primary lifting fixtures. The HPI is shielded using encapsulated depleted uranium within both a top and a bottom plug. The top plug has a stepped design and an optional spacer may be added to provide additional **shielding**.

A material basket is also used for the shipment of contents described in 5(b)(1)(ii).

(3) Drawings

- (i) With the exception of packaging Serial No. 2001, the packaging is constructed and assembled in accordance with the following General Electric Company Drawings:

Drawing No.	Drawing Title	Revision
129D4946	Model 2000 Transport Container	12
105E9520	Model 2000 Shipping Cask all S/N's Except S/N 2001	9 (Sheet 1 of 2) 9 (Sheet 2 of 2)
105E9521	Model 2000 Cask Overpack All S/N's Except S/N 2001	7

- (ii) Packaging Serial No. 2001 is constructed and assembled in accordance with the following General Electric Company Drawings:

Drawing No.	Drawing Title	Revision
129D4946	Model 2000 Transport Container	12
101E8718	Model 2000 Shipping Cask S/N 2001	17 (Sheet 1 of 2) 17 (Sheet 2 of 2)
101E8719	Model 2000 Shipping Cask Overpack S/N 2001	14

- (ii) The HPI and HPI material basket are constructed and assembled in accordance with the following General Electric Company Drawings:

Drawing No.	Drawing Title	Revision
001N8422	GE 2000 HPI and Material Basket Licensing Drawing	3
001N8423	GE 2000 HPI Licensing Drawing	2
001N8424	GE 2000 HPI Material Basket Assembly Licensing Drawing	2
001N8425	GE 2000 HPI Body Licensing Drawing	2
001N8427	GE 2000 HPI Top Plug Assembly Licensing Drawing	2
001N8428	GE 2000 HPI Bottom Plug Assembly Licensing Drawing	2

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9228	27	71-9228	USA/9228/B(U)-96	3	OF 4

5.(b) (1) Contents

- (i) Irradiated hardware components composed of stainless steels, carbon steels, nickel alloys and zirconium alloys. Irradiated byproducts such as control rods and/or control blades containing either hafnium or boron carbide. The minimum cooling time for either irradiated hardware or irradiated byproducts shall be at least 30 days prior to shipment.
- (ii)  $^{60}\text{Co}$  as either normal form rods or special form pellets.

5.(b) (2) Maximum quantity of material per package

- (i) For the contents described in 5(b)(1)(i), the maximum quantity of material shall not exceed the limits specified in Section 7.5.1 of the safety analysis report.
- (ii) For the contents described in 5(b)(1)(ii), the maximum quantity of material shall not exceed the limits specified in Section 7.5.2 of the safety analysis report, and the total activity in any axial 1-inch increment shall be less than or equal to 17,000 Curies.
- (iii) For a combination of contents described in 5(b)(i) and 5 (b)(ii), the maximum quantity of material shall not exceed the limits specified in Section 7.5.3 of the safety analysis report.
- (iv) The contents described in 5(b)(1)(i) and 5(b)(ii) may contain fissile material provided the quantity of material does not exceed a Type A quantity and qualifies as an exempt quantity under 10 CFR 71.15.
- (v) The thermal heat load of the package shall not exceed 1500 W.
- (vi) The combined weight of the HPI, HPI basket, radioactive material, shoring, and secondary containers shall not exceed 5,450 lbs.

6. Appropriate shoring must be provided as necessary to minimize content movement during accident conditions of transport.

7. The package shall be shipped in a vertical orientation.

8. Air transport is not authorized.

9. In addition to the requirements of Subpart G of 10 CFR Part 71:

- (a) The package shall be prepared for shipment and operated in accordance with the Package Operations in Section 7.0 of the application, as supplemented.
- (b) The package must meet the Acceptance Tests and Maintenance Program in Section 8.0 of the application, as supplemented.

10. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9228	27	71-9228	USA/9228/B(U)-96	4	OF 4

11. Expiration date: March 31, 2023.

REFERENCES

GE Hitachi Nuclear Energy Company application dated April 28, 2016.

Supplements dated: May 4, 2016; June 13, and September 29, 2017; January 9, 2018.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

John McKirgan, Chief  
Spent Fuel Licensing Branch  
Division of Spent Fuel Management  
Office of Nuclear Material Safety  
and Safeguards

Date: March XX, 2018