



SYMBOL EXPLANATION

ENGINEERING PARAMETERS
PI — plasticity index
minus 200 — percent passing #200 sieve
W/C — percent moisture
g/d — dry density
ASTM: D 422 (1972)
ASTM: D 423
ASTM: D 424 (1971)
ASTM: D 2216-71

SAMPLE TYPE
— Drive Sample
+ Pitcher Tube Sample
95 / / NX Core, No. Indicates % Recovery
63 — Standard Penetration Test, "N" value
ASTM: D 1586-67

CARBONATE CONTENT
— No Reaction
+ Slightly Reactive
⊕ Moderately Reactive
+ Highly Reactive
(based on sample reaction to a 10% HCl solution)

UNITS
Units column refers to general stratigraphic divisions identified within the basin sediments.

PALEOMAGNETIC POLARITY
Inclination of remnant magnetic vector in general agreement with (⊕) or opposition to (⊖) the present magnetic field.
— Magnetic vector indeterminate
Paleomagnetic Reversal — R 126 10 827
depth
elevation

DESCRIPTORS
Lithologic descriptions were compiled from geologists' field logs, laboratory test data, and down-hole geophysics. Field logs were prepared in accordance with ASTM: D2488-69. Classifications based on laboratory test data are in accordance with ASTM: D2487-69. Rock descriptions follow procedures outlined in the QUARTERLY OF THE COLORADO SCHOOL OF MINES, Volume 50, No. 1. Descriptions for rotary borings are based upon cuttings samples, geophysical logs and drillers' comments.