

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

| 1 a. CERTIFICATE NUMBER | b. REVISION NUMBER | c. DOCKET NUMBER | d. PACKAGE IDENTIFICATION NUMBER | PAGE | PAGES |
|-------------------------|--------------------|------------------|----------------------------------|------|-------|
| 9310                    | 7                  | 71-9310          | USA/9310/B(U)-96                 | 1    | OF 4  |

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- a. ISSUED TO (*Name and Address*)  
Best Theratronics  
413 March Road  
Ottawa, Ontario  
Canada K2K 0E4
- b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION  
Best Theratronics application dated July 29, 2019,  
as supplemented.

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

(a) Packaging

- (1) Model No. F-431 Transport Package
- (2) Description

The Model No. F-431 Transport Package is designed to transport Cesium-137 in either special form or RAMCO-50 non-special form sealed sources. The F-431 Transport Package consist of the following components: (1) the overpack which provides impact and thermal protection; (2) either the Gammacell-1000 irradiator (GC-1000), or the Gammacell-3000 irradiator (GC-3000) which provides shielding protection; and (3) the radioactive contents in either special form or RAMCO-50 non-special form sealed sources which provide containment.

The F-431 Transport Package is a stainless-steel cylindrical package with a 1,067-millimeter (mm) [42-inch (in.)] outside diameter and a height of 1,283 mm (50.5 in.) that is placed on a removable mild steel skid. The maximum weight of the package is 2,270 kilograms (kg) [5,000 pounds (lb.)].

The overpack consists of nested cylindrical shells. The shells are made from stainless steel and the volume between the shells is filled with rigid foam. This foam provides insulation during an accidental fire. Vent holes, plugged with material designed to melt in a fire, are provided between the shells to prevent pressure buildup and allow a pathway for escape of gases from foam during an accidental fire.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

|                          |                    |                  |                                  |      |       |
|--------------------------|--------------------|------------------|----------------------------------|------|-------|
| 1. a. CERTIFICATE NUMBER | b. REVISION NUMBER | c. DOCKET NUMBER | d. PACKAGE IDENTIFICATION NUMBER | PAGE | PAGES |
| 9310                     | 7                  | 71-9310          | USA/9310/B(U)-96                 | 2    | OF 4  |

5.(a)(2) continued

The GC-1000 and the GC-3000 are lead-shielding casks each with a source cavity. The package contents may consist of up to eight Cesium-137 special form sealed sources or RAMCO-50 non-special form sealed sources (provided Condition 5.(b)(1)(ii) is met) inside a source holder, within the source cavity. The maximum total activity of Cesium-137 is 113 tera-Becquerels (TBq) [3,050 Curies (Ci)]. The following are the features of the GC-1000 and GC-3000:

| <b>Irradiator Model</b> | <b>Rated Capacity</b> | <b>Diameter*</b>   | <b>Height*</b>     | <b>Lead Thickness*</b> | <b>Steel Shell Thickness*</b> | <b>Weight*</b>         |
|-------------------------|-----------------------|--------------------|--------------------|------------------------|-------------------------------|------------------------|
| <b>GC-1000</b>          | 113 TBq<br>(3,050 Ci) | 457 mm<br>(18 in.) | 610 mm<br>(24 in.) | 150 mm<br>(6 in.)      | 9.5 mm<br>(0.375 in.)         | 1,054 kg<br>(2,324 lb) |
| <b>GC-3000</b>          | 113 TBq<br>(3,050 Ci) | 457 mm<br>(18 in.) | 610 mm<br>(24 in.) | 110 mm<br>(4.35 in.)   | 9.5 mm<br>(0.375 in.)         | 1,091 kg<br>(2,404 lb) |

\* Nominal Values

The approximate dimensions and weights of the package are as follows:

|                          |  |
|--------------------------|--|
| Package outside diameter | 1,067mm (42 in.)   |
| Package height           | 1,283 mm (50.5 in.)                                      |
| Cavity diameter          | 559 mm (22 in.)  |
| Cavity height            | 813 mm (32 in.)  |
| Removable skid           | 1,118 mm (44 in.) x 1,003 mm (39.5 in.) x 203 mm (8 in.) |
| Overpack weight          | 1,044 kg (2,300 lbs.)                                    |
| Contents weight (max.)   | 1,225 kg (2,700 lbs.)                                    |
| Maximum package weight   | 2,270 kg (5,000 lbs.)                                    |

(3) Drawings

The packaging is constructed in accordance with the Best Theratronics drawing F643101-001, "F-431/GC-1000/3000 Transportation Package Information Drawing," Sheet 1, Revision K, and Sheet 2, Revision F.

(b) Contents

(1) Type and form of material

- (i) Cesium-137 as a sealed source which meets the requirements of special form radioactive material. The sealed sources consist of the following special form sources: C-378, C-1000, C-1001, C-3000, C-3001, C3100, or ISO-1000.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

| 1. | a. CERTIFICATE NUMBER | b. REVISION NUMBER | c. DOCKET NUMBER | d. PACKAGE IDENTIFICATION NUMBER | PAGE | PAGES |
|----|-----------------------|--------------------|------------------|----------------------------------|------|-------|
|    | 9310                  | 7                  | 71-9310          | USA/9310/B(U)-96                 | 3    | OF 4  |

5.(b) continued

(ii) Cesium-137 as the RAMCO-50 non-special form sealed source, provided the following conditions are met:

- a. Source must conform to the specifications given in Figure 4.8 of the Safety Analysis Report and sealed source registry Certificate No. NR-0880-S-804-S.
- b. Source must have been shown to not be leaking within six months prior to shipment.
- c. Source must not have been damaged during its service in the GC-1000.

(2) Maximum quantity of material per package

113 TBq (3,050 Curies)

6. In addition to the requirements of Subpart G of 10 CFR Part 71:

- (a) The package must be prepared for shipment and operated in accordance with the Operating Procedures in Chapter 7 of the application.
- (b) Each packaging must be acceptance tested and maintained in accordance with the Acceptance Tests and Maintenance Program in Chapter 8 of the application.

7. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.

8. Transport by air of fissile material is not authorized.

9. Revision No. 6 of this certificate may be used until November 30, 2020.

10. Expiration date: November 30, 2024.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

| 1. | a. CERTIFICATE NUMBER | b. REVISION NUMBER | c. DOCKET NUMBER | d. PACKAGE IDENTIFICATION NUMBER | PAGE | PAGES |
|----|-----------------------|--------------------|------------------|----------------------------------|------|-------|
|    | 9310                  | 7                  | 71-9310          | USA/9310/B(U)-96                 | 4    | OF 4  |

REFERENCES

Best Theratronics application dated July 29, 2019.

Supplement dated: November 5, 2019.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

**/RA/**

Daniel Doyle, Acting Chief  
Storage and Transportation Licensing Branch  
Division of Fuel Management  
Office of Nuclear Material Safety  
and Safeguards

Date: 11/26/2019

