

MATERIALS LICENSE

Pursuant to the Atomic Energy Act of 1954, as amended, the Energy Reorganization Act of 1974 (Public Law 93-438), and Title 10, Code of Federal Regulations, Chapter I, Parts 30, 31, 32, 33, 34, 35, 36, 39, 40, and 70, and in reliance on statements and representations heretofore made by the licensee, a license is hereby issued authorizing the licensee to receive, acquire, possess, and transfer byproduct, source, and special nuclear material designated below, to use such material for the purposes and at the places designated below, to deliver or transfer such material to persons authorized to receive it in accordance with the regulations of the applicable Part(s). This license shall be deemed to contain the conditions specified in Section 183 of the Atomic Energy Act of 1954, as amended, and is subject to all applicable rules, regulations, and orders of the Nuclear Regulatory Commission now or hereafter in effect and to any conditions specified below.

Licensee		3. License Number
1. Energy Fuels Nuclear, Inc.		SUA-1358
2. 6425 S. Highway 191 P.O. Box 789 Blanding, Utah 84511		4. Expiration Date March 31, 2007
		5. Docket or Reference No. 40-8681
6. Byproduct, Source, and/or Special Nuclear Material	7. Chemical and/or Physical Form	8. Maximum Amount that Licensee May Possess at Any One Time Under This License
Natural Uranium	Any	Unlimited

SECTION 9: Administrative Conditions

- 9.1 The authorized place of use shall be the licensee's White Mesa uranium milling facility, located in San Juan County, Utah.
- 9.2 All written notices and reports to the NRC required under this license, with the exception of incident and event notifications under 10 CFR 20.2202 and 10 CFR 40.60 requiring telephone notification, shall be addressed to the Chief, Uranium Recovery Branch, Division of Waste Management, Office of Nuclear Material Safety and Safeguards.

Incident and event notifications that require telephone notification shall be made to the NRC Operations Center at (301) 816-5100.

- 9.3 The licensee shall conduct operations in accordance with statements, representations, and conditions contained in the license renewal application submitted by letter dated August 23, 1991, as revised by submittals dated January 13, and April 7, 1992, November 22, 1994, July 27, 1995, December 15, 1996, and January 30, 1997, which are hereby incorporated by reference, and May 10, 1994, for the Standby Trust Agreement, except where superseded by license conditions below.

Whenever the word "will" is used in the above referenced documents, it shall denote a requirement.

- 9.4 A. The licensee may, without prior NRC approval, and subject to the conditions specified in Part B of this condition:

9703190298 970314
PDR ADDCK 04008681
C PDR

**MATERIALS LICENSE
SUPPLEMENTARY SHEET**

License Number

SUA-1358

Docket or Reference Number

40-8681

March 14, 1997

- (1) Make changes in the facility or process, as presented in the application.
 - (2) Make changes in the procedures presented in the application.
 - (3) Conduct tests or experiments not presented in the application.
- B. The licensee shall file an application for an amendment to the license, unless the following conditions are satisfied.
- (1) The change, test, or experiment does not conflict with any requirement specifically stated in this license, or impair the licensee's ability to meet all applicable NRC regulations.
 - (2) There is no degradation in the essential safety or environmental commitments in the license application, or provided by the approved reclamation plan.
 - (3) The change, test, or experiment are consistent with the conclusions of actions analyzed and selected in this EA.
- C. The licensee's determinations concerning Part B of this condition, shall be made by a "Safety and Environmental Review Panel (SERP)." The SERP shall consist of a minimum of three individuals. One member of the SERP shall have expertise in management and shall be responsible for managerial and financial approval changes; one member shall have expertise in operations and/or construction and shall have responsibility for implementing any operational changes; and, one member shall be the corporate radiation safety officer (CRSO) or equivalent, with the responsibility of assuring changes conform to radiation safety and environmental requirements. Additional members may be included in the SERP as appropriate, to address technical aspects such as health physics, groundwater hydrology, surface-water hydrology, specific earth sciences, and other technical disciplines. Temporary members or permanent members, other than the three above-specified individuals, may be consultants.
- D. The licensee shall maintain records of any changes made pursuant to this condition until license termination. These records shall include written safety and environmental evaluations, made by the SERP, that provide the basis for determining changes are in compliance with the requirements referred to in Part B of this condition. The licensee shall furnish, in an annual report to NRC, a description of such changes, tests, or experiments, including a summary of the safety and environmental evaluation of each. In addition, the licensee shall annually submit to the NRC changed pages to the Operations Plan and Reclamation Plan of the approved license application to reflect changes made under this condition.

**MATERIALS LICENSE
SUPPLEMENTARY SHEET**

License Number

SUA-1358

Docket or Reference Number

40-8681

March 14, 1997

The licensee shall submit to the NRC by April 30, 1997, for review, the standard operating procedures (SOPs) needed to implement this license condition. The licensee shall not implement any provision of this license condition until NRC has found the proposed SOPs acceptable.

- 9.5 The licensee shall maintain an NRC-approved financial surety arrangement, consistent with 10 CFR 40, Appendix A, Criteria 9 and 10, adequate to cover the estimated costs, if accomplished by a third party, for decommissioning and decontamination of the mill and mill site, for reclamation of any tailings or waste disposal areas, ground-water restoration as warranted and for the long-term surveillance fee. Within three months of NRC approval of a revised reclamation/decommissioning plan, the licensee shall submit, for NRC review and approval, a proposed revision to the financial surety arrangement if estimated costs in the newly approved plan exceed the amount covered in the existing financial surety. The revised surety shall then be in effect within 3 months of written NRC approval.

Annual updates to the surety amount, required by 10 CFR 40, Appendix A, Criteria 9 and 10, shall be submitted to the NRC at least 3 months prior to the anniversary date which is designated as June 4 of each year. If the NRC has not approved a proposed revision to the surety coverage 30 days prior to the expiration date of the existing surety arrangement, the licensee shall extend the existing surety arrangement for 1 year. Along with each proposed revision or annual update, the licensee shall submit supporting documentation showing a breakdown of the costs and the basis for the cost estimates with adjustments for inflation, maintenance of a minimum 15 percent contingency fee, changes in engineering plans, activities performed and any other conditions affecting estimated costs for site closure. The basis for the cost estimate is the NRC approved reclamation/decommissioning plan or NRC approved revisions to the plan. The previously provided guidance entitled "Recommended Outline for Site Specific Reclamation and Stabilization Cost Estimates" outlines the minimum considerations used by the NRC in the review of site closure estimates. Reclamation/decommissioning plans and annual updates should follow this outline.

The currently approved surety instrument, Irrevocable Letter of Credit No. S00017012, issued by The Bank of New York in favor of the NRC, as amended, May 10, 1994, to include a Standby Trust Agreement, shall be continuously maintained by UMETCO in an amount not less than \$10,915,467 for the purpose of complying with 10 CFR 40, Appendix A, Criteria 9 and 10, until a replacement is authorized by the NRC.

- 9.6 Standard operating procedures shall be established and followed for all operational process activities involving radioactive materials that are handled, processed, or stored. SOPs for operational activities shall enumerate pertinent radiation safety practices to be followed. Additionally, written procedures shall be established for non-operational activities to include in-plant and environmental monitoring, bioassay

**MATERIALS LICENSE
SUPPLEMENTARY SHEET**

License Number

SUA-1358

Docket or Reference Number

40-8681

March 14, 1997

analyses, and instrument calibrations. An up-to-date copy of each written procedure shall be kept in the mill area to which it applies.

All written procedures for both operational and non-operational activities shall be reviewed and approved in writing by the radiation safety officer (RSO) before implementation and whenever a change in procedure is proposed to ensure that proper radiation protection principles are being applied. In addition, the RSO shall perform a documented review of all existing operating procedures at least annually.

9.7

Before engaging in any activity not previously assessed by the NRC, the licensee shall administer a cultural resource inventory. All disturbances associated with the proposed development will be completed in compliance with the National Historic Preservation Act (as amended) and its implementing regulations (36 CFR 800), and the Archaeological Resources Protection Act (as amended) and its implementing regulations (43 CFR 7).

In order to ensure that no unapproved disturbance of cultural resources occurs, any work resulting in the discovery of previously unknown cultural artifacts shall cease. The artifacts shall be inventoried and evaluated in accordance with 36 CFR Part 800, and no disturbance shall occur until the licensee has received authorization from the NRC to proceed.

The licensee shall avoid by project design, where feasible, the archeological sites designated "contributing" in the report submitted by letter dated July 28, 1988. When it is not feasible to avoid a site designated "contributing" in the report, the licensee shall institute a data recovery program for that site based on the research design submitted by letter from C. E. Baker of Energy Fuels Nuclear to Mr. Melvin T. Smith, Utah State Historic Preservation Officer (SHPO), dated April 13, 1981.

The licensee shall recover through archeological excavation all "contributing" sites listed in the report which are located in or within 100 feet of borrow areas, stockpile areas, construction areas, or the perimeter of the reclaimed tailings impoundment. Data recovery fieldwork at each site meeting these criteria shall be completed prior to the start of any project related disturbance within 100 feet of the site, but analysis and report preparation need not be complete.

Additionally, the licensee shall conduct such testing as is required to enable the Commission to determine if those sites designated as "Undetermined" in the report and located within 100 feet of present or known future construction areas are of such significance to warrant their redesignation as "contributing." In all cases, such testing shall be completed before any aspect of the undertaking affects a site.

Archeological contractors shall be approved in writing by the Commission. The Commission will approve an archeological contractor who meets the minimum standards for a principal investigator set forth in 36 CFR Part 66, Appendix C, and whose qualifications are found acceptable by the SHPO.

MATERIALS LICENSE
SUPPLEMENTARY SHEET

License Number

SUA-1358

Docket or Reference Number

40-8681

March 14, 1997

- 9.8 The licensee is hereby authorized to possess byproduct material in the form of uranium waste tailings and other uranium byproduct waste generated by the licensee's milling operations authorized by this license. Mill tailings shall not be transferred from the site without specific prior approval of the NRC in the form of a license amendment. The licensee shall maintain a permanent record of all transfers made under the provisions of this condition.
- 9.9 The licensee is hereby exempted from the requirements of Section 20.1902 (e) of 10 CFR Part 20 for areas within the mill, provided that all entrances to the mill are conspicuously posted in accordance with Section 20.1902 (e) and with the words, "Any area within this mill may contain radioactive material."
- 9.10 Release of equipment or packages from the restricted area shall be in accordance with "Guidelines for Decontamination of Facilities and Equipment Prior to Release for Unrestricted Use or Termination of Licenses for Byproduct, Source, or Special Nuclear Material," dated May 1987, or suitable alternative procedures approved by the NRC prior to any such release.

SECTION 10: Operational Controls, Limits, and Restrictions

- 10.1 The mill production rate shall not exceed 4380 tons of yellowcake per year.
- 10.2 All liquid effluents from mill process buildings, with the exception of sanitary wastes, shall be returned to the mill circuit or discharged to the tailings impoundment.
- 10.3 Freeboard limits for Cells 1-1, 3, and 4A, and tonnage limits for Cell 3, shall be as stated in Section 3.0 to Appendix E of the approved license application.
- 10.4 Disposal of material and equipment generated at the mill site shall be conducted as described in the licensee's submittals dated December 12, 1994 and May 23, 1995, with the following addition:
- A. The maximum lift thickness for materials placed over tailings shall be less than 4-feet thick. Subsequent lifts shall be less than 2-feet thick. Each lift shall be compacted by tracking of heavy equipment, such as a Cat D-6, at least 4 times prior to placement of subsequent lifts.
- 10.5 In accordance with the licensee's submittal dated May 20, 1993, the licensee is hereby authorized to dispose of byproduct material generated at licensed in situ leach facilities, subject to the following conditions:
- A. Disposal of waste is limited to 5000 cubic yards from a single source.

MATERIALS LICENSE
SUPPLEMENTARY SHEET

License Number

SUA-1358

Docket or Reference Number

40-8681

March 14, 1997

- B. All contaminated equipment shall be dismantled, crushed, or sectioned to minimize void spaces. Barrels containing waste other than soil or sludges shall be emptied into the disposal area and the barrels crushed. Barrels containing soil or sludges shall be verified to be full prior to disposal. Barrels not completely full shall be filled with tailings or soil.
- C. All waste shall be buried in Cell No. 3 unless prior written approval is obtained from the NRC for alternate burial locations.
- D. All disposal activities shall be documented. The documentation shall include descriptions of the waste and the disposal locations, as well as all actions required by this condition. An annual summary of the amounts of waste disposed of from off-site generators shall be sent to the NRC.
- 10.6 The licensee is authorized to receive and process source materials from the Allied Signal Corporation's Metropolis, Illinois, facility in accordance with the amendment request dated June 15, 1993.
- 10.7 The licensee is authorized to receive and process source material from Allied Signal, Inc. of Metropolis, Illinois, in accordance with the amendment request dated September 20, 1996, and amended by letters dated October 30, and November 11, 1996.

SECTION 11: Monitoring, Recording, and Bookkeeping Requirements

- 11.1 The results of sampling, analyses, surveys and monitoring, the results of calibration of equipment, reports on audits and inspections, all meetings and training courses required by this license and any subsequent reviews, investigations, and corrective actions, shall be documented. Unless otherwise specified in the NRC regulations all such documentation shall be maintained for a period of at least five (5) years.
- 11.2 The licensee shall implement the effluent and environmental monitoring program specified in Section 5.5 of the renewal application as revised with the following modifications or additions:
- A. Stack sampling shall include a determination of flow rate.
- B. Surface water samples shall also be analyzed semiannually for total and dissolved U-nat, Ra-226, and Th-230, with the exception of the Westwater Creek, which shall be sampled annually for water sediments and analyzed as above. A sediment sample shall not be taken in place of a water sample unless a water sample was not available.
- C. Groundwater sampling shall be conducted in accordance with the requirements in License Condition 11.3.

**MATERIALS LICENSE
SUPPLEMENTARY SHEET**

License Number

SUA-1358

Docket or Reference Number

40-8681

March 14, 1997

- D. The licensee shall utilize lower limits of detection in accordance with Section 5 of Regulatory Guide 4.14 (Revision 1), for analysis of effluent and environmental samples.
- E. The inspections performed semiannually of the critical orifice assembly committed to in the submittal dated March 15, 1986, shall be documented. The critical orifice assembly shall be calibrated at least every 2 years against a positive displacement Roots meter to obtain the required calibration curve.

11.3 The licensee shall implement a groundwater detection monitoring program to ensure compliance to 10 CFR Part 40, Appendix A. The detection monitoring program shall be in accordance with the report entitled, "Points of Compliance, White Mesa Uranium Mill," submitted by letter dated October 5, 1994, as modified by the following:

- A. The leak detection system for all ponds will be checked weekly. If liquid is present, it shall be analyzed for chloride, sulfate, selenium, and pH. The samples will be statistically analyzed to determine if significant linear trends exist, and the results will be submitted to NRC for review.
- B. If a significant linear trend is indicated, the licensee will submit a proposed corrective action for review and approval to NRC. The corrective action shall include a discussion on delineation of the areal extent and concentration of hazardous constituents.
- C. The licensee shall sample monitoring wells WMMW-5, -11, -12, -14, -15, and -17, on a quarterly basis. Samples shall be analyzed for chloride, potassium, nickel, and uranium, and the results of such sampling shall be included with the environmental monitoring reports submitted in accordance with 10 CFR 40.65.

11.4 During extended periods of mill standby, eight-hour annual sampling for U-nat, Ra-226, Th-230 and Pb-210 may be eliminated if routine airborne sampling show levels below 10 percent of the appropriate 10 CFR Part 20 limits.

During periods of standby, sampling frequencies for area airborne uranium sampling within the mill may be reduced to quarterly, provided measured levels remain below 10 percent of the derived air concentration (DAC). If these levels exceed 10 percent of the DAC, the sampling frequency should follow the recommendations in Regulatory Guide 8.30.

11.5 Calibration of in-plant air and radiation monitoring equipment shall be performed as specified in the license renewal application, under Section 3.0 of the "Radiation Protection Procedures Manual," with the exception that in-plant air sampling equipment shall be calibrated at least quarterly and air sampling equipment checks shall be documented.

**MATERIALS LICENSE
SUPPLEMENTARY SHEET**

License Number

SUA-1358

Docket or Reference Number

40-8681

March 14, 1997

- 11.6 The licensee shall perform an annual ALARA audit of the radiation safety program in accordance with Regulatory Guide 8.31.

SECTION 12: Reporting Requirements

- 12.1 The licensee shall submit to NRC for review, by June 30, 1997, a detailed reclamation plan for the authorized tailings disposal area which includes the following:
- A. A post-operations interim stabilization plan which details methods to prevent wind and water erosion and recharge of the tailings area.
 - B. A plan to determine the best methodology to dewater and/or consolidate the tailings cells prior to placement of the final reclamation cover.
 - C. Plan and cross-sectional views of a final reclamation cover which details the location and elevation of tailings. The plan shall include details on cover thickness, physical characteristics of cover materials, proposed testing of cover materials (specifications and quality assurance), the estimated volumes of cover materials and their availability and location.
 - D. Detailed plans for placement of rock or vegetative cover on the final reclaimed tailings pile and mill site area.
 - E. A proposed implementation schedule for items A through D above which defines the sequence of events and expected time ranges.
 - F. An analysis to show that the proposed type and thickness of soil cover is adequate to provide attenuation of radon and is adequate to assure long-term stability, as well as an analysis and proposal on methodology and time required to restore ground water in conformance to regulatory requirements.
 - G. The licensee shall include a detailed cost analysis of each phase of the reclamation plan to include contractor costs, projected costs of inflation based upon the schedule proposed in item E, a proposed contingency cost, and the costs of long-term maintenance and monitoring.

**MATERIALS LICENSE
SUPPLEMENTARY SHEET**

License Number

SUA-1358

Docket or Reference Number

40-8681


March 14, 1997

- 12.2 The licensee shall submit a detailed decommissioning plan to the NRC at least twelve (12) months prior to planned final shutdown of mill operations.

FOR THE NUCLEAR REGULATORY COMMISSION

Date

March 14, 1997


Joseph J. Holonich, Chief
Uranium Recovery Branch
Division of Waste Management
Office of Nuclear Material Safety
and Safeguards

Enclosure 5

**"Guidelines for Decontamination of Facilities and Equipment
Prior to Release for Unrestricted Use
or Termination of Licenses for Byproduct, Source,
or Special Nuclear Material"**

May 1987 revision

GUIDELINES FOR DECONTAMINATION OF FACILITIES AND EQUIPMENT
PRIOR TO RELEASE FOR UNRESTRICTED USE
OR TERMINATION OF LICENSES FOR BYPRODUCT, SOURCE,
OR SPECIAL NUCLEAR MATERIAL

U.S. Nuclear Regulatory Commission
Division of Fuel Cycle, Medical, Academic,
and Commercial Use Safety
Washington, DC 20555

May 1987

8705050168 4pp

TABLE 1

ACCEPTABLE SURFACE CONTAMINATION LEVELS

NUCLIDES ^a	AVERAGE ^{b c f}	MAXIMUM ^{b d f}	REMOVABLE ^{b e f}
U-nat, U-235, U-238, and associated decay products	5,000 dpm α /100 cm ²	15,000 dpm α /100 cm ²	1,000 dpm α /100 cm ²
Transuranics, Ra-226, Ra-228, Th-230, Th-228, Pa-231, Ac-227, I-125, I-129	100 dpm/100 cm ²	300 dpm/100 cm ²	20 dpm/100 cm ²
Th-nat, Th-232, Sr-90, Ra-223, Ra-224, U-232, I-126, I-131, I-133	1000 dpm/100 cm ²	3000 dpm/100 cm ²	200 dpm/100 cm ²
Beta-gamma emitters (nuclides with decay modes other than alpha emission or spontaneous fission) except Sr-90 and others noted above.	5000 dpm $\beta\gamma$ /100 cm ²	15,000 dpm $\beta\gamma$ /100 cm ²	1000 dpm $\beta\gamma$ /100 cm ²

^aWhere surface contamination by both alpha- and beta-gamma-emitting nuclides exists, the limits established for alpha- and beta-gamma-emitting nuclides should apply independently.

^bAs used in this table, dpm (disintegrations per minute) means the rate of emission by radioactive material as determined by correcting the counts per minute observed by an appropriate detector for background, efficiency, and geometric factors associated with the instrumentation.

^cMeasurements of average contaminant should not be averaged over more than 1 square meter. For objects of less surface area, the average should be derived for each such object.

^dThe maximum contamination level applies to an area of not more than 100 cm².

^eThe amount of removable radioactive material per 100 cm² of surface area should be determined by wiping that area with dry filter or soft absorbent paper, applying moderate pressure, and assessing the amount of radioactive material on the wipe with an appropriate instrument of known efficiency. When removable contamination on objects of less surface area is determined, the pertinent levels should be reduced proportionally and the entire surface should be wiped.

^fThe average and maximum radiation levels associated with surface contamination resulting from beta-gamma emitters should not exceed 0.2 mrad/hr at 1 cm and 1.0 mrad/hr at 1 cm, respectively, measured through not more than 7 milligrams per square centimeter of total absorber.

The instructions in this guide, in conjunction with Table 1, specify the radionuclides and radiation exposure rate limits which should be used in decontamination and survey of surfaces or premises and equipment prior to abandonment or release for unrestricted use. The limits in Table 1 do not apply to premises, equipment, or scrap containing induced radioactivity for which the radiological considerations pertinent to their use may be different. The release of such facilities or items from regulatory control is considered on a case-by-case.

1. The licensee shall make a reasonable effort to eliminate residual contamination.
2. Radioactivity on equipment or surfaces shall not be covered by paint, plating, or other covering material unless contamination levels, as determined by a survey and documented, are below the limits specified in Table 1 prior to the application of the covering. A reasonable effort must be made to minimize the contamination prior to use of any covering.
3. The radioactivity on the interior surfaces of pipes, drain lines, or ductwork shall be determined by making measurements at all traps, and other appropriate access points, provided that contamination at these locations is likely to be representative of contamination on the interior of the pipes, drain lines, or ductwork. Surfaces of premises, equipment, or scrap which are likely to be contaminated but are of such size, construction, or location as to make the surface inaccessible for purposes of measurement shall be presumed to be contaminated in excess of the limits.
4. Upon request, the Commission may authorize a licensee to relinquish possession or control of premises, equipment, or scrap having surfaces contaminated with materials in excess of the limits specified. This may include, but would not be limited to, special circumstances such as razing of buildings, transfer to premises to another organization continuing work with radioactive materials, or conversion of facilities to a long-term storage or standby status. Such requests must:
 - a. Provide detailed, specific information describing the premises, equipment or scrap, radioactive contaminants, and the nature, extent, and degree of residual surface contamination.
 - b. Provide a detailed health and safety analysis which reflects that the residual amounts of materials on surface areas, together with other considerations such as prospective use of the premises, equipment, or scrap, are unlikely to result in an unreasonable risk to the health and safety of the public.

5. Prior to release of premises for unrestricted use, the licensee shall make a comprehensive radiation survey which establishes that contamination is within the limits specified in Table 1. A copy of the survey report shall be filed with the Division of Fuel Cycle, Medical, Academic, and Commercial Use Safety, U. S. Nuclear Regulatory Commission, Washington, DC 20555, and also the Administrator of the NRC Regional Office having jurisdiction. The report should be filed at least 30 days prior to the planned date of abandonment. The survey report shall:

- a. Identify the premises.
- b. Show that reasonable effort has been made to eliminate residual contamination.
- c. Describe the scope of the survey and general procedures followed.
- d. State the findings of the survey in units specified in the instruction.

Following review of the report, the NRC will consider visiting the facilities to confirm the survey.