

## INTERNATIONAL NUTRONICS, INC.

December 22, 1983

### Amendment to Procedure #9 Pertaining to Respirator Fit Check

According to procedure #3 Respirator Protective Program we employ the Willson 3195 full face respirator with NIOSH/MSHA TC-23C-142 approved filter & the Norton 100 disposable half face respirator with NIOSH/MSHA TC-21C-251 approved filter. The filters being employed are particle filters rather than organic vapor filters, thus isoamyl acetate provided by the Cesco Qualfit test kit is improper. We will employ the 3M Qualitative Fit Test kit utilizing a Nebulizer which is sensed by taste rather than smell. The following procedure will be employed for proper fit of respirators:

1. Don the Norton or Willson respirator according to manufacturer's fitting instructions.
2. Perform a positive or negative pressure fit check and adjust face piece, if necessary.
3. The person wearing the respirator will employ Nebulizer by spraying 3 to 4 inches away from respirator seams. The person shall breath through his mouth because a leak is detected by taste rather than smell.
4. Leakage will be noted by a sweet taste. If wearer senses a sweet taste he fails the test and must readjust respirator and re-test his respirator's fit.
5. Once, respirator fit test is passed he is permitted entry into the ARA.

LNm/lnm

8506180332 850426  
PDR FOIA  
TERPILAB4-763 PDR