Honeywell

THE POWER OF **CONNECTED**

Performance Materials & Technologies
2768 North U.S. 45 Road
P.O. Box 430
Metropolis, IL 62960
www.honeywell.com

August 31st, 2022

UPS/Next Day Air

Attn: Document Control Desk
U.S. Nuclear Regulatory Commission
11555 Rockville Pike
Rockville, MD 20852

Docket No. 40-3392; License No. SUB-526
Subject: Honeywell Metopolis Works 6 Month Facility Effluent Report

Enclosed are six copies of Honeywell Metropolis Works Facility Effluent Report representing the period January 1 through June 30, 2022.

Sincerely,

Brian Hunt
Plant Manager

Enclosure: Facility Effluent Report (6)

Cc:
ALARA Committee – Jeff Fulks, Brian Hunt, Jessica Carillo Morris, Sean Patterson, and Michael Dawson

U.S. Nuclear Regulatory Commission - Region II
Marquis One Tower
245 Peachtree Center Ave. NE, Suite 1200
Atlanta, GA 30303

Adnan G. Khayyat
IL Emergency Management Agency
1035 Outer Park Drive
Springfield, IL 62704

US NRC
Osiris Siurano – Project Manager
Fuel Facility Licensing and Oversight Branch
Division of Fuel Cycle Safety, Safeguards, and Environmental Review
Office of NMSS
11555 Rockville Pike
Rockville, MD 20852

NMSS01
NMSS

FACILITY EFFLUENT REPORT
TYPE OF FACILITY:

UF6 Conversion

LICENSE:

Source Materials No. SUB-526
Docket No. 40-3392

FACILITY ADDRESS:

Honeywell – Metropolis Works
P.O. Box 430
Metropolis, IL 62960

REPORTING PERIOD:

Januray 1, 2022 – June 30, 2022

GASEOUS EFFLUENTS:

1. The average release rate for the reporting period = 1.4×10^{5} ACFM.

2. The principle radionuclides released are particulate, oxides and fluorides as follows:

Uranium (Nat.)	=	1.95×10^{-3} curies (measured)
Ra^{226}	=	2.82×10^{-4} curies (Note 1)
Th^{230}	=	9.17×10^{-5} curies (Note 1)

LIQUID EFFLUENTS: (Note 2)

1. The average release rate for the reporting period = 732 GPM.

2. The principle radionuclides released are as follows:

Uranium (Nat.)	=	1.14×10^{-1} curies (measured)
Ra^{226}	=	1.68×10^{-3} curies (measured)
Th^{230}	=	9.21×10^{-4} curies (measured)

NOTE 1: Calculated from a measured ratio of Th^{230} and Ra^{226} compared to total uranium collected at environmental air sample locations around the facility. These ratios were then used to determine Th^{230} and Ra^{226} activity discharged based upon measured uranium from process stacks and fans.

NOTE 2: Quantities include storm water effluent discharge.

FACILITY EFFLUENT REPORT
TYPE OF FACILITY:

UF6 Conversion

LICENSE:

Source Materials No. SUB-526
Docket No. 40-3392

FACILITY ADDRESS:

Honeywell – Metropolis Works
P.O. Box 430
Metropolis, IL 62960

REPORTING PERIOD:

Januray 1, 2022 – June 30, 2022

GASEOUS EFFLUENTS:

1. The average release rate for the reporting period = 1.4×10^{5} ACFM.

2. The principle radionuclides released are particulate, oxides and fluorides as follows:

Uranium (Nat.)	=	1.95×10^{-3} curies (measured)
Ra^{226}	=	2.82×10^{-4} curies (Note 1)
Th^{230}	=	9.17×10^{-5} curies (Note 1)

LIQUID EFFLUENTS: (Note 2)

1. The average release rate for the reporting period = 732 GPM.

2. The principle radionuclides released are as follows:

Uranium (Nat.)	=	1.14×10^{-1} curies (measured)
Ra^{226}	=	1.68×10^{-3} curies (measured)
Th^{230}	=	9.21×10^{-4} curies (measured)

NOTE 1: Calculated from a measured ratio of Th^{230} and Ra^{226} compared to total uranium collected at environmental air sample locations around the facility. These ratios were then used to determine Th^{230} and Ra^{226} activity discharged based upon measured uranium from process stacks and fans.

NOTE 2: Quantities include storm water effluent discharge.

FACILITY EFFLUENT REPORT
TYPE OF FACILITY:

UF6 Conversion

LICENSE:

Source Materials No. SUB-526
Docket No. 40-3392

FACILITY ADDRESS:

Honeywell – Metropolis Works
P.O. Box 430
Metropolis, IL 62960

REPORTING PERIOD:

Januray 1, 2022 – June 30, 2022

GASEOUS EFFLUENTS:

1. The average release rate for the reporting period = 1.4×10^{5} ACFM.

2. The principle radionuclides released are particulate, oxides and fluorides as follows:

Uranium (Nat.)	=	1.95×10^{-3} curies (measured)
Ra^{226}	=	2.82×10^{-4} curies (Note 1)
Th^{230}	=	9.17×10^{-5} curies (Note 1)

LIQUID EFFLUENTS: (Note 2)

1. The average release rate for the reporting period = 732 GPM.

2. The principle radionuclides released are as follows:

Uranium (Nat.)	=	1.14×10^{-1} curies (measured)
Ra^{226}	=	1.68×10^{-3} curies (measured)
Th^{230}	=	9.21×10^{-4} curies (measured)

NOTE 1: Calculated from a measured ratio of Th^{230} and Ra^{226} compared to total uranium collected at environmental air sample locations around the facility. These ratios were then used to determine Th^{230} and Ra^{226} activity discharged based upon measured uranium from process stacks and fans.

NOTE 2: Quantities include storm water effluent discharge.

FACILITY EFFLUENT REPORT
TYPE OF FACILITY:

UF6 Conversion

LICENSE:

Source Materials No. SUB-526
Docket No. 40-3392

FACILITY ADDRESS:

Honeywell – Metropolis Works
P.O. Box 430
Metropolis, IL 62960

REPORTING PERIOD:

Januray 1, 2022 – June 30, 2022

GASEOUS EFFLUENTS:

1. The average release rate for the reporting period = 1.4×10^{5} ACFM.

2. The principle radionuclides released are particulate, oxides and fluorides as follows:

Uranium (Nat.)	=	1.95×10^{-3} curies (measured)
Ra^{226}	=	2.82×10^{-4} curies (Note 1)
Th^{230}	=	9.17×10^{-5} curies (Note 1)

LIQUID EFFLUENTS: (Note 2)

1. The average release rate for the reporting period = 732 GPM.

2. The principle radionuclides released are as follows:

Uranium (Nat.)	=	1.14×10^{-1} curies (measured)
Ra^{226}	=	1.68×10^{-3} curies (measured)
Th^{230}	=	9.21×10^{-4} curies (measured)

NOTE 1: Calculated from a measured ratio of Th^{230} and Ra^{226} compared to total uranium collected at environmental air sample locations around the facility. These ratios were then used to determine Th^{230} and Ra^{226} activity discharged based upon measured uranium from process stacks and fans.

NOTE 2: Quantities include storm water effluent discharge.

FACILITY EFFLUENT REPORT
TYPE OF FACILITY:

UF6 Conversion

LICENSE:

Source Materials No. SUB-526
Docket No. 40-3392

FACILITY ADDRESS:

Honeywell – Metropolis Works
P.O. Box 430
Metropolis, IL 62960

REPORTING PERIOD:

Januray 1, 2022 – June 30, 2022

GASEOUS EFFLUENTS:

1. The average release rate for the reporting period = 1.4×10^{5} ACFM.

2. The principle radionuclides released are particulate, oxides and fluorides as follows:

Uranium (Nat.)	=	1.95×10^{-3} curies (measured)
Ra^{226}	=	2.82×10^{-4} curies (Note 1)
Th^{230}	=	9.17×10^{-5} curies (Note 1)

LIQUID EFFLUENTS: (Note 2)

1. The average release rate for the reporting period = 732 GPM.

2. The principle radionuclides released are as follows:

Uranium (Nat.)	=	1.14×10^{-1} curies (measured)
Ra^{226}	=	1.68×10^{-3} curies (measured)
Th^{230}	=	9.21×10^{-4} curies (measured)

NOTE 1: Calculated from a measured ratio of Th^{230} and Ra^{226} compared to total uranium collected at environmental air sample locations around the facility. These ratios were then used to determine Th^{230} and Ra^{226} activity discharged based upon measured uranium from process stacks and fans.

NOTE 2: Quantities include storm water effluent discharge.

FACILITY EFFLUENT REPORT
TYPE OF FACILITY:

UF6 Conversion

LICENSE:

Source Materials No. SUB-526
Docket No. 40-3392

FACILITY ADDRESS:

Honeywell – Metropolis Works
P.O. Box 430
Metropolis, IL 62960

REPORTING PERIOD:

Januray 1, 2022 – June 30, 2022

GASEOUS EFFLUENTS:

1. The average release rate for the reporting period = 1.4×10^{5} ACFM.

2. The principle radionuclides released are particulate, oxides and fluorides as follows:

Uranium (Nat.)	=	1.95×10^{-3} curies (measured)
Ra^{226}	=	2.82×10^{-4} curies (Note 1)
Th^{230}	=	9.17×10^{-5} curies (Note 1)

LIQUID EFFLUENTS: (Note 2)

1. The average release rate for the reporting period = 732 GPM.

2. The principle radionuclides released are as follows:

Uranium (Nat.)	=	1.14×10^{-1} curies (measured)
Ra^{226}	=	1.68×10^{-3} curies (measured)
Th^{230}	=	9.21×10^{-4} curies (measured)

NOTE 1: Calculated from a measured ratio of Th^{230} and Ra^{226} compared to total uranium collected at environmental air sample locations around the facility. These ratios were then used to determine Th^{230} and Ra^{226} activity discharged based upon measured uranium from process stacks and fans.

NOTE 2: Quantities include storm water effluent discharge.